BaseX Documentation

Version 9.0



BaseX Documentation:

Version 9.0



Publication date 2018-03-23

Content is available under Attribution-ShareAlike 3.0 Unported (CC BY-SA 3.0).

Table of Contents

1. Main Page 1
    Getting Started 1
    XQuery Portal 1
    Advanced User's Guide 2
I. Getting Started 3
    2. Getting Started 4
        Overview 4
    3. Startup 6
        Getting Started 6
            Requirements 6
            Concurrent Operations 6
        Standalone 6
        Graphical User Interface 7
        Client/Server 7
            Server 7
            Client 7
        HTTP Server 8
        Changelog 8
    4. Command-Line Options 9
        Standalone 9
        Server 11
        Client 12
        HTTP Server 14
        GUI 15
        Changelog 16
    5. Start Scripts 17
        Main Package 17
            Windows: basex.bat 17
            Linux/Mac: basex 17
        HTTP Server 18
            Windows: basexhttp.bat 18
            Linux/Mac: basexhttp 18
        Changelog 18
II. User Interfaces 19
    6. Graphical User Interface 20
        Startup 20
        Input Bar 20
            Find 20
            XQuery 20
            Command 21
        Text Editor 21
            Project View 21
        Realtime Options 21
        Visualizations 21
        Look and Feels 23
        Changelog 23
    7. Shortcuts 24
        Editor 24
            Code Completions 24
            Editor Shortcuts 24
        Changelog 26
    8. Database Server 28
        Startup 28
            Working on Command-Line 28
    9. Standalone Mode 29

Startup 29
Create a Database 29
Execute a Query 29
Database Commands 29
Multiple Resources 30
Backup and Restore 30
10. Web Application 31
Servlet Container 31
Configuration 31
Available Services 32
Maven 33
Configuration 33
User Management 33
Changelog 33
11. DBA 35
Startup 35
First Steps 35
Editor 35
Changelog 36
III. General Info 37
12. Databases 38
Create Databases 38
Access Resources 38
XML Documents 38
Raw Files 39
HTTP Services 39
Update Resources 39
Export Data 40
Main-Memory Database Instances 40
Changelog 40
13. Binary Data 42
Storage 42
Usage 42
14. Parsers 43
XML Parsers 43
GUI 43
Command Line 43
XQuery 43
HTML Parser 43
Installation 43
Options 44
JSON Parser 45
GUI 45
Command Line 45
XQuery 45
CSV Parser 45
GUI 45
Command Line 45
XQuery 45
Text Parser 46
GUI 46
Command Line 46
XQuery 46
Changelog 46
15. Commands 47
Basics 47
Command Scripts 47
Glob Syntax 47

Valid Names 48
Aliases 48
Database Operations 48
CREATE DB 48
OPEN 48
CHECK 49
CLOSE 49
EXPORT 49
CREATE INDEX 49
DROP INDEX 49
Administration 50
ALTER DB 50
DROP DB 50
CREATE BACKUP 50
RESTORE 50
INSPECT 51
DROP BACKUP 51
SHOW BACKUPS 51
COPY 51
INFO DB 51
INFO INDEX 51
INFO STORAGE 52
Querying 52
LIST 52
XQUERY 52
RETRIEVE 52
FIND 53
TEST 53
REPO INSTALL 53
REPO LIST 53
REPO DELETE 53
Updates 54
ADD 54
DELETE 54
RENAME 54
REPLACE 55
STORE 55
OPTIMIZE 55
FLUSH 55
Monitoring 56
SHOW SESSIONS 56
SHOW USERS 56
KILL 56
JOBS LIST 56
JOBS RESULT 56
JOBS STOP 57
User Management 57
CREATE USER 57
ALTER USER 57
ALTER PASSWORD 57
DROP USER 57
GRANT 58
PASSWORD 58
General Commands 58
RUN 58
EXECUTE 58
GET 59
SET 59

INFO 59
HELP 59
EXIT 59
QUIT 59
Changelog 60
16. Options 62
Global Options 63
General Options 63
Client/Server Architecture 64
HTTP Services 67
Create Options 68
General 68
Parsing 68
XML Parsing 70
Indexing 71
Full-Text Indexing 74
Query Options 74
QUERYINFO 74
XQUERY3 75
MIXUPDATES 75
BINDINGS 75
INLINELIMIT 75
TAILCALLS 76
DEFAULTDB 76
FORCECREATE 76
CHECKSTRINGS 76
LSERROR 76
RUNQUERY 77
RUNS 77
ENFORCEINDEX 77
COPYNODE 77
Serialization Options 77
SERIALIZE 77
SERIALIZER 77
EXPORTER 78
XMLPLAN 78
COMPPLAN 78
DOTPLAN 78
DOTCOMPACT 78
Other Options 78
AUTOFLUSH 78
WRITEBACK 79
MAXSTAT 79
Changelog 79
IV. Integration 82
17. Integrating oXygen 83
Access Database Resources 83
Preparations 83
Configuration 83
Perform Queries 84
One-Time Setup 84
Execute Query 85
18. Integrating IntelliJ IDEA 86
Installation 86
From the Start Screen 86
From the File Menu 86
Setting Up 86
File Extensions and XQuery Flavor 86

Configuring The Processor 86
19. Integrating Eclipse 88
Installation 88
Windows 88
Linux 88
Mac OSX 88
Setting up 89
Setting up as Standalone 89
Setting up as Client 89
Usage 90
V. Query Features 91
20. XQuery 92
21. XQuery 3.0 93
Enhanced FLWOR Expressions 93
group by 93
count 94
allowing empty 94
window 94
Function Items 95
Simple Map Operator 95
Try/Catch 96
Switch 96
Expanded QNames 97
Namespace Constructors 97
String Concatenations 97
External Variables 97
Serialization 97
Context Item 97
Annotations 98
Functions 98
Changelog 98
22. Higher-Order Functions 100
Function Items 100
Function Types 100
Higher-Order Functions 100
Sequences 101
Folds 103
23. XQuery 3.1 106
Maps 106
Arrays 106
Atomization 107
Lookup Operator 107
Arrow Operator 108
String Constructor 108
Serialization 109
Adaptive Serialization 109
JSON Serialization 109
Functions 110
Map Functions 110
Array Functions 110
JSON Functions 110
fn:sort 111
fn:contains-token 111
fn:parse-ietf-date 112
fn:apply 112
fn:random-number-generator 112
fn:format-number 113
fn:tokenize 113

fn:trace 113
fn:string-join 113
fn:default-language 113
Appendix 113
Binary Data 113
Collations 113
Enclosed Expressions 114
Changelog 114
24. XQuery Extensions 115
Suffixes 115
Option Declarations 115
Pragmas 115
BaseX Pragmas 115
Database Pragmas 115
Annotations 116
basex:inline 116
basex:lazy 117
Serialization 117
Non-determinism 117
Miscellaneous 118
25. Module Library 119
26. Java Bindings 122
Identification 122
Classes 122
Functions and Variables 122
Namespace Declarations 122
Module Imports 123
Integration 123
Annotations 124
Locking 125
Data Types 125
URI Rewriting 126
Changelog 126
27. Repository 128
Introduction 128
Accessing Modules 128
Commands 128
Installation 129
Listing 129
Removal 129
Packaging 129
XQuery 129
Java 129
Combined 131
EXPath Packaging 132
XQuery 132
Java 132
Performance 133
Changelog 133
28. Full-Text 134
Introduction 134
Combining Results 134
Positional Filters 135
Match Options 135
BaseX Features 136
Languages 136
Scoring 137
Thesaurus 137

Fuzzy Querying 138
Mixed Content 138
Functions 139
Collations 139
Changelog 140
29. Full-Text: Japanese 141
Introduction 141
Lexical Analysis 141
Parsing 141
Token Processing 142
Stemming 142
Wildcards 142
30. XQuery Update 143
Features 143
Updating Expressions 143
Non-Updating Expressions 144
Functions 145
Concepts 146
Pending Update List 146
Returning Results 147
Effects 147
Original Files 147
Indexes 147
Error Messages 147
Changelog 147
31. Indexes 149
Structural Indexes 149
Name Index 149
Path Index 149
Document Index 150
Value Indexes 150
Text Index 150
Attribute Index 151
Token Index 151
Full-Text Index 152
Selective Indexing 152
Enforce Rewritings 153
Custom Index Structures 154
Performance 154
Updates 155
Changelog 155
32. Serialization 156
Parameters 156
Character mappings 159
Changelog 159
33. XQuery Errors 161
Static Errors 161
Type Errors 163
Dynamic Errors 163
Functions Errors 164
Serialization Errors 166
Update Errors 166
Full-Text Errors 168
BaseX Errors 168
VI. XQuery Modules 170
34. Admin Module 171
Conventions 171
Functions 171

admin:sessions 171
admin:logs 171
admin:write-log 171
admin:delete-logs 172
Errors 172
Changelog 172
35. Archive Module 173
Conventions 173
Functions 173
archive:create 173
archive:create-from 174
archive:entries 174
archive:options 174
archive:extract-text 175
archive:extract-binary 175
archive:extract-to 175
archive:update 176
archive:delete 176
Errors 176
Changelog 177
36. Array Module 178
Conventions 178
Functions 178
array:size 178
array:get 178
array:append 178
array:subarray 178
array:put 178
array:remove 179
array:insert-before 179
array:head 179
array:tail 179
array:reverse 179
array:join 179
array:flatten 180
array:for-each 180
array:filter 180
array:fold-left 180
array:fold-right 181
array:for-each-pair 181
array:sort 181
Errors 181
Changelog 182
37. Binary Module 183
Conventions 183
Constants and Conversions 183
bin:hex 183
bin:bin 183
bin:octal 183
bin:to-octets 184
bin:from-octets 184
Basic Operations 184
bin:length 184
bin:part 184
bin:join 184
bin:insert-before 184
bin:pad-left 185
bin:pad-right 185

bin:find 185
Text Decoding and Encoding 185
bin:decode-string 185
bin:encode-string 185
Packing and Unpacking of Numeric Values 186
bin:pack-double 186
bin:pack-float 186
bin:pack-integer 186
bin:unpack-double 186
bin:unpack-float 187
bin:unpack-integer 187
bin:unpack-unsigned-integer 187
Bitwise Operations 187
bin:or 187
bin:xor 187
bin:and 188
bin:not 188
bin:shift 188
Errors 188
Changelog 188
38. Client Module 189
Conventions 189
Functions 189
client:connect 189
client:execute 189
client:info 190
client:query 190
client:close 190
Errors 190
Changelog 191
39. Conversion Module 192
Conventions 192
Strings 192
convert:binary-to-string 192
convert:string-to-base64 192
convert:string-to-hex 192
Binary Data 193
convert:integers-to-base64 193
convert:integers-to-hex 193
convert:binary-to-integers 193
convert:binary-to-bytes 193
Numbers 194
convert:integer-to-base 194
convert:integer-from-base 194
Dates and Durations 194
convert:integer-to-dateTime 194
convert:dateTime-to-integer 194
convert:integer-to-dayTime 195
convert:dayTime-to-integer 195
Errors 195
Changelog 195
40. Cryptographic Module 196
Conventions 196
Message Authentication 196
crypto:hmac 196
Encryption & Decryption 196
crypto:encrypt 197
crypto:decrypt 197

XML Signatures 197
crypto:generate-signature 198
crypto:validate-signature 199
Errors 200
Changelog 200
41. CSV Module 201
Conventions 201
Conversion 201
Options 202
Functions 203
csv:parse 203
csv:serialize 203
Examples 203
Errors 204
Changelog 204
42. Database Module 206
Conventions 206
Database Nodes 206
General Functions 206
db:system 206
db:option 206
db:info 206
db:property 206
db:list 207
db:list-details 207
db:backups 207
Read Operations 208
db:open 208
db:open-pre 208
db:open-id 208
db:node-pre 208
db:node-id 208
db:retrieve 209
db:export 209
Value Indexes 210
db:text 210
db:text-range 210
db:attribute 210
db:attribute-range 210
db:token 211
Updates 211
db:create 211
db:drop 212
db:add 212
db:delete 212
db:copy 213
db:alter 213
db:create-backup 213
db:drop-backup 213
db:restore 213
db:optimize 214
db:rename 214
db:replace 214
db:store 215
db:flush 215
Helper Functions 215
db:name 215
db:path 215

db:exists 216
db:is-raw 216
db:is-xml 216
db:content-type 216
Errors 216
Changelog 217
43. Fetch Module 219
Conventions 219
Functions 219
fetch:binary 219
fetch:text 219
fetch:xml 220
fetch:xml-binary 220
fetch:content-type 220
Errors 221
Changelog 221
44. File Module 222
Conventions 222
File Paths 222
Read Operations 222
file:list 222
file:children 222
file:read-binary 222
file:read-text 223
file:read-text-lines 223
Write Operations 223
file:create-dir 223
file:create-temp-dir 224
file:create-temp-file 224
file:delete 224
file:write 224
file:write-binary 225
file:write-text 225
file:write-text-lines 225
file:append 225
file:append-binary 226
file:append-text 226
file:append-text-lines 226
file:copy 226
file:move 226
File Properties 227
file:exists 227
file:is-dir 227
file:is-absolute 227
file:is-file 227
file:last-modified 227
file:size 227
Path Functions 227
file:name 227
file:parent 227
file:path-to-native 228
file:resolve-path 228
file:path-to-uri 228
System Properties 228
file:dir-separator 228
file:path-separator 228
file:line-separator 228
file:temp-dir 228

file:current-dir ... 229
file:base-dir ... 229
Errors ... 229
Changelog ... 229
45. Full-Text Module ... 231
Conventions ... 231
Functions ... 231
ft:search ... 231
ft:contains ... 232
ft:mark ... 233
ft:extract ... 233
ft:count ... 234
ft:score ... 234
ft:tokens ... 234
ft:tokenize ... 234
ft:normalize ... 235
Errors ... 235
Changelog ... 235
46. Geo Module ... 236
Conventions ... 236
General Functions ... 236
geo:dimension ... 236
geo:geometry-type ... 236
geo:srid ... 236
geo:envelope ... 237
geo:as-text ... 237
geo:as-binary ... 237
geo:is-simple ... 238
geo:boundary ... 238
geo:num-geometries ... 238
geo:geometry-n ... 239
geo:length ... 239
geo:num-points ... 239
geo:area ... 240
geo:centroid ... 240
geo:point-on-surface ... 240
Spatial Predicate Functions ... 241
geo:equals ... 241
geo:disjoint ... 241
geo:intersects ... 242
geo:touches ... 242
geo:crosses ... 242
geo:within ... 243
geo:contains ... 243
geo:overlaps ... 244
geo:relate ... 244
Analysis Functions ... 245
geo:distance ... 245
geo:buffer ... 245
geo:convex-hull ... 246
geo:intersection ... 246
geo:union ... 246
geo:difference ... 247
geo:sym-difference ... 247
Functions Specific to Geometry Type ... 247
geo:x ... 247
geo:y ... 248
geo:z ... 248

geo:start-point 248
geo:end-point 248
geo:is-closed 249
geo:is-ring 249
geo:point-n 249
geo:exterior-ring 250
geo:num-interior-ring 250
geo:interior-ring-n 250
Errors 251
Changelog 251
47. Hashing Module 252
Conventions 252
Functions 252
hash:md5 252
hash:sha1 252
hash:sha256 252
hash:hash 252
Errors 253
Changelog 253
48. Higher-Order Functions Module 254
Conventions 254
Loops 254
hof:fold-left1 254
hof:until 254
hof:scan-left 255
hof:take-while 255
Sorting 255
hof:top-k-by 255
hof:top-k-with 256
IDs 256
hof:id 256
hof:const 256
Changelog 257
49. HTML Module 258
Conventions 258
Functions 258
html:parser 258
html:parse 258
Examples 258
Basic Example 258
Specifying Options 258
Parsing Binary Input 259
Errors 259
Changelog 259
50. HTTP Module 260
Conventions 260
Functions 260
http:send-request 260
Examples 260
Status Only 260
Google Homepage 261
POST Request 262
Errors 263
Changelog 263
51. Index Module 264
Conventions 264
Functions 264
index:facets 264

index:texts 264
index:attributes 264
index:tokens 265
index:element-names 265
index:attribute-names 265
Changelog 265
52. Inspection Module 266
Conventions 266
Reflection 266
inspect:functions 266
inspect:function-annotations 266
inspect:static-context 267
Documentation 267
inspect:function 267
inspect:context 268
inspect:module 268
inspect:xqdoc 268
Examples 269
Errors 270
Changelog 271
53. Jobs Module 272
Conventions 272
Services 272
Basic Functions 272
jobs:current 272
jobs:list 272
jobs:list-details 273
jobs:finished 273
Execution 273
jobs:eval 274
jobs:invoke 275
jobs:result 275
jobs:stop 276
jobs:wait 276
Errors 276
Changelog 277
54. JSON Module 278
Conventions 278
Conversion Formats 278
Options 279
Functions 280
json:parse 280
json:serialize 280
Examples 280
BaseX Format 280
JsonML Format 282
XQuery Format 283
Errors 284
Changelog 284
55. Lazy Module 286
Conventions 286
Functions 286
lazy:cache 286
lazy:is-lazy 287
lazy:is-cached 287
Changelog 287
56. Map Module 288
Conventions 288

Functions 288
map:contains 288
map:entry 288
map:find 289
map:for-each 289
map:get 289
map:keys 290
map:merge 290
map:put 290
map:remove 290
map:size 291
Changelog 291
57. Math Module 292
Conventions 292
W3 Functions 292
math:pi 292
math:sqrt 292
math:sin 292
math:cos 292
math:tan 292
math:asin 292
math:acos 293
math:atan 293
math:atan2 293
math:pow 293
math:exp 293
math:log 293
math:log10 293
Additional Functions 294
math:e 294
math:sinh 294
math:cosh 294
math:tanh 294
math:crc32 294
Changelog 294
58. Output Module 295
Conventions 295
Functions 295
out:cr 295
out:nl 295
out:tab 295
out:format 295
Errors 295
Changelog 295
59. Process Module 297
Conventions 297
Functions 297
proc:system 297
proc:execute 298
proc:fork 298
proc:property 298
proc:property-names 299
Errors 299
Changelog 299
60. Profiling Module 300
Conventions 300
Performance Functions 300
prof:track 300

prof:time 301
prof:memory 301
prof:current-ms 301
prof:current-ns 301
Debugging Functions 302
prof:dump 302
prof:variables 302
prof:type 302
Helper Functions 302
prof:void 302
prof:sleep 302
prof:human 302
Changelog 303
61. Random Module 304
Conventions 304
Functions 304
random:double 304
random:integer 304
random:seeded-double 304
random:seeded-integer 304
random:gaussian 304
random:seeded-permutation 305
random:uuid 305
Errors 305
Changelog 305
62. Repository Module 306
Conventions 306
Functions 306
repo:install 306
repo:delete 306
repo:list 306
Errors 306
Changelog 307
63. Request Module 308
Conventions 308
General Functions 308
request:method 308
request:attribute 308
URI Functions 308
request:scheme 308
request:hostname 309
request:port 309
request:path 309
request:query 309
request:uri 309
request:context-path 309
Connection Functions 309
request:address 309
request:remote-hostname 309
request:remote-address 310
request:remote-port 310
Parameter Functions 310
request:parameter-names 310
request:parameter 310
Header Functions 310
request:header-names 310
request:header 310
Cookie Functions 310

request:cookie-names 310
request:cookie 311
Changelog 311
64. RESTXQ Module 312
Conventions 312
General Functions 312
rest:base-uri 312
rest:uri 312
rest:wadl 312
rest:init 312
Changelog 312
65. Session Module 313
Conventions 313
Functions 313
session:id 313
session:created 313
session:accessed 313
session:names 313
session:get 314
session:set 314
session:delete 314
session:close 314
Errors 314
Changelog 315
66. Sessions Module 316
Conventions 316
Functions 316
sessions:ids 316
sessions:created 316
sessions:accessed 316
sessions:names 316
sessions:get 316
sessions:set 317
sessions:delete 317
sessions:close 317
Errors 317
Changelog 317
67. SQL Module 318
Conventions 318
Functions 318
sql:init 318
sql:connect 318
sql:execute 318
sql:execute-prepared 319
sql:prepare 319
sql:commit 319
sql:rollback 320
sql:close 320
Examples 320
Direct queries 320
Prepared Statements 320
SQLite 321
Errors 321
Changelog 321
68. Strings Module 322
Conventions 322
Functions 322
strings:levenshtein 322

strings:soundex 322
strings:cologne-phonetic 322
Changelog 323
69. Unit Module 324
Introduction 324
Usage 324
Conventions 324
Annotations 324
%unit:test 324
%unit:before 324
%unit:after 325
%unit:before-module 325
%unit:after-module 325
%unit:ignore 325
Functions 325
unit:assert 325
unit:assert-equals 325
unit:fail 326
Example 326
Query 326
Result 327
Errors 327
Changelog 328
70. Update Module 329
Conventions 329
Updates 329
update:apply 329
update:for-each 329
update:for-each-pair 329
update:map-for-each 330
Output 330
update:output 330
update:output-cache 330
Changelog 331
71. User Module 332
Conventions 332
Read Operations 332
user:current 332
user:list 332
user:list-details 332
user:exists 332
user:check 333
user:info 333
Updates 333
user:create 333
user:grant 333
user:drop 334
user:alter 334
user:password 334
user:update-info 334
Errors 335
Changelog 335
72. Validation Module 336
Conventions 336
DTD Validation 336
validate:dtd 336
validate:dtd-info 336
validate:dtd-report 337

XML Schema Validation 337
validate:xsd 337
validate:xsd-info 338
validate:xsd-report 338
RelaxNG Validation 338
validate:rng 339
validate:rng-info 339
validate:rng-report 339
Errors 339
Changelog 339
73. Web Module 341
Conventions 341
Functions 341
web:content-type 341
web:create-url 341
web:encode-url 341
web:decode-url 341
web:redirect 342
web:response-header 342
Errors 343
Changelog 343
74. XQuery Module 344
Conventions 344
Functions 344
xquery:eval 344
xquery:eval-update 345
xquery:invoke 345
xquery:invoke-update 346
xquery:parse 346
xquery:parse-uri 346
Parallelized Execution 347
xquery:fork-join 347
Errors 347
Changelog 347
75. XSLT Module 349
Conventions 349
Functions 349
xslt:processor 349
xslt:version 349
xslt:transform 349
xslt:transform-text 350
Examples 350
Errors 351
Changelog 352
76. ZIP Module 353
Conventions 353
Functions 353
zip:binary-entry 353
zip:text-entry 353
zip:xml-entry 353
zip:html-entry 353
zip:entries 353
zip:zip-file 354
zip:update-entries 354
Errors 354
VII. Developing 356
77. Developing 357
78. Developing with Eclipse 358

Prerequisites 358
Check Out 358
Start in Eclipse 358
Alternative 359
79. Git 360
Using Git to contribute to BaseX 360
Using Git & Eclipse 360
Links 364
80. Maven 365
Using Maven 365
Artifacts 365
81. Releases 367
Official Releases 367
Stable Snapshots 367
Code Base 367
Maven Artifacts 367
Linux 367
82. Translations 368
Working with the sources 368
Updating BaseX.jar 368
VIII. Web Technology 370
83. RESTXQ 371
Introduction 371
Preliminaries 371
Examples 371
Request 372
Constraints 372
Content Types 374
Parameters 375
Query Execution 376
Response 377
Custom Response 377
Forwards and Redirects 377
Output 378
Error Handling 379
XQuery Errors 379
HTTP Errors 380
User Authentication 380
Functions 380
References 380
Changelog 381
84. Permissions 382
Preliminaries 382
Annotations 382
Permission Strings 382
Checking Permissions 383
Authentication 384
Changelog 384
85. REST 385
Usage 385
URL Architecture 385
Parameters 385
Request 386
GET Method 386
POST Method 386
PUT Method 387
DELETE Method 388
Assigning Variables 388

GET Method 388
POST Method 389
Response 389
Content Type 389
Usage Examples 390
Java 390
Command Line 390
Changelog 391
86. WebDAV 392
Usage 392
Authorization 392
Root Directory 392
Resources 392
XML Documents 392
Binary Files 392
Locking 392
WebDAV Clients 393
Changelog 393
87. WebDAV: Windows 7 394
88. WebDAV: Windows XP 396
89. WebDAV: Mac OSX 400
90. WebDAV: GNOME 403
91. WebDAV: KDE 405
92. XForms 407
Internals 407
Run the example 407
Further reading 408
IX. Client APIs 409
93. Clients 410
Changelog 411
94. Standard Mode 412
Usage 412
Example in PHP 412
95. Query Mode 413
Usage 413
PHP Example 413
Changelog 414
96. Server Protocol 415
Workflow 415
Transfer Protocol 415
Example 417
Constructors and Functions 418
97. Server Protocol: Types 420
XDM Meta Data 420
Type IDs 420
98. Java Examples 422
Local Examples 422
Server Examples 422
XQuery Module Examples 422
Client API 423
REST API 423
XML:DB API (deprecated) 423
X. Extensions 424
99. Docker 425
Running a BaseX Container 425
Security Considerations 425
Running your own Application 425
Example: DBA 426

Advanced Usage 426
100. YAJSW 427
Some basics of YAJSW 427
Gather the files 427
Install BaseX as a Windows Service 427
101. Android 429
Creating the Android Library Project 429
Adjusting the Code 429
Using the BaseX Android Library 432
XI. Advanced User's Guide 433
102. Advanced User's Guide 434
103. Configuration 435
Configuration Files 435
Home Directory 435
Database Directory 435
Log Files 436
Changelog 436
104. Backups 437
GUI Example 437
Console Example 437
105. Catalog Resolver 438
Overview 438
XML Entity and URI Resolvers 438
Using other Resolvers 439
More Information 439
106. Storage Layout 440
Data Types 440
Database Files 440
Meta Data, Name/Path/Doc Indexes: `inf` 440
Node Table: `tbl`, `tbli` 441
Texts: `txt`, `atv` 441
Value Indexes: `txtl`, `txtr`, `atvl`, `atvr` 441
Full-Text Fuzzy Index: `ftxx`, `ftxy`, `ftxz` 441
107. Node Storage 442
Node Table 442
PRE Value 442
ID Value 442
Block Storage 442
108. User Management 444
Rules 444
Operations 444
Commands 444
XQuery 445
Storage 445
Changelog 445
109. Transaction Management 446
Introduction 446
XQuery Update 446
Concurrency Control 446
XQuery Locks 447
Limitations 447
File-System Locks 448
Update Operations 448
Database Locks 448
Changelog 448
110. Logging 450
Introduction 450
RESTXQ 450

Format 450
Changelog 451
XII. Use Cases 452
111. Statistics 453
Databases 453
Sources 455
112. Twitter 457
BaseX as Twitter Storage 457
Twitter's Streaming Data 457
Statistics 457
Example Tweet (JSON) 458
Example Tweet (XML) 459
BaseX Performance 460
Insert with XQuery Update 460

Chapter 1. Main Page

Read this entry online in the BaseX Wiki.



BaseX GUI BaseX is a light-weight, high-performance and scalable XML Database and an XQuery 3.1 Processor with full support for the W3C Update and Full Text extensions. It allows you to store, query and process large corpora of textual data (XML, JSON, CSV, many others). With RESTXQ, you can develop full web applications. The visual frontend includes an XQuery editor for running your expressions in realtime, and various visualizations to interactively explore data. BaseX is platform-independent and distributed under the free BSD License (find more in Wikipedia).

This documentation is based on **BaseX 9.0**. New and updated features are *highlighted* and can also be searched for.

If you have questions, or if you want to have direct contact to the developer team and users of BaseX, please write to our basex-talk mailing list. Many questions are being discussed at StackOverflow, and planned features are listed in our GitHub repository.

Getting Started

The getting started section gives you a quick introduction to BaseX. We suggest you to start with the Graphical User Interface as this is the easiest way to access your XML data, and to get an idea of how XQuery and BaseX works.

XQuery Portal

More information on using the wide range of XQuery functions and performing XPath and XQuery requests with BaseX can be found in our XQuery Portal.

Developer Section

The developer section provides useful information for developers. Here you can find information on our supported client APIs and HTTP services, and we present different ways how you can integrate BaseX into your own project.

Advanced User's Guide

Information for advanced users can be found in our advanced user's guide, which contains details on the BaseX storage, the Client/Server architecture, and some querying features.

Part I. Getting Started

Chapter 2. Getting Started

Read this entry online in the BaseX Wiki.

This page is one of the Main Sections of the documentation. It gives a quick introduction on how to start, run, and use BaseX.

Overview

First Steps

- Startup : How to get BaseX running
- Command-Line Options

User Interfaces

- Graphical User Interface (see available Shortcuts)
- Database Server : The client/server architecture
- Standalone Mode : The comand-line interface
- Web Application : The HTTP server
- DBA : Browser-based database administration

General Info

- Databases : How databases are created, populated and deleted
- Parsers : How different input formats can be converted to XML
- Commands : Full overview of all database commands
- Options : Listing of all database options

Integration

- Integrating oXygen
- Integrating IntelliJ IDEA
- Integrating Eclipse

Tutorials and Slides

BaseX: Introduction

- BaseX for Dummies. Written by Paul Swennenhuis:Part I, Part I (files), Part II.
- BaseX Adventures . Written by Neven Jovanovi#.
- Tutorial . Written by Imed Bouchrika.
- XQuery pour les Humanités Numériques . Written by Farid Djaïdja (French).

XML and XQuery

- XML Technologies . Our university course on XML, XPath, XQuery, XSLT, Validation, Databases, etc.
- XQuery Tutorial . From W3 Schools.

- XQuery: A Guided Tour . From the book "XQuery from the Experts".
- XQuery Summer Institute . Exercises and Answers.

BaseX: Talks, Questions

- Our Annual User Meetings . Slides and videos.
- Our Mailing List . Join and contribute.
- GitHub Issue Tracker . Please use our mailing list before entering new issues.
- Stack Overflow . Questions on `basex`.

Chapter 3. Startup

Read this entry online in the BaseX Wiki.

This article is part of the Getting Started Guide. It tells you how to get BaseX running.

Getting Started

First of all, download BaseX from our homepage. The following distributions are available:

- the **Core Package** is a JAR file, which contains the database system, the query processor and the GUI frontend. It is runs completely without additional libraries.
- the **ZIP Archive** and the **Windows Installer** contain libraries for web applications and advanced features, Start Scripts, and some additional optional files.
- the **WAR Archive** can be embedded in existing Java web servers.

Some additional distributions are available from the download page, most of which contain only the core package and, optionally, scripts for starting BaseX.

BaseX is very light-weight. It can be run and used in various ways:

- as standalone application, using the Standalone mode or the Graphical User Interface,
- as Client/Server application, or
- as Web Application, called from a web server.

It can also be embedded as a library in your own application.

Requirements

BaseX is platform-independent and runs on any system that provides an implementation of the Java Runtime Environment (JRE). Since **Version 9.0** of BaseX, Java 8 is required. BaseX 8.x works with Java 7, and previous versions were based on Java 6.

BaseX has been tested on several platforms, including Windows (2000, XP, Vista, 7), Max OS X (10.x), Linux (SuSE xxx, Debian, Ubuntu) and OpenBSD (4.x).

Concurrent Operations

If you plan to perform concurrent read and write operations on databases, you must use the client/server architecture or deploy BaseX as web application. You can safely open a database in different JVMs (Java virtual machines) for read-only access, and you will not encounter any problems when reading from and writing to different databases, but update operations from different JVMs to the same database will be rejected or may even lead to corrupt databases. More details are found in the Transaction Management article.

Standalone

The Standalone Mode can be used to execute XQuery expressions or run database commands on command line. It can also be used both for scripting and batch processing your XML data. It can be started as follows (get more information on all Startup Options):

- Run one of the `basex` or `basex.bat` scripts.
- Execute the following command: `java -cp BaseX.jar org.basex.BaseX`
- On *Windows*: Double click on the **BaseX** icon.

It is important to remember that the standalone mode does *not* interact with the Client/Server architecture.

Graphical User Interface

The GUI is the visual interface to the features of BaseX. It can be used to create new databases, perform queries or interactively explore your XML data.

It can be started as follows (get more information on all Startup Options):

- Double click on the `BaseX.jar` file.
- Run one of the `basexgui` or `basexgui.bat` scripts.
- Execute the following command: `java -cp BaseX.jar org.basex.BaseXGUI`
- On *Windows*: Double click on the **BaseX GUI** icon.
- For Maven users: type in `mvn exec:java` in the main directory of the `basex` project.

Note that the GUI does *not* interact with the client/server architecture.

Client/Server

Server

The Database Server comes into play if BaseX is to be used by more than one user (client). It handles concurrent read and write transactions, provides user management and logs all user interactions.

By default, the server listens to the port `1984`. There are several ways of starting and stopping the server (get more information on all Startup Options):

- Run one of the `basexserver` or `basexserver.bat` scripts. Add the `stop` keyword to gracefully shut down the server.
- Execute the following command: `java -cp BaseX.jar org.basex.BaseXServer`. Again, the `stop` keyword will ensure a graceful shutdown.
- On *Windows*: Double click on the **BaseX Server** icon, which will also start the HTTP Server, or the **BaseX Server (stop)** icon.

Pressing `Ctrl+c` will close all connections and databases and shut down the server process.

Client

The BaseX Client interface can be used to send commands and queries to the server instance on command line.

It can be started as follows (get more information on all Startup Options):

- Run one of the `basexclient` or `basexclient.bat` scripts.
- Execute the following command: `java -cp BaseX.jar org.basex.BaseXClient`
- On *Windows*: Double click on the **BaseX Client** icon.

The default `admin` user can be used to connect to the server:

- **Username:** `admin`
- **Password:** `admin`

The password should be changed with the `PASSWORD` command after the first login.

We provide additional clients in various programming languages.

HTTP Server

With the HTTP Server, BaseX can be used as Web Application. It provides access to the REST, RESTXQ and WebDAV services. An instance of the Jetty Web Server will be created, which by default listens to the port `8984`. Additionally, the BaseX Server will be started, which is accessible on port `1984`.

It can be started as follows (get more information on all Startup Options):

- Run one of the `basexhttp` or `basexhttp.bat` scripts. Call the script with the `stop` keyword to gracefully shut down the server.
- On *Windows*: Double click on the **BaseX Server** or **BaseX Server (stop)** icon.
- BaseX can also be deployed as web servlet.

In the first two cases, the command-line output will look similar to the following lines (the JSP warning message can be ignored):

```
[main] INFO org.eclipse.jetty.server.Server - jetty-8.1.18.v20150929
[main] INFO org.eclipse.jetty.webapp.StandardDescriptorProcessor - NO JSP Support
 for /, did not find org.apache.jasper.servlet.JspServlet
[main] INFO org.eclipse.jetty.server.AbstractConnector - Started
 SelectChannelConnector@0.0.0.0:8984
HTTP Server was started (port: 8984).
```

You can adjust the Jetty logging level by adding the following properties to the start script:

```
-Dorg.eclipse.jetty.util.log.class=org.eclipse.jetty.util.log.StdErrLog -
D{classref}.LEVEL=DEBUG
```

After that, you can e. g. open your browser and navigate to the RESTXQ start page http://localhost:8984.

Changelog

Version 8.0

- Update: Switched to Java 7

Version 7.0

- Updated: BaseXJAXRX has been replaced with BaseXHTTP

Chapter 4. Command-Line Options

Read this entry online in the BaseX Wiki.

This article is part of the Getting Started Guide. It gives more details on the command-line options of all BaseX Startup modes.

Options can be specified multiple times. Please note that all options will be evaluated in the given order. The standard input can be parsed by specifying a single dash (`-`) as argument.

Standalone

Launch the console mode

```
$ basex
BaseX [Standalone]
Try "help" to get more information.
> _
```

Available command-line flags can be listed with `-h`:

```
$ basex -h
BaseX [Standalone]
Usage: basex [-bcdiLoqrRsuvVwxXz] [input]
  [input]     Execute input file or expression
  -b<pars>    Bind external query variables
  -c<input>   Execute commands from file or string
  -d          Activate debugging mode
  -i<input>   Open XML file or database
  -I<input>   Assign input string to context
  -o<output>  Write output to file
  -q<expr>    Execute XQuery expression
  -r<num>     Set number of query executions
  -R          Turn query execution on/off
  -s<pars>    Set serialization parameter(s)
  -t[path]    Run tests in file or directory
  -u          Write updates back to original files
  -v/V        Show (all) process info
  -w          Preserve whitespaces from input files
  -x          Show query execution plan
  -X          Show query plan before/after compilation
  -z          Skip output of results
```

The meaning of all flags is listed in the following table. If an equivalent database option exists (which can be specified via the `SET` command), it is listed as well. For the examples to work escaping some characters might be necessary, depending on your Operating System.

Flag	Description	Option	Default	Examples

`[input]`	Evaluates the specified input:
	• The input string may point to an existing file. If the file suffix is `.bxs`, the file contents will be evaluated as Command Script; otherwise, it will be evaluated as XQuery expression.
	• Otherwise, the input string itself is evaluated as XQuery expression.
				`"doc('X')//head"`
				`query.xq`
				`commands.bxs`

`-b<pars>`	Binds external variables to XQuery expressions. This flag may be specified multiple times. Variables names and their values are delimited by equality signs (=). The names may be optionally prefixed with dollar signs. If a variable uses a namespace different to the default namespace, it can be specified with the Clark Notation.	`BINDINGS`		`-bv=example "declare variable $v external; $v" -b{URL}ln=value"declare namespace ns='URL'; declare variable $ns:ln external; $ns:ln"`
`-c<input>`	Executes Commands: • Several commands in the input can be separated by semicolons (`;`). • If the specified input is a valid URL or file reference, this file will be evaluated as Commands#Command_ScriptsCommand Script.			`-c"list;info" -ccommands.txt -c"<info/>"`
`-d`	Toggles the debugging mode. Debugging information is output to *standard error*.	`DEBUG`	`false`	
`-i<input>`	Opens an XML file or database specified by the argument. The opened input can then be processed by a command or XQuery expression.			`-iitems.xml "//item"`
`-I<input>`	Assigns an input string as item of type `xs:untypedAtomic` to the query context.			`-I "Hello Universe" -q "."`
`-o<file>`	All command and query output is written to the specified file.			`-o output.txt`
`-q<expr>`	Executes the specified string as XQuery expression.			`-q"doc('input')//head"`
`-r<num>`	Specifies how often a specified query will be evaluated.	`RUNS`	`1`	`-V -r10 "1"`
`-R`	Specifies if a query will be executed or parsed only.	`RUNQUERY`	`true`	`-V -R "1"`
`-s<pars>`	Specifies parameters for serializing XQuery results; see Serialization for more details. This flag may be specified multiple times. Key and values are separated by the equality sign (=).	`SERIALIZER`		`-smethod=text`
`-t`	Runs all Unit tests in the specified file or directory.			-t project/tests
`-u`	Propagates updates on input files back to disk.	`WRITEBACK`	`false`	
`-v`	Prints process and timing information to the *standard output*.		`false`	

`-V`	Prints detailed query information to the *standard output*, including details on the compilation and profiling steps.	`QUERYINFO`	`false`	
`-w`	Specifies if whitespaces in XML text nodes should be chopped (which is the default) or preserved.	`CHOP`	`true`	
`-x`	This flags turn on the output of the query execution plan, formatted in XML.	`XMLPLAN`	`false`	
`-X`	Generates the query plan before or after query compilation. `-x` needs to be activated to make the plan visible.	`COMPPLAN`	`true`	
`-z`	Turns the serialization of XQuery results on/off. This flag is useful if the query is profiled or analyzed.	`SERIALIZE`	`true`	

Server

Updated with Version 9.0: `-c` flag now accepts valid URLs and file references.

Launch the server

```
$ basexserver
BaseX [Server]
Server was started (port: 1984)
```

Available command-line flags can be listed with `-h`:

```
$ basexserver -h
BaseX [Server]
Usage: basexserver [-cdinpSz] [stop]
  stop       Stop running server
  -c<input>  Execute commands from file or string
  -d         Activate debugging mode
  -n<name>   Set host the server is bound to
  -p<port>   Set server port
  -S         Start as service
  -z         Suppress logging
```

The flags have the following meaning (equivalent database options are shown in the table as well). For the examples to work escaping some characters might be necessary, depending on your Operating System.

Flag	Description	Option	Default	Examples
`stop`	Stops a local database server instance and quits.			
`-c<cmd>`	Executes Commands: • Several commands in the input can be separated by semicolons (`;`). • If the specified input is a valid URL or file reference, this file will be evaluated as Commands#Command_ScriptsCommand Script.			`-c"open database;info"`
`-d`	Turns on the debugging mode. Debugging information is output to *standard error*.	`DEBUG`	`false`	

`-n<name>`	Specifies the host the server will be bound to.	`SERVERHOST`		`-p127.0.0.1`
`-p<num>`	Specifies the port on which the server will be addressable.	`SERVERPORT`	`1984`	`-p9999`
`-S`	Starts the server as service (i.e., in the background). Use YAJSW, or start BaseX as an ordinary background process, to get more options.			
`-z`	Does not generate any log files.	`LOG`	`true`	

Multiple `-c` and `-i` flags can be specified. All other options will be set before any other operation takes place. The specified inputs, query files, queries and commands will be subsequently evaluated after that in the given order. The standard input can be parsed by specifying a single dash (`-`) as argument.

Client

Launch the console mode
communicating with the server

The user name and password will be requested. The default user/password combination is **admin**/**admin**:

```
$ basexclient
Username: admin
Password: *****
BaseX [Client]
Try "help" to get more information.
> _
```

Available command-line flags can be listed with `-h`:

```
$ basexclient -h
BaseX [Client]
Usage: basexclient [-bcdiLnopPqrRsUvVwxXz] [input]
  [input]     Execute input file or expression
  -b<pars>    Bind external query variables
  -c<input>   Execute commands from file or string
  -d          Activate debugging mode
  -i<input>   Open XML file or database
  -I<input>   Assign input string to context
  -n<name>    Set server (host) name
  -o<output>  Write output to file
  -p<port>    Set server port
  -P<pass>    Specify user password
  -q<expr>    Execute XQuery expression
  -r<num>     Set number of query executions
  -R          Turn query execution on/off
  -s<pars>    Set serialization parameter(s)
  -U<name>    Specify user name
  -v/V        Show (all) process info
  -w          Preserve whitespaces from input files
  -x          Show query execution plan
  -X          Show query plan before/after compilation
  -z          Skip output of results
```

The flags have the following meaning (equivalent database options are shown in the table as well). For the examples to work escaping some characters might be necessary, depending on your Operating System.

Flag	Description	Option	Default	Examples
`[input]`	Evaluates the specified input:			`"doc('X')//head"`

	• The input string may point to an existing file. If the file suffix is `.bxs`, the file contents will be evaluated as Command Script; otherwise, it will be evaluated as XQuery expression. • Otherwise, the input string itself is evaluated as XQuery expression.			`query.xq` `commands.bxs`
`-b<pars>`	Binds external variables to XQuery expressions. This flag may be specified multiple times. Variables names and their values are delimited by equality signs (`=`). The names may be optionally prefixed with dollar signs. If a variable uses a namespace different to the default namespace, it can be specified with the Clark Notation or Expanded QName Notation.	`BINDINGS`		`-b $v=example "declare variable $v external; $v" -b{URL}ln=value"declare namespace ns='URL'; declare variable $ns:ln external; $ns:ln"`
`-c<input>`	Executes Commands: • Several commands in the input can be separated by semicolons (`;`). • If the specified input is a valid file reference or URL, its content will be executed instead. Empty lines and lines starting with the number sign # will be ignored.			`-c"list;info" -ccommands.txt -c"<info/>"`
`-d`	Toggles the debugging mode. Debugging information is output to *standard error*.	`DEBUG`	`false`	
`-i<input>`	Opens an XML file or database specified by the argument. The opened input can then be processed by a command or XQuery expression.			`-iitems.xml "//item"`
`-I<input>`	Assigns an input string as item of type `xs:untypedAtomic` to the query context.			`-I "Hello Universe" -q "."`
`-n<name>`	Specifies the host name on which the server is running.	`HOST`	`localhost`	`-nserver.basex.org`
`-o<file>`	All command and query output is written to the specified file.			
`-p<num>`	Specifies the port on which the server is running.	`PORT`	`1984`	`-p9999`
`-P<pass>`	Specifies the user password. If this flag is omitted, the password will be requested on command line. *Warning*: when the password is specified with this flag, it may get visible to others.	`PASSWORD`		`-Uadmin -Padmin`

`-q<expr>`	Executes the specified string as XQuery expression.		`-q"doc('input')//head"`	
`-r<num>`	Specifies how often a specified query will be evaluated.	`RUNS`	`1`	`-V -r10 "1"`
`-R`	Specifies if a query will be executed or parsed only.	`RUNQUERY`	`true`	`-V -R "1"`
`-s<pars>`	Specifies parameters for serializing XQuery results; see Serialization for more details. This flag may be specified multiple times. Key and values are separated by the equality sign (=).	`SERIALIZER`		`-smethod=text`
`-U<name>`	Specifies the user name. If this flag is omitted, the user name will be requested on command line.	`USER`		`-Uadmin`
`-v`	Prints process and timing information to the *standard output*.		`false`	
`-V`	Prints detailed query information to the *standard output*, including details on the compilation and profiling steps.	`QUERYINFO`	`false`	
`-w`	Specifies if whitespaces in XML text nodes should be chopped (which is the default) or preserved.	`CHOP`	`chop`	
`-x`	This flags turn on the output of the query execution plan, formatted in XML.	`XMLPLAN`	`false`	
`-X`	Generates the query plan before or after query compilation. `-x` needs to be activated to make the plan visible.	`COMPPLAN`	`after`	
`-z`	Turns the serialization of XQuery results on/off. This flag is useful if the query is profiled or analyzed.	`SERIALIZE`	`true`	

HTTP Server

Introduced with Version 9.0: `-c` flag accepts commands and valid URLs and file references.

Launch the HTTP server

```
$ basexhttp
BaseX [Server]
Server was started (port: 1984)
HTTP Server was started (port: 8984)
```

Available command-line flags can be listed with `-h`:

```
$ basexhttp -h
BaseX [HTTP]
Usage: basexhttp [-dhlnpPRUWz] [stop]
  stop       Stop running server
  -c<input>  Execute commands from file or string
  -d         Activate debugging mode
  -h<port>   Set port of HTTP server
  -l         Start in local mode
  -n<name>   Set host name of database server
```

```
  -p<port>   Set port of database server
  -s<port>   Specify port to stop HTTP server
  -S         Start as service
  -U<name>   Specify user name
  -z         Suppress logging
```

The flags have the following meaning (equivalent database options are shown in the table as well). For the examples to work escaping some characters might be necessary, depending on your Operating System.

Flag	Description	Option	Default	Examples
`stop`	Stops a local HTTP server and quits. The database server will be stopped as well, unless `-l` is specified.	`pom.xml`		
`-c<cmd>`	Executes Commands: • Several commands in the input can be separated by semicolons (`;`). • If the specified input is a valid URL or file reference, this file will be evaluated as Commands#Command_ScriptsCommand Script.			`-c"open database"`
`-d`	Turns on the debugging mode. Debugging information is output to *standard error*.	`DEBUG`		
`-h<num>`	Specifies the port on which the HTTP server will be addressable.	`jetty.xml`	`8984`	`-h9999`
`-l`	Starts the server in *local mode*, and executes all commands in the embedded database context.	`HTTPLOCAL`		
`-n<name>`	Specifies the host name on which the server is running.	`HOST`	`localhost`	`-nserver.basex.org`
`-p<num>`	Specifies the port on which the database server will be addressable.	`SERVERPORT`	`1984`	`-p9998`
`-s<num>`	Specifies the port that will be used to stop the HTTP server.	`STOPPORT` or`pom.xml`	`8985`	
`-S`	Starts the server as service (i.e., in the background). Use YAJSW, or start BaseX as an ordinary background process, to get more options.			
`-U<name>`	Specifies a user name, which will be used by the HTTP services for opening a new session.	`USER`		`-Uadmin`
`-z`	Does not generate any log files.	`LOG`		

GUI

Launch the GUI

```
$ basexgui [file]
```

One or more XML and XQuery files can be passed on as parameters. If an XML file is specified, a database instance is created from this file, or an existing database is opened. XQuery files are opened in the XQuery editor.

Changelog

Version 9.0

- Added: BaseXHTTP, command-line option `-c`.
- Updated: BaseXHTTP, command-line option `-c`, additionally accepts valid URLs and file references.

Version 8.2

- Removed: Event ports, `-e`.

Version 8.1

- Added: Bind input strings to the query context with `-I`.

Version 8.0

- Removed: Command-line option `-L` (results will now be automatically separated by newlines).

Version 7.9

- Added: Runs tests in file or directory with `-t`.
- Removed: interactive server mode.

Version 7.8

- Added: Specify if a query will be executed or parsed only with `-R`.

Version 7.7

- Added: Bind host to the BaseX Server with `-n`.

Version 7.5

- Added: detection of Command Scripts.
- Removed: HTTP server flags `-R`, `-W`, and `-X`.

Version 7.3

- Updated: all options are now evaluated in the given order.
- Updated: Create main-memory representations for specified sources with `-i`.
- Updated: Options `-C`/`-c` and `-q`/`[input]` merged.
- Updated: Option `-L` also separates serialized items with newlines (instead of spaces).

Version 7.2

- Added: RESTXQ Service

Version 7.1.1

- Added: Options `-C` and `-L` in standalone and client mode.

Version 7.1

- Updated: Multiple query files and `-c`/`-i`/`-q` flags can be specified.

Chapter 5. Start Scripts

Read this entry online in the BaseX Wiki.

The following scripts, which are referenced in the Startup and Command-Line Options articles, are also included in the Windows and ZIP distributions.

- We recommend you to manually add the `bin` directory of your BaseX directory to the PATH variable of your environment.
- You can copy the start scripts to another location in your file system. After that, you should edit the scripts and assign the BaseX directory to the `MAIN` variable.
- The Windows installer automatically adds the project's `bin` directory to your path environment.
- If you work with Maven, you can directly run the scripts in the basex-core/etc and basex-api/etc sub-directories of the project.

If BaseX terminates with an `Out of Memory` error, you can assign more RAM via the `-Xmx` flag (see below). The chosen value ensures that BaseX will also run on 32 bit JVMs.

Main Package

The following scripts can be used to launch the standalone version of BaseX. Please replace the class name in `org.basex.BaseX` with either `BaseXClient`, `BaseXServer`, or `BaseXGUI` to run the client, server or GUI version.

Windows: basex.bat

```
@echo off
setLocal EnableDelayedExpansion

REM Path to core and library classes
set MAIN=%~dp0/..
set CP=%MAIN%/BaseX.jar;%MAIN%/lib/*;%MAIN%/lib/custom/*

REM Options for virtual machine
set BASEX_JVM=-Xmx1200m %BASEX_JVM%

REM Run code
java -cp "%CP%" %BASEX_JVM% org.basex.BaseX %*
```

Linux/Mac: basex

```
#!/usr/bin/env bash

# Path to this script
FILE="${BASH_SOURCE[0]}"
while [ -h "$FILE" ] ; do
  SRC="$(readlink "$FILE")"
  FILE="$( cd -P "$(dirname "$FILE")" && \
           cd -P "$(dirname "$SRC")" && pwd )/$(basename "$SRC")"
done
MAIN="$( cd -P "$(dirname "$FILE")/.." && pwd )"

# Core and library classes
CP=$MAIN/BaseX.jar:$MAIN/lib/*:$MAIN/lib/custom/*:$CLASSPATH

# Options for virtual machine (can be extended by global options)
```

```
BASEX_JVM="-Xmx2g $BASEX_JVM"

# Run code
java -cp "$CP" $BASEX_JVM org.basex.BaseX "$@"
```

HTTP Server

The scripts for starting the HTTP server, which gives access to the REST, RESTXQ and WebDAV services, can be found below.

Windows: basexhttp.bat

```
@echo off
setLocal EnableDelayedExpansion

REM Path to core and library classes
set MAIN=%~dp0/..
set CP=%MAIN%/BaseX.jar;%MAIN%/lib/*;%MAIN%/lib/custom/*

REM Options for virtual machine
set BASEX_JVM=-Xmx1200m %BASEX_JVM%

REM Run code
java -cp "%CP%" %BASEX_JVM% org.basex.BaseXHTTP %*
```

Linux/Mac: basexhttp

```
#!/usr/bin/env bash

# Path to this script
FILE="${BASH_SOURCE[0]}"
while [ -h "$FILE" ] ; do
  SRC="$(readlink "$FILE")"
  FILE="$( cd -P "$(dirname "$FILE")" && \
           cd -P "$(dirname "$SRC")" && pwd )/$(basename "$SRC")"
done
MAIN="$( cd -P "$(dirname "$FILE")/.." && pwd )"

# API, core, and library classes
CP=$MAIN/BaseX.jar:$MAIN/lib/*:$MAIN/lib/custom/*:$CLASSPATH

# Options for virtual machine (can be extended by global options)
BASEX_JVM="-Xmx2g $BASEX_JVM"

# Run code
java -cp "$CP" $BASEX_JVM org.basex.BaseXHTTP "$@"
```

Changelog

Version 7.5

- Updated: Static dependencies removed from Windows batch scripts.

Version 7.2

- Updated: The `BaseXHTTP` start class moved from `org.basex.api` to `org.basex`.

Version 7.0

- Updated: The `basexjaxrx` scripts have been replaced with the `basexhttp` scripts.

Part II. User Interfaces

Chapter 6. Graphical User Interface

Read this entry online in the BaseX Wiki.

This page is part of the Getting Started Section.

Startup

First of all, launch a GUI instance of BaseX. Depending on your operating system, double click on the **BaseX GUI** start icon or run the `basexgui` script. Beside that, some more startup options are available.

Select *Database* → *New* and browse to an XML document of your choice. As an example, you can start with the `factbook.xml` document, which contains statistical information on the worlds' countries. It is included in our full releases (in the `etc` directory) and can also be downloaded (1.3 MB). If you type nothing in the input field, an empty database will be created. Next, choose the *OK* button, and the database will be created.

If no XML document is available, the Text Editor can also be used to create an initial XML document. After saving the entered XML document to disk, it can be supplied as database input in the above dialog.

Input Bar

On top of the main window, you can find an input bar. The attached dropdown menu provides three modes: **Find**, **XQuery** and **Command**:



The upcoming example queries can all be used with an instance of the `factbook` database:

Find

In the **Find** mode, the input bar can be used to find single elements and texts in the currently opened database. The following syntax is supported:

Query	Description
`city`	Find elements named `city`, and texts containing this token.
`=India`	Find texts matching the exact string `India`.
`~Cing`	Find texts equal or similar to the token `Cingdom`.
`id`	Find attributes named `id` and attribute values containing this token.
`@=f0_119`	Find attribute values matching the exact string `f0_119`.
`"European Chinese"`	Find texts containing the phrase `"European Chinese"`.
`//city`	Leading slash: Interpret the input as XPath expression (see below).

XQuery

In the **XQuery** mode, XPath and XQuery expressions can be entered in the input bar.

To evaluate the following example queries: enter them in the input bar, and press ENTER or click on the START button:

Query	Description
`//country`	Return all `country` elements.
`//country[name = "Switzerland"]`	Return the `country` element of "Switzerland".
`for $city in //citywhere $city/population > 1000000order by $city ascendingreturn $city/name`	Return the names of all cities with a population larger than one million and order the results by the name of the city.

Command

In the **Command** mode, BaseX Commands can be entered and executed. Just try the following examples:

- `INFO` : Returns system information.
- `CREATE DB TEST` : Creates an empty database named "TEST".
- `LIST` : Lists all databases.

Text Editor

The built-in text editor is a helpful tool for writing XQuery code that spans multiple lines or files. It can also be used to edit XML documents, Command Scripts, and any other textual files:

- XQuery and XML files will be **parsed** with each key click, and **errors** will be highlighted.
- XQuery and command scripts can be **executed** by clicking on the green triangle.
- **Syntax highlighting** is available for XQuery, XML, JSON and JavaScript files.

Numerous keyboard shortcuts are available to speed up editing and debugging.

Project View

The Project View is attached to the editor panel. It displays all files of the current project directory in a tree structure. Files can be renamed and deleted by right-clicking on the files. The project directory can be changed as well; the most recent directories will be kept in the history.

All XQuery files in the project directory will be parsed in the background. Buggy XQuery modules, and files importing these modules, will be marked red. With the text fields on top, you can interactively search for file names and contents.

Realtime Options

Via the *Options* menu, you can change how queries are executed and visualized:

- **Realtime Execution** : If realtime execution is enabled, your searches and queries will be executed with each key click and the results will be instantly shown.
- **Realtime Filtering** : If enabled, all visualizations will be limited to the actual results in realtime. If this feature is disabled, the query results are highlighted in the visualizations and can be explicitly filtered with the 'Filter' button.

Visualizations

The BaseX GUI offers various visualizations, which help you to explore your XML data instances from different perspectives:

Text View **Result**

Displays query results and other textual output. Query results can be saved in a file.



Map View **Map**

Displays all data in a TreeMap. All nodes of the XML document are represented as rectangles, filling the complete area. You can choose different layout algorithms in the Menu *Options* → *Map Layout*.



Tree View **Tree**

Displays all XML nodes in a top down tree with edges and nodes. You can change some settings of the Tree in the Menu *Options* → *Tree Options*.



Folder View **Folder**

Displays all nodes in an Explorer-like folder view. Nodes can be expanded or closed by clicking on the arrows.



Scatterplot View **Plot**

Displays all nodes in a scatterplot, which is particularly helpful if you want to explore analyze your data. Three drop down menus allow custom axis assignments.



The Table View **Table**

Comes in handy if your data is highly regular. It displays all nodes in a table with rows and columns. Different assignments can be chosen by clicking on the arrow in the right upper corner.



Explorer View **Explorer**

Can be used to explore the contents of your database via drop-down menus, search fields and double sliders.



Info View **Info**

Helpful for analyzing the query plans of your XQuery expressions. It also displays information on the compilation and evaluation of queries.

Look and Feels

By default, the Look and Feel of your operating system will be used in the GUI. In the *Preferences* dialog, you can choose among some more window themes.

The JTattoo library offers some more look and feels. If you download and copy the JTattoo jar file into the `lib` directory provided by the ZIP and EXE distribution of BaseX, 13 additional looks and feels will get available.



Default Look & Feel



HiFi Look & Feel

Changelog

Version 8.4

- Added: highlighting of erroneous XQuery modules in the project view.

Version 8.0

- Updated: support for dark look and feels; support for JTatto library

Chapter 7. Shortcuts

Read this entry online in the BaseX Wiki.

This article is about the GUI of BaseX. It gives you an overview of the most important hotkeys available in the visual frontend.

Editor

Code Completions

The GUI editor provides various code completions, which simplify the authoring of complex XQuery applications. Opening elements, comments, quotes or brackets will automatically be closed, and new lines will automatically be indented.

If some characters have been entered, and if the shortcut for code completions is pressed (Ctrl Space), a popup menu will appear and provides some code templates. If only one completion is possible, it will automatically be inserted.

Editor Shortcuts

The text editor can be used to create, edit, save and execute XQuery expressions, XML documents and any other textual files.

Custom Editing

Description	Win/Linux	Mac
Performs Code Completions	Ctrl Space	Ctrl Space
Sort lines	Ctrl U	# U
Format code (experimental)	Ctrl Shift F	# Shift F
(Un)comment selection/line	Ctrl K	# K
Delete complete line	Ctrl Shift D	# Shift D
Lower case	Ctrl Shift L	# Shift L
Upper case	Ctrl Shift U	# Shift U
Title case	Ctrl Shift T	# Shift T

Finding

Description	Win/Linux	Mac
Find files (or currently highlighted text)	Ctrl H	# Shift H
Jump to next error in project	Ctrl . (period)	# . (period)
Jump to currently edited file	Ctrl J	# J
Go to line	Ctrl L	# L
Find and replace text	Ctrl F	# F
Find next instance of text	F3Ctrl G	# F3# G
Find previous instance of text	Shift F3Ctrl Shift G	# Shift F3# Shift G

Standard Editing

Description	Win/Linux	Mac

Undo recent changes	Ctrl Z	# Z
Redo recent changes	Ctrl Y	# Shift Z
Cut selection	Ctrl XCtrl Delete	# X
Copy selection to clipboard	Ctrl CCtrl Insert	# C
Paste from clipboard	Ctrl VShift Insert	# V
Select All	Ctrl A	# A
Delete character left of cursor	Backspace	Backspace
Delete character right of cursor	Delete	Delete (fn Backspace)
Delete word left of cursor	Ctrl Backspace	Alt Backspace
Delete word right of cursor	Ctrl Delete	Alt Delete
Delete text left of cursor	Ctrl Shift Backspace	# Backspace
Delete text right of cursor	Ctrl Shift Delete	# Delete

Navigation

Description	**Win/Linux**	**Mac**
Move one character to the left/right	←/→	←/→
Move one word to the left/right	Ctrl ←/→	Alt ←/→
Move to beginning/end of line	Home/End	# ←/→
Move one line up/down	↑/↓	↑/↓
Move one screen-full up/down	Page ↑/↓	Page ↑/↓ (fn ↑/↓)
Move to top/bottom	Ctrl Home/End	#/# (# ↑/↓)
Scroll one line up/down	Ctrl ↑/↓	Alt ↑/↓

GUI

Global Shortcuts

The following shortcuts are available from most GUI components:

Description	**Win/Linux**	**Mac**
Focus input bar	F6	# F6
Focus editor	F12	# F12
Jump to next/previous panel	Ctrl (Shift) Tab	Ctrl (Shift) Tab
Increase/Decrease font size	Ctrl +/-	# +/-
Reset font size	Ctrl 0	# 0

Description	**Win/Linux**	**Mac**
Browse back/forward	Alt ←/#Backspace	# ←/→
Browse one level up	Alt ↑	# ↑
Browse to the root node	Alt Home	# Home

Menu Shortcuts

The following commands and options are also linked from the main menu:

Database

Description	**Win/Linux**	**Mac**
Create new database	Ctrl N	# N

Open/manage existing databases	Ctrl M	# M
View/edit database properties	Ctrl D	# D
Close opened database	Ctrl Shift W	# Shift W
Exit application	Ctrl Q	# Q

Editor

Description	Win/Linux	Mac
Create new tab	Ctrl T	# T
Open existing file	Ctrl O	# O
Save file	Ctrl S	# S
Save copy of file	Ctrl Shift S	# Shift S
Close tab	Ctrl W, Ctrl F4	# W, # F4

View

Description	Win/Linux	Mac
Toggle query/text editor	Ctrl E	# E
Toggle project structure	Ctrl P	# P
Toggle result view	Ctrl R	# R
Toggle query info view	Ctrl I	# I

Options

Description	Win/Linux	Mac
Open preference dialog	Ctrl Shift P	# , (comma)

Visualization

Description	Win/Linux	Mac
Toggle map view	Ctrl 1	# 1
Toggle tree view	Ctrl 2	# 2
Toggle folder view	Ctrl 3	# 3
Toggle plot view	Ctrl 4	# 4
Toggle table view	Ctrl 5	# 5
Toggle explorer view	Ctrl 6	# 6

Help

Description	Win/Linux	Mac
Show Help	F1	F1

Additionally, the names of HTML entities will be converted to their Unicode representation (as an example, `Auml` will be translated to).

Changelog

Version 8.4

- Added: Lower case (Ctrl Shift L), Upper case (Ctrl Shift U), Title case (Ctrl Shift T)

Version 8.0

- Added: New code completions, popup menu

Version 7.8.2

- Added: Sort lines (Ctrl U)

Version 7.8

- Added: Code Completions, Project (Ctrl P), Find Files (Ctrl Shift F)

Version 7.5

- Added: go to line (Ctrl F)

Version 7.3

- Added: delete complete line (Ctrl Shift D), jump to highlighted error (Ctrl .)

Chapter 8. Database Server

Read this entry online in the BaseX Wiki.

This step by step tutorial is part of the Getting Started Guide. It shows you how to run BaseX in client-server mode from a terminal. You can copy and paste all commands to get them running on your machine. After you finished this tutorial, you will be familiar with the basic administration of BaseX. Visit the commands section for a complete list of database commands.

Startup

First, launch a **Server** and **Client** instance of BaseX: double click on the **BaseX Server/Client** icons, or run the `basexserver` and `basexclient` scripts. Follow this link for more information (or check out the additional command-line options).

Working on Command-Line

The BaseX command-line client provides similar features to the Standalone Mode. The major difference is that all commands will be executed by the BaseX server instance. As a consequence, paths/URIs to resources need to be resolvable by the server (file contents will not be transfered to the server).

Username and password can also be specified as command-line option. To evaluate commands without entering the console mode, you can use the `-c` option on the command line:

```
basexclient -V -Uadmin -Padmin -c "CREATE DB input <example/>; XQUERY /"

Database 'input' created in 13.85 ms.
<example/>
Query:
/

Parsing: 0.18 ms
Compiling: 0.04 ms
Evaluating: 0.12 ms
Printing: 0.07 ms
Total Time: 0.41 ms

Hit(s): 1 Item
Updated: 0 Items
Printed: 10 Bytes
Read Locking: local [input]
Write Locking: none

Query "user" executed in 0.41 ms.
```

Chapter 9. Standalone Mode

Read this entry online in the BaseX Wiki.

This page is part of the Getting Started Section. BaseX offers a standalone console mode from which all database commands can be executed. The article on the Database Server provides numerous examples for running commands in the console mode (note that the GUI does *not* interact with the client/server architecture).

Startup

First of all, please launch a **standalone** version of BaseX: double click on the **BaseX** icon, or run the `basex` script. Follow this link for more information (or check out the additional command-line options).

Create a Database

- To create a database you need an XML document, e.g. factbook.xml.
- Save this document to your working directory.
- Type in the following command to create and open the database:

```
> CREATE DB factbook factbook.xml
```

factbook is the name of the database

factbook.xml is the initial input of the database

Where is the database stored?

By default, databases are stored in the `basex/data` directory, which is located in your home folder. Depending on your Configuration, the location of your home folder varies. For example, on a Mac it's `/Users/John`, if your name is John.

Execute a Query

The XQUERY command lets you run a query.

- For example, this query returns all country nodes in the currently opened database.

```
> XQUERY //country
```

- You can also run queries in files:

```
> RUN /Users/John/query.xq
```

Database Commands

- The following command lists all databases than can be opened by the currently logged in user:

```
> LIST
```

- To open an existing database, execute the following:

```
> OPEN factbook
```

- To get information on the currently opened database, type:

```
> INFO
```

- You can also address a database within your query with the db:open function:

```
> XQUERY db:open("factbook")//country
```

- To close the current database, please type:

```
> CLOSE
```

- Use the DROP DB command to delete a database:

```
> DROP DB factbook
```

Multiple Resources

One database can contain not only a single, but millions of documents. All documents can have a different structure.

With the following commands, you can create an empty database and add two documents. It is also possible to address resources via URLs:

```
> CREATE DB store > ADD factbook.xml > ADDhttp://files.basex.org/xml/xmark.xml
```

- Deleting a document from a database is easy:

```
> DELETE factbook.xml
```

Make sure that the database, which contains the addressed document, is currently opened.

Backup and Restore

- To backup your database, type:

```
> CREATE BACKUP factbook
```

- To restore your database, type:

```
> RESTORE factbook
```

The backup file is stored in the database directory. The contains the name of the database and a timestamp: `[db-name]-[timestamp].zip`. If a database is restored, and if several backups exist, the backup with the newest timestamp is taken.

Chapter 10. Web Application

Read this entry online in the BaseX Wiki.

This page is part of the Getting Started Section. It describes how BaseX can be used to both provide simple APIs and build complex web applications. The following three HTTP services are available:

- REST offers a straightforward RESTful API for accessing database resources via URLs,
- RESTXQ allows you to write more complex APIs and full web applications with XQuery, and
- WebDAV gives access to databases via the file system.

This article describes different ways of deploying and configuring these services. The services can be deployed as follows:

- as standalone application, by running the BaseX HTTP Server,
- as web servlet in a Servlet Container, and
- as web servlet, using Maven.

Authentication:

- If a user is defined in the `web.xml` file via the key `org.basex.user`, no password must be specified.
- If the `admin` user is specified for an API, all features will be available without restriction.
- Predefined authentication methods and default users cannot be overwritten by client.

Servlet Container

In order to deploy BaseX HTTP Services in a servlet container, you can download the WAR distribution of BaseX from the download site, or compile it by calling `mvn compile war:war` in the `basex-api` directory. The WAR file can then be deployed following the instructions of the corresponding servlet container (jetty, tomcat, etc.).

You can configure the port, context path, etc. by following the instructions of the corresponding servlet container. This is needed if you want to replace the default URL path (e.g. http://localhost:8080/rest) with a custom one (e.g. http://localhost:8984/basex/rest).

If you use Jetty (which is the default HTTP server of BaseX), the server configuration is available via the `jetty.xml` file, which is stored in the `WEB-INF` directory next to the `web.xml`. For detailed configuration refer to the Jetty Documentation.

To run on Apache Tomcat, start the Tomcat server and add any `*.war` distribution to deploy via the Tomcat web interface. By default, the interface is accessible via http://localhost:8080/manager/html/.

Configuration

All database options can be specified in the `web.xml` file. They need to be defined as context parameters and prefixed with `org.basex.`. The most important options for the web application context are as follows:

Option	Default	Description
`USER`	`admin`	If a user is specified, no credentials must be passed on by the client.
`HTTPLOCAL`	`false`	Operation mode. By default, a database server instance will be started, as soon as the first HTTP service is called. The database server can be disabled by setting this flag to `true`.

RESTXQPATH	.	Relative or absolute directory referencing the RESTXQ modules. By default, the option points to the standard web application directory.
RESTPATH	.	Relative or absolute directory referencing queries and command-scripts that can be invoked via the run operation of REST. By default, the option points to the standard web application directory.
AUTHMETHOD	Basic	The default authentication method proposed by the server. The available methods are Basic and Digest.

Path options may contain an absolute or relative path. If a relative path is specified, its root will be the servlet (webapp) path:

```
<context-param>
  <param-name>org.basex.dbpath</param-name>
  <!-- will be rewritten to ..../webapp/WEB-INF/data -->
  <param-value>WEB-INF/data</param-value>
</context-param>
<context-param>
  <param-name>org.basex.repopath</param-name>
  <!-- will be kept as is -->
  <param-value>f:/basex/repository</param-value>
</context-param>
```

Context parameters can be requested from XQuery via proc:property-names and proc:property. How to set these options is specific to the servlet container. For example, in Jetty it can be done by overriding the web.xml file. Another option is to directly edit the WEB-INF/web.xml file in the WAR archive (WAR files are simple ZIP files). Refer to the sample web.xml of the basex-api package.

Different credentials can be assigned to the REST and WebDAV service by specifying local init parameters. In the following example, an alternative user is specified for the REST service:

```
<servlet>
  <servlet-name>REST</servlet-name>
  <servlet-class>org.basex.http.rest.RESTServlet</servlet-class>
  <init-param>
    <param-name>org.basex.user</param-name>
    <param-value>rest-user</param-value>
  </init-param>
</servlet>
```

Available Services

To enable or disable one of the provided services, the corresponding servlet entry in the web.xml file needs to be removed/commented. The default URL paths are listed in the following table:

Service	URL	Usage
Default web server	http://[host]:[port]/[servlet_context_path]/static	Access your standard web files (e.g. HTML, JavaScript or CSS).
RESTXQ	http://[host]:[port]/[servlet_context_path]	Create XQuery web services and applications.
REST	http://[host]:[port]/[servlet_context_path]/rest	Access XML database and its resources.
WebDAV	http://[host]:[port]/[servlet_context_path]/webdav orwebdav://[host]:[port]/	Access databases via the filesystem.

`[servlet_context_path]/webdav` (depending on client)

Maven

Check out the BaseX sources via Eclipse or Git. Execute `mvn install` in the main project directory and then `mvn install jetty:run` in the `basex-api` sub-directory. This will start a Jetty instance in which the servlets will be deployed.

Configuration

The same options as in the case of deployment apply in a servlet container. In this case, however, there is no WAR archive. Instead, Jetty looks up all files in the directory `basex-api/src/main/webapp`. Jetty and servlet options can be configured in the `jetty.xml` and `web.xml` files as described above in the Servlet Container Configuration. The Jetty stop port can be changed in the Maven Jetty Plugin sesion in the `pom.xml` file.

User Management

By default, RESTXQ uses the admin user, whereas the REST and WebDAV services require client-side authentication. A default user can be specified via command-line arguments. In the `web.xml` file, both a global and a servlet-specific user can be added (see above).

If the HTTP server is started with no pre-defined user, the credentials must be passed on by the client via Basic Authentication or Digest Authentication (depending on the server setting).

With cURL, internet browsers, and other tools, you can specify basic authentication credentials within the request string as plain text, using the format `USER:PASSWORD@URL`. An example:

```
http://admin:admin@localhost:8984/
```

Users are specified in a `users.xml` file, which is stored in the database directory (see User Management for more information).

Changelog

Version 8.6

- Updated: Authentication readded to RESTXQ.
- Updated: No password must be specified in the `web.xml` file anymore.
- Updated: Server-side user and authentication method is now enforced (cannot be overwritten by client).

Version 8.0

- Added: digest authentication
- Updated: user management
- Updated: default user/password disabled in web.xml

Version 7.7

- Added: service-specific permissions

Version 7.5

- Added: `jetty.xml`: configuration for Jetty Server
- Updated: `server` replaced with `httplocal` mode

Version 7.3

- Updated: `client` mode replaced with `server` mode

Version 7.2

- Web Application concept revised

Chapter 11. DBA

Read this entry online in the BaseX Wiki.

This page is part of the Getting Started Section.

The full distributions of BaseX are equipped with a powerful browser-based database administration interface, the **DBA**. It allows you to create and administrate databases, evaluate queries in realtime, view log files, manage users, etc. The server-side code is completely written in XQuery and RESTXQ.

These were our design goals:

- The code base is supposed to help and motivate you developing your own RESTXQ web applications.
- The XQuery DBA code consumes only around 100 KB. It uses simple backward-compatible Javascript code. The interface is functional, but limited in terms of flashiness and interactivity.
- We tried to make the DBA features as self-explanatory as possible. All functionalities are also available via Commands, XQuery Modules or the Java GUI.
- The `dba` sub-directory can simply be copied and moved to any other place. All URL paths point to the same directory; it should be straightforward to adjust the RESTXQ path.

If you put DBA online along with your web page, please ensure at the very least that:

- you have changed the password of your BaseX `admin` user, and
- the BaseX process has not been started with admin privileges.

Startup

- Download the **ZIP Archive** or the **Windows Installer** from the download page
- Start the BaseX HTTP Server
- Open a browser and visit the URL `http://localhost:8984/dba`

First Steps

On the welcome page, you need to authenticate yourself by entering the name and password of an admin user. The default user is `admin`/`admin`; after the first login, the password should be changed via the Users panel.

The main page of the DBA interface contains a list of all databases on the left. On the right, the global and local options are listed, along with some system information.

With the "Create…" button, a new database can be created. Existing database can be viewed, optimized, and dropped.



DBA Main Page

Editor

In the editor panel, you can execute XQuery expressions. If evaluation takes too long, or if it consumes too much memory, it will be interrupted. You need to choose if your query is updating. Inside the editor area, you can press Ctrl-Enter to execute the query.

You can press Shift-Ctrl-Enter to run your XQuery expression as updating query (or non-updating, if "Updating" is choosen in the dropdown menu). The realtime mode was removed.

Changelog

Version 8.6

- Updated: Always accessible, even if job queue is full
- Removed: Remote connections (to allow for better optimizations and less locking)

Version 8.4

- Added: Editor: Key combination 'Shift-Ctrl-Enter', realtime mode removed.

Introduced with Version 8.0.

Part III. General Info

Chapter 12. Databases

Read this entry online in the BaseX Wiki.

This page is part of the Getting Started Section.

In BaseX, a *database* is a pretty light-weight concept. It contains an arbitrary number of **resources**, which are addressed by a unique database path. There is no explicit layer for collections. Instead, collections are implicitly created and deleted once you add and remove resources to a database. Resources can either be **XML documents** or **raw files** (binaries). Some information on binary data can be found on an extra page.

Create Databases

New databases can be created via commands, via XQuery, in the GUI, or with any of our APIs. If initial input is specified with create, some time can be saved, as it will be added to the database in a bulk operation:

- Console : `CREATE DB db /path/to/resources` will add initial documents to a database
- GUI : Go to *Database* → *New*, press *Browse* to choose an initial file or directory, and press *OK*

Database must follow the valid names constraints. Various parsers can be chosen to influence the database creation, or to convert different formats to XML.

Note: A main-memory database will be created if the `MAINMEM` option is enabled (see below for more).

Access Resources

Stored resources and external documents can be accessed in different ways:

XML Documents

Various XQuery functions exist to access XML documents in databases:

Function	Example	Description
db:open	`db:open("db", "path/to/docs")`	Returns all documents that are found in the database `db` at the (optional) path `path/to/docs`.
fn:collection	`collection("db/path/to/docs")`	Returns all documents at the location `path/to/docs` in the database `db`.If no path is specified after the database, all documents in the database will be returned.If no argument is specified, all documents of the database will be returned that has been opened in the global context.
fn:doc	`doc("db/path/to/doc.xml")`	Returns the document at the location `path/to/docs` in the database `db`.An error is raised if the specified yields zero or more than one document.

You can access multiple databases in a single query:

```
for $i in 1 to 100
return db:open('books' || $i)//book/title
```

If the DEFAULTDB option is turned on, the path argument of the `fn:doc` or `fn:collection` function will first be resolved against the globally opened database.

Two more functions are available for retrieving information on database nodes:

Function	Example	Description
db:name	`db:name($node)`	Returns the name of the database in which the specified `$node` is stored.
db:path	`db:path($node)`	Returns the path of the database document in which the specified `$node` is stored.

The `fn:document-uri` and `fn:base-uri` functions return URIs that can also be reused as arguments for the `fn:doc` and `fn:collection` functions. As a result, the following example query always returns `true`:

```
every $c in collection('anyDB')
satisfies doc-available(document-uri($c))
```

If the argument of `fn:doc` or `fn:collection` does not start with a valid database name, or if the addressed database does not exist, the string is interpreted as URI reference, and the documents found at this location will be returned. Examples:

- `doc("http://web.de")` : retrieves the addressed URI and returns it as a main-memory document node.
- `doc("myfile.xml")` : retrieves the given file from the file system and returns it as a main-memory document node. Note that updates to main-memory nodes are not automatically written back to disk unless the `WRITEBACK` option is set.
- `collection("/path/to/docs")` : returns a main-memory collection with all XML documents found at the addressed file path.

Raw Files

The `RETRIEVE` command and the `db:retrieve` function can be used to return files in their native byte representation.

If the API you use does not support binary output (this is e.g. the case for various Client language bindings), you need to convert your binary data to its string representation before returning it to the client:

```
string(db:retrieve('multimedia', 'sample.avi'))
```

HTTP Services

- With REST and WebDAV, all database resources can be requested in a uniform way, no matter if they are well-formed XML documents or binary files.

Update Resources

Once you have created a database, additional commands exist to modify its contents:

- XML documents can be added with the `ADD` command.
- Raw files are added with `STORE`.
- Existing resources can be replaced with the `REPLACE` command.
- Resources can be deleted via `DELETE`.

The AUTOFLUSH option can be turned off before *bulk operations* (i.e. before a large number of new resources is added to the database).

The ADDCACHE option will first cache the input before adding it to the database. This is helpful when the input documents to be added are expected to eat up too much main memory.

The following commands create an empty database, add two resources, explicitly flush data structures to disk, and finally delete all inserted data:

```
CREATE DB example
SET AUTOFLUSH false
ADD example.xml
SET ADDCACHE true
ADD /path/to/xml/documents
STORE TO images/ 123.jpg
FLUSH
DELETE /
```

You may also use the BaseX-specific XQuery Database Functions to create, add, replace, and delete XML documents:

```
let $root := "/path/to/xml/documents/"
for $file in file:list($root)
return db:add("database", $root || $file)
```

Last but not least, XML documents can also be added via the GUI and the *Database* menu.

Export Data

All resources stored in a database can be *exported*, i.e., written back to disk. This can be done in several ways:

- Commands: `EXPORT` writes all resources to the specified target directory
- GUI: Go to *Database* → *Export*, choose the target directory and press *OK*
- WebDAV: Locate the database directory (or a sub-directory of it) and copy all contents to another location

Main-Memory Database Instances

- In the standalone context, a main-memory database can be created (using `CREATE DB`), which can then be accessed by subsequent commands.
- If a BaseX server instance is started, and if a database is created in its context (using `CREATE DB`), other BaseX client instances can access (and update) this database (using OPEN, db:open, etc.) as long as no other database is opened/created by the server.
- You can force an ordinary database to being copied to memory by using `db:open('some-db') update {}`

Note: If you address a URI with `fn:doc` or `fn:collection` for which no database exists, the resulting internal representation is identical to those of main-memory database instances (no matter which value is set for `MAINMEM`).

Changelog

Version 8.4

- Updated: Raw Files: Items of binary type can be output without specifying the obsolete `raw` serialization method.

Version 7.2.1

- Updated: `fn:document-uri` and `fn:base-uri` now return strings that can be reused with `fn:doc` or `fn:collection` to reopen the original document.

Chapter 13. Binary Data

Read this entry online in the BaseX Wiki.

This page is linked from the Database page.

The BaseX store also provides support for *raw files* (binary data). A database may contain both XML documents and raw files. XML and binary data is handled in a uniform way: a unique database path serves as key, and the contents can be retrieved via database commands, XQuery, or the various APIs.

Storage

XML documents are stored in a proprietary format to speed up XPath axis traversals and update operations, and raw data is stored in its original format in a dedicated sub-directory (called `raw`). Several reasons exist why we did not extend our existing storage to binary data:

- **Good Performance** : the file system generally performs very well when it comes to the retrieval and update of binary files.
- **Key/Value Stores** : we do not want to compete with existing key/value database solutions. Again, this is not what we are after.
- **Our Focus** : our main focus is the efficient storage of hierarchical data structures and file formats such as XML or (more and more) JSON. The efficient storage of arbitrary binary resources would introduce many new challenges that would distract us from more pressing tasks.

For some use cases, the chosen database design may bring along certain limitations:

- **Performance Limits** : most file system are not capable of handling thousands or millions of binary resources in a single directory in an efficient way. The same problem happens if you have a large number of XML documents that need to imported in or exported from a BaseX database. The general solution to avoid this bottleneck is to distribute the relevant binaries in additional sub-directories.
- **Keys** : if you want to use arbitrary keys for XML and binary resources, which are not supported by the underlying file system, you may either add an XML document in your database that contains all key/path mappings.

In the latter case, a key/value store might be the better option anyway.

Usage

More information on how to store, retrieve, update and export binary data is found in the general Database documentation.

Chapter 14. Parsers

Read this entry online in the BaseX Wiki.

This article is part of the Getting Started Section. It presents the available parsers that can be used to import various data sources in BaseX databases. Please visit the Serialization article if you want to know how to export data.

XML Parsers

BaseX provides two alternatives for parsing XML:

- By default, Java's SAXParser is used to parse XML documents.
- The internal, built-in XML parser is more fault-tolerant than Java's XML parser. It supports standard HTML entities out of the box, and it is faster than the default parser, in particular if small documents are to be parsed. However, the internal parser does not support the full range of DTD features and cannot resolve catalogs.

GUI

Go to Menu *Database* → *New*, then choose the *Parsing* tab and (de)activate *Use internal XML parser*. The parsing of DTDs can be turned on/off by selecting the checkbox below.

Command Line

To turn the internal XML parser and DTD parsing on/off, modify the `INTPARSE` and `DTD` options:

```
SET INTPARSE true
SET DTD true
```

XQuery

The db:add and db:replace functions can also be used to add new XML documents to the database. The following example query uses the internal XML parser and adds all files to the database `DB` that are found in the directory `2Bimported`:

```

for $file in file:list("2Bimported")
return db:add('DB', $file, '', map { 'intparse': true() })
```

HTML Parser

With TagSoup, HTML can be imported in BaseX without any problems. TagSoup ensures that only well-formed HTML arrives at the XML parser (correct opening and closing tags, etc.). Hence, if TagSoup is not available on a system, there will be a lot of cases where importing HTML fails, no matter whether you use the GUI or the standalone mode.

Installation

Downloads

TagSoup is already included in the full BaseX distributions (`BaseX.zip`, `BaseX.exe`, etc.). It can also be manually downloaded and embedded on the appropriate platforms.

Maven

An easy way to add TagSoup to your project is to follow this steps:

1. visit MVN TagSoup Repository

2. click on the version you want

3. on the first tab, you can see an XML snippet like this:

```
<dependency>
  <groupId>org.ccil.cowan.tagsoup</groupId>
  <artifactId>tagsoup</artifactId>
  <version>1.2.1</version>
</dependency>
```

4. copy that in your own maven project's `pom.xml` file into the `<dependencies>` element.

5. don't forget to run `mvn jetty:run` again

Debian

With Debian, TagSoup will be automatically detected and included after it has been installed via:

```
apt-get install libtagsoup-java
```

Options

TagSoup offers a variety of options to customize the HTML conversion. For the complete list please visit the TagSoup website. BaseX supports most of these options with a few exceptions:

- **encoding** : BaseX tries to guess the input encoding, but this can be overwritten by this option.
- **files** : not supported as input documents are piped directly to the XML parser.
- **method** : set to 'xml' as default. If this is set to 'html' ending tags may be missing for instance.
- **version** : dismissed, as TagSoup always falls back to 'version 1.0', no matter what the input is.
- **standalone** : deactivated.
- **pyx** , **pyxin**: not supported as the XML parser can't handle this kind of input.
- **output-encoding** : not supported, BaseX already takes care of that.
- **reuse** , **help**: not supported.

GUI

Go to Menu *Database* → *New* and select "HTML" in the input format combo box. There's an info in the "Parsing" tab about whether TagSoup is available or not. The same applies to the "Resources" tab in the "Database Properties" dialog.

These two dialogs come with an input field 'Parameters' where TagSoup options can be entered.

Command Line

Turn on the HTML Parser before parsing documents, and set a file filter:

```
SET PARSER html
SET HTMLPARSER
method=xml,nons=true,nocdata=true,nodefaults=true,nobogons=true,nocolons=true,ignorable=true
SET CREATEFILTER *.html
```

XQuery

The HTML Module provides a function for converting HTML to XML documents.

Documents can also be converted by specifying the parser and additional options as function arguments:

```
fetch:xml("index.html", map {
  'parser': 'html',
  'htmlparser': map { 'html': false(), 'nodefaults': true() }
})
```

JSON Parser

BaseX can also import JSON documents. The resulting format is described in the documentation for the XQuery JSON Module:

GUI

Go to Menu *Database* → *New* and select "JSON" in the input format combo box. You can set the following options for parsing JSON documents in the "Parsing" tab:

- **Encoding** : Choose the appropriate encoding of the JSON file.
- **JsonML** : Activate this option if the incoming file is a JsonML file.

Command Line

Turn on the JSON Parser before parsing documents, and set some optional, parser-specific options and a file filter:

```
SET PARSER json
SET JSONPARSER encoding=utf-8, jsonml=true
SET CREATEFILTER *.json
```

XQuery

The JSON Module provides functions for converting JSON objects to XML documents.

CSV Parser

BaseX can be used to import CSV documents. Different alternatives how to proceed are shown in the following:

GUI

Go to Menu *Database* → *New* and select "CSV" in the input format combo box. You can set the following options for parsing CSV documents in the "Parsing" tab:

- **Encoding** : Choose the appropriate encoding of the CSV file.
- **Separator** : Choose the column separator of the CSV file. Possible: `comma`, `semicolon`, `tab` or `space` or an arbitrary character.
- **Header** : Activate this option if the incoming CSV files have a header line.

Command Line

Turn on the CSV Parser before parsing documents, and set some optional, parser-specific options and a file filter. Unicode code points can be specified as separators; `32` is the code point for spaces:

```
SET PARSER csv
SET CSVPARSER encoding=utf-8, lines=true, header=false, separator=space
SET CREATEFILTER *.csv
```

XQuery

The CSV Module provides a function for converting CSV to XML documents.

Documents can also be converted by specifying the parser in an XQuery function. The following example query adds all CSV files that are located in the directory `2Bimported` to the database `DB` and interprets the first lines as column headers:

```
for $file in file:list("2Bimported", false(), "*.csv")
return db:add("DB", $file, "", map {
  'parser': 'csv',
  'csvparser': map { 'header': true() }
})
```

Text Parser

Plain text can be imported as well:

GUI

Go to Menu *Database* → *New* and select "TEXT" in the input format combobox. You can set the following option for parsing text documents in the "Parsing" tab:

- **Encoding** : Choose the appropriate encoding of the text file.
- **Lines** : Activate this option to create a `<line>...</line>` element for each line of the input text file.

Command Line

Turn on the CSV Parser before parsing documents and set some optional, parser-specific options and a file filter:

```
SET PARSER text
SET TEXTPARSER lines=yes
SET CREATEFILTER *
```

XQuery

Similar to the other formats, the text parser can also be specified via XQuery:

```
for $file in file:list("2Bimported", true(), "*.txt")
return db:add("DB", $file, "", map { 'parser': 'text' })
```

Changelog

Version 7.8

- Updated: parser options

Version 7.7.2

- Removed: CSV option "format"

Version 7.3

- Updated: the CSV `SEPARATOR` option may now be assigned arbitrary single characters

Version 7.2

- Updated: Enhanced support for TagSoup options

Chapter 15. Commands

Read this entry online in the BaseX Wiki.

This article is part of the Getting Started Section. It lists all database commands supported by BaseX.

Commands can be executed from the Command Line, as part of Scripts, via the Clients, REST, the input field in the GUI, and other ways. If the GUI is used, all commands that are triggered by the GUI itself will show up in the Info View. The Permission fields indicate which rights are required by a user to perform a command in the client/server architecture.

Basics

Command Scripts

On command line, multiple commands can be written down in a single line (separated by semicolons). You can also put them into a command script: Database commands in both string and XML syntax can be placed in a text file and stored as file with the BaseX command script suffix `.bxs`. If the path to a script file is passed on to BaseX on command-line, or if it is opened in the GUI editor, it will be recognized and evaluated as such.

String Syntax

Lines starting with # are interpreted as comments and are skipped. With the following script, a database is created, two documents are added to it, and a query is performed:

```
CREATE DB test
ADD TO embedded.xml <root>embedded</root>
# run query
XQUERY <hits>{ count(//text()) }</hits>
CLOSE
```

XML Syntax

The string syntax is limited when XML snippets need to be embedded in a command, or when complex queries are to be specified.

The XML syntax provides more flexibility here. Multiple commands can be enclosed by a `<commands/>` root element. Some commands, such as `ADD`, allow you to directly embed XML documents. If you want to embed XML in XQuery expressions, entities should be encoded, or the `CDATA` syntax should be used:

```
<commands>
  <create-db name='test'/>
  <add path='embedded.xml'><root>embedded</root></add>
  <!-- run query -->
  <xquery><![CDATA[
    <hits>{ count(//text()) }</hits>
  ]]></xquery>
  <close/>
</commands>
```

Glob Syntax

Some commands support the glob syntax to address more than one database or user. Question marks and asterisks can be used to match one or more characters, and commas can be used to separate multiple patterns. Some examples:

- `AB?` addresses all names with the characters `AB` and one more character.

- `*AB` addresses all names ending with the characters `AB`.
- `X*,Y*,Z*` addresses all names starting with the characters `X`, `Y`, or `Z`.

Valid Names

Database and user names follow the same naming constraints: Names are restricted to ASCII characters. They must at least have one character, and they may contain letters, numbers and any of the special characters `!#$%&'()+-=@[]^_`{}~`. The following characters are reserved for other features:

- `,?*` : glob syntax
- `;` : Separator for multiple database commands on the command line
- `\/` : Directory path separators
- `:*?\"<>|}` : invalid filename characters on Windows
- Names starting or ending with `.`: hidden folders (e.g. the .logs directory)

Aliases

In all commands, the `DB` keyword can be replaced by `DATABASE`.

Database Operations

CREATE DB

Syntax	`CREATE DB [name] ([input])`
XML Syntax	`<create-db name='...'>([input])</create-db>`
Permission	*CREATE*
Summary	Creates a new database with the specified `name` and, optionally, an initial `input`, and opens it. An existing database will be overwritten.The input can be a file or directory path to XML documents, a remote URL, or a string containing XML: • `name` must be a valid database name • database creation can be controlled by setting Create Options
Errors	The command fails if a database with the specified name is currently used by another process, if one of the documents to be added is not well-formed or if it cannot be parsed for some other reason.
Examples	• `CREATE DB input` creates an empty database `input`. • `CREATE DB xmark http://files.basex.org/xml/xmark.xml` creates the database `xmark`, containing a single initial document called `xmark.xml`. • `CREATE DATABASE coll /path/to/input` creates the database `coll` with all documents found in the `input` directory. • `SET INTPARSE false; CREATE DB input input.xml` creates a database `input` with `input.xml` as initial document, which will be parsed with Java's default XML parser. • `<create-db name='simple'><hello>Universe</hello></create-db>` creates a database named `simple` with an initial document `<hello>Universe</hello>`.

OPEN

Syntax	`OPEN [name] ([path])`

XML Syntax	`<open name='...' (path='...')/>`
Permission	*READ*
Summary	Opens the database specified by `name`. The documents to be opened can be specified by the [path] argument.
Errors	The command fails if the specified database does not exist, is currently being updated by another process or cannot be opened for some other reason.

CHECK

Syntax	`CHECK [input]`
XML Syntax	`<check input='...'/>`
Permission	*READ/CREATE*
Summary	This convenience command combines `OPEN` and `CREATE DB`: if a database with the name `input` exists, it is opened. Otherwise, a new database is created; if the specified input points to an existing resource, it is stored as initial content.
Errors	The command fails if the addressed database could neither be opened nor created.

CLOSE

Syntax	`CLOSE`
XML Syntax	`<close/>`
Permission	*READ*
Summary	Closes the currently opened database.
Errors	The command fails if the database files could not be closed for some reason.

EXPORT

Syntax	`EXPORT [path]`
XML Syntax	`<export path='...'/>`
Permission	*CREATE*
Summary	Exports all documents in the database to the specified file `path`, using the serializer options specified by the `EXPORTER` option.
Errors	The command fails if no database is opened, if the target path points to a file or is invalid, if the serialization parameters are invalid, or if the documents cannot be serialized for some other reason.

CREATE INDEX

Updated with Version 8.4: Token index added.

Syntax	`CREATE INDEX [TEXT|ATTRIBUTE|TOKEN|FULLTEXT]`
XML Syntax	`<create-index type='text|attribute|token|fulltext'/>`
Permission	*WRITE*
Summary	Creates the specified Value Index. The current Index Options will be considered when creating the index.
Errors	The command fails if no database is opened, if the specified index is unknown, or if indexing fails for some other reason.

DROP INDEX

Syntax	`DROP INDEX [TEXT|ATTRIBUTE|TOKEN|FULLTEXT]`

XML Syntax	`<drop-index type='text|attribute|token|fulltext'/>`
Permission	*WRITE*
Summary	Drops the specified Value Index.
Errors	The command fails if no database is opened, if the specified index is unknown, or if it could not be deleted for some other reason.

Administration

ALTER DB

Syntax	`ALTER DB [name] [newname]`
XML Syntax	`<alter-db name='...' newname='...'/>`
Permission	*CREATE*
Summary	Renames the database specified by `name` to `newname`. `newname` must be a valid database name.
Errors	The command fails if the target database already exists, if the source database does not exist or is currently locked, or if it could not be renamed for some other reason.
Examples	• `ALTER DB db tempdb` renames the database `db` into `tempdb`.

DROP DB

Syntax	`DROP DB [name]`
XML Syntax	`<drop-db name='...'/>`
Permission	*CREATE*
Summary	Drops the database with the specified `name`. The Glob Syntax can be used to address more than one database.
Errors	The command fails if the specified database does not exist or is currently locked, or if the database could not be deleted for some other reason.

CREATE BACKUP

Syntax	`CREATE BACKUP [name]`
XML Syntax	`<create-backup name='...'/>`
Permission	*CREATE*
Summary	Creates a zipped backup of the database specified by `name`. The backup file will be suffixed with the current timestamp and stored in the database directory. The Glob Syntax can be used to address more than one database.
Errors	The command fails if the specified database does not exist, or if it could not be zipped for some other reason.
Examples	• `BACKUP db` creates a zip archive of the database `db` (e.g. `db-2014-04-01-12-27-28.zip`) in the database directory.

RESTORE

Syntax	`RESTORE [name]`
XML Syntax	`<restore name='...'/>`
Permission	*CREATE*
Summary	Restores a database with the specified `name`. The name may include the timestamp of the backup file.

Errors	The command fails if the specified backup does not exist, if the database to be restored is currently locked, or if it could not be restored for some other reason.

INSPECT

Syntax	`INSPECT`
XML Syntax	`<inspect/>`
Permission	*READ*
Summary	Performs some integrity checks on the opened database and returns a brief summary.

DROP BACKUP

Syntax	`DROP BACKUP [name]`
XML Syntax	`<drop-backup name='...'/>`
Permission	*CREATE*
Summary	Drops all backups of the database with the specified `name`. The Glob Syntax can be used to address more than one database.
Examples	• `DROP BACKUP abc*` deletes the backups of all databases starting with the characters `abc`.

SHOW BACKUPS

Syntax	`SHOW BACKUPS`
XML Syntax	`<show-backups/>`
Permission	*CREATE*
Summary	Shows all database backups.

COPY

Syntax	`COPY [name] [newname]`
XML Syntax	`<copy name='...' newname='...'/>`
Permission	*CREATE*
Summary	Creates a copy of the database specified by `name`. `newname` must be a valid database name.
Errors	The command fails if the target database already exists, or if the source database does not exist.

INFO DB

Syntax	`INFO DB`
XML Syntax	`<info-db/>`
Permission	*READ*
Summary	Shows general information and meta data on the currently opened database.
Errors	The command fails if no database is opened.

INFO INDEX

Syntax	`INFO INDEX ([ELEMNAME|ATTRNAME|PATH|TEXT|ATTRIBUTE|TOKEN|FULLTEXT])`
XML Syntax	`<info-index type='elemname|attrname|path|text|attribute|token|fulltext'/>`
Permission	*READ*

Summary	Shows information on the existing index structures. The output can be optionally limited to the specified index.
Errors	The command fails if no database is opened, or if the specified index is unknown.

INFO STORAGE

Syntax	`INFO STORAGE [start end]`
XML Syntax	`<info-storage (start='...') (end='...')/>`
Permission	*READ*
Summary	Shows the internal main table of the currently opened database. An integer range may be specified as argument.
Errors	The command fails if no database is opened, or if one of the specified arguments is invalid.

Querying

LIST

Syntax	`LIST ([name] ([path]))`
XML Syntax	`<list (name='...' (path='...'))/>`
Permission	*NONE*
Summary	Lists all available databases. If `name` is specified, the resources of a database are listed. The output can be further restricted to the resources matching the specified `path`.If database resources are listed, the size is either the number of nodes (for XML resources) or the number of bytes (for binary resources).
Errors	The command fails if the optional database cannot be opened, or if the existing databases cannot be listed for some other reason.

XQUERY

Syntax	`XQUERY [query]`
XML Syntax	`<xquery>[query]</xquery>`
Permission	*depends on query*
Summary	Runs the specified `query` and prints the result.
Errors	The command fails if the specified query is invalid.
Examples	• `XQUERY 1 to 10` returns the sequence `(1, 2, 3, 4, 5, 6, 7, 8, 9, 10)`. • `SET RUNS 10; XQUERY 1 to 10` returns the results after having run the query 10 times. • `SET XMLPLAN true; XQUERY 1 to 10` returns the result and prints the query plan as XML.

RETRIEVE

Syntax	`RETRIEVE [path]`
XML Syntax	`<retrieve path='...'/>`
Permission	*READ*
Summary	Retrieves a raw file from the opened database at the specified `path`.
Errors	The command fails if no database is opened, if the source path is invalid or if the data cannot not be retrieved for some other reason.

FIND

Syntax	`FIND [query]`
XML Syntax	`<find>[query]</find>`
Permission	*READ*
Summary	Builds and runs a query for the specified `query` terms. Keywords can be enclosed in quotes to look for phrases. The following modifiers can be used to further limit search: = looks for exact text nodes~ looks for approximate hits@= looks for exact attribute values@ looks for attributes
Errors	The command fails if no database is opened.

TEST

Syntax	`TEST [path]`
XML Syntax	`<test path='...'/>`
Permission	*ADMIN*
Summary	Runs all XQUnit tests in the specified `path`. The path can point to a single file or a directory.Unit testing can also be triggered via `-t` on command line.
Errors	The command fails if at least one test fails.
Examples	• `TEST project/tests` runs all tests in the directory `project/tests`.

REPO INSTALL

Syntax	`REPO INSTALL [path]`
XML Syntax	`<repo-install path='...'/>`
Permission	*CREATE*
Summary	Installs the package with path `path`.
Errors	The command fails in the following cases: • The package to be installed is not a xar file. • The package to be installed does not exist or is already installed. • The package descriptor is with invalid syntax. • The package to be installed depends on a package which is not installed. • The package is not supported by the current version of BaseX. • A component of the package is already installed as part of another package.

REPO LIST

Syntax	`REPO LIST`
XML Syntax	`<repo-list/>`
Permission	*READ*
Summary	Lists all installed packages.

REPO DELETE

Syntax	`REPO DELETE [name]`
XML Syntax	`<repo-delete name='...'/>`

Permission	*CREATE*
Summary	Deletes the specified package with the specified `name`. What is called "name" can also be the id (which is the name followed by the version) or the directory of the package.
Errors	The command fails if the package to be deleted is required by another package.

Updates

ADD

Syntax	`ADD (TO [path]) [input]`
XML Syntax	`<add (path='...')>[input]</add>`
Permission	*WRITE*
Summary	Adds a file, directory or XML string specified by `input` to the currently opened database at the specified `path`: • `input` may either be a single XML document, a directory, a remote URL or a plain XML string. • A document with the same path may occur than once in a database. If this is unwanted, the `REPLACE` command can be used. • If a file is too large to be added in one go, its data structures will be cached to disk first. Caching can be enforced by turning the `ADDCACHE` option on. If files are to be added to an empty database, it is usually faster to use the `CREATE DB` command and specify the initial input as argument.
Errors	The command fails if no database is opened, if one of the documents to be added is not well-formed, or if it could not be parsed for some other reason.
Examples	• `ADD input.xml` adds the file `input.xml` to the database. • `ADD TO temp/one.xml input.xml` adds `input.xml` to the database and moves it to `temp/one.xml`. • `ADD TO target/ xmldir` adds all files from the `xmldir` directory to the database in the `target` path.

DELETE

Syntax	`DELETE [path]`
XML Syntax	`<delete path='...'/>`
Permission	*WRITE*
Summary	Deletes all documents from the currently opened database that start with the specified `path`.
Errors	The command fails if no database is opened.

RENAME

Syntax	`RENAME [path] [newpath]`
XML Syntax	`<rename path='...' newpath='...'/>`
Permission	*WRITE*
Summary	Renames all document paths in the currently opened database that start with the specified `path`. The command may be used to either rename single documents or directories.
Errors	The command fails if no database is opened, or if the target path is empty.
Examples	• `RENAME one.xml two.xml` renames the document `one.xml` to `two.xml`.

- `RENAME / TOP` moves all documents to a `TOP` root directory.

REPLACE

Syntax	`REPLACE [path] [input]`
XML Syntax	`<replace path='...'>[input]</replace>`
Permission	*WRITE*
Summary	Replaces resources in the currently opened database, addressed by `path`, with the file, directory or XML string specified by `input`, or adds new documents if no resource exists at the specified path.
Errors	The command fails if no database is opened or if the specified path is invalid.
Examples	• `REPLACE one.xml input.xml` replaces the document `one.xml` with the contents of the file `input.xml`. • `REPLACE top.xml <xml/>` replaces the document `top.xml` with the document `<xml/>`.

STORE

Syntax	`STORE (TO [path]) [input]`
XML Syntax	`<store (path='...')>[input]</store>`
Permission	*WRITE*
Summary	Stores a raw file specified via `input` in the opened database to the specified `path`: • The input may either be a file reference, a remote URL, or a plain string. • If the path denotes a directory, it needs to be suffixed with a slash (`/`). • An existing resource will be replaced.
Errors	The command fails if no database is opened, if the specified resource is not found, if the target path is invalid or if the data cannot not be written for some other reason.

OPTIMIZE

Syntax	`OPTIMIZE (ALL)`
XML Syntax	`<optimize/>` `<optimize-all/>`
Permission	*WRITE*
Summary	Optimizes the index structures, meta data and statistics of the currently opened database: • If `ALL` is specified, all database structures are completely reconstructed. The database size will be reduced, and all orphaned data will be deleted. • Without `ALL`, only the outdated index structures and database statistics will be updated. If the database is completely up-to-date, nothing will be done. • Database options will be adopted from the original database. Only `AUTOOPTIMIZE` and (if `ALL` is specified) `UPDINDEX` will be adopted from the current options.
Errors	The command fails if no database is opened, or if the currently opened database is a main-memory instance.

FLUSH

Syntax	`FLUSH`
XML Syntax	`<flush/>`

Permission	*WRITE*
Summary	Explicitly flushes the buffers of the currently opened database to disk. This command is applied if `AUTOFLUSH` has been set to `false`.
Errors	The command fails if no database is opened.

Monitoring

SHOW SESSIONS

Syntax	`SHOW SESSIONS`
XML Syntax	`<show-sessions/>`
Permission	*ADMIN*
Summary	Shows all sessions that are connected to the current server instance.

SHOW USERS

Syntax	`SHOW USERS (ON [database])`
XML Syntax	`<show-users (database='...')/>`
Permission	*ADMIN*
Summary	Shows all users that are visible to the current user. If a `database` is specified, only those users will be shown for which a pattern was specified that matches the database name.
Errors	The command fails if the optional database could not be opened.

KILL

Syntax	`KILL [target]`
XML Syntax	`<kill target='...'/>`
Permission	*ADMIN*
Summary	Kills sessions of a user or an IP:port combination, specified by `target`. The Glob Syntax can be used to address more than one user.
Errors	The command fails if a user tried to kill his/her own session.

JOBS LIST

Syntax	`JOBS LIST`
XML Syntax	`<jobs-list/>`
Permission	*ADMIN*
Summary	Returns information on all jobs that are currently queued or executed.

JOBS RESULT

Syntax	`JOBS RESULT [id]`
XML Syntax	`<jobs-result id='...'/>`
Permission	*ADMIN*
Summary	Returns the cached result of a query with the specified job id: • Results can only be retrieved once. After retrieval, the cached result will be dropped. • If the original query has raised an error, the cached error will be raised instead.

Errors	The command fails if the addressed job is still running or if the result has already been retrieved.

JOBS STOP

Syntax	`JOBS STOP [id]`
XML Syntax	`<jobs-stop id='...'/>`
Permission	*ADMIN*
Summary	Cancels the execution of a job with the specified id, or drops the cached result of a query. Unknown ids are ignored. All jobs are gracefully stopped; it is up to the process to decide when it is safe to shut down.

User Management

CREATE USER

Syntax	`CREATE USER [name] ([password])`
XML Syntax	`<create-user name='...'>([password])</create-user>`
Permission	*ADMIN*
Summary	Creates a user with the specified `name` and `password`. If no password is specified, it is requested via the chosen frontend (GUI or bash).
Errors	The command fails if the specified user already exists.

ALTER USER

Syntax	`ALTER USER [name] ([newname])`
XML Syntax	`<alter-user name='...' newname='...'/>`
Permission	*ADMIN*
Summary	Renames the user with the specified `name` to `newname`.
Errors	The command fails if the specified user does not exist, or if the new user already exists.

ALTER PASSWORD

Syntax	`ALTER PASSWORD [name] ([password])`
XML Syntax	`<alter-password name='...'>([password])</alter-password>`
Permission	*ADMIN*
Summary	Alters the `password` of the user with the specified `name`. If no password is specified, it is requested via the chosen frontend (GUI or bash).
Errors	The command fails if the specified user does not exist.

DROP USER

Syntax	`DROP USER [name] (ON [pattern])`:
XML Syntax	`<drop-user name='...' (pattern='...')/>`
Permission	*ADMIN*
Summary	Drops the user with the specified `name`. The Glob Syntax can be used to address more than one database or user. If a glob `pattern` is specified, only the pattern will be removed.
Errors	The command fails if `admin` is specified as user name, or if the specified user does not exist or is currently logged in.

GRANT

Syntax	`GRANT [NONE|READ|WRITE|CREATE|ADMIN] (ON [pattern]) TO [user]`
XML Syntax	`<grant name='...' permission='none|read|write|create|admin' (pattern='...')/>`
Permission	*ADMIN*
Summary	Grants the specified permission to the specified `user`. The Glob Syntax can be used to address more than one user. If a glob `pattern` is specified, the permission will be applied to all databases that match this pattern.
Errors	The command fails if `admin` is specified as user name or if the specified user does not exist.
Examples	• `GRANT READ TO JoeWinson` grants `READ` permission to the user `JoeWinson`. • `GRANT WRITE ON Wiki TO editor*` grants `WRITE` permissions on the `Wiki` database to all users starting with the characters `editor*`.

PASSWORD

Syntax	`PASSWORD ([password])`
XML Syntax	`<password>([password])</password>`
Permission	*NONE*
Summary	Changes the `password` of the current user. If no password is specified, it is requested via the chosen frontend (GUI or bash).

General Commands

RUN

Syntax	`RUN [file]`
XML Syntax	`<run file='...'/>`
Permission	*depends on input*
Summary	Evaluates the contents of `file` as XQuery expression. If the file ends with the suffix `.bxs`, the file contents will be evaluated as command script. This command can be used to run several commands in a row, with no other transaction intervening the execution.
Errors	The command fails if the specified file does not exist, or if the retrieved input is invalid. It will be canceled as soon as one of the executed commands fails.
Examples	• `RUN query.xq` will evaluate the specified file as XQuery expression • `RUN commands.bxs` will evaluate the specified file as command script

EXECUTE

Syntax	`EXECUTE [input]`
XML Syntax	`<execute>[input]</execute>`
Permission	*depends on input*
Summary	Evaluates the specified `input` as command script. This command can be used to run several commands in a row, with no other transaction intervening the execution.
Errors	The command fails if the syntax of the specified input is invalid. It will be canceled as soon as one of the executed commands fails.
Examples	• `EXECUTE "create db db1; create db db2"`

- `EXECUTE "<commands><create-db name='db1'/><create-db name='db2'/></commands>"` both commands will create two databases `db1` and `db2` in a single transaction.

GET

Syntax	`GET [option]`
XML Syntax	`<get (option='...')/>`
Permission	*NONE*
Summary	Returns the current value of the Option specified via `option`. Global options can only be requested by users with ADMIN permissions.
Errors	The command fails if the specified option is unknown.

SET

Syntax	`SET [option] ([value])`
XML Syntax	`<set option='...'>([value])</set>`
Permission	*NONE*
Summary	Sets the Option specified by `option` to a new `value`. Only local options can be modified. If no value is specified, and if the value is boolean, it will be inverted.
Errors	The command fails if the specified option is unknown or if the specified value is invalid.

INFO

Syntax	`INFO`
XML Syntax	`<info/>`
Permission	*READ*
Summary	Shows global information.

HELP

Syntax	`HELP ([command])`
XML Syntax	`<help>([command])</help>`
Permission	*NONE*
Summary	If `command` is specified, information on the specific command is printed; otherwise, all commands are listed.
Errors	The command fails if the specified command is unknown.

EXIT

Syntax	`EXIT`
XML Syntax	`<exit/>`
Permission	*NONE*
Summary	Exits the console mode.

QUIT

Syntax	`QUIT`
XML Syntax	`<quit/>`

Permission	*NONE*
Summary	Exits the console mode (alias of `EXIT`).

Changelog

Version 8.6

- Updated: `SHOW USERS`: If called by non-admins, will only return the current user

Version 8.5

- Added: `JOBS LIST`, `JOBS RESULT`, `JOBS STOP`
- Updated: Valid Names: allow dots (except as first and last character)

Version 8.4

- Updated: `CREATE INDEX`, `DROP INDEX`, `INFO INDEX`: token index added
- Updated: `INFO STORAGE`: Query argument removed, start/end added to XML syntax.
- Updated: `INFO INDEX`: Token index added; index `TAG` renamed to `ELEMNAME`; index `ATTNAME` renamed to `ATTRNAME`
- Updated: `OPTIMIZE`: adopt original index options

Version 8.2

- Removed: `CREATE EVENT`, `DROP EVENT` and `SHOW EVENTS` command

Version 8.0

- Updated: commands for User Management
- Updated: `OPEN`: path argument added
- Removed: `CS` command
- Added: `QUIT`

Version 7.9

- Added: `TEST` runs XQUnit tests.

Version 7.7

- Updated: syntax of valid names.

Version 7.5

- Added: `EXECUTE` executes a command script.
- Added: `INSPECT` performs integrity checks.
- Added: automatic detection of Command Scripts.
- Removed: `SHOW DATABASES`; information is also returned by `SHOW SESSIONS`.
- Removed: `OPEN`: path argument.

Version 7.3

- Added: XML Syntax added.
- Updated: `CHECK` can now be used to create empty databases.
- Updated: Names and paths in `OPEN` and `LIST` are now specified as separate arguments.

Version 7.2.1

- Updated: permissions for `GET` and `SET` changed from `READ` to `NONE`.

Version 7.2

- Updated: `CREATE INDEX`, `DROP INDEX` (`PATH` argument removed. Path summary is always available now and updated with `OPTIMIZE`).
- Updated: permissions for `REPO DELETE`, `REPO INSTALL` and `REPO LIST`.

Version 7.1

- Updated: `KILL` (killing sessions by specifying IP:port)

Version 7.0

- Added: `FLUSH`, `RETRIEVE`, `STORE`.
- Updated: `ADD`: simplified arguments.

Chapter 16. Options

Read this entry online in the BaseX Wiki.

This page is linked from the Getting Started Section.

The options listed on this page influence the way how database commands are executed and XQuery expressions are evaluated. Two kinds of options exist:

- **Global Options** are valid for all BaseX instances in the same JVM. This is particularly relevant if you are working with the client/server architecture.
- **Local options** (all remaining ones) are specific to a client or session.

Values of options are either *strings*, *numbers* or *booleans*. Options are *static* and not bound to a single operation (for example, the next command). Various ways exist to access and change options:

- The current value of an option can be requested with the `GET` command. Local options can be changed via `SET` (all global options, except for `DEBUG`, can only be changed at startup time). If an option is of type *boolean*, and if no value is specified, its current value will be inverted.
- The `.basex` configuration file is parsed by every new local BaseX instance. It contains all global options. Local options can be specified at the end of the file after the `Local Options` comment:

```
# General Options
DEBUG = false
...

# Local Options
CHOP = false
```

- Initial values for global options can also be specified via system properties, which can e.g. be passed on with the -D flag on command line, or using System.setProperty() before creating a BaseX instance. The specified keys need to be prefixed with `org.basex.`. An example:

```
java -Dorg.basex.CHOP=false -cp basex.jar org.basex.BaseX -c"get chop"
CHOP: false
```

- If using the Mac OS X packaged application then global options can be set within the Info.plist file within the Contents folder of the application package. For example:

```
<key>JVMOptions</key>
<array>
  <string>-Dorg.basex.CHOP=false</string>
</array>
```

- In a Web Application, the default can be adjusted in the `web.xml` file as follows:

```
<context-param>
  <param-name>org.basex.chop</param-name>
  <param-value>false</param-value>
</context-param>
```

- In XQuery, local options can be set via option declarations and pragmas.

If options are changed by operations in the GUI, the underlying commands will be listed in the Info View.

Global Options

Global options are constants. They can only be set in the configuration file or via system properties (see above). One exception is the DEBUG option, which can also be changed at runtime by users with admin permissions.

General Options

DEBUG

Signature	`DEBUG [boolean]`
Default	`false`
Summary	Sends internal debug info to STDERR. This option can be turned on to get additional information for development and debugging purposes. It can also be triggered on command line via `-d`.

DBPATH

Signature	`DBPATH [path]`
Default	`<code>{home}/data`
Summary	Points to the directory in which all databases are located.

LOGPATH

Signature	`LOGPATH [path]`
Default	`.logs`
Summary	Points to the directory in which all log files are stored. Relative paths will be resolved against the `DBPATH` directory.

REPOPATH

Signature	`REPOPATH [path]`
Default	`{home}/repo`
Summary	Points to the Repository, in which all XQuery modules are located.

LANG

Signature	`LANG [language]`
Default	`English`
Summary	Specifies the interface language. Currently, seven languages are available: 'English', 'German', 'French', 'Dutch', 'Italian', 'Japanese', and 'Vietnamese'.

LANGKEY

Signature	`LANGKEY [boolean]`
Default	`false`
Summary	Prefixes all texts with the internal language keys. This option is helpful if BaseX is translated into another language, and if you want to see where particular texts are displayed.

FAIRLOCK

Signature	`FAIRLOCK [boolean]`
Default	`false`
Summary	Defines the locking strategy:

- By default, non-fair is used. Read transactions will be favored, and transactions that access no databases can be evaluated even if the limit of parallel transactions (specified via PARALLEL) has been reached. This prevents update operations from blocking all other requests. For example, the DBA can further be used to see which jobs are running, even if the queue is full.
- If fair locking is enabled, read and write transactions will be treated equally (first in, first out). This avoids starvation of update operations, and it should be used if the prompt evaluation of update operations is critical.

CACHETIMEOUT

Signature	`CACHETIMEOUT [seconds]`
Default	`3600`
Summary	Specifies how many seconds the results of queries, which have been queued by the asynchronously executed, will be cached in main memory.

Client/Server Architecture

HOST

Signature	`HOST [host]`
Default	`localhost`
Summary	This host name is used by the client when connecting to a server. This option can also be changed when running the client on command line via `-n`.

PORT

Signature	`PORT [port]`
Default	`1984`
Summary	This port is used by the client when connecting to a server. This option can also be changed when running the client on command line via `-p`.

SERVERPORT

Signature	`SERVERPORT [port]`
Default	`1984`
Summary	This is the port the database server will be listening to. This option can also be changed when running the server on command line via `-p`.

USER

Signature	`USER [name]`
Default	*empty*
Summary	Represents a user name, which is used for accessing the server or an HTTP service: • The default value will be overwritten if a client specifies its own credentials. • If the default value is empty, login will only be possible if the client specifies credentials. • The option can also be changed on command line via `-U`.

PASSWORD

Signature	`PASSWORD [password]`

Default	*empty*
Summary	Represents a password, which is used for accessing the server: • The default value will be overwritten if a client specifies its own credentials. • If the default value is empty, login will only be possible if the client specifies credentials. • The option can also be changed on command line via `-P`. • Please note that it is a security risk to specify your password in plain text.

AUTHMETHOD

Signature	`AUTHMETHOD [method]`
Default	*Basic*
Summary	Specifies the default authentication method, which will be used by the HTTP server for negotiating credentials. Allowed values are `Basic`, `Digest`, and `Custom`: • If basic access is chosen, the client can still request digest authentication. • This is different for digest access, which cannot be overwritten. • With custom authentication, the server will not do any authentication.

SERVERHOST

Signature	`SERVERHOST [host|ip]`
Default	*empty*
Summary	This is the host name or ip address the server is bound to. If the option is set to an empty string (which is the default), the server will be open to all clients.

PROXYHOST

Signature	`PROXYHOST [host]`
Default	*empty*
Summary	This is the host name of a proxy server. If the value is an empty string, it will be ignored.

PROXYPORT

Signature	`PROXYPORT [port]`
Default	`0`
Summary	This is the port number of a proxy server. If the value is set to `0`, it will be ignored.

NONPROXYHOSTS

Signature	`NONPROXYHOSTS [hosts]`
Default	*empty*
Summary	This is a list of hosts that should be directly accessed. If the value is an empty string, it will be ignored.

IGNOREHOSTNAME

Introduced with Version 9.0.

Signature	`IGNOREHOSTNAME [boolean]`
Default	`false`
Summary	If this option is enabled, hostnames of certificates will not be verified. Use `IGNORECERT` to completely disable certificate verification.

IGNORECERT

Signature	`IGNORECERT [boolean]`
Default	`false`
Summary	This option can be turned on to ignore untrusted certificates when connecting to servers. Use `IGNOREHOSTNAME` to suppress only the hostname verification.

TIMEOUT

Signature	`TIMEOUT [seconds]`
Default	`30`
Summary	Specifies the maximum time a transaction triggered by a client may take. If an operation takes longer than the specified number of seconds, it will be aborted. Active update operations will not be affected by this timeout, as this would corrupt the integrity of the database. The timeout is deactivated if the timeout is set to `0`. It is ignored for operations with admin permissions.

KEEPALIVE

Signature	`KEEPALIVE [seconds]`
Default	`600`
Summary	Specifies the maximum time a client will be remembered by the server. If there has been no interaction with a client for a longer time than specified by this timeout, it will be disconnected. Running operations will not be affected by this option. The keepalive check is deactivated if the value is set to `0`.

PARALLEL

Signature	`PARALLEL [number]`
Default	`8`
Summary	Denotes the maximum allowed number of parallel transactions: • If `FAIRLOCK` is enabled, the number of parallel transactions will never exceed the specified value. • If the option is disabled (which is the default), the limit only applies to transactions that access databases. • The main reason for allowing parallel operations is to prevent slow transactions from blocking all other operations. A higher number of parallel operations may increase disk activity and thus slow down queries. In some cases, a single transaction may even give you better results than any parallel activity.

LOG

Signature	`LOG [boolean]`
Default	`true`
Summary	Turns Logging of server operations and HTTP requests on/off. This option can also be changed when running the server on command line via `-z`.

LOGMSGMAXLEN

Signature	`LOGMSGMAXLEN [length]`
Default	`1000`
Summary	Specifies the maximum length of a single log message.

HTTP Services

Most HTTP options are defined in the `jetty.xml` and `web.xml` configuration files in the `webapp/WEB-INF` directory. Some additional BaseX-specific options exist that will be set before the web server is started:

WEBPATH

Signature	`WEBPATH [path]`
Default	`{home}/webapp`
Summary	Points to the directory in which all the Web Application contents are stored, including XQuery, Script, RESTXQ and configuration files. This option is ignored if BaseX is deployed as web servlet.

RESTXQPATH

Signature	`RESTXQPATH [path]`
Default	*empty*
Summary	Points to the directory which contains the RESTXQ modules of a web application. Relative paths will be resolved against the `WEBPATH` directory.

PARSERESTXQ

Signature	`PARSERESTXQ`
Default	`3`
Summary	Timeout after which the RESTXQ directory will be parsed for changes: • If `0` is specified, the directory will be parsed every time a RESTXQ function is called. • A positive value defines the idle time in seconds after which parsing will be enforced. The default value is `3`: Changes in the RESTXQ directory will be detected after 3 seconds without RESTXQ function calls. • Monitoring is completely disabled if a negative value is specified. See RESTXQ Preliminaries for more details.

RESTPATH

Signature	`RESTPATH [path]`
Default	*empty*
Summary	Points to the directory which contains XQuery files and command scripts, which can be evaluated via the REST run operation. Relative paths will be resolved against the `WEBPATH` directory.

HTTPLOCAL

Signature	`HTTPLOCAL [boolean]`
Default	`false`

Summary	By default, if BaseX is run as Web Application, a database server instance will be started as well. The server can then be addressed by other BaseX clients in parallel to the HTTP services.If the option is set to `true`, the database server will be disabled.

STOPPORT

Signature	`STOPPORT [port]`
Default	`8985`
Summary	This is the port on which the HTTP Server can be locally closed: • The listener for stopping the web server will only be started if the specified value is greater than `0`. • The option is ignored if BaseX is used as a Web Application or started via Maven. • This option can also be changed when running the HTTP server on command line via `-s`.

Create Options

General

MAINMEM

Signature	`MAINMEM [boolean]`
Default	`false`
Summary	If this option is turned on, new databases will be created in main memory: • Most queries will be evaluated faster in main-memory mode, but all data is lost if the BaseX instance in which the database was created is shut down. • It is not possible to store binary resources in a main-memory database. • A main-memory database will have no disk representation. However, it is possible to export the database via the `EXPORT` command, and create a new database from the exported file in a second step. • This option will not be available for db:create, because the database would not be accessible anymore after database creation, i. e., outside the query scope.

ADDCACHE

Signature	`ADDCACHE [boolean]`
Default	`false`
Summary	If this option is activated, data structures of documents will first be cached to disk before being added to the final database. This option is helpful when larger documents need to be added, and if the existing heuristics cannot estimate the input size (e.g. when adding directories or sending input streams).

Parsing

CREATEFILTER

Signature	`CREATEFILTER [filter]`
Default	`*.xml`

Summary	File filter in the Glob Syntax, which is applied whenever new databases are created, or resources are added to a database.

ADDARCHIVES

Signature	`ADDARCHIVES [boolean]`
Default	`true`
Summary	If this option is set to `true`, files within archives (ZIP, GZIP, TAR, TGZ, DOCX, etc.) are parsed whenever new databases are created or resources are added to a database.

ARCHIVENAME

Signature	`ARCHIVENAME [boolean]`
Default	`false`
Summary	If this option is set to `true`, the file name of parsed archives will be included in the document paths.

SKIPCORRUPT

Signature	`SKIPCORRUPT [boolean]`
Default	`false`
Summary	Skips corrupt (i.e., not well-formed) files while creating a database or adding new documents. If this option is activated, document updates are slowed down, as all files will be parsed twice. Next, main memory consumption will be higher as parsed files will be cached in main memory.

ADDRAW

Signature	`ADDRAW [boolean]`
Default	`false`
Summary	If this option is activated, and if new resources are added to a database, all files that are not filtered by the `CREATEFILTER` option will be added as *raw* files (i.e., in their binary representation).

PARSER

Signature	`PARSER [type]`
Default	`XML`
Summary	Defines a parser for importing new files to the database. Available parsers are `XML`, `JSON`, `CSV`, `TEXT`, and `HTML`. HTML will be parsed as normal XML files if Tagsoup is not found in the classpath.

CSVPARSER

Signature	`CSVPARSER [options]`
Default	*empty*
Summary	Specifies the way how CSV data will be parsed. Keys and values are delimited with `=`, and multiple options are delimited with `,`. The available options (except for the additional `encoding` option) are described in the CSV Module.
Examples	`encoding=CP1252,header=true` parses the input as CP1252 and the first line as header.

JSONPARSER

Signature	`JSONPARSER [options]`

Default	*empty*
Summary	Specifies the way how JSON data will be parsed. Keys and values are delimited with `=`, and multiple options are delimited with `,`. The available options (except for the additional `encoding` option) are described in the JSON Module.
Examples	`format=jsonml,lax=yes` interprets the input as JSONML and uses lax parsing.

HTMLPARSER

Signature	`HTMLPARSER [options]`
Default	*empty*
Summary	Specifies the way how HTML data will be parsed. Keys and values are delimited with `=`, and multiple options are delimited with `,`. The available options are described in the Parsers article.
Examples	• `encoding=Shift-JIS,nons=true` parses the input as Sihft-JIS and suppresses namespaces. • `lexical=true` preserves comments.

TEXTPARSER

Signature	`TEXTPARSER [options]`
Default	*empty*
Summary	Specifies the way how TEXT data will be parsed. Keys and values are delimited with `=`, and multiple options are delimited with `,`. The available options are listed in the Parsers article.
Examples	`lines=true` creates a single element for each line of text.

XML Parsing

CHOP

Signature	`CHOP [boolean]`
Default	`true`

Summary	Many XML documents include whitespaces that have been added to improve readability. This option controls the white-space processing mode of the XML parser:
	• With the default value `true`, leading and trailing whitespaces from text nodes will be chopped and all empty text nodes will be discarded.
	• The flag should be turned off if a document contains mixed content.
	• The flag can also be turned off on command line via `-w`.
	• If the `xml:space="preserve"` attribute is attached to an element, chopping will be turned off for all descendant text nodes.
	In the following example document, the whitespaces in the text nodes of the `text` element will not be chopped:
	`<xml>`
	`  <title>`
	`  Demonstrating the CHOP flag`
	`  </title>`
	`  <text xml:space="preserve">To <b>be</b>, or not to <b>be</b>, that is the question.</text>`
	`</xml>`

It is recommendable to additionally assign `indent=no` to the `SERIALIZER` option; otherwise the serialized documents will automatically be indented.

STRIPNS

Signature	`STRIPNS [boolean]`
Default	`false`
Summary	Strips all namespaces from an XML document and all elements while parsing.

INTPARSE

Signature	`INTPARSE [boolean]`
Default	`false`
Summary	Uses the internal XML parser instead of the standard Java XML parser. Here are some reasons for using the internal parser: • Performance: Documents (in particular small ones) will be parsed faster • Fault tolerance: invalid characters will automatically be replaced with the Unicode replacement character `FFFD` (#) • Entities: around 250 HTML entities will be detected and decoded You will be able to correctly parse most XML documents with the internal parser. Java's Xerces parser is still used as default, however, because it supports all features of the XML standard and advanced DTD features, such as recursive entity expansion.

DTD

Signature	`DTD [boolean]`
Default	`false`
Summary	Parses referenced DTDs and resolves XML entities. By default, this option is switched to `false`, as many DTDs are located externally, which may completely block the process of creating new databases. The `CATFILE` option can be changed to locally resolve DTDs.

XINCLUDE

Signature	`XINCLUDE [boolean]`
Default	`true`
Summary	Resolves XInclude inclusion tags and merges referenced XML documents. By default, this option is switched to `true`. This option is only available if the standard Java XML Parser is used (see `INTPARSE`).

CATFILE

Signature	`CATFILE [path]`
Default	*empty*
Summary	Specifies a catalog file to locally resolve DTDs. See the entry on Catalog Resolvers for more details.

Indexing

The following options control the creation of index structures. The current values will be considered if a new database is created. See Indexes for more details.

TEXTINDEX

Signature	`TEXTINDEX [boolean]`
Default	`true`
Summary	Creates a text index whenever a new database is created. A text index speeds up queries with equality comparisons on text nodes. See Text Index for more details.

ATTRINDEX

Signature	`ATTRINDEX [boolean]`
Default	`true`
Summary	Creates an attribute index whenever a new database is created. An attribute index speeds up queries with equality comparisons on attribute values. See Attribute Index for more details.

TOKENINDEX

Signature	`TOKENINDEX [boolean]`
Default	`true`
Summary	Creates a token index whenever a new database is created. A token index speeds up searches for single tokens in attribute values. See Token Index for more details.

FTINDEX

Signature	`FTINDEX [boolean]`
Default	`false`
Summary	Creates a full-text index whenever a new database is created. A full-text index speeds up queries with full-text expressions. See Full-Text Index for more details.

TEXTINCLUDE

Signature	`TEXTINCLUDE [names]`
Default	*empty*
Summary	Defines name patterns for the parent elements of texts that are indexed. By default, all text nodes will be indexed.Name patterns are separated by commas. See Selective Indexing for more details.

ATTRINCLUDE

Signature	`ATTRINCLUDE [names]`
Default	*empty*
Summary	Defines name patterns for the attributes to be indexed. By default, all attribute nodes will be indexed.Name patterns are separated by commas. See Selective Indexing for more details.

TOKENINCLUDE

Signature	`TOKENINCLUDE [names]`
Default	*empty*
Summary	Defines name patterns for the attributes to be indexed. By default, tokens in all attribute nodes will be indexed.Name patterns are separated by commas. See Selective Indexing for more details.

FTINCLUDE

Signature	`FTINCLUDE [names]`

Default	*empty*
Summary	Defines name patterns for the parent elements of texts that are indexed. By default, all text nodes will be indexed.Name patterns are separated by commas. See Selective Indexing for more details.

MAXLEN

Signature	`MAXLEN [int]`
Default	`96`
Summary	Specifies the maximum length of strings that are to be indexed by the name, path, value, and full-text index structures. The value of this option will be assigned once to a new database, and cannot be changed after that.

MAXCATS

Signature	`MAXCATS [int]`
Default	`100`
Summary	Specifies the maximum number of distinct values (categories) that will be stored together with the element/attribute names or unique paths in the Name Index or Path Index. The value of this option will be assigned once to a new database, and cannot be changed after that.

UPDINDEX

Signature	`UPDINDEX [boolean]`
Default	`false`
Summary	If turned on, incremental indexing will be enabled: • The current value of this option will be assigned to new databases. It can be changed for existing databases by running `OPTIMIZE` with the `ALL` keyword or db:optimize($db, true()). • After each update, the value indexes will be refreshed as well. Incremental updates are currently not available for the full-text index and database statistics. • Find more details in the article on Index Structures.

AUTOOPTIMIZE

Signature	`AUTOOPTIMIZE [boolean]`
Default	`false`
Summary	If turned on, auto optimization will be applied to new databases: • With each update, outdated indexes and database statistics will be recreated. • As a result, the index structures will always be up-to-date. • However, updates can take much longer, so this option should only be activated for medium-sized databases. • The value of this option will be assigned once to a new database. It can be reassigned by running `OPTIMIZE` or db:optimize.

SPLITSIZE

Signature	`SPLITSIZE [num]`
Default	`0`

Summary	This option affects the construction of new value indexes. It controls the number of index build operations that are performed before writing partial index data to disk: • The larger the assigned value is, the less splits will take place, and the more main memory will be required. • By default, if the value is set to `0`, some heuristics are applied, based on the current memory consumption. Usually, this works fine. If explicit garbage collection is disabled when running Java (e.g. via the JVM option `-XX:+DisableExplicitGC`), you may need to choose a custom split size.

Full-Text Indexing

STEMMING

Signature	`STEMMING [boolean]`
Default	`false`
Summary	If `true`, all tokens will be stemmed during full-text indexing, using a language-specific stemmer implementation. By default, tokens will not be stemmed. See Full-Text Index for more details.

CASESENS

Signature	`CASESENS [boolean]`
Default	`false`
Summary	If `true`, the case of tokens will be preserved during full-text indexing. By default, case will be ignored (all tokens will be indexed in lower case). See Full-Text Index for more details.

DIACRITICS

Signature	`DIACRITICS [boolean]`
Default	`false`
Summary	If set to `true`, diacritics will be preserved during full-text indexing. By default, diacritics will be removed. See Full-Text Index for more details.

LANGUAGE

Signature	`LANGUAGE [lang]`
Default	`en`
Summary	The specified language will influence the way how texts will be tokenized and stemmed. It can be the name of a language or a language code. See Full-Text Index for more details.

STOPWORDS

Signature	`STOPWORDS [path]`
Default	*empty*
Summary	A new full-text index will drop tokens that are listed in the specified stopword list. A stopword list may decrease the size of the full text index. See Full-Text Index for more details.

Query Options

QUERYINFO

Signature	`QUERYINFO [boolean]`

Default	`false`
Summary	Prints more information on internal query rewritings, optimizations, and performance. By default, this info is shown in the Info View in the GUI. It can also be activated on command line via `-V`.

XQUERY3

Signature	`XQUERY3`
Default	`true`
Summary	Enables all XQuery 3.0 features supported by BaseX. If this option is set to `false`, the XQuery parser will only accept expressions of the XQuery 1.0 specification.

MIXUPDATES

Signature	`MIXUPDATES`
Default	`false`
Summary	Allows queries to both contain updating and non-updating expressions. All updating constraints will be turned off, and nodes to be returned will be copied before they are modified by an updating expression. – By default, this option is set to `false`, because the XQuery Update Facility does not allow an updating query to return results.

BINDINGS

Signature	`BINDINGS [vars]`
Default	*empty*
Summary	Contains external variables to be bound to a query. The string must comply with the following rules: • Variable names and values must be separated by equality signs. • Multiple variables must be delimited by commas. • Commas in values must be duplicated. • Variables may optionally be introduced with a leading dollar sign. • If a variable uses a namespace different to the default namespace, it can be specified with the Clark Notation or Expanded QName Notation. This option can also be used on command line with the flag `-b`.

Examples	• `$a=1,$b=2` binds the values `1` and `2` to the variables $a and $b
	• `a=1,,2` binds the value `1,2` to the variable $a
	• `{URI}a=x` binds the value `x` to the variable $a with the namespace `URI`.
	• In the following Command Script, the value `hello world!` is bound to the variable $GREETING:
	`SET BINDINGS GREETING="hello world!"`
	`XQUERY declare variable $GREETING external; $GREETING`

INLINELIMIT

Signature	`INLINELIMIT`
Default	`100`

Summary	This option controls inlining of XQuery functions: • The XQuery compiler inlines functions to speed up query evaluation. • Inlining will only take place if a function body is not too large (i.e., if it does not contain too many expressions). • With this option, this maximum number of expressions can be specified. • Function inlining can be turned off by setting the value to `0`. • The limit can be locally overwritten via the %basex:inline annotation (follow the link to get more information on function inlining).

TAILCALLS

Signature	`TAILCALLS`
Default	`256`
Summary	Specifies how many stack frames of tail-calls are allowed on the stack at any time. When this limit is reached, tail-call optimization takes place and some call frames are eliminated. The feature can be turned off by setting the value to `-1`.

DEFAULTDB

Signature	`DEFAULTDB`
Default	`false`
Summary	If this option is turned on, paths specified in the fn:doc and fn:collection functions will first be resolved against a database that has been opened in the global context outside the query (e.g. by the `OPEN` command). If the path does not match any existing resources, it will be resolved as described in the article on accessing database resources.

FORCECREATE

Signature	`FORCECREATE [boolean]`
Default	`false`
Summary	By activating this option, database instances will be created with the XQuery functions fn:doc and fn:collection.

CHECKSTRINGS

Signature	`CHECKSTRINGS [boolean]`
Default	`true`
Summary	By default, characters from external sources that are invalid in XML will trigger an error. If the option is set to `false`, these characters will be replaced with the Unicode replacement character `FFFD` (#). The option affects Java Bindings and string conversion and input functions such as archive:create, archive:extract-text, archive:update, and zip:text-entry.

LSERROR

Signature	`LSERROR [error]`
Default	`0`
Summary	This option specifies the maximum Levenshtein error for the BaseX-specific fuzzy match option. See the page on Full-Texts for more information on fuzzy querying.

RUNQUERY

Signature	`RUNQUERY [boolean]`
Default	`true`
Summary	Specifies if a query will be executed or parsed only. This option can also be changed on command line via `-R`.

RUNS

Signature	`RUNS [num]`
Default	`1`
Summary	Specifies how often a query will be evaluated. The result is serialized only once, and the measured times are averages of all runs. This option can also be changed on command line via `-r`.

ENFORCEINDEX

Introduced with Version 9.0:

Signature	`ENFORCEINDEX [boolean]`
Default	`false`
Summary	Enforces index rewritings in path expressions (see Enforce Rewritings for details).

COPYNODE

Introduced with Version 9.0:

Signature	`COPYNODE [boolean]`
Default	`true`
Summary	When creating new nodes in XQuery via Node Constructors, all enclosed nodes will be copied, and all resulting nodes will get new node identities. This step can be very expensive, and it can be disabled with this option. The option should be used carefully, as it changes the standard behavior of XQuery. It should preferrably be used in Pragmas.

Serialization Options

SERIALIZE

Signature	`SERIALIZE [boolean]`
Default	`true`
Summary	Results of XQuery expressions will be serialized if this option is turned on. For debugging purposes and performance measurements, this option can be set to `false`. It can also be turned off on command line via `-z`.

SERIALIZER

Signature	`SERIALIZER [params]`
Default	*empty*
Summary	Parameters for serializing query results. The string must comply with the following rules: • Variable names and values must be separated by equality signs. • Multiple variables must be delimited by commas.

	• Commas in values must be duplicated. The option can also be used on command line with the flag `-s`.
Examples	• `indent=no` : disables indentation of XML nodes (by default, this is enabled) • `encoding=US-ASCII,omit-xml-declaration=no` : sets the encoding to `US-ASCII` and prints the XML declaration. • `item-separator=,,` : separates serialized items by a single comma.

EXPORTER

Signature	`EXPORTER [params]`
Default	*empty*
Summary	Contains parameters for exporting all resources of a database. Keys and values are separated by equality signs, multiple parameters are delimited by commas. See Serialization for more details.

XMLPLAN

Signature	`XMLPLAN [boolean]`
Default	`false`
Summary	Prints the execution plan of an XQuery expression in its XML representation. This option can also be activated on command line via `-x`.

COMPPLAN

Signature	`COMPPLAN [boolean]`
Default	`true`
Summary	Generates the query plan, which can be activated via `XMLPLAN`, before or after query compilation. This option can also be activated on command line via `-X`.

DOTPLAN

Signature	`DOTPLAN [boolean]`
Default	`false`
Summary	Saves the query plan of an XQuery expression as `.dot` file in the current working directory, using the graph description language. The output file can e.g. be visualized with Graphviz.

DOTCOMPACT

Signature	`DOTCOMPACT [boolean]`
Default	`false`
Summary	Chooses a compact dot representation.

Other Options

AUTOFLUSH

Signature	`AUTOFLUSH [boolean]`
Default	`true`

Summary	Flushes database buffers to disk after each update. If this option is set to `false`, bulk operations (multiple single updates) will be evaluated faster. As a drawback, the chance of data loss increases if the database is not explicitly flushed via the `FLUSH` command.

WRITEBACK

Signature	`WRITEBACK [boolean]`
Default	`false`
Summary	Propagates updates on main-memory instances of files that have been retrieved via fn:doc and fn:collection back to disk. This option can also be activated on command line via `-u`. Please note that, when turning this option on, your original files will not be backed up.

MAXSTAT

Signature	`MAXSTAT [num]`
Default	`30`
Summary	Specifies the maximum number of index occurrences printed by the `INFO INDEX` command.

Changelog

Version 9.0

- Added: `ENFORCEINDEX`, `COPYNODE`, `IGNOREHOSTNAME`

Version 8.6

- Added: `FAIRLOCK`, `PARSERESTXQ`
- Removed: `GLOBALLOCK` (exclusive use of database lock)
- Removed: `QUERYPATH` (will now be internally assigned)
- Removed: `CACHERESTXQ` (replaced with PARSERESTXQ)

Version 8.5

- Added: `CACHETIMEOUT`, `LOGPATH`
- Updated: `AUTHMETHOD`: `custom` value added.

Version 8.4

- Added: `TOKENINDEX`, `TOKENINCLUDE`
- Added: `SPLITSIZE` (replacing `INDEXSPLITSIZE` and `FTINDEXSPLITSIZE`)
- Removed: `INDEXSPLITSIZE`, `FTINDEXSPLITSIZE`

Version 8.3

- Added: `CACHERESTXQ`, `TEXTINCLUDE`, `ATTRINCLUDE`, `FTINCLUDE`, `ARCHIVENAME`

Version 8.2

- Removed: `EVENTPORT`, `CACHEQUERY`

Version 8.1

- Added: `IGNORECERT`, `RESTPATH`

Version 8.0

- Added: MIXUPDATES, AUTOOPTIMIZE, AUTHMETHOD, XINCLUDE
- Updated: PROXYPORT: default set to 0; will be ignored. PROXYHOST, NONPROXYHOSTS: empty strings will be ignored.

Version 7.8.1

- Updated: ADDARCHIVES: parsing of TAR and TGZ files.

Version 7.8

- Added: CSVPARSER, JSONPARSER, TEXTPARSER, HTMLPARSER, INLINELIMIT, TAILCALLS, DEFAULTDB, RUNQUERY
- Updated: WRITEBACK only applies to main-memory document instances.
- Updated: DEBUG option can be changed at runtime by users with admin permissions.
- Updated: default of INTPARSE is now `false`.
- Removed: HTMLOPT (replaced with HTMLPARSER), PARSEROPT (replaced with parser-specific options), DOTDISPLAY, DOTTY

Version 7.7

- Added: ADDCACHE, CHECKSTRINGS, FTINDEXSPLITSIZE, INDEXSPLITSIZE

Version 7.6

- Added: GLOBALLOCK
- Added: store local options in configuration file after `# Local Options` comments.

Version 7.5

- Added: options can now be set via system properties
- Added: a pragma expression can be used to locally change database options
- Added: USER, PASSWORD, LOG, LOGMSGMAXLEN, WEBPATH, RESTXQPATH HTTPLOCAL, CREATEONLY, STRIPNS
- Removed: HTTPPATH; HTTPPORT: `jetty.xml` configuration file is used instead
- Removed: global options cannot be changed anymore during the lifetime of a BaseX instance

Version 7.3

- Updated: KEEPALIVE, TIMEOUT: default values changed
- Removed: WILDCARDS; new index supports both fuzzy and wildcard queries
- Removed: SCORING; new scoring model will focus on lengths of text nodes and match options

Version 7.2

- Added: PROXYHOST, PROXYPORT, NONPROXYHOSTS, HTMLOPT
- Updated: TIMEOUT: ignore timeout for admin users

Version 7.1

- Added: ADDRAW, MAXLEN, MAXCATS, UPDINDEX
- Updated: BINDINGS

Version 7.0

- Added: SERVERHOST, KEEPALIVE, AUTOFLUSH, QUERYPATH

Part IV. Integration

Chapter 17. Integrating oXygen

Read this entry online in the BaseX Wiki.

This tutorial is part of the Getting Started Section. It describes how to access BaseX from the oXygen XML Editor. Currently, there are two variants how to use BaseX in oXygen:

- Resources in databases can be opened and modified.
- XPath/XQuery 3.0 expressions can be run by the query processor of BaseX.

Access Database Resources

Preparations

- First, start the BaseX WebDAV service.

Configuration

1. Go to menu *Options* → *Preferences* → *Data Sources*
2. In the Connections panel (in the lower area of the screen), click the *New* button (+)
3. Enter "BaseX-WebDAV" as connection name
4. Select "WebDAV" in the Data Source combo box
5. Fill in the appropriate connection details. Below, the default values are shown:
   - Set the URL to `http://localhost:8984/webdav`
   - Set the user name to `admin`
   - Set the password to `admin`
6. Now press *OK*, and your Data Source is ready for use



You can then access the database files via the Data Source Explorer: *Windows* → *Show View* → *Data Source Explorer*



Perform Queries

One-Time Setup

Preparations

1. Download one of the complete BaseX distributions (ZIP, EXE).
2. Charles Foster's XQJ implementation provides a default (client/server) and a local driver. If you want to use the first flavor, you need to start a BaseX Server instance.

Configure Data Source

1. Start oXygen and select *Options* → *Preferences* → *Data Sources*.
2. In the Data Sources panel, add a new data source using the *New* button (+).
3. Enter "BaseX" as name and select *XQuery API for Java (XQJ)* as type.
4. Add the following JAR files (downloaded in Preparations procedure) with the *Add Files* Button. The versions of the JAR files may differ.
   - `lib/xqj-api-1.0.jar`
   - `lib/xqj2-0.2.0.jar`
   - `lib/basex-xqj-8.6.jar`
   - `basex.jar` , if you want to use BaseX embedded
5. Under "Driver class", choose the preferred driver class:
   - Embedded: `net.xqj.basex.BaseXXQDataSource`
   - Client/server: `net.xqj.basex.local.BaseXXQDataSource`
6. Click *OK*.

Configure Connection

1. In the Connections section (in the same Preferences dialog from the Configure Data Source procedure), click *New* (+).
2. Enter "BaseX" as name and select "BaseX XQJ" as data source.
3. If you use the default driver, enter these values in the Connection Details section:

- port: `1984`
- serverName: `localhost`
- user: `admin`
- password: `admin`

4. Click *OK* to complete the connection configuration.
5. Click *OK* again to close the Preferences dialog.

Configure New Transformation Scenario

1. Select *Window* → *Show View* → *Transformation Scenarios*.
2. Select the *XQuery transformation* tree entry, and click + to add a new scenario.

   If this entry does not appear in the tree, click + and select *XQuery transformation* in the dropdown list.
3. Enter a name and an optional XML and XQuery URL (e.g. your query document/file).
4. Choose "BaseX XQJ" as Transformer from the combo box.
5. Click *OK* to complete the scenario configuration.

Execute Query

After the one-time setup steps are complete, execute a query using the transformation scenario. Start the transformation by clicking the red *Apply associated scenarios* button in the Transformation Scenarios window.



The results should immediately occur in the result panel.

Chapter 18. Integrating IntelliJ IDEA

Read this entry online in the BaseX Wiki.

This article is part of the Getting Started Section. It describes how to run XPath/XQuery code from within the IntelliJ IDEA IDE.

Installation

The following steps apply to all operating systems:

- Install either version of IntelliJ IDEA: the Community or Ultimate edition.
- Download your favorite BaseX distribution (JAR, ZIP, EXE): http://basex.org/download/.

This article focuses on Grzegorz Ligas'XQuery Support plugin.

After installing IDEA and BaseX, install the XQuery Support plugin by one of the following methods:

From the Start Screen

1. Start IDEA and select *Configure Plugins*.
2. In the Plugins window select *Browse Repositories*.
3. In the Browse Repositories window, search for (or scroll to) *XQuery Support*.
4. You will be prompted to restart IDEA to load the new plugin.

From the File Menu

1. Select *Settings*.
2. In the Settings window select *Plugins*.
3. In the Plugins window select *Browse Repositories*.
4. In the Browse Repositories window, search for (or scroll to) *XQuery Support*.
5. You will be prompted to restart IDEA to load the new plugin.

Setting Up

File Extensions and XQuery Flavor

- Start IDEA and navigate to *Settings* (OS dependent).
- In the Settings window select *Other Settings XQuery* and choose which XQuery flavor you would like to use, as well as new file extensions. (see attached screenshot)

Configuring The Processor

You can set up the plugin as a standalone processor or client.

Standalone

1. Start IDEA and navigate to *Settings* (OS dependent).
2. In the settings window select *Other Settings XQuery Data Sources*

3. Select *BaseX (native embedded)*.
4. Check the *User defined XQJ Driver* radio box.
5. Using the +, add the following `jars`: BaseX.jar, basex-api-8.6.1.jar, basex-xqj-8.6.jar, and xqj2-0.2.0.jar from your BaseX distribution.

Client

This assumes that you already have a database named `factbook`.

1. Start IDEA and navigate to *Settings* (OS dependent).
2. In the settings window select *Other Settings XQuery Data Sources*
3. Using the +, select *BaseX* as your data source
4. Fill in the appropriate connection details; e.g. default values:
   - `Host = localhost`
   - `Port = 1984`
   - `Database name = factbook`
   - `Username = admin`
   - `Password = admin`
5. Select *Apply*, then *OK* and your BaseX `factbook` database is ready to query.

Chapter 19. Integrating Eclipse

Read this entry online in the BaseX Wiki.

This article is part of the Getting Started Section. It describes how to run XPath/XQuery code from within the Eclipse IDE.

Another article describes how to compile and run BaseX with Eclipse.

Installation

The following steps apply to all operating systems:

- Install Version 3.7 (Indigo) of Eclipse: http://www.eclipse.org. Please note that more recent versions may work as well, but haven't been tested so far.
- download your favorite BaseX distribution (JAR, ZIP, EXE): http://basex.org/download/

Windows

It should be sufficient to install the official XQuery Development Tools Plugin (XQDT): http://www.xqdt.org/ Update Site: http://download.eclipse.org/webtools/incubator/repository/xquery/milestones/

Linux

- First, install the Dynamic Languages Toolkit (DLTK)Update Site: http://download.eclipse.org/releases/indigo/
- Next, install Marklogic's XQDT Dropin

Mac OSX

- Install Marklogic's XQDT Dropin

Setting up



Use BaseX as query processor in Eclipse You can set up the XQuery interpreter as standalone or client version, as shown on the screenshot:

Setting up as Standalone

1. Start Eclipse and go to *Preferences* → *XQuery* → *Interpreters*.
2. Add a new Interpreter with the *Add* button.
3. Enter "BaseX" as name and choose "Java XQuery Engine" as Interpreter type.
4. Point *Interpreter JAR/WAR* to the BaseX JAR archive
5. Choose `org.basex.BaseX` as *Main class*

Setting up as Client

1. Start Eclipse and go to *Preferences* → *XQuery* → *Interpreters*.
2. Add a new Interpreter with the *Add* button.
3. Enter "BaseX" as name and choose "Java XQuery Engine" as Interpreter type.
4. Point *Interpreter JAR/WAR* to the BaseX JAR archive
5. Choose `org.basex.BaseXClient` as *Main class*
6. Set interpreter arguments for your server, port, username and password, e.g. `-Uadmin -Padmin -nlocalhost -p1984`.

Usage

The query execution works as follows:

1. Create a new XQuery Project with *File* → *New* → *XQuery Project*.
2. Add a new XQuery Module with *File* → *New* → *XQuery Module*.
3. Edit your XQuery Module and execute it with *Run*.
4. The results are displayed in the Console window of Eclipse.

Part V. Query Features

Chapter 20. XQuery

Read this entry online in the BaseX Wiki.

Welcome to the Query Portal, which is one of the Main Sections of this documentation. BaseX provides an implementation of the W3 XPath and XQuery languages, which are tightly coupled with the underlying database store. However, the processor is also a flexible general purpose processor, which can access local and remote sources. High conformance with the official specifications is one of our main objectives, as the results of the XQuery Test Suite demonstrate. This section contains information on the query processor and its extensions:

XQuery 3.0 and XQuery 3.1

Features of the new XQuery Recommendations.

XQuery Extensions

Specifics of the BaseX XQuery processor.

Module Library

Additional functions included in the internal modules.

Java Bindings

Accessing and calling Java code from XQuery.

Repository

Install and manage XQuery and Java modules.

Full-Text

How to use BaseX as a full-fledged full-text processor.

Updates

Updating databases and local resources via XQuery Update.

Indexes

Available index structures and their utilization.

Serialization

Serialization parameters supported by BaseX.

Errors

Errors raised by XQuery expressions.

Chapter 21. XQuery 3.0

Read this entry online in the BaseX Wiki.

This article is part of the XQuery Portal. It provides a summary of the most important features of the XQuery 3.0 Recommendation.

Enhanced FLWOR Expressions

Most clauses of FLWOR expressions can be specified in an arbitrary order: additional `let` and `for` clauses can be put after a `where` clause, and multiple `where`, `order by` and `group by` statements can be used. This means that many nested loops can now be rewritten to a single FLWOR expression.

Example:

```
for $country in db:open('factbook')//country
where $country/@population > 100000000
for $city in $country//city[population > 1000000]
group by $name := $country/name[1]
count $id
return <country id='{ $id }' name='{ $name }'>{ $city/name }</country>
```

group by

FLWOR expressions have been extended to include the group by clause, which is well-established in SQL. `group by` can be used to apply value-based partitioning to query results:

XQuery:

```
for $ppl in doc('xmark')//people/person
let $ic := $ppl/profile/@income
let $income :=  if($ic < 30000) then
                   "challenge"
                else if($ic >= 30000 and $ic < 100000) then
                   "standard"
                else if($ic >= 100000) then
                   "preferred"
                else
                   "na"
group by $income
order by $income
return element { $income } { count($ppl) }
```

This query is a rewrite of Query #20 contained in the XMark Benchmark Suite to use `group by`. The query partitions the customers based on their income.

Result:

```
<challenge>4731</challenge>
<na>12677</na>
<preferred>314</preferred>
<standard>7778</standard>
```

In contrast to the relational GROUP BY statement, the XQuery counterpart concatenates the values of all non-grouping variables that belong to a specific group. In the context of our example, all nodes in `//people/person` that belong to the `preferred` partition are concatenated in `$ppl` after grouping has finished. You can see this effect by changing the return statement to:

```
...
return element { $income } { $ppl }
```

Result:

```
<challenge>
  <person id="person0">
    <name>Kasidit Treweek</name>
    …
  <person id="personX">
    …
</challenge>
```

Moreover, a value can be assigned to the grouping variable. This is shown in the following example:

XQuery:

```
let $data :=
  <xml>
    <person country='USA' name='John'/>
    <person country='USA' name='Jack'/>
    <person country='Germany' name='Johann'/>
  </xml>
for $person in $data/person
group by $country := $person/@country/string()
return element persons {
  attribute country { $country },
  $person/@name ! element name { data() }
}
```

Result:

```
<persons country="USA">
  <name>John</name>
  <name>Jack</name>
</persons>
<persons country="Germany">
  <name>Johann</name>
</persons>
```

count

The `count` clause enhances the FLWOR expression with a variable that enumerates the iterated tuples.

```
for $n in (1 to 10)[. mod 2 = 1]
count $c
return <number count="{ $c }" number="{ $n }"/>
```

allowing empty

The `allowing empty` provides functionality similar to outer joins in SQL:

```
for $n allowing empty in ()
return 'empty? ' || empty($n)
```

window

Window clauses provide a rich set of variable declarations to process sub-sequences of iterated tuples. An example:

```
for tumbling window $w in (2, 4, 6, 8, 10, 12, 14)
    start at $s when fn:true()
    only end at $e when $e - $s eq 2
return <window>{ $w }</window>
```

More information on window clauses, and all other enhancements, can be found in the specification.

Function Items

One of the most distinguishing features added in *XQuery 3.0* are *function items*, also known as *lambdas* or *lambda functions*. They make it possible to abstract over functions and thus write more modular code.

Examples:

Function items can be obtained in three different ways:

- Declaring a new *inline function*:

  ```
  let $f := function($x, $y) { $x + $y }
  return $f(17, 25)
  ```

  Result: `42`

- Getting the function item of an existing (built-in or user-defined) XQuery function. The arity (number of arguments) has to be specified as there can be more than one function with the same name:

  ```
  let $f := math:pow#2
  return $f(5, 2)
  ```

  Result: `25`

- *Partially applying* another function or function item. This is done by supplying only some of the required arguments, writing the placeholder `?` in the positions of the arguments left out. The produced function item has one argument for every placeholder.

  ```
  let $f := fn:substring(?, 1, 3)
  return (
    $f('foo123'),
    $f('bar456')
  )
  ```

  Result: `foo bar`

Function items can also be passed as arguments to and returned as results from functions. These so-called Higher-Order Functions like `fn:map` and `fn:fold-left` are discussed in more depth on their own Wiki page.

Simple Map Operator

The simple map operator `!` provides a compact notation for applying the results of a first to a second expression: the resulting items of the first expression are bound to the context item one by one, and the second expression is evaluated for each item. The map operator may be used as replacement for FLWOR expressions:

Example:

```
(: Simple map notation :)
(1 to 10) ! element node { . },
(: FLWOR notation :)
for $i in 1 to 10
return element node { $i }
```

In contrast to path expressions, the results of the map operator will not be made duplicate-free and returned in document order.

Try/Catch

The try/catch construct can be used to handle errors at runtime:

Example:

```
try {
  1 + '2'
} catch err:XPTY0004 {
  'Typing error: ' || $err:description
} catch * {
  'Error [' || $err:code || ']: ' || $err:description
}
```

Result: `Typing error: '+' operator: number expected, xs:string found.`

Within the scope of the catch clause, a number of variables are implicitly declared, giving information about the error that occurred:

- `$err:code` error code
- `$err:description` : error message
- `$err:value` : value associated with the error (optional)
- `$err:module` : URI of the module where the error occurred
- `$err:line-number` : line number where the error occurred
- `$err:column-number` : column number where the error occurred
- `$err:additional` : error stack trace

Switch

The switch statement is available in many other programming languages. It chooses one of several expressions to evaluate based on its input value.

Example:

```
for $fruit in ("Apple", "Pear", "Peach")
return switch ($fruit)
  case "Apple" return "red"
  case "Pear"  return "green"
  case "Peach" return "pink"
  default      return "unknown"
```

Result: `red green pink`

The expression to evaluate can correspond to multiple input values.

Example:

```
for $fruit in ("Apple", "Cherry")
return switch ($fruit)
  case "Apple"
  case "Cherry"
     return "red"
  case "Pear"
     return "green"
  case "Peach"
```

```
    return "pink"
  default
    return "unknown"
```

Result: `red red`

Expanded QNames

A *QName* can be prefixed with the letter "Q" and a namespace URI in the Clark Notation.

Examples:

- `Q{http://www.w3.org/2005/xpath-functions/math}pi()` returns the number π
- `Q{java:java.io.FileOutputStream}new("output.txt")` creates a new Java file output stream

Namespace Constructors

New namespaces can be created via so-called 'Computed Namespace Constructors'.

```
element node { namespace pref { 'http://url.org/' } }
```

String Concatenations

Two vertical bars `||` (also named *pipe characters*) can be used to concatenate strings. This operator is a shortcut for the `fn:concat()` function.

```
'Hello' || '' || 'Universe'
```

External Variables

Default values can be attached to external variable declarations. This way, an expression can also be evaluated if its external variables have not been bound to a new value.

```
declare variable $user external := "admin";
"User:", $user
```

Serialization

Serialization parameters can be defined within XQuery expressions. Parameters are placed in the query prolog and need to be specified as option declarations, using the `output` prefix.

Example:

```
declare namespace output = "http://www.w3.org/2010/xslt-xquery-serialization";
declare option output:omit-xml-declaration "no";
declare option output:method "xhtml";
<html/>
```

Result: `<?xml version="1.0" encoding="UTF-8"?><html></html>`

In BaseX, the `output` prefix is statically bound and can thus be omitted. Note that all namespaces need to be specified when using external APIs, such as XQJ.

Context Item

The context item can be specified in the prolog of an XQuery expression:

Example:

```
declare context item := document {
  <xml>
    <text>Hello</text>
    <text>World</text>
  </xml>
};

for $t in .//text()
return string-length($t)
```

Result: `5 5`

Annotations

XQuery 3.0 introduces annotations to declare properties associated with functions and variables. For instance, a function may be declared %public, %private, or %updating.

Example:

```
declare %private function local:max($x1, $x2) {
  if($x1 > $x2) then $x1 else $x2
};

local:max(2, 3)
```

Functions

The following functions have been added in the XQuery 3.0 Functions and Operators Specification:

`fn:analyze-string*` `fn:available-environment-variables`, `fn:element-with-id`, `fn:environment-variable`, `fn:filter`, `fn:fold-left`, `fn:fold-right`, `fn:for-each`, `fn:for-each-pair`, `fn:format-date`, `fn:format-dateTime`, `fn:format-integer`, `fn:format-number`, `fn:format-time`, `fn:function-arity`, `fn:function-lookup`, `fn:function-name`, `fn:generate-id`, `fn:has-children`, `fn:head`, `fn:innermost`, `fn:outermost`, `fn:parse-xml`, `fn:parse-xml-fragment`, `fn:path`, `fn:serialize`, `fn:tail`, `fn:unparsed-text`, `fn:unparsed-text-available`, `fn:unparsed-text-lines`, `fn:uri-collection`

New signatures have been added for the following functions:

`fn:document-uri`, `fn:string-join`, `fn:node-name`, `fn:round`, `fn:data`

Changelog

Version 8.4

- Added: %non-deterministic

Version 8.0

- Added: %basex:inline, %basex:lazy

Version 7.7

- Added: Enhanced FLWOR Expressions

Version 7.3

- Added: Simple Map Operator

Version 7.2

- Added: Annotations
- Updated: Expanded QNames

Version 7.1

- Added: Expanded QNames, Namespace Constructors

Version 7.0

- Added: String Concatenations

Chapter 22. Higher-Order Functions

Read this entry online in the BaseX Wiki.

This page present some *higher-order functions* of the XQuery specification. The BaseX-specific Higher-Order Functions Module contains some additional useful functions.

Function Items

Probably the most important new feature in XQuery 3.0 are *function items*, i. e., items that act as functions, but can also be passed to and from other functions and expressions. This feature makes functions *first-class citizens* of the language. The XQuery 3.0 page goes into details on how function items can be obtained.

Function Types

Like every XQuery item, function items have a *sequence type*. It can be used to specify the *arity* (number of arguments the function takes) and the argument and result types.

The most general function type is `function(*)`. It's the type of all function items. The following query for example goes through a list of XQuery items and, if it is a function item, prints its arity:

```
for $item in (1, 'foo', fn:concat#3, function($a) { 42 * $a })
where $item instance of function(*)
return fn:function-arity($item)
```

Result: `3 1`

The notation for specifying argument and return types is quite intuitive, as it closely resembles the function declaration. The XQuery function

```
declare function local:char-at(
  $str as xs:string,
  $pos as xs:integer
) as xs:string {
  fn:substring($str, $pos, 1)
};
```

for example has the type `function(xs:string, xs:integer) as xs:string`. It isn't possible to specify only the argument and not the result type or the other way round. A good place-holder to use when no restriction is wanted is `item()*`, as it matches any XQuery value.

Function types can also be nested. As an example we take `local:on-sequences`, which takes a function defined on single items and makes it work on sequences as well:

```
declare function local:on-sequences(
  $fun as function(item()) as item()*
) as function(item()*) as item()* {
  fn:for-each($fun, ?)
};
```

We willl see later how `fn:for-each(...)` works. The type of `local:on-sequences(...)` on the other hand is easily constructed, if a bit long:

`function(function(item()) as item()*) as function(item()*) as item()*`.

Higher-Order Functions

A *higher-order function* is a function that takes other functions as arguments and/or returns them as results. `fn:for-each` and `local:on-sequences` from the last chapter are nice examples.

With the help of higher-order functions, one can extract common patterns of *behavior* and abstract them into a library function.

Sequences

Some usage patterns on sequences are so common that the higher-order functions describing them are in the XQuery standard libraries. They are listed here, together with their possible XQuery implementation and some motivating examples.

fn:for-each

Signatures	`fn:for-each($seq as item()*, $function as function(item()) as item()*)) as item()*`
Summary	Applies the specified `$function` to every item of `$seq` and returns all results as a single sequence.

Examples	• Square all numbers from 1 to 10:
	`fn:for-each(1 to 10, math:pow(?, 2))`
	Result: `1 4 9 16 25 36 49 64 81 100`
	• Apply a list of functions to a string:
	`let $fs := (`
	`  fn:upper-case#1,`
	`  fn:substring(?, 4),`
	`  fn:string-length#1`
	`)`
	`return fn:for-each($fs, function($f) { $f('foobar') })`
	Result: `FOOBAR bar 6`
	• Process each item of a sequence with the arrow operator:
	`("one", "two", "three") => fn:for-each(fn:upper-case(?))`
	Result: `ONE TWO THREE`

XQuery 1.0	At the core, for-each is nothing else than a simple FLWOR expression:
	`declare function local:for-each(`
	`  $seq as item()*,`
	`  $fun as function(item()) as item()*`
	`) as item()* {`
	`  for $s in $seq`
	`  return $fun($s)`
	`};`

fn:filter

Signatures	`fn:filter($seq as item()*, $pred as function(item()) as xs:boolean)) as item()*`
Summary	Applies the boolean predicate `$pred` to all elements of the sequence `$seq`, returning those for which it returns `true()`.
Examples	• All even integers until 10: `fn:filter(1 to 10, function($x) { $x mod 2 eq 0 })`

Result: `2 4 6 8 10`

- Strings that start with an upper-case letter:

```
let $first-upper := function($str) {
  let $first := fn:substring($str, 1, 1)
  return $first eq fn:upper-case($first)
}
return fn:filter(('FooBar', 'foo', 'BAR'), $first-upper)
```

Result: `FooBar BAR`

- Inefficient prime number generator:

```
let $is-prime := function($x) {
  $x gt 1 and (every $y in 2 to ($x - 1) satisfies $x mod $y ne 0)
}
return filter(1 to 20, $is-prime)
```

Result: `2 3 5 7 11 13 17 19`

Note

`fn:filter` can be easily implemented with `fn:for-each`:

```
declare function local:filter($seq, $pred) {
  for-each(
    $seq,
    function($x) {
      if($pred($x)) then $x else ()
    }
  )
};
```

XQuery 1.0

At the core, for-each is nothing else than a filter expression:

```
declare function local:filter(
  $seq as item()*,
  $pred as function(item()) as xs:boolean
) as item()* {
  $seq[$pred(.)]
};
```

fn:for-each-pair

Signatures

`fn:for-each-pair($seq1 as item()*, $seq2 as item()*, $function as function(item(), item()) as item()*) as item()*`

Summary

Applies the specified `$function` to the successive pairs of items of `$seq1` and `$seq2`. Evaluation is stopped if one sequence yields no more items.

Examples

- Adding one to the numbers at odd positions:

```
fn:for-each-pair(
  fn:for-each(1 to 10, function($x) { $x mod 2 }),
  (1, 1, 1, 1, 1),
  function($a, $b) { $a + $b }
)
```

Result: `2 1 2 1 2`

- Line numbering:

```
let $number-words := function($str) {
  fn:string-join(
    fn:for-each-pair(
      1 to 1000000000,
      tokenize($str, ' +'),
      concat(?, ': ', ?)
    ),
    ''
  )
}
return $number-words('how are you?')
```

Result:

```
1: how
2: are
3: you?
```

- Checking if a sequence is sorted:

```
let $is-sorted := function($seq) {
  every $b in
    fn:for-each-pair(
      $seq,
      fn:tail($seq),
      function($a, $b) { $a le $b }
    )
  satisfies $b
}
return (
  $is-sorted(1 to 10),
  $is-sorted((1, 2, 42, 4, 5))
)
```

Result: `true false`

XQuery 1.0

```
declare function local:for-each-pair(
  $seq1 as item()*,
  $seq2 as item()*,
  $fun as function(item(), item()) as item()*
) as item()* {
  for $pos in 1 to min((count($seq1), count($seq2)))
  return $fun($seq1[$pos], $seq2[$pos])
};
```

Folds

A *fold*, also called *reduce* or *accumulate* in other languages, is a very basic higher-order function on sequences. It starts from a seed value and incrementally builds up a result, consuming one element from the sequence at a time and combining it with the aggregate of a user-defined function.

Folds are one solution to the problem of not having *state* in functional programs. Solving a problem in *imperative* programming languages often means repeatedly updating the value of variables, which isn't allowed in functional languages.

Calculating the *product* of a sequence of integers for example is easy in `Java`:

```
public int product(int[] seq) {
  int result = 1;
```

```
  for(int i : seq) {
    result = result * i;
  }
  return result;
}
```

Nice and efficient implementations using folds will be given below.

The *linear* folds on sequences come in two flavors. They differ in the direction in which they traverse the sequence:

fn:fold-left

Signatures	`fn:fold-left($seq as item()*, $seed as item()*, $function as function(item()*, item()) as item()*) as item()*`
Summary	The *left fold* traverses the sequence from the left. The query `fn:fold-left(1 to 5, 0, $f)` for example would be evaluated as: `$f($f($f($f($f(0, 1), 2), 3), 4), 5)`

Examples	• Product of a sequence of integers:
	`fn:fold-left(1 to 5, 1, function($result, $curr) { $result * $curr })`
	Result: `120`
	• Illustrating the evaluation order:
	`fn:fold-left(1 to 5, '$seed', concat('$f(', ?, ', ', ?, ')'))`
	Result: `$f($f($f($f($f($seed, 1), 2), 3), 4), 5)`
	• Building a decimal number from digits:
	`let $from-digits := fold-left(?, 0, function($n, $d) { 10 * $n + $d }) return ( $from-digits(1 to 5), $from-digits((4, 2)) )`
	Result: `12345 42`

XQuery 1.0	As folds are more general than *FLWOR* expressions, the implementation isn't as concise as the former ones: `declare function local:fold-left( $seq as item()*, $seed as item()*, $function as function(item()*, item()) as item()* ) as item()* { if(empty($seq)) then $seed else local:fold-left( fn:tail($seq), $function($seed, fn:head($seq)), $function`

```
  )
};
```

fn:fold-right

Signatures	`fn:fold-right($seq as item()*, $seed as item()*, $function as function(item(), item()*) as item()*) as item()*`
Summary	The *right fold* `fn:fold-right($seq, $seed, $fun)` traverses the sequence from the right. The query `fn:fold-right(1 to 5, 0, $f)` for example would be evaluated as: `$f(1, $f(2, $f(3, $f(4, $f(5, 0)))))`

Examples	• Product of a sequence of integers:
	
	`fn:fold-right(1 to 5, 1,`
	`  function($curr, $result) { $result * $curr }`
	`)`
	
	Result: `120`
	
	• Illustrating the evaluation order:
	
	`fn:fold-right(1 to 5, '$seed',`
	`  concat('$f(', ?, ', ', ?, ')')`
	`)`
	
	Result: `$f(1, $f(2, $f(3, $f(4, $f(5, $seed)))))`
	
	• Reversing a sequence of items:
	
	`let $reverse := fn:fold-right(?, (),`
	`  function($item, $rev) {`
	`  $rev, $item`
	`  }`
	`)`
	`return $reverse(1 to 10)`
	
	Result: `10 9 8 7 6 5 4 3 2 1`

XQuery 1.0	`declare function local:fold-right(`
	`  $seq as item()*,`
	`  $seed as item()*,`
	`  $function as function(item(), item()*) as item()*`
	`) as item()* {`
	`  if(empty($seq)) then $seed`
	`  else $function(`
	`  fn:head($seq),`
	`  local:fold-right(tail($seq), $seed, $function)`
	`  )`
	`};`
	
	Note that the order of the arguments of `$fun` are inverted compared to that in `fn:fold-left(...)`.

Chapter 23. XQuery 3.1

Read this entry online in the BaseX Wiki.

This article is part of the XQuery Portal. It provides a summary of the most important features of the XQuery 3.1 Recommendation.

Maps

A *map* is a function that associates a set of keys with values, resulting in a collection of key/value pairs. Each key/value pair in a map is called an entry. A key is an arbitrary atomic value, and the associated value is an arbitrary sequence. Within a map, no two entries have the same key, when compared using the `eq` operator. It is not necessary that all the keys should be mutually comparable (for example, they can include a mixture of integers and strings).

Maps can be constructed as follows:

```
map { },                                    (: empty map :)
map { 'key': true(), 1984: (<a/>, <b/>) },  (: map with two entries :)
map:merge(                                  (: map with ten entries :)
  for $i in 1 to 10
  return map { $i: 'value' || $i }
)
```

The function corresponding to the map has the signature `function($key as xs:anyAtomicType) as item()*`. The expression `$map($key)` returns the associated value; the function call `map:get($map, $key)` is equivalent. For example, if `$books-by-isbn` is a map whose keys are ISBNs and whose associated values are `book` elements, then the expression `$books-by-isbn("0470192747")` returns the `book` element with the given ISBN. The fact that a map is a function item allows it to be passed as an argument to higher-order functions that expect a function item as one of their arguments. As an example, the following query uses the higher-order function `fn:map($f, $seq)` to extract all bound values from a map:

```
let $map := map { 'foo': 42, 'bar': 'baz', 123: 456 }
return fn:for-each(map:keys($map), $map)
```

This returns some permutation of `(42, 'baz', 456)`.

Because a map is a function item, functions that apply to functions also apply to maps. A map is an anonymous function, so `fn:function-name` returns the empty sequence; `fn:function-arity` always returns `1`.

Like all other values, maps are immutable. For example, the `map:remove` function creates a new map by removing an entry from an existing map, but the existing map is not changed by the operation. Like sequences, maps have no identity. It is meaningful to compare the contents of two maps, but there is no way of asking whether they are "the same map": two maps with the same content are indistinguishable.

Maps may be compared using the `fn:deep-equal` function. The Map Module describes the available set of map functions.

Arrays

An *array* is a function that associates a set of positions, represented as positive integer keys, with values. The first position in an array is associated with the integer `1`. The values of an array are called its members. In the type hierarchy, array has a distinct type, which is derived from function. In BaseX, arrays (as well as sequences) are based on an efficient Finger Tree implementation.

Arrays can be constructed in two ways. With the square bracket notation, the comma serves as delimiter:

```
[],            (: empty array :)
[ (1, 2) ],    (: array with single member :)
[ 1 to 2, 3 ]  (: array with two members; same as: [ (1, 2), 3 ] :)
```

With the `array` keyword and curly brackets, the inner expression is evaluated as usual, and the resulting values will be the members of the array:

```
array { },           (: empty array;              same as: array { () } :)
array { (1, 2) },    (: array with two members;   same as: array { 1, 2 } :)
array { 1 to 2, 3 }  (: array with three members; same as: array { 1, 2, 3 } :)
```

The function corresponding to the array has the signature `function($index as xs:integer) as item()*`. The expression `$array($index)` returns an addressed member of the array. The following query returns the five array members `48 49 50 51 52` as result:

```
let $array := array { 48 to 52 }
for $i in 1 to array:size($array)
return $array($i)
```

Like all other values, arrays are immutable. For example, the `array:reverse` function creates a new array containing a re-ordering of the members of an existing array, but the existing array is not changed by the operation. Like sequences, arrays have no identity. It is meaningful to compare the contents of two arrays, but there is no way of asking whether they are "the same array": two arrays with the same content are indistinguishable.

Atomization

If an array is *atomized*, all of its members will be atomized. As a result, an atomized item may now result in more than one item. Some examples:

```
fn:data([1 to 2])        (: returns the sequence 1, 2 :)
[ 'a', 'b', 'c' ] = 'b'  (: returns true :)
<a>{ [ 1, 2 ] }</a>      (: returns <a>1 2</a> :)
array { 1 to 2 } + 3     (: error: the left operand returns two items :)
```

Atomization also applies to function arguments. The following query returns 5, because the array will be atomized to a sequence of 5 integers:

```
let $f := function($x as xs:integer*) { count($x) }
return $f([1 to 5])
```

However, the next query returns 1, because the array is already of the general type `item()`, and no atomization will take place:

```
let $f := function($x as item()*) { count($x) }
return $f([1 to 5])
```

Arrays can be compared with the `fn:deep-equal` function. The Array Module describes the available set of array functions.

Lookup Operator

The lookup operator provides some syntactic sugar to access values of maps or array members. It is introduced by the question mark (`?`) and followed by a specifier. The specifier can be:

1. A wildcard `*`,

2. The name of the key,

3. The integer offset, or

4. Any other parenthesized expression.

The following example demonstrates the four alternatives:

```
let $map := map { 'R': 'red', 'G': 'green', 'B': 'blue' }
return (
  $map?*          (: 1. returns all values; same as: map:keys($map) ! $map(.) :),
  $map?R          (: 2. returns the value associated with the key 'R'; same as:
 $map('R') :),
  $map?('G','B')  (: 3. returns the values associated with the key 'G' and 'B' :)
),

let $array := [ 'one', 'two', 'three' ]
return (
  $array?*         (: 1. returns all values; same as: (1 to array:size($array)) !
 $array(.) :),
  $array?1         (: 2. returns the first value; same as: $array(1) :),
  $array?(2 to 3)  (: 3. returns the second and third values; same as: (1 to 2) !
 $array(.) :)
)
```

The lookup operator can also be used without left operand. In this case, the context item will be used as input. This query returns `Akureyri`:

```
let $maps := (
  map { 'name': 'Guðrún', 'city': 'Reykjavík' },
  map { 'name': 'Hildur', 'city': 'Akureyri' }
)
return $maps[?name = 'Hildur'] ?city
```

Arrow Operator

The arrow operator `=>` provides a convenient alternative syntax for passing on functions to a value. The expression that precedes the operator will be supplied as first argument of the function that follows the arrow. If `$v` is a value and `f()` is a function, then `$v => f()` is equivalent to `f($v)`, and `$v => f($j)` is equivalent to `f($v, $j)`:

```
(: Returns 3 :)
count(('A', 'B', 'C')),
('A', 'B', 'C') => count(),
('A', 'B', 'C') => (function( $sequence) { count( $sequence)})(),

(: Returns W-E-L-C-O-M-E :)
string-join(tokenize(upper-case('w e l c o m e')), '-'),
'w e l c o m e' => upper-case() => tokenize() => string-join('-'),

(: Returns xfmdpnf :)
codepoints-to-string(
  for $i in string-to-codepoints('welcome')
  return $i + 1
),
(for $i in 'welcome' => string-to-codepoints()
 return $i + 1) => codepoints-to-string()
```

The syntax makes nested function calls more readable, as it is easy to see if parentheses are balanced.

String Constructor

The string constructor has been inspired by here document literals of the Unix shell and script languages. It allows you to generate strings that contain various characters that would otherwise be interpreted as XQuery delimiters.

The string constructors syntax uses two backticks and a square bracket for opening and closing a string:

```
(: Returns "This is a 'new' & 'flexible' syntax." :)
``["This is a 'new' & 'flexible' syntax."]``
```

XQuery expressions can be embedded via backticks and a curly bracket. The evaluated results will be separated with spaces, and all strings will eventually be concatenated:

```
(: Returns »Count 1 2 3, and I will be there.« :)
let $c := 1 to 3
return ``[»Count `{ $c }`, and I will be there.«]``
```

Serialization

Two Serialization methods have been added to the Serialization spec:

Adaptive Serialization

The `adaptive` serialization provides an intuitive textual representation for all XDM types, including maps and arrays, functions, attributes, and namespaces. All items will be separated by the value of the `item-separator` parameter, which by default is a newline character. It is utilized by the functions `prof:dump` and `fn:trace`.

Example:

```
declare option output:method 'adaptive';
<element id='id0'/>/@id,
xs:token("abc"),
map { 'key': 'value' },
true#0
```

Result:

```
id="id0"
xs:token("abc"),
map {
  "key": "value"
}
fn:true#0
```

JSON Serialization

The new `json` serialization output method can be used to serialize XQuery maps, arrays, atomic values and empty sequences as JSON.

The `json` output method has been introduced in BaseX before it was added to the official specification. It complies with the standard serialization rules and, at the same time, preserves the existing semantics:

- If an XML node of type `element(json)` is found, it will be serialized following the serialization rules of the JSON Module.
- Any other node or atomic value, map, array, or empty sequence will be serialized according to the rules in the specification.

The following two queries will both return the JSON snippet `{ "key": "value" }`:

```
declare option output:method 'json';
map { "key": "value" }
```

```
declare option output:method 'json';
<json type='object'>
  <key>value</key>
</json>
```

Functions

The following functions have been added in the XQuery 3.1 Functions and Operators Specification:

Map Functions

`map:merge`, `map:size`, `map:keys`, `map:contains`, `map:get`, `map:entry`, `map:put`, `map:remove`, `map:for-each`

Please check out the Map Module for more details.

Array Functions

`array:size`, `array:append`, `array:subarray`, `array:remove`, `array:insert-before`, `array:head`, `array:tail`, `array:reverse`, `array:join`, `array:flatten`, `array:for-each`, `array:filter`, `array:fold-left`, `array:fold-right`, `array:for-each-pair`

JSON Functions

With XQuery 3.1, native support for JSON objects was added. Strings and resources can be parsed to XQuery items and, as shown above, serialized back to their original form.

fn:parse-json

Signatures

- `fn:parse-json($input as xs:string) as item()?`
- `fn:parse-json($input as xs:string, $options as map(*)) as item()?`

Parses the supplied string as JSON text and returns its item representation. The result may be a map, an array, a string, a double, a boolean, or an empty sequence. The allowed options can be looked up in the specification.

```
parse-json('{ "name": "john" }')   (: yields { "name": "json" } :),
parse-json('[ 1, 2, 4, 8, 16]')    (: yields [ 1, 2, 4, 8, 16 ] :)
```

fn:json-doc

Signatures

- `fn:json-doc($uri as xs:string) as item()?`
- `fn:json-doc($uri as xs:string, $options as map(*)) as item()?`

Retrieves the text from the specified URI, parses the supplied string as JSON text and returns its item representation (see fn:parse-json for more details).

```
json-doc("http://ip.jsontest.com/")('ip')  (: returns your IP address :)
```

fn:json-to-xml

Signatures

- `fn:json-to-xml($string as xs:string?) as node()?`

Converts a JSON string to an XML node representation. The allowed options can be looked up in the specification.

```
json-to-xml('{ "message": "world" }')

(: result:
<map xmlns="http://www.w3.org/2005/xpath-functions">
  <string key="message">world</string>
</map> :)
```

fn:xml-to-json

Signatures

- `fn:xml-to-json($node as node()?) as xs:string?`

Converts an XML node, whose format conforms to the results created by fn:json-to-xml, to a JSON string representation. The allowed options can be looked up in the specification.

```
(: returns "JSON" :)
xml-to-json(<string xmlns="http://www.w3.org/2005/xpath-functions">JSON</string>)
```

fn:sort

Signatures

- `fn:sort($input as item()*) as item()*`
- `fn:sort($input as item()*, $collation as xs:string?) as xs:anyAtomicType*)) as item()*`
- `fn:sort($input as item()*, $collation as xs:string?, $key as function(item()*) as xs:anyAtomicType*)) as item()*`

Returns a new sequence with sorted `$input` items, using an optional `$collation`. If a `$key` function is supplied, it will be applied on all items. The items of the resulting values will be sorted using the semantics of the `lt` expression.

```
sort(reverse(1 to 3))                    (: yields 1, 2, 3 :),
reverse(sort(1 to 3))                    (: returns the sorted order in descending
 order :),
sort((3,-2,1), (), abs#1)                (: yields 1, -2, 3 :),
sort((1,2,3), (), function($x) { -$x })  (: yields 3, 2, 1 :),
sort((1,'a'))                            (: yields an error, as strings and
 integers cannot be compared :)
```

fn:contains-token

Signatures

- `fn:contains-token($input as xs:string*, $token as string) as xs:boolean`
- `fn:contains-token($input as xs:string*, $token as string, $collation as xs:string) as xs:boolean`

The supplied strings will be tokenized at whitespace boundaries. The function returns `true` if one of the strings equals the supplied token, possibly under the rules of a supplied collation:

```
contains-token(('a', 'b c', 'd'), 'c')               (: yields true :)
```

```
<xml class='one two'/>/contains-token(@class, 'one')  (: yields true :)
```

fn:parse-ietf-date

Signature

- `fn:parse-ietf-date($input as xs:string?) as xs:string?`

Parses a string in the IETF format (which is widely used on the Internet) and returns a `xs:dateTime` item:

```
fn:parse-ietf-date('28-Feb-1984 07:07:07')"             (: yields
 1984-02-28T07:07:07Z :),
fn:parse-ietf-date('Wed, 01 Jun 2001 23:45:54 +02:00')"  (: yields
 2001-06-01T23:45:54+02:00 :)
```

fn:apply

Signatures

- `fn:apply($function as function(*), $arguments as array(*)) as item()*`

The supplied `$function` is invoked with the specified `$arguments`. The arity of the function must be the same as the size of the array.

Example:

```
fn:apply(concat#5, array { 1 to 5 })           (: 12345 :)
fn:apply(function($a) { sum($a) }, [ 1 to 5 ])  (: 15 :)
fn:apply(count#1, [ 1,2 ])                     (: error. the array has two
 members :)
```

fn:random-number-generator

Signatures

- `fn:random-number-generator() as map(xs:string, item())`
- `fn:random-number-generator($seed as xs:anyAtomicType) as map(xs:string, item())`

Creates a random number generator, using an optional seed. The returned map contains three entries:

- `number` is a random double between 0 and 1
- `next` is a function that returns another random number generator
- `permute` is a function that returns a random permutation of its argument

The returned random generator is *deterministic*: If the function is called twice with the same arguments and in the same execution scope, it will always return the same result.

Example:

```
let $rng := fn:random-number-generator()
let $number := $rng('number')               (: returns a random number :)
let $next-rng := $rng('next')()             (: returns a new generator :)
let $next-number := $next-rng('number')     (: returns another random number :)
let $permutation := $rng('permute')(1 to 5) (: returns a random permutation of
 (1,2,3,4,5) :)
return ($number, $next-number, $permutation)
```

fn:format-number

The function has been extended to support scientific notation:

```
format-number(1984.42, '00.0e0')  (: yields 19.8e2 :)
```

fn:tokenize

If no separator is specified as second argument, a string will be tokenized at whitespace boundaries:

```
fn:tokenize("  a b  c d")  (: yields "a", "b", "c", "d" :)
```

fn:trace

The second argument can now be omitted:

```
fn:trace(<xml/>, "Node: ")/node()  (: yields the debugging output "Node: <xml/
>" :),
fn:trace(<xml/>)/node()            (: returns the debugging output "<xml/>" :)
```

fn:string-join

The type of the first argument is now `xs:anyAtomicType*`, and all items will be implicitly cast to strings:

```
fn:string-join(1 to 3)  (: yields the string "123" :)
```

fn:default-language

Returns the default language used for formatting numbers and dates. BaseX always returns `en`.

Appendix

The three functions `fn:transform`, `fn:load-xquery-module` and `fn:collation-key` may be added in a future version of BaseX as their implementation might require the use of additional external libraries.

Binary Data

Items of type `xs:hexBinary` and `xs:base64Binary` can be compared against each other. The following queries all yield `true`:

```
xs:hexBinary('') < xs:hexBinary('bb'),
xs:hexBinary('aa') < xs:hexBinary('bb'),
max((xs:hexBinary('aa'), xs:hexBinary('bb'))) = xs:hexBinary('bb')
```

Collations

XQuery 3.1 provides a default collation, which allows for a case-insensitive comparison of ASCII characters (`A-Z` = `a-z`). This query returns `true`:

```
declare default collation 'http://www.w3.org/2005/xpath-functions/collation/html-
ascii-case-insensitive';
'HTML' = 'html'
```

If the ICU Library is downloaded and added to the classpath, the full Unicode Collation Algorithm features get available in BaseX:

```
(: returns 0 (both strings are compared as equal) :)
compare('a-b', 'ab', 'http://www.w3.org/2013/collation/UCA?alternate=shifted')
```

Enclosed Expressions

Enclosed expression is the syntactical term for the expressions that are specified inside a function body, try/catch clauses, node constructors and some other expressions. In the following example expressions, its the empty sequence:

```
declare function local:x() { () }; i
try { () } catch * { () },
element x { () },
text { () }
```

With XQuery 3.1, the expression can be omitted. The following query is equivalent to the upper one:

```
declare function local:x() { };
try { } catch * { },
element x { }
text { }
```

Changelog

Version 8.6

- Updated: Collation argument was inserted between first and second argument.

Version 8.4

- Added: String Constructors, fn:default-language, Enclosed Expressions
- Updated: Adaptive Serialization, fn:string-join

Version 8.2

- Added: fn:json-to-xml, fn:xml-to-json.

Version 8.1

- Updated: arrays are now based on a Finger Tree implementation.

Introduced with Version 8.0.

Chapter 24. XQuery Extensions

Read this entry online in the BaseX Wiki.

This article is part of the XQuery Portal. It lists extensions and optimizations that are specific to the BaseX XQuery processor.

Suffixes

In BaseX, files with the suffixes `.xq`, `.xqm`, `.xqy`, `.xql`, `.xqu` and `.xquery` are treated as XQuery files. In XQuery, there are main and library modules:

- Main modules have an expression as query body. Here is a minimum example:

```
'Hello World!'
```

- Library modules start with a module namespace declaration and have no query body:

```
module namespace hello = 'http://basex.org/examples/hello';

declare function hello:world() {
  'Hello World!'
};
```

We recommend `.xq` as suffix for for main modules, and `.xqm` for library modules. However, the actual module type will dynamically be detected when a file is opened and parsed.

Option Declarations

Local database options can be set in the prolog of an XQuery main module. In the option declaration, options need to be bound to the Database Module namespace. All values will be reset after the evaluation of a query:

```
declare option db:chop 'false';
doc('doc.xml')
```

Pragmas

BaseX Pragmas

Many optimizations in BaseX will only be performed if an expression is *deterministic* (i. e., if it always yields the same output and does not have side effects). By flagging an expression as non-deterministic, optimizations and query rewritings can be suppressed:

```
sum( (# basex:non-deterministic #) {
  1 to 100000000
})
```

This pragma can be helpful when debugging your code.

Database Pragmas

All local database options can be assigned via pragmas. Some examples:

- *Version 9.0* : Enforce query to be rewritten for index access. This can e. g. be helpful if the name of a database is not static (see Enforce Rewritings for more examples):

```
(# db:enforceindex #) {
  for $db in ('persons1', 'persons2', 'persons3')
  return db:open($db)//name[text() = 'John']
}
```

- *Version 9.0* : Temporarily disable node copying in node constructors (see `COPYNODE` for more details). The following query will be evaluated faster, and take much less memory, than without pragma, because the database nodes will not be fully copied, but only attached to the new `xml` parent element:

```
file:write(
  'wrapped-db-nodes.xml',
  (# db:copynode false #) {
    <xml>{ db:open('huge') }</xml>
  }
)
```

Annotations

basex:inline

`%basex:inline([limit])` controls if functions will be inlined.

If XQuery functions are *inlined*, the function call will be replaced by a FLWOR expression, in which the function variables are bound to let clauses, and in which the function body is returned. This optimization triggers further query rewritings that will speed up your query. An example:

Query:

```
declare function local:square($a) { $a * $a };
for $i in 1 to 3
return local:square($i)
```

Query after function inlining:

```
for $i in 1 to 3
return
  let $a := $i
  return $a * $a
```

Query after further optimizations:

```
for $i in 1 to 3
return $i * $i
```

By default, XQuery functions will be *inlined* if the query body is not too large and does not exceed a fixed number of expressions, which can be adjusted via the `INLINELIMIT` option.

The annotation can be used to overwrite this global limit: Function inlining can be enforced if no argument is specified. Inlining will be disabled if `0` is specified.

Example:

```
(: disable function inlining; the full stack trace will be shown... :)
declare %basex:inline(0) function local:e() { error() };
local:e()
```

Result:

```
Stopped at query.xq, 1/53:
[FOER0000] Halted on error().

Stack Trace:
- query.xq, 2/9
```

basex:lazy

`%basex:lazy` enforces the lazy evaluation of a global variable. An example:

Example:

```
declare %basex:lazy variable $january := doc('does-not-exist');
if(month-from-date(current-date()) == 1) then $january else ()
```

The annotation ensures that an error will only be thrown if the condition yields true. Without the annotation, the error will always be raised, because the referenced document is not found.

Serialization

- `basex` is used as the default serialization method: nodes are serialized as XML, atomic values are serialized as string, and items of binary type are output in their native byte representation. Function items (including maps and arrays) are output just like with the adaptive method.
- `csv` allows you to output XML nodes as CSV data (see the CSV Module for more details).

For more information and some additional BaseX-specific parameters, see the article on Serialization.

Non-determinism

In XQuery, *deterministic* functions are "guaranteed to produce ·identical· results from repeated calls within a single ·execution scope· if the explicit and implicit arguments are identical". In BaseX, many extension functions are non-deterministic or side-effecting. If an expression is internally flagged as non-deterministic, various optimizations that might change their execution order will not be applied.

```
(: QUERY A... :)
let $n := 456
for $i in 1 to 2
return $n

(: ...will be optimized to :)
for $i in 1 to 2
return 456

(: QUERY B will not be rewritten :)
let $n := random:integer()
for $i in 1 to 2
return $n
```

In some cases, functions may contain non-deterministic code, but the query compiler may not be able to detect this statically. See the following example:

```
for $read in (file:read-text#1, file:read-binary#1)
let $ignored := non-deterministic $read('input.file')
return ()
```

Two non-deterministic functions will be bound to `$read`, and the result of the function call will be bound to `$ignored`. As the variable is not referenced in the subsequent code, the let clause would usually be discarded

by the compiler. In the given query, however, execution will be enforced because of the BaseX-specific `non-deterministic` keyword.

Miscellaneous

Various other extensions are described in the articles on XQuery Full Text and XQuery Update.

Chapter 25. Module Library

Read this entry online in the BaseX Wiki.

This article is part of the XQuery Portal.

In addition to the standard XQuery Functions, BaseX comes with some hundred additional functions, which are packaged in various modules.

The namespaces of the following modules are statically known. This means that they need not be (but may be) declared in the query prolog.

Module	Description	Prefix	Namespace URI
Admin	Functions restricted to admin users.	`admin`	`http://basex.org/modules/admin`
Archive	Creating and processing ZIP archives.	`archive`	`http://basex.org/modules/archive`
Array	Functions for handling arrays.	`array`	`http://www.w3.org/2005/xpath-functions/array`
Binary	Processing binary data.	`bin`	`http://expath.org/ns/binary`
Client	Executing commands and queries on remote BaseX servers.	`client`	`http://basex.org/modules/client`
Conversion	Converting data (binary, numeric) to other formats.	`convert`	`http://basex.org/modules/convert`
Cryptography	Cryptographic functions, based on the EXPath Cryptograhic module.	`crypto`	`http://expath.org/ns/crypto`
CSV	Functions for processing CSV input.	`csv`	`http://basex.org/modules/csv`
Database	Functions for accessing and updating databases.	`db`	`http://basex.org/modules/db`
Fetch	Functions for fetching resources identified by URIs.	`fetch`	`http://basex.org/modules/fetch`
File	File handling, based on the latest draft of the EXPath File module.	`file`	`http://expath.org/ns/file`
Full-Text	Functions for performing full-text operations.	`ft`	`http://basex.org/modules/ft`
Hashing	Cryptographic hash functions.	`hash`	`http://basex.org/modules/hash`
Higher-Order	Additional higher-order functions that are not in the standard libraries.	`hof`	`http://basex.org/modules/hof`
HTML	Functions for converting HTML input to XML documents.	`html`	`http://basex.org/modules/html`

HTTP	Sending HTTP requests, based on the EXPath HTTP module.	`http`	`http://expath.org/ns/http-client`
Index	Functions for requesting details on database indexes.	`index`	`http://basex.org/modules/index`
Inspection	Functions for extracting internal module information.	`inspect`	`http://basex.org/modules/inspect`
Jobs	Organization of running commands and queries.	`jobs`	`http://basex.org/modules/jobs`
JSON	Parsing and serializing JSON documents.	`json`	`http://basex.org/modules/json`
Lazy	Functions for handling lazy items.	`lazy`	`http://basex.org/modules/lazy`
Map	Functions for handling maps (key/value pairs).	`map`	`http://www.w3.org/2005/xpath-functions/map`
Math	Mathematical operations, extending the W3C Working Draft.	`math`	`http://www.w3.org/2005/xpath-functions/math`
Output	Functions for simplifying formatted output.	`out`	`http://basex.org/modules/out`
Process	Executing system commands from XQuery.	`proc`	`http://basex.org/modules/proc`
Profiling	Functions for profiling code snippets.	`prof`	`http://basex.org/modules/prof`
Random	Functions for creating random numbers.	`random`	`http://basex.org/modules/random`
Repository	Installing, deleting and listing packages.	`repo`	`http://basex.org/modules/repo`
SQL	JDBC bridge to access relational databases.	`sql`	`http://basex.org/modules/sql`
Strings	Functions for performing string computations.	`strings`	`http://basex.org/modules/strings`
Unit	Unit testing framework.	`unit`	`http://basex.org/modules/unit`
Update	Functions for performing updates. *Introduced with Version 9.0.*	`update`	`http://basex.org/modules/update`
User	Creating and administering database users.	`user`	`http://basex.org/modules/user`
Utility	Various utility and helper functions.	`util`	`http://basex.org/modules/util`
Validation	Validating documents: DTDs, XML Schema, RelaxNG.	`validate`	`http://basex.org/modules/validate`

Web	Convenience functions for building web applications.	`web`	`http://basex.org/modules/web`
XQuery	Evaluating new XQuery expressions at runtime.	`xquery`	`http://basex.org/modules/xquery`
XSLT	Stylesheet transformations, based on Java's and Saxon's XSLT processor.	`xslt`	`http://basex.org/modules/xslt`
ZIP	ZIP functionality, based on the EXPath ZIP module (soon obsolete).	`zip`	`http://expath.org/ns/zip`

Some additional external modules exist, which can be used as follows:

- The `basex-api` package must be included in the classpath. This is automatically the case if you use one of the complete distributions (zip, exe, war) of BaseX.
- The modules must be explicitly imported in the query prolog.

Module	Description	Prefix	Namespace URI
Geo	Functions for processing geospatial data.	`geo`	`http://expath.org/ns/geo`
Request	Server-side functions for handling HTTP Request data.	`request`	`http://exquery.org/ns/request`
RESTXQ	Helper functions for the RESTXQ API.	`rest`	`http://exquery.org/ns/restxq`
Session	Functions for handling server-side HTTP Sessions.	`session`	`http://basex.org/modules/session`
Sessions	Functions for managing all server-side HTTP Sessions.	`sessions`	`http://basex.org/modules/sessions`

Chapter 26. Java Bindings

Read this entry online in the BaseX Wiki.

This article is part of the XQuery Portal. It demonstrates different ways to invoke Java code from XQuery, and it presents extensions to access the current query context from Java.

The Java Binding feature is an extensibility mechanism which enables developers to directly access Java variables and execute code from XQuery. Addressed Java code must either be contained in the Java classpath, or it must be located in the Repository.

Please bear in mind that the execution of Java code may cause side effects that conflict with the functional nature of XQuery, or may introduce new security risks to your project.

Identification

Classes

A Java class is identified by a namespace URI. The original URI is rewritten as follows:

1. The URI Rewriting steps are applied to the URI.
2. Slashes in the resulting URI are replaced with dots.
3. The last path segment of the URI is capitalized and rewritten to CamelCase.

The normalization steps are skipped if the URI is prefixed with `java:`. See the following examples:

- `http://basex.org/modules/meta-data` → `org.basex.modules.MetaData`
- `java:java.lang.String` → `java.lang.String`

Functions and Variables

Java functions and variables can be referenced and evaluated by the existing XQuery function syntax:

- The namespace of the function name identifies the Java class.
- The local part of the name, which is rewritten to camel case, identifies a variable or function of that class.
- The middle dot character (·, a valid character in XQuery names, but not in Java) can be used to append exact Java parameter types to the function name. Class types must be referenced by their full path.

Type	XQuery	Java
Variable	`Q{java.lang.Integer}MIN_VALUE`	`Integer.MIN_VALUE`
Function	`Q{java.lang.Object}hash-code()`	`object.hashCode()`
Function with types	`Q{java.lang.String}split·Q{java.lang.String}Q{java.lang.int}(';', 3)`	`java.lang.String.split(';', 3)`

As XQuery and Java have different type systems, XQuery arguments are converted to equivalent Java values, and the result of a Java function is converted back to an XQuery value (see Data Types).

If a Java function is not found, XQuery values may need to be cast the target type. For example, if a Java function expects a primitive `int` value, you will need to convert your XQuery integers to `xs:int`.

Namespace Declarations

In the following example, Java's `Math` class is referenced. When executed, the query returns the cosine of an angle by calling the static method `cos()`, and the value of π by addressing the static variable via `PI()`:

```
declare namespace math = "java:java.lang.Math";
math:cos(xs:double(0)), math:PI()
```

With the Expanded QName notation of XQuery 3.0, the namespace can directly be embedded in the function call:

```
Q{java:java.lang.Math}cos(xs:double(0))
```

The constructor of a class can be invoked by calling the virtual function `new()`. Instance methods can then called by passing on the resulting Java object as first argument. In the following example, 256 bytes are written to the file `output.txt`. First, a new `FileWriter` instance is created, and its `write()` function is called in the next step:

```
declare namespace fw = "java.io.FileWriter";
let $file := fw:new('output.txt')
return (
  for $i in 0 to 255
  return fw:write($file, xs:int($i)),
  fw:close($file)
)
```

If the result of a Java call contains invalid XML characters, it will be rejected. The validity check can be disabled by setting the CHECKSTRINGS option to false. The following query writes a file with a single 00-byte, which will then be successfully read via Java functions:

```
declare namespace br = 'java.io.BufferedReader';
declare namespace fr = 'java.io.FileReader';

declare option db:checkstrings 'false';

file:write-binary('00.bin', xs:hexBinary('00')),
br:new(fr:new('00.bin')) ! (br:readLine(.), br:close(.))
```

Note that Java code cannot be pre-compiled, and will as such be evaluated slower than optimized XQuery code.

Module Imports

An alternative solution is to access Java code by *importing* classes as modules. A new instance of the addressed class will be created, which can then be referenced in the query body.

The following (side-effecting) example returns the number of distinct values added to a hash set. The boolean values returned by `set:add()` will be swallowed:

```
import module namespace set = "java:java.util.HashSet";
prof:void(
  for $s in ("one", "two", "one")
  return set:add($s)
),
set:size()
```

The advantages of this approach is the execution of imported classes is more efficient than the execution of instances that are created at runtime via `new()`. A drawback is that no arguments can be passed on to the class constructor. As a consequence, the import fails if the addressed class has no default constructor, but at least one constructor with arguments.

Integration

Java classes can be coupled even more closely to the BaseX core library. If a class inherits the abstract QueryModule class, the two variables queryContext and staticContext get available, which provide access to the global and static context of a query.

The QueryResource interface can be implemented to enforce finalizing operations, such as the closing of opened connections or resources in a module. Its `close()` method will be called after a query has been fully evaluated.

Annotations

The internal properties of functions can be assigned via annotations:

- Java functions can only be executed by users with Admin permissions. You may annotate a function with `@Requires(<Permission>)` to also make it accessible to users with less privileges.
- Java code is treated as *non-deterministic*, as its behavior cannot be predicted by the XQuery processor. You may annotate a function as `@Deterministic` if you know that it will have no side-effects and will always yield the same result.
- Java code is treated as *context-independent*. If a function accesses the query context, it should be annotated as `@ContextDependent`
- Java code is treated as *focus-independent*. If a function accesses the current context item, position or size, it should be annotated as `@FocusDependent`

The following XQuery code invokes two Java methods. The first Java function retrieves information from the static query context, and the second one throws a query exception:

```
import module namespace context = 'org.basex.examples.query.ContextModule';

element user {
  context:user()
},
element to-int {
  try { context:to-int('abc') }
  catch * { 'Error in line', $err:line-number }
}
```

The imported Java class is shown below:

```
package org.basex.examples.query;

import org.basex.query.*;
import org.basex.query.value.item.*;
import org.basex.util.*;

/**
 * This example inherits the {@link QueryModule} class and
 * implements the QueryResource interface.
 */
public class ContextModule extends QueryModule implements QueryResource {
  /**
   * Returns the name of the logged in user.
   * @return user
   */
  @Requires(Permission.NONE)
  @Deterministic
  @ContextDependent
  public String user() {
    return queryContext.context.user.name;
  }

  /**
   * Converts the specified string to an integer.
   * @param value string representation
   * @return integer
```

```
   * @throws QueryException query exception
   */
  @Requires(Permission.NONE)
  @Deterministic
  public int toInt(final String value) throws QueryException {
    try {
      return Integer.parseInt(value);
    } catch(NumberFormatException ex) {
      throw new QueryException(ex.getMessage());
    }
  }

  @Override
  public void close() {
    // see description above
  }
}
```

The result will look as follows:

```
<user>admin</admin>
<to-int>Error in line 6</to-int>
```

Please visit the XQuery 3.0 specification if you want to get more insight into function properties.

Locking

By default, a Java function will be executed in parallel with other code. However, if a Java function performs sensitive write operations, it is advisable to explicitly lock the code. This can be realized via locking annotations:

```
  @Lock(write = { "HEAVYIO" })
  public void write() {
    // ...
  }

  @Lock(read = { "HEAVYIO" })
  public void read() {
    // ...
  }
```

If an XQuery expression is run which calls the Java `write()` function, every other query that calls `write()` or `read()` needs to wait for the query to be finished. If a query calls the `read()` function, only those queries are queued that call `write()`, because this function is only annotated with a `read` lock. More details on parallel query execution can be found in the article on Transaction Management.

Data Types

The following table lists the mappings of XQuery and Java types:

XQuery Type	Java Type
`xs:string`	`String`, `char`, `Character`
`xs:boolean`	`boolean`, `Boolean`
`xs:byte`	`byte`, `Byte`
`xs:short`	`short`, `Short`
`xs:int`	`int`, `Integer`
`xs:long`	`long`, `Long`
`xs:float`	`float`, `Float`

`xs:double`	`double`, `Double`
`xs:decimal`	`java.math.BigDecimal`
`xs:integer`	`java.math.BigInteger`
`xs:QName`	`javax.xml.namespace.QName`
`xs:anyURI`	`java.net.URI`, `java.net.URL`
empty sequence	`null`

URI Rewriting

Before a Java class or module is accessed, its namespace URI will be normalized:

1. If the URI is a URL:
   a. colons will be replaced with slashes,
   b. in the URI authority, the order of all substrings separated by dots is reversed, and
   c. dots in the authority and the path are replaced by slashes. If no path exists, a single slash is appended.
2. Otherwise, if the URI is a URN, colons will be replaced with slashes.
3. Characters other than letters, dots and slashes will be replaced with dashes.
4. If the resulting string ends with a slash, the `index` string is appended.

If the resulting path has no file suffix, it may point to either an XQuery module or a Java archive. The following examples show some rewritings:

- `http://basex.org/modules/hello/World` → `org/basex/modules/hello/World`
- `http://www.example.com` → `com/example/www/index`
- `a/little/example` → `a/little/example`
- `a:b:c` → `a/b/c`

Changelog

Version 8.4

- Updated: Rewriting rules

Version 8.2

- Added: URI Rewriting: support for URNs

Version 8.0

- Added: `QueryResource` interface, called after a query has been fully evaluated.

Version 7.8

- Added: Java locking annotations
- Updated: `context` variable has been split into `queryContext` and `staticContext`.

Version 7.2.1

- Added: import of Java modules, context awareness

- Added: Packaging, URI Rewriting

Chapter 27. Repository

Read this entry online in the BaseX Wiki.

This article is part of the XQuery Portal. It describes how external XQuery modules and Java code can be installed in the XQuery module repository, and how new packages are built and deployed.

Introduction

One of the things that makes languages successful is the availability of external libraries. As XQuery comes with only 150 pre-defined functions, which cannot meet all requirements, additional library modules exist – such as FunctX – which extend the language with new features.

BaseX offers the following mechanisms to make external modules accessible to the XQuery processor:

1. The internal Packaging mechanism will install single XQuery and JAR modules in the repository.
2. The EXPath Packaging system provides a generic mechanism for adding XQuery modules to query processors. A package is defined as a `.xar` archive, which encapsulates one or more extension libraries.

Accessing Modules

Library modules can be imported with the `import module` statement, followed by a freely choosable prefix and the namespace of the target module. The specified location may be absolute or relative; in the latter case, it is resolved against the location (i.e., *static base URI*) of the calling module. Import module statements must be placed at the beginning of a module:

Main Module `hello-universe.xq`:

```
import module namespace m = 'http://basex.org/modules/hello' at 'hello-world.xqm';
m:hello("Universe")
```

Library Module `hello-world.xqm` (in the same directory):

```
module namespace m = 'http://basex.org/modules/Hello';
declare function m:hello($world) {
  'Hello ' || $world
};
```

Repository modules are stored in the `repo` directory, which resides in your home directory. XQuery modules can be manually copied to the repository directory or installed and deleted via commands.

If a module has been placed in the repository (see below), there is no need to specify the location. The following example calls a function from the FunctX module:

```
import module namespace functx = 'http://www.functx.com';
functx:capitalize-first('test')
```

Commands

There are various ways to organize your packages:

- Execute BaseX REPO commands (listed below)
- Call XQuery functions of the Repository Module
- Use the GUI (*Options* → *Packages*)

You can even manually add and remove packages in the repository directory; all changes will automatically be detected by BaseX.

Installation

A module or package can be installed with `REPO INSTALL`. The path to the file has to be given as a parameter:

```
REPO INSTALL http://files.basex.org/modules/expath/functx-1.0.xar
REPO INSTALL hello-world.xqm
```

The installation will only succeed if the specified file conforms to the constraints described below. If you know that your input is valid, you may as well copy the files directly to the repository directory, or edit its contents in the repository without deleting and reinstalling them.

Listing

All currently installed packages can be listed with `REPO LIST`. The names of all packages are listed, along with their version, their package type, and the repository path:

```
Name                   Version  Type      Path
-----------------------------------------------------------------
http://www.functx.com  1.0      EXPath    http-www.functx.com-1.0
```

Removal

A package can be deleted with `REPO DELETE` and an additional argument, containing its name or the name suffixed with a hyphen and the package version:

```
REPO DELETE http://www.functx.com
REPO DELETE http://www.functx.com-1.0
```

Packaging

XQuery

If an XQuery file is specified as input for the install command, it will be parsed as XQuery library module. If the file can successfully be parsed, the module URI will be rewritten to a file path and attached with the `.xqm` file suffix, and the original file will possibly be renamed and copied to that path into the repository.

Example:

Installation (the original file will be copied to the `org/basex/modules/Hello` sub-directory of the repository):

```
REPO INSTALL http://files.basex.org/modules/org/basex/modules/Hello/HelloWorld.xqm
```

Importing the repository module:

```
import module namespace m = 'http://basex.org/modules/Hello';
m:hello("Universe")
```

Java

For general notes on importing Java classes, please read the Java Bindings article on Module Imports.

Java archives (JARs) may contain one or more class files. One of them will be chosen as main class, which must be specified in a `Main-Class` entry in the manifest file (`META-INF/MANIFEST.MF`). This fully qualified Java class name will be rewritten to a file path by replacing the dots with slashes and attaching the `.jar` file suffix, and the original file will be renamed and copied to that path into the repository.

If the class will be imported in the prolog of the XQuery module, an instance of it will be created, and its public functions can then be addressed from XQuery. A class may extend the `QueryModule` class to get access to the current query context and to be enriched by some helpful annotations (see Annotations).

Example:

Structure of the `HelloWorld.jar` archive:

```
META-INF/
  MANIFEST.MF
org/basex/modules/
  Hello.class
```

Contents of the file `MANIFEST.mf` (the whitespaces are obligatory):

```
Manifest-Version: 1.0
Main-Class: org.basex.modules.Hello
```

Contents of the file `Hello.java` (comments removed):

```
package org.basex.modules;
public class Hello {
  public String hello(final String world) {
    return "Hello " + world;
  }
}
```

Installation (the file will be copied to `org/basex/modules/Hello.jar`):

```
REPO INSTALL HelloWorld.jar
```

XQuery file `HelloUniverse.xq` (same as above):

```
import module namespace m = 'http://basex.org/modules/Hello';
m:hello("Universe")
```

After having installed the module, all of the following URIs can be used in XQuery to import this module or call its functions (see URI Rewriting for more information):

```
http://basex.org/modules/Hello
org/basex/modules/Hello
org.basex.modules.Hello
```

Additional Libraries

Introduced with Version 9.0:

A Java class may depend on additional libraries. The dependencies can be resolved by creating a fat JAR file, i.e., extracting all files of the library archives and producing a single, flat JAR package.

Another solution is to copy the libraries into a `lib` directory of the JAR package. If the package will be installed, the additional library archives will be extracted and copied to a hidden sub-directory in the repository. If the package will be deleted, the hidden sub-directory will be removed as well.

Examplary contents of
`Image.jar`

```
lib/
  Images.jar
META-INF/
  MANIFEST.MF
org/basex/modules/
```

```
  Image.class
```

Directory structure of the repository directory after installing the package

```
org/basex/modules/
  Image.class
  .Images/
    Images.jar
```

Combined

Introduced with Version 9.0:

It makes sense to combine the advantages of XQuery and Java packages:

- Instead of directly calling Java code, a wrapper module can be provided. This module contains functions that invoke the Java functions.
- These functions can be strictly typed. This reduces the danger of erroneous or unexpected conversions between XQuery and Java code.
- In addition, the entry functions can have properly maintained XQuery comments.

XQuery and Java can be combined as follows:

- First, a JAR package is created (as described above).
- A new XQuery wrapper module is created, which is named identically to the Java main class.
- The URL of the `import module` statement in the wrapper module must start with the `java:` prefix.
- The finalized XQuery module must be copied into the JAR file, and placed in the same directory as the Java main class.

If the resulting JAR file is installed, the embedded XQuery module will be extracted, and will be called first if the module will be imported.

Main Module `hello-universe.xq`

```
import module namespace m = 'http://basex.org/modules/Hello';
m:hello("Universe")
```

Wrapper Module `Hello.xqm`

```
module namespace hello = 'http://basex.org/modules/Hello';

(: Import JAR file :)
import module namespace java = 'java:org.basex.modules.Hello';

(:~
 : Say hello to someone.
 : @param  $world  the one to be greeted
 : @return welcome string
 :)
declare function hello:hello(
  $world  as xs:string
) as xs:string {
  java:hello($world)
```

```
};
```

Java class `Hello.java`

```
package org.basex.modules;

public class Hello {
  public String hello(final String world) {
    return "Hello " + world;
  }
}
```

If the JAR file is installed, `Combined` will be displayed as type:

```
REPO INSTALL http://files.basex.org/modules/org/basex/modules/Hello.jar
REPO LIST

Name                      Version  Type      Path
------------------------------------------------------------------------
org.basex.modules.Hello   -        Combined  org/basex/modules/Hello.xqm
```

EXPath Packaging

The EXPath specification defines how the structure of a .xar archive shall look like. The package contains at its root a package descriptor named `expath-pkg.xml`. This descriptor presents some meta data about the package as well as the libraries which it contains and their dependencies on other libraries or processors.

XQuery

Apart from the package descriptor, a `.xar` archive contains a directory which includes the actual XQuery modules. For example, the FunctX XAR archive is packaged as follows:

```
expath-pkg.xml
functx/
  functx.xql
  functx.xsl
```

Java

If you want to package an EXPath archive with Java code, some additional requirements have to be fulfilled:

- Apart from the package descriptor `expath-pkg.xml`, the package has to contain a descriptor file at its root, defining the included jars and the binary names of their public classes. It must be named `basex.xml` and must conform to the following structure:

```
<package xmlns="http://expath.org/ns/pkg">
  <jar>...</jar>
    ....
    <class>...</class>
    <class>...</class>
    ....
</package>
```

- The jar file itself along with an XQuery file defining wrapper functions around the java methods has to reside in the module directory. The following example illustrates how java methods are wrapped with XQuery functions:

Example: Suppose we have a simple class `Printer` having just one public method `print()`:

```
package test;
```

```
public final class Printer {
  public String print(final String s) {
    return new Writer(s).write();
  }
}
```

We want to extend BaseX with this class and use its method. In order to make this possible we have to define an XQuery function which wraps the `print` method of our class. This can be done in the following way:

```
import module namespace j="http://basex.org/lib/testJar";

declare namespace p="java:test.Printer";

declare function j:print($str as xs:string) as xs:string {
  let $printer := p:new()
  return p:print($printer, $str)
};
```

As it can be seen, the class `Printer` is declared with its binary name as a namespace prefixed with "java" and the XQuery function is implemented using the Java Bindings offered by BaseX.

On our file server, you can find some example libraries packaged as XML archives (xar files). You can use them to try our packaging API or just as a reference for creating your own packages.

Performance

Importing XQuery modules that are located in the repository is just as fast as importing any other modules. Modules that are imported several times in a project will only be compiled once.

Imported Java archives will be dynamically added to the classpath and unregistered after query execution. This requires some constant overhead and may lead to unexpected effects in scenarios with highly concurrent read operations. If you want to get optimal performance, it is recommendable to move your JAR files into the `lib/custom` directory of BaseX. This way, the archive will be added to the classpath if BaseX is started. If you have installed a Combined Package, you can simply keep your XQuery module in the repository, and the Java classes will be automatically detected.

Changelog

Version 9.0

- Added: Combined XQuery and Java packages
- Added: Additional Libraries

Version 7.2.1

- Updated: Installation: existing packages will be replaced without raising an error
- Updated: Removal: remove specific version of a package

Version 7.1

- Added: Repository Module

Version 7.0

- Added: EXPath Packaging

Chapter 28. Full-Text

Read this entry online in the BaseX Wiki.

This article is part of the XQuery Portal. It summarizes the fulltext features of BaseX.

Full-text retrieval in XML documents is an essential requirement in many use cases. BaseX was the first query processor that supported the W3C XQuery Full Text 1.0 Recommendation, and it additionally comes with a powerful Full-Text Index, which allows you to evaluate full-text queries on large databases within milliseconds.

Introduction

The XQuery and XPath Full Text Recommendation (XQFT) is a feature-rich extension of the XQuery language. It can be used to both query XML documents and single strings for words and phrases. This section gives you a quick insight into the most important features of the language.

This is a simple example for a basic full-text expression:

```
"This is YOUR World" contains text "your world"
```

It yields `true`, because the search string is *tokenized* before it is compared with the tokenized input string. In the tokenization process, several normalizations take place. Many of those steps can hardly be simulated with plain XQuery: as an example, upper/lower case and diacritics (umlauts, accents, etc.) are removed and an optional, language-dependent stemming algorithm is applied. Beside that, special characters such as whitespaces and punctuation marks will be ignored. Thus, this query also yields true:

```
"Well... Done!" contains text "well, done"
```

The `occurs` keyword comes into play when more than one occurrence of a token is to be found:

```
"one and two and three" contains text "and" occurs at least 2 times
```

Varius range modifiers are available: `exactly`, `at least`, `at most`, and `from ... to ...`.

Combining Results

In the given example, curly braces are used to combine multiple keywords:

```
for $country in doc('factbook')//country
where $country//religions[text() contains text { 'Sunni', 'Shia' } any]
return $country/name
```

The query will output the names of all countries with a religion element containing `sunni` or `shia`. The `any` keyword is optional; it can be replaced with:

- `all` : all strings need to be found
- `any word` : any of the single words within the specified strings need to be found
- `all words` : all single words within the specified strings need to be found
- `phrase` : all strings need to be found as a single phrase

The keywords `ftand`, `ftor` and `ftnot` can also be used to combine multiple query terms. The following query yields the same result as the last one does:

```
doc('factbook')//country[descendant::religions contains text 'sunni' ftor 'shia']/
name
```

The keywords `not in` are special: they are used to find tokens which are not part of a longer token sequence:

```
for $text in ("New York", "new conditions")
return $text contains text "New" not in "New York"
```

Due to the complex data model of the XQuery Full Text spec, the usage of `ftand` may lead to a high memory consumption. If you should encounter problems, simply use the `all` keyword:

```
doc('factbook')//country[descendant::religions contains text { 'Christian',
 'Jewish'} all]/name
```

Positional Filters

A popular retrieval operation is to filter texts by the distance of the searched words. In this query…

```
<xml>
  <text>There is some reason why ...</text>
  <text>For some good yet unknown reason, ...</text>
  <text>The reason why some people ...</text>
</xml>//text[. contains text { "some", "reason" } all ordered distance at most 3
 words]
```

…the two first texts will be returned as result, because there are at most three words between `some` and `reason`. Additionally, the `ordered` keyword ensures that the words are found in the specified order, which is why the third text is excluded. Note that `all` is required here to guarantee that only those hits will be accepted that contain all searched words.

The `window` keyword is related: it accepts those texts in which all keyword occur within the specified number of tokens. Can you guess what is returned by the following query?

```
("A C D", "A B C D E")[. contains text { "A", "E" } all window 3 words]
```

Sometimes it is interesting to only select texts in which all searched terms occur in the `same sentence` or `paragraph` (you can even filter for `different` sentences/paragraphs). This is obviously not the case in the following example:

```
'Mary told me, “I will survive!”.' contains text { 'will', 'told' } all words same
 sentence
```

By the way: In some examples above, the `words` unit was used, but `sentences` and `paragraphs` would have been valid alternatives.

Last but not least, three specifiers exist to filter results depending on the position of a hit:

- `at start` expects tokens to occur at the beginning of a text
- `at end` expects tokens to occur at the text end
- `entire content` only accepts texts which have no other words at the beginning or end

Match Options

As indicated in the introduction, the input and query texts are tokenized before they are compared with each other. During this process, texts are split into tokens, which are then normalized, based on the following matching options:

- If `case` is insensitive, no distinction is made between characters in upper and lower case. By default, the option is `insensitive`; it can also be set to `sensitive`:

```
"Respect Upper Case" contains text "Upper" using case sensitive
```

- If `diacritics` is insensitive, characters with and without diacritics (umlauts, characters with accents) are declared as identical. By default, the option is `insensitive`; it can also be set to `sensitive`:

```
"'Äpfel' will not be found..." contains text "Apfel" diacritics sensitive
```

- If `stemming` is activated, words are shortened to a base form by a language-specific stemmer:

```
"catch" contains text "catches" using stemming
```

- With the `stop words` option, a list of words can be defined that will be ignored when tokenizing a string. This is particularly helpful if the full-text index takes too much space (a standard stopword list for English texts is provided in the directory `etc/stopwords.txt` in the full distributions of BaseX, and available online at http://files.basex.org/etc/stopwords.txt):

```
"You and me" contains text "you or me" using stop words ("and", "or"),
"You and me" contains text "you or me" using stop words at "http://files.basex.org/
etc/stopwords.txt"
```

- Related terms such as synonyms can be found with the sophisticated Thesaurus option.

The `wildcards` option facilitates search operations similar to simple regular expressions:

- `.` matches a single arbitrary character.
- `.?` matches either zero or one character.
- `.*` matches zero or more characters.
- `.+` matches one or more characters.
- `.{min,max}` matches *min max* number of characters.

```
"This may be interesting in the year 2000" contains text { "interest.*", "2.
{3,3}" } using wildcards
```

This was a quick introduction to XQuery Full Text; you are invited to explore the numerous other features of the language!

BaseX Features

Languages

The chosen language determines how strings will be tokenized and stemmed. Either names (e.g. `English`, `German`) or codes (`en`, `de`) can be specified. A list of all language codes that are available on your system can be retrieved as follows:

```
declare namespace locale = "java:java.util.Locale";
distinct-values(locale:getAvailableLocales() ! locale:getLanguage(.))
```

By default, unless the languages codes `ja`, `ar`, `ko`, `th`, or `zh` are specified, a tokenizer for Western texts is used:

- Whitespaces are interpreted as token delimiters.
- Sentence delimiters are `.`, `!`, and `?`.
- Paragraph delimiters are newlines (`
`).

The basic JAR file of BaseX comes with built-in stemming support for English, German, Greek and Indonesian. Some more languages are supported if the following libraries are found in the classpath:

- lucene-stemmers-3.4.0.jar includes the Snowball and Lucene stemmers for the following languages: Bulgarian, Catalan, Czech, Danish, Dutch, Finnish, French, Hindi, Hungarian, Italian, Latvian, Lithuanian, Norwegian, Portuguese, Romanian, Russian, Spanish, Swedish, Turkish.
- igo-0.4.3.jar : An additional article explains how Igo can be integrated, and how Japanese texts are tokenized and stemmed.

The JAR files are included in the ZIP and EXE distributions of BaseX.

The following two queries, which both return `true`, demonstrate that stemming depends on the selected language:

```
"Indexing" contains text "index" using stemming,
"häuser" contains text "haus" using stemming using language "German"
```

Scoring

The XQuery Full Text Recommendation allows for the usage of scoring models and values within queries, with scoring being completely implementation-defined.

The scoring model of BaseX takes into consideration the number of found terms, their frequency in a text, and the length of a text. The shorter the input text is, the higher scores will be:

```
(: Score values: 1 0.62 0.45 :)
for $text score $score in ("A", "A B", "A B C")[. contains text "A"]
order by $score descending
return <hit score='{ format-number($score, "0.00") }'>{ $text }</hit>
```

This simple approach has proven to consistently deliver good results, and in particular when little is known about the structure of the queried XML documents.

Please note that scores will only be computed if a parent expression requests them:

```
(: Computes and returns a scoring value. :)
let score $score := <x>Hello Universe</x> contains text "hello"
return $score

(: No scoring value will be computed here. :)
let $result := <x>Hello Universe</x> contains text "hello"
let score $score := $result
return $score
```

Scores will be propagated by the `and` and `or` expressions and in predicates. In the following query, all returned scores are equal:

```
let $text := "A B C"
let score $s1 := $text contains text "A" ftand "B C"
let score $s2 := $text contains text "A" ftand "B C"
let score $s3 := $text contains text "A" and $text contains text "B C"
let score $s4 := $text contains text "A" or $text contains text "B C"
let score $s5 := $text[. contains text "A"][. contains text "B C"]
return ($s1, $s2, $s3, $s4, $s5)
```

Thesaurus

BaseX supports full-text queries using thesauri, but it does not provide a default thesaurus. This is why queries such as:

```
'computers' contains text 'hardware'
  using thesaurus default
```

will return `false`. However, if the thesaurus is specified, then the result will be `true`:

```
'computers' contains text 'hardware'
  using thesaurus at 'XQFTTS_1_0_4/TestSources/usability2.xml'
```

The format of the thesaurus files must be the same as the format of the thesauri provided by the XQuery and XPath Full Text 1.0 Test Suite. It is an XML with structure defined by an XSD Schema.

Fuzzy Querying

In addition to the official recommendation, BaseX supports a fuzzy search feature. The XQFT grammar was enhanced by the `fuzzy` match option to allow for approximate results in full texts:

Document 'doc.xml':

```
<doc>
   <a>house</a>
   <a>hous</a>
   <a>haus</a>
</doc>
```

Query:

```
//a[text() contains text 'house' using fuzzy]
```

Result:

```
<a>house</a>
<a>hous</a>
```

Fuzzy search is based on the Levenshtein distance. The maximum number of allowed errors is calculated by dividing the token length of a specified query term by 4, preserving a minimum of 1 errors. A static error distance can be set by adjusting the `LSERROR` property (default: `SET LSERROR 0`). The query above yields two results as there is no error between the query term “house” and the text node “house”, and one error between “house” and “hous”.

Fuzzy search is also supported by the full-text index.

Mixed Content

When working with so-called narrative XML documents, such as HTML, TEI, or DocBook documents, you typically have *mixed content*, i.e., elements containing a mix of text and markup, such as:

```
<p>This is only an illustrative <hi>example</hi>, not a <q>real</q> text.</p>
```

Since the logical flow of the text is not interrupted by the child elements, you will typically want to search across elements, so that the above paragraph would match a search for “real text”. For more examples, see XQuery and XPath Full Text 1.0 Use Cases.

To enable this kind of searches, it is recommendable to:

- Turn off *whitespace chopping* when importing XML documents. This can be done by setting the option `CHOP` to `OFF`. This can also be done in the GUI if a new database is created (*Database* → *New…* → *Parsing* → *Chop Whitespaces*).

- Turn off automatic indentation by assigning `indent=no` to the `SERIALIZER` option.

A query such as `//p[. contains text 'real text']` will then match the example paragraph above. However, the full-text index will **not** be used in this query, so it may take a long time. The full-text index would be used for the query `//p[text() contains text 'real text']`, but this query will not find the example paragraph, because the matching text is split over two text nodes.

Note that the node structure is ignored by the full-text tokenizer: The `contains text` expression applies all full-text operations to the *string value* of its left operand. As a consequence, the `ft:mark` and `ft:extract` functions (see Full-Text Functions) will only yield useful results if they are applied to single text nodes, as the following example demonstrates:

```
(: Structure is ignored; no highlighting: :)
ft:mark(//p[. contains text 'real'])
(: Single text nodes are addressed: results will be highlighted: :)
ft:mark(//p[.//text() contains text 'real'])
```

BaseX does **not** support the *ignore option* (`without content`) of the W3C XQuery Full Text 1.0 Recommendation. If you want to ignore descendant element content, such as footnotes or other material that does not belong to the same logical text flow, you can build a second database from and exclude all information you do not want to search for. See the following example (visit XQuery Update to learn more about updates):

```
let $docs := db:open('docs')
return db:create(
  'index-db',
  $docs update delete node (
    .//footnote
  ),
  $docs/db:path(.),
  map { 'ftindex': true() }
)
```

Functions

Some additional Full-Text Functions have been added to BaseX to extend the official language recommendation with useful features, such as explicitly requesting the score value of an item, marking the hits of a full-text request, or directly accessing the full-text index with the default index options.

Collations

See XQuery 3.1 for standard collation features.

By default, string comparisons in XQuery are based on the Unicode codepoint order. The default namespace URI `http://www.w3.org/2003/05/xpath-functions/collation/codepoint` specifies this ordering. In BaseX, the following URI syntax is supported to specify collations:

```
http://basex.org/collation?lang=...;strength=...;decomposition=...
```

Semicolons can be replaced with ampersands; for convenience, the URL can be reduced to its *query string component* (including the question mark). All arguments are optional:

Argument	Description
`lang`	A language code, selecting a Locale. It may be followed by a language variant. If no language is specified, the system's default will be chosen. Examples: `de`, `en-US`.
`strength`	Level of difference considered significant in comparisons. Four strengths are supported: `primary`, `secondary`, `tertiary`, and `identical`. As an example, in German: • "Ä" and "A" are considered primary differences,

	• "Ä" and "ä" are secondary differences, • "Ä" and "Ä" (see http://www.fileformat.info/info/unicode/char/308/index.htm) are tertiary differences, and • "A" and "A" are identical.
`decomposition`	Defines how composed characters are handled. Three decompositions are supported: `none`, `standard`, and `full`. More details are found in the JavaDoc of the JDK.

Some Examples:

- If a default collation is specified, it applies to all collation-dependent string operations in the query. The following expression yields `true`:

```
declare default collation 'http://basex.org/collation?lang=de;strength=secondary';
'Straße' = 'Strasse'
```

- Collations can also be specified in `order by` and `group by` clauses of FLWOR expressions. This query returns `à plutôt! bonjour!`:

```
for $w in ("bonjour!", "à plutôt!") order by $w collation "?lang=fr" return $w
```

- Various string function exists that take an optional collation as argument: The following functions give us `a` and `1 2 3` as results:

```
distinct-values(("a", "á", "à"), "?lang=it-IT;strength=primary"),
index-of(("a", "á", "à"), "a", "?lang=it-IT;strength=primary")
```

Changelog

Version 8.0

- Updated: Scores will be propagated by the `and` and `or` expressions and in predicates.

Version 7.7

- Added: Collations support.

Version 7.3

- Removed: Trie index, which was specialized on wildcard queries. The fuzzy index now supports both wildcard and fuzzy queries.
- Removed: TF/IDF scoring was discarded in favor of the internal scoring model.

Chapter 29. Full-Text: Japanese

Read this entry online in the BaseX Wiki.

This article is linked from the Full-Text page. It gives some insight into the implementation of the full-text features for Japanese text corpora. The Japanese version is also available as PDF. Thank you to Toshio HIRAI for integrating the lexer in BaseX!

Introduction

The lexical analysis of Japanese documents is performed by Igo. Igo is a *morphological analyser*, and some of the advantages and reasons for using Igo are:

- compatible with the results of a prominent morphological analyzer "MeCab"
- it can use the dictionary distributed by the Project MeCab
- the morphological analyzer is implemented in Java and is relatively fast

Japanese tokenization will be activated in BaseX if Igo is found in the classpath. igo-0.4.3.jar of Igo is currently included in all distributions of BaseX.

In addition to the library, one of the following dictionary files must either be unzipped into the current directory, or into the `etc` sub-directory of the project's Home Directory:

- IPA Dictionary: http://files.basex.org/etc/ipadic.zip
- NAIST Dictionary: http://files.basex.org/etc/naistdic.zip

Lexical Analysis

The example sentence "##########(I wrote a book.)" is analyzed as follows.

```
##########
#       ##,###,##,*,*,*,#,###,###
#       ##,###,*,*,*,*,#,#,#
#       ##,##,*,*,*,*,#,##,##
#       ##,###,##,*,*,*,#,#,#
##     ##,##,*,*,########,###,##,##,##
##     ###,*,*,*,#####,###,##,##,##
#       ###,*,*,*,####,###,#,#,#
#       ##,##,*,*,*,*,#,#,#
```

The element of the decomposed part is called "Surface", the content analysis is called "Morpheme". The Morpheme component is built as follows:

```
##,#####1,#####2,#####3,###,###,##,##,##
(POS, subtyping POS 1, subtyping POS 2, subtyping POS 3, inflections, use type,
 prototype, reading, pronunciation)
```

Of these, the surface is used as a token. Also, The contents of analysis of a morpheme are used in indexing and stemming.

Parsing

During indexing and parsing, the input strings are split into single *tokens*. In order to reduce the index size and speed up search, the following word classes have been intentionally excluded:

- Mark

- Filler
- Postpositional particle
- Auxiliary verb

Thus, in the example above, , , and ## will be passed to the indexer for each token.

Token Processing

"Fullwidth" and "Halfwidth" (which is defined by East Asian Width Properties) are not distinguished (this is the so-called ZENKAKU/HANKAKU problem). For example, ### and `XML` will be treated as the same word. If documents are *hybrid*, i.e. written in multiple languages, this is also helpful for some other options of the XQuery Full Text Specification, such as the Case or the Diacritics Option.

Stemming

Stemming in Japanese means to analyze the results of morphological analysis ("verbs" and "adjectives") that are processed using the "prototype".

If the stemming option is enabled, for example, the two statements "####### (I wrote the book)" and "###### (I write the book)" can be led back to the same prototype by analyzing their verb:

```
##    ##,##,*,*,########,###,[##],##,##

##    ##,##,*,*,########,#####,[##],##,##
#      ###,*,*,*,####,###,#,#,#
```

Because the "auxiliary verb" is always excluded from the tokens, there is no need to consider its use. Therefore, the same result (`true`) is returned for the following two types of queries:

```
'#######' contains text '##' using stemming using language 'ja'
'######' contains text '###' using stemming using language 'ja'
```

Wildcards

The Wildcard option in XQuery Full-Text is available for Japanese as well. The following example is based on '## ###(AKUTAGAWA, Ryunosuke)', a prominent Japanese writer, the first name of whom is often spelled as "## ##". The following two queries both return `true`:

```
'#####' contains text '.##' using wildcards using language 'ja'
'#####' contains text '.##' using wildcards using language 'ja'
```

However, there is a special case that requires attention. The following query will yield `false`:

```
'#####' contains text '##.##' using wildcards using language 'ja'
```

This is because the next word boundary metacharacters cannot be determined in the query. In this case, you may insert an additional whitespaces as word boundary:

```
'#####' contains text '##  .##' using wildcards using language 'ja'
```

As an alternative, you may modify the query as follows:

```
'#####' contains text '##' ftand '.##' using wildcards using language 'ja'
```

Chapter 30. XQuery Update

Read this entry online in the BaseX Wiki.

This article is part of the XQuery Portal. It summarizes the update features of BaseX.

BaseX offers a complete implementation of the XQuery Update Facility (XQUF). This article aims to provide a very quick and basic introduction to the XQUF. First, some examples for update expressions are given. After that, a few problems are addressed that frequently arise due to the nature of the language. These are stated in the Concepts paragraph.

Features

Updating Expressions

There are five new expressions to modify data. While `insert`, `delete`, `rename` and `replace` are basically self-explanatory, the `transform` expression is different, as modified nodes are copied in advance and the original databases remain untouched.

An expression consists of a target node (the node we want to alter) and additional information like insertion nodes, a QName, etc. which depends on the type of expression. Optional modifiers are available for some of them. You can find a few examples and additional information below.

insert

```
insert node (attribute { 'a' } { 5 }, 'text', <e/>) into /n
```

Insert enables you to insert a sequence of nodes into a single target node. Several modifiers are available to specify the exact insert location: insert into **as first**/**as last**, insert **before**/**after** and insert **into**.

Note: in most cases, **as last** and **after** will be evaluated faster than **as first** and **before**!

delete

```
delete node //n
```

The example query deletes all <n> elements in your database. Note that, in contrast to other updating expressions, the delete expression allows multiple nodes as a target.

replace

```
replace node /n with <a/>
```

The target element is replaced by the DOM node <a/>. You can also replace the value of a node or its descendants by using the modifier **value of**.

```
replace value of node /n with 'newValue'
```

All descendants of /n are deleted and the given text is inserted as the only child. Note that the result of the insert sequence is either a single text node or an empty sequence. If the insert sequence is empty, all descendants of the target are deleted. Consequently, replacing the value of a node leaves the target with either a single text node or no descendants at all.

rename

```
for $n in //originalNode
return rename node $n as 'renamedNode'
```

All `originalNode` elements are renamed. An iterative approach helps to modify multiple nodes within a single statement. Nodes on the descendant- or attribute-axis of the target are not affected. This has to be done explicitly as well.

Non-Updating Expressions

copy/modify/return

```
copy $c := doc('example.xml')//originalNode[@id = 1]
modify rename node $c as 'copyOfNode'
return $c
```

The `originalNode` element with `@id=1` is copied and subsequently assigned a new QName using the rename expression. Note that the transform expression is the only expression which returns an actual XDM instance as a result. You can therefore use it to modify results and especially DOM nodes. This is an issue beginners are often confronted with. More on this topic can be found in the XQUF Concepts section.

The following example demonstrates a common use case:

Query:

```
copy $c :=
  <entry>
    <title>Transform expression example</title>
    <author>BaseX Team</author>
  </entry>
modify (
  replace value of node $c/author with 'BaseX',
  replace value of node $c/title with concat('Copy of: ', $c/title),
  insert node <author>Joey</author> into $c
)
return $c
```

Result:

```
<entry>
  <title>Copy of: Transform expression example</title>
  <author>BaseX</author>
  <author>Joey</author>
</entry>
```

The `<entry>` element (here it is passed to the expression as a DOM node) can also be replaced by a database node, e.g.:

```
copy $c := (db:open('example')//entry)[1]
...
```

In this case, the original database node remains untouched as well, as all updates are performed on the node copy.

Here is an example where we return an entire document, parts modified and all:

```
copy $c := doc("zaokeng.kml")
modify (
  for $d in $c//*:Point
  return insert node (
    <extrude>1</extrude>,
```

```
    <altitudeMode>relativeToGround</altitudeMode>
  )  before $d/*:coordinates
)
return $c
```

update

The `update` expression is a BaseX-specific convenience operator for the `copy/modify/return` construct:

- Similar to the XQuery 3.0 map operator, the value of the first

expression is bound as context item, and the second expression performs updates on this item. The updated item is returned as result:

```
for $item in db:open('data')//item
return $item update delete node text()
```

- More than one node can be specified as source:

```
db:open('data')//item update delete node text()
```

- If wrapped with curly braces, update expressions can be chained:

```
<root/> update {
  insert node <child/> into .
} update {
  insert node "text" into child
}
```

transform with

The `transform with` expression was added to the current XQuery Update 3.0 working draft. It is a simple version of the update expression and also availablein BaseX:

```
<xml>text</xml> transform with {
  replace value of node . with 'new-text'
}
```

Functions

Built-in Functions

`fn:put()` is can be used to serialize XDM instances to secondary storage. It is executed at the end of a snapshot. Serialized documents therefore reflect all changes made effective during a query. No files will be created if the addressed nodes have been deleted.

With *Version 9.0*, serialization parameters can be specified as third argument (more details are found in the XQUF 3.0 Specification).

Numerous additional database functions exist for performing updates on document and database level.

User-Defined Functions

If an updating function item is called, the function call must be prefixed with the keyword `updating`. This ensures that the query compiler can statically detect if an invoked function item will perform updates or not:

```
let $node := <node>TO-BE-DELETED</node>
let $delete-text := %updating function($node) {
```

```
  delete node $node//text()
}
return $node update (
  updating $delete-text(.)
)
```

As shown in the example, user-defined and anonymous functions can additionally be annotated as `%updating`.

Concepts

There are a few specialties around XQuery Update that you should know about. In addition to the **simple expression**, the XQUF adds the **updating expression** as a new type of expression. An updating expression returns only a Pending Update List (PUL) as a result which is subsequently applied to addressed databases and DOM nodes. A simple expression cannot perform any permanent changes and returns an empty or non-empty sequence.

Pending Update List

The most important thing to keep in mind when using XQuery Update is the Pending Update List (PUL). Updating statements are not executed immediately, but are first collected as update primitives within a set-like structure. At the end of a query, after some consistency checks and optimizations, the update primitives will be applied in the following order:

- **Backups (1)** : `db:create-backup()`
- **XQuery Update** : `insert before`, `delete`, `replace`, `rename`, `replace value`, `insert attribute`, `insert into first`, `insert into`, `insert into last`, `insert`, `insert after`, `put`
- **Documents** : `db:add()`, `db:store()`, `db:replace()`, `db:rename()`, `db:delete()`, `db:optimize()`, `db:flush()`,
- **Users** : `user:grant()`, `user:password()`, `user:drop()`, `user:alter()`, `user:create()`
- **Databases** : `db:copy()`, `db:drop()`, `db:alter()`, `db:create()`
- **Backups (2)** : `db:restore()`, `db:drop-backup()`

If an inconsistency is found, an error message is returned and all accessed databases remain untouched (atomicity). For the user, this means that updates are only visible **after** the end of a snapshot.

It may be surprising to see `db:create` in the lower part of this list. This means that newly created database cannot be accessed by the same query, which can be explained by the semantics of updating queries: all expressions can only be evaluated on databases that already exist while the query is evaluated. As a consequence, `db:create` is mainly useful in the context of Command Scripts, or Web Applications, in which a redirect to another page can be triggered after having created a database.

Example

The query…

```
insert node <b/> into /doc,
for $n in /doc/child::node()
return rename node $n as 'justRenamed'
```

…applied on the document…

```
<doc> <a/> </doc>
```

…results in the following document:

```
<doc> <justRenamed/><b/> </doc>
```

Despite explicitly renaming all child nodes of `<doc/>`, the former `<a/>` element is the only one to be renamed. The `<b/>` element is inserted within the same snapshot and is therefore not yet visible to the user.

Returning Results

By default, it is not possible to mix different types of expressions in a query result. The outermost expression of a query must either be a collection of updating or non-updating expressions. But there are two ways out:

- The BaseX-specific `db:output()` function bridges this gap: it caches the results of its arguments at runtime and returns them after all updates have been processed. The following example performs an update and returns a success message:

```
db:output("Update successful."), insert node <c/> into doc('factbook')/mondial
```

- With the MIXUPDATES option, all updating constraints will be turned off. Returned nodes will be copied before they are modified by updating expressions. An error is raised if items are returned within a transform expression.

If you want to modify nodes in main memory, you can use the transform expression.

Effects

Original Files

In BaseX, all updates are performed on database nodes or in main memory. By default, update operations do not affect the original input file (the info string "Updates are not written back" appears in the query info to indicate this). The following solutions exist to write XML documents and binary resources to disk:

- Updates on main-memory instances of files that have been retrieved via `fn:doc` or `fn:collection` will be propagated back to disk when the `WRITEBACK` option is turned on. This option can also be activated on command line via `-u`. Make sure you back up the original documents before running your queries.
- Functions like `fn:put` or `file:write` can be used to write single XML documents to disk. With `file:write-binary`, you can write binary resources.
- The EXPORT command can be used write all resources of a databases to disk.

Indexes

Index structures are discarded after update operations when UPDINDEX is turned off (which is the default). More details are found in the article on Indexing.

Error Messages

Along with the Update Facility, a number of new error codes and messages have been added to the specification and BaseX. All errors are listed in the XQuery Errors overview.

Please remember that the collected updates will be executed after the query evaluation. If errors occur at this final stage, they cannot be caught via try/catch.

Changelog

Version 9.0

- Updated: Built-in Functions: serialization parameters

Version 8.5

- Added: transform with
- Updated: update was extended.

Version 8.0

- Added: `MIXUPDATES` option for Returning Results in updating expressions
- Added: information message if files are not written back

Version 7.8

- Added: update convenience operator

Chapter 31. Indexes

Read this entry online in the BaseX Wiki.

This article is part of the XQuery Portal. It contains information on the available index structures.

The query compiler tries to optimize and speed up queries by applying the index whenever it is possible and seems promising. To see how a query is rewritten, and if an index is used, you can turn on the Info View in the GUI or use the -V flag on the command line:

- A message like `Applying text index for "Japan"` indicates that the text index is applied to speed up the search of the shown string. The following message…
- `Removing path with no index results` indicates that a string in a path expression will never yield results. Because of that, the path does not need to be evaluated at all.
- If you cannot find any index optimization hints in the info output, it often helps if you rewrite and simplify your query.

Structural Indexes

Structural indexes are automatically created and cannot be dropped by the user:

Name Index

The name index contains references to the names of all elements and attributes in a database. It contains some basic statistical information, such as the number of occurrence of a name.

The name index is e.g. applied to discard location steps that will never yield results:

```
(: will be rewritten to an empty sequence :)
/non-existing-name
```

The contents of the name indexes can be directly accessed with the XQuery functions index:element-names and index:attribute-names.

If a database is updated, new names will be added incrementally, but the statistical information will get out-dated.

Path Index

The path index (which is also called *path summary* or *data guide*) stores all distinct paths of the documents in the database. It contains additional statistical information, such as the number of occurrence of a path, its distinct string values, and the minimum/maximum of numeric values. The maximum number of distinct values to store per name can be changed via `MAXCATS`. Distinct values are also stored for elements and attributes of numeric type.

Various queries will be evaluated much faster if an up-to-date path index is available (as can be observed when opening the Info View):

- Descendant steps will be rewritten to multiple child steps. Child steps are evaluated faster, as fewer nodes have to be traversed:

```
doc('factbook.xml')//province,
(: ...will be rewritten to... :)
doc('factbook.xml')/mondial/country/province
```

- The `fn:count` function will be pre-evaluated by looking up the number in the index:

```
count(doc('factbook')//country)
```

- The distinct values of elements or attributes can be looked up in the index as well:

```
distinct-values(db:open('factbook')//religions)
```

The contents of the path index can be directly accessed with the XQuery function index:facets.

If a database is updated, the statistics in the path index will be invalidated.

Document Index

The document index contains references to all document nodes in a database. Once documents with specific paths are requested, the index will be extended to also contain document paths.

The index generally speeds up access to single documents and database paths. It will always be kept up-to-date.

Value Indexes

Value indexes can be created and dropped by the user. Four types of values indexes are available: a text and attribute index, and an optional token and full-text index. By default, the text and attribute index will automatically be created.

In the GUI, index structures can be managed in the dialog windows for creating new databases or displaying the database properties. On command-line, the commands `CREATE INDEX` and `DROP INDEX` are used to create and drop index structures. With `INFO INDEX`, you get some insight into the contents of an index structure, and `SET` allows you to change the index defaults for new databases:

- `OPEN factbook; CREATE INDEX fulltext` : Open database; create full-text index
- `OPEN factbook; INFO INDEX TOKEN` : Open database; show info on token index
- `SET ATTRINDEX true; SET ATTRINCLUDE id name; CREATE DB factbook.xml` : Enable attribute index; only index 'id' and 'name' attributes; create database

With XQuery, index structures can be created and dropped via db:optimize:

```
(: Optimize specified database, create full-text index for texts of the specified
 elements :)
db:optimize(
  'factbook',
  false(),
  map { 'ftindex': true(), 'ftinclude': 'p div' }
)
```

Text Index

Exact Queries

This index speeds up string-based equality tests on text nodes. The following queries will all be rewritten for index access:

```
(: 1st example :)
//*[text() = 'Germany'],
(: 2nd example :)
doc('factbook.xml')//name[. = 'Germany'],
(: 3rd example :)
for $c in db:open('factbook')//country
where $c//city/name = 'Hanoi'
return $c/name
```

Matching text nodes can be directly requested from the index with the XQuery function db:text. The index contents can be accessed via index:text.

The `UPDINDEX` option can be activated to keep this index up-to-date, for example:

```
db:optimize(
  'mydb',
  true(),
  map { 'updindex':true(), 'textindex': true(), 'textinclude':'id' }
)
```

Range Queries

The text index also supports range queries based on string comparisons:

```
(: 1st example :)
db:open('Library')//Medium[Year >= '2011' and Year <= '2016'],
(: 2nd example :)
let $min := '2014-04-16T00:00:00'
let $max := '2014-04-19T23:59:59'
return db:open('news')//entry[date-time > $min and date-time < $max]
```

Text nodes can directly be retrieved from the index via the XQuery function db:text-range.

Please note that the current index structures do not support queries for numbers and dates.

Attribute Index

Similar to the text index, this index speeds up string-based equality and range tests on attribute values. Additionally, the XQuery function `fn:id` takes advantage of the index whenever possible. The following queries will all be rewritten for index access:

```
(: 1st example :)
//country[@car_code = 'J'],
(: 2nd example :)
//province[@* = 'Hokkaido']//name,
(: 3rd example :)
//sea[@depth > '2100' and @depth < '4000']
(: 4th example :)
fn:id('f0_119', db:open('factbook'))
```

Attribute nodes can directly be retrieved from the index with the XQuery functions db:attribute and db:attribute-range. The index contents can be accessed with index:attributes.

The `UPDINDEX` option can be activated to keep this index up-to-date.

Token Index

In many XML dialects, such as HTML or DITA, multiple tokens are stored in attribute values. The token index can be created to speed up the retrieval of these tokens. The XQuery functions `fn:contains-token`, `fn:tokenize` and `fn:idref` are rewritten for index access whenever possible. If a token index exists, it will e.g. be utilized for the following queries:

```
(: 1st example :)
//div[contains-token(@class, 'row')],
(: 2nd example :)
//p[tokenize(@class) = 'row'],
(: 3rd example :)
doc('graph.xml')/idref('edge8')
```

Attributes with tokens can be directly retrieved from the index with the XQuery function db:token. The index contents can be accessed with index:tokens.

Full-Text Index

The Full-Text index contains the normalized tokens of text nodes of a document. It is utilized to speed up queries with the `contains text` expression, and it is capable of processing wildcard and fuzzy search operations. Three evaluation strategies are available: the standard sequential database scan, a full-text index based evaluation and a hybrid one, combining both strategies (see XQuery Full Text implementation in BaseX).

If the full-text index exists, the following queries will all be rewritten for index access:

```
(: 1st example :)
//country[name/text() contains text 'and'],
(: 2nd example :)
//religions[.//text() contains text { 'Catholic', 'Roman' }
    using case insensitive distance at most 2 words]
```

The index provides support for the following full-text features (the values can be changed in the GUI or via the `SET` command):

- **Stemming** : tokens are stemmed before being indexed (option: `STEMMING`)
- **Case Sensitive** : tokens are indexed in case-sensitive mode (option: `CASESENS`)
- **Diacritics** : diacritics are indexed as well (option: `DIACRITICS`)
- **Stopword List** : a stop word list can be defined to reduce the number of indexed tokens (option: `STOPWORDS`)
- **Language** : see Languages for more details (option: `LANGUAGE`)

The options that have been used for creating the full-text index will also be applied to the optimized full-text queries. However, the defaults can be overwritten if you supply options in your query. For example, if words were stemmed in the index, and if the query can be rewritten for index access, the query terms will be stemmed as well, unless stemming is not explicitly disabled. This is demonstrated in the following Command Script:

```
<commands>
  <!-- Create database with stemmed full-text index -->
  <set option='stemming'>true</set>
  <set option='ftindex'>true</set>
  <create-db name='test-db'> <text>house</text> </create-db>
  <!-- Index access: Query term will be stemmed -->
  <xquery> /text[. contains text { 'houses' }] </xquery>
  <!-- Disable stemming (query will not be evaluated by the index) -->
  <xquery> /text[. contains text { 'houses' } using no stemming] </xquery>
</commands>
```

Text nodes can be directly requested from the index via the XQuery function ft:search. The index contents can be accessed with ft:tokens.

Selective Indexing

Value indexing can be restricted to specific elements and attributes. The nodes to be indexed can be restricted via the `TEXTINCLUDE`, `ATTRINCLUDE`, `TOKENINCLUDE` and `FTINCLUDE` options. The options take a list of name patterns, which are separated by commas. The following name patterns are supported:

- `*` : all names
- `name` : elements or attributes called `name`, which are in the empty default namespace
- `*:name` : elements or attributes called `name`, no matter which namespace

- `Q{uri}*` : all elements or attributes in the `uri` namespace
- `Q{uri}name` : elements or attributes called `name` in the `uri` namespace

The options can either be specified via the `SET` command or via XQuery. With the following operations, an attribute index is created for all `id` and `name` attributes:

Commands

```
SET ATTRINCLUDE id,name
CREATE DB factbook http://files.basex.org/xml/factbook.xml'
# Restore default
SET ATTRINCLUDE
```

XQuery

```
db:create('factbook', 'http://files.basex.org/xml/factbook.xml', '',
  map { 'attrinclude': 'id,name' })
```

With `CREATE INDEX` and db:optimize, new selective indexing options will ba applied to an existing database.

Enforce Rewritings

In various cases, existing index structures will not be utilized by the query optimizer. This is usually the case if the name of the database is not a static string (e.g., because it is bound to a variable or passed on as argument of a function call). Furthermore, several candidates for index rewritings may exist, and the query optimizer may decide for a rewriting that turns out to be suboptimal.

With *Version 9.0*, the `ENFORCEINDEX` option was introduced, which allows you to enforce certain index rewritings. While the option can be globally enabled, it is usually better to supply it as Pragma. Two examples:

- In the query below, 10 databases will be addressed. If it is known in advance that these databases contain an up-to-date text index, the index rewriting can be enforced as follows:

```
(# db:enforceindex #) {
  for $n in 1 to 10
  let $db := 'persons' || $n
  return db:open($db)//person[name/text() = 'John']
}
```

- The following query contains two predicates that may both be rewritten for index access. If the automatically chosen rewriting is known not to be optimal, another index rewriting can enforced by surrounding the specific expression with the pragma:

```
db:open('factbook')//country
  [(# db:enforceindex #) {
   @population > '10000000' and
   @population < '10999999'
  }]
  [religions/text() = 'Protestant']
```

Please note that:

- The option should only be enabled if the addressed databases exist, have all required index structures and are up-to-date (otherwise, you will be given an error message).
- The enforcement of index rewritings gives you no guarantee that an index will be used. There are many expressions that cannot be rewritten for index access.

- If you have more than one enforce pragma in a single path expression, only the first will be considered.

Custom Index Structures

With XQuery, it is comparatively easy to create your own, custom index structures. The following query demonstrate how you can create a `factbook-index` database, which contains all texts of the original database in lower case:

```
let $db := 'factbook'

let $index := <index>{
  for $nodes in db:open($db)//text()
  group by $text := lower-case($nodes)
  return <text string='{ $text }'>{
    for $node in $nodes
    return <id>{ db:node-id($node ) }</id>
  }</text>
}</index>

return db:create($db || '-index', $index, $db || '-index.xml')
```

In the following query, a text string is searched, and the text nodes of the original database are retrieved:

```
let $db := 'factbook'
let $text := 'italian'
for $id in db:open($db || '-index')//*[@string = $text]/id
return db:open-id($db, $id)/..
```

With some extra effort, and if `UPDINDEX` is enabled for both your original and your index database (see below), your index database will support updates as well (try it, it's fun!).

Performance

If main memory runs out while creating a value index, the current index structures will be partially written to disk and eventually merged. If the memory heuristics fail for some reason (i.e., because multiple index operations run at the same time, or because the applied JVM does not support explicit garbage collections), a fixed index split sizes may be chosen via the `SPLITSIZE` option.

If `DEBUG` is enabled, the command-line output might help you to find a good split size. The following example shows the output for creating a database for an XMark document with 1 GB, and with 128 MB assigned to the JVM:

```
> basex -d -c"SET FTINDEX ON; SET TOKENINDEX ON; CREATE DB xmark 1gb.xml"
Creating Database...
............................... 76559.99 ms (29001 KB)
Indexing Text...
....|...|...|.....|. 9.81 M operations, 18576.92 ms (13523 KB). Recommended
 SPLITSIZE: 20.
Indexing Attribute Values...
.........|....... 3.82 M operations, 7151.77 ms (6435 KB). Recommended SPLITSIZE:
 20.
Indexing Tokens...
.......|..|.....|.. 3.82 M operations, 9636.73 ms (10809 KB). Recommended
 SPLITSIZE: 10.
Indexing Full-Text...
..|.|.|.|...|...|..|.|..| 116.33 M operations, 138740.94 ms (106 MB). Recommended
 SPLITSIZE: 12.
```

The output can be interpreted as follows:

- The vertical bar `|` indicates that a partial index structure was written to disk.

- The mean value of the recommendations can be assigned to the `SPLITSIZE` option. Please note that the recommendation is only a vague proposal, so try different values if you get main-of-memory errors or indexing gets too slow. Greater values will require more main memory.
- In the example, the full-text index was split 12 times. 116 million tokens were indexed, processing time was 2,5 minutes, and final main memory consumption (after writing the index to disk) was 76 MB. A good value for the split size option could be `15`.

Updates

Generally, update operations are very fast in BaseX. By default, the index structures will be invalidated by updates; as a result, queries that benefit from index structures may slow down after updates. There are different alternatives to cope with this:

- After the execution of one or more update operations, the `OPTIMIZE` command or the db:optimize function can be called to rebuild the index structures.
- The `UPDINDEX` option can be activated before creating or optimizing the database. As a result, the text, attribute and token indexes will be incrementally updated after each database update. Please note that incremental updates are not available for the full-text index and database statistics. This is also explains why the UPTODATE flag, which is e.g. displayed via `INFO DB` or db:info, will be set to `false` until the database will be optimized again (various optimizations won't be triggered. For example, count(//item) can be extremely fast if all meta data is up-to-date.
- The `AUTOOPTIMIZE` option can be enabled before creating or optimizing the database. All outdated index structures and statistics will then be recreated after each database update. This option should only be done for small and medium-sized databases.
- Both options can be used side by side: `UPDINDEX` will take care that the value index structures will be updated as part of the actual update operation. `AUTOOPTIMIZE` will update the remaining data structures (full-text index, database statistics).

Changelog

Version 9.0

- Added: Enforce Rewritings

Version 8.4

- Updated: Name Index, Path Index

Version 8.4

- Added: Token Index

Version 8.3

- Added: Selective Indexing

Version 8.0

- Added: AUTOOPTIMIZE option

Version 7.2.1

- Added: string-based range queries

Chapter 32. Serialization

Read this entry online in the BaseX Wiki.

This page is part of the XQuery Portal. Serialization parameters define how XQuery items and XML nodes are textually output, i.e., *serialized*. (For input, see Parsers.) They have been formalized in the W3C XQuery Serialization 3.1 document. In BaseX, they can be specified by…

- including them in the prolog of the XQuery expression,
- specifying them in the XQuery functions file:write() or fn:serialize(). The serialization parameters are specified as
  - children of an `<output:serialization-parameters/>` element, as defined for the fn:serialize() function, or as
  - map, which contains all key/value pairs: `map { "method": "xml", "cdata-section-elements": "div", ... }`,
- using the `-s` flag of the BaseX command-line clients,
- setting the SERIALIZER option before running a query,
- setting the EXPORTER option before exporting a database, or
- setting them as REST query parameters.

Parameters

The following table gives a brief summary of all serialization parameters recognized by BaseX. For details, please refer to official specification.

Parameter	Description	Allowed	Default
`method`	Specifies the serialization method. `xml`, `xhtml`, `html`, `text`, `json`, and `adaptive` are adopted from the official specification. The methods `basex` and `csv` are specific to BaseX (see XQuery Extensions).	`xml`, `xhtml`, `html`, `text`, `json`, `adaptive`, `csv`, `basex`	`basex`
`version`	Specifies the version of the serialization method.	xml/xhtml: `1.0`, `1.1`html: `4.0`, `4.01`, `5.0`	`1.0`
`html-version`	Specifies the version of the HTML serialization method.	`4.0`, `4.01`, `5.0`	`4.0`
`item-separator`	Determines a string to be used as item separator. If a separator is specified, the default separation of atomic values with single whitespaces will be skipped.	*arbitrary strings*, `\n`, `\r\n`, `\r`	*empty*
`encoding`	Encoding to be used for outputting the data.	*all encodings supported by Java*	`UTF-8`
`indent`	Adjusts whitespaces to make the output better readable.	`yes`, `no`	`yes`

cdata-section-elements	List of elements to be output as CDATA, separated by whitespaces.Example: <text><![CDATA[<>]]></text>		
omit-xml-declaration	Omits the XML declaration, which is serialized before the actual query resultExample: <?xml version="1.0" encoding="UTF-8"?>	yes, no	yes
standalone	Prints or omits the "standalone" attribute in the XML declaration.	yes, no, omit	omit
doctype-system	Introduces the output with a document type declaration and the given system identifier.Example: <!DOCTYPE x SYSTEM "entities.dtd">		
doctype-public	If doctype-system is specified, adds a public identifier.Example: <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01//EN""http://www.w3.org/TR/html4/strict.dtd">		
undeclare-prefixes	Undeclares prefixes in XML 1.1.	yes, no	no
normalization-form	Specifies a normalization form. BaseX supports Form C (NFC).	NFC, none	NFC
media-type	Specifies the media type.		application/xml
parameter-document	Parses the value as XML document with additional serialization parameters (see the Serialization Specification for more details).		
use-character-maps	Defines character mappings. May only occur in documents parsed with parameter-document.		
byte-order-mark	Prints a byte-order-mark before starting serialization.	yes, no	no
escape-uri-attributes	Escapes URI information in certain HTML attributesExample: <a href="%C3%A4%C3%B6%C3%BC">äöü<a>	yes, no	no
include-content-type	Inserts a meta content-type element into the head element if the result is output as HTMLExample: <head><meta http-	yes, no	no

	`equiv="Content-Type" content="text/html; charset=UTF-8"></head>`. The head element must already exist or nothing will be added. Any existing `meta` content-type elements will be removed.	

BaseX provides some additional serialization parameters:

Parameter	Description	Allowed	Default
`csv`	Defines the way how data is serialized as CSV.	see CSV Module	
`json`	Defines the way how data is serialized as JSON.	see JSON Module	
`tabulator`	Uses tab characters (`\t`) instead of spaces for indenting elements.	`yes`, `no`	`no`
`indents`	Specifies the number of characters to be indented.	*positive number*	`2`
`newline`	Specifies the type of newline to be used as end-of-line marker.	`\n`, `\r\n`, `\r`	*system dependent*
`limit`	Stops serialization after the specified number of bytes has been serialized. If a negative number is specified, everything will be output.	*positive number*	`-1`
`binary`	Indicates if items of binary type are output in their native byte representation. Only applicable to the `base` serialization method.	`yes`, `no`	`yes`

The `csv` and `json` parameters are supplied with a list of options. Option names and values are combined with `=`, several options are separated by `,`:

Query:

```
(: The output namespace declaration is optional, because it is statically declared
 in BaseX) :)
declare namespace output = "http://www.w3.org/2010/xslt-xquery-serialization";
declare option output:method "csv";
declare option output:csv "header=yes, separator=semicolon";
<csv>
  <record>
    <Name>John</Name>
    <City>Newton</City>
  </record>
  <record>
    <Name>Jack</Name>
    <City>Oldtown</City>
  </record>
</csv>
```

Result:

```
Name;City
John;Newton
Jack;Oldtown
```

Character mappings

Character maps allow a specific character in the instance of the data model to be replaced with a specified string of characters during serialization. The string that is substituted is output "as is," and the serializer performs no checks that the resulting document is well-formed. This may only occur in documents parsed with `parameter-document`. If a character is mapped, then it is not subjected to XML or HTML escaping. For details refer to section 11 Character maps in the W3C XQuery Serialization 3.1 document

This example maps the Unicode U+00A0 NO-BREAK SPACE as   (without the serialization parameter, the Unicode character would be output):

Example query:

```
declare option output:parameter-document "map.xml";
<x> </x>
```

Example parameter-document:

```
<serialization-parameters
   xmlns="http://www.w3.org/2010/xslt-xquery-serialization">
   <use-character-maps>
     <character-map character=" " map-string="&amp;#160;"/>
   </use-character-maps>
</serialization-parameters>
```

Changelog

Version 8.4

- Added: Serialization parameter `binary`.
- Updated: New serialization method `basex`. By default, items of binary type are now output in their native byte representation. The method `raw` was removed.

Version 8.0

- Added: Support for `use-character-maps` and `parameter-document`.
- Added: Serialization method `adaptive`.
- Updated: `adaptive` is new default method (before: `xml`).
- Removed: `format`, `wrap-prefix`, `wrap-uri`.

Version 7.8.2

- Added: `limit`: Stops serialization after the specified number of bytes has been serialized.

Version 7.8

- Added: `csv` and `json` serialization parameters.
- Removed: `separator` option (use `item-separator` instead).

Version 7.7.2

- Added: `csv` serialization method.
- Added: temporary serialization methods `csv-header`, `csv-separator`, `json-unescape`, `json-spec`, `json-format`.

Version 7.5

- Added: official `item-separator` and `html-version` parameter.
- Updated: `method=html5` removed; serializers updated with the latest version of the specification, using `method=html` and `version=5.0`.

Version 7.2

- Added: `separator` parameter.

Version 7.1

- Added: `newline` parameter.

Version 7.0

- Added: Serialization parameters added to REST API; JSON/JsonML/raw methods.

Chapter 33. XQuery Errors

Read this entry online in the BaseX Wiki.

This article is part of the XQuery Portal. It summarizes the codes of errors that are raised by the standard features and functions of XQuery. As the original specifications are pretty comprehensive, we tried our best to make this overview comprehensible to a wider range of readers.

The following tables list the error codes that are known to BaseX, a short description, and examples of queries raising that errors. Errors that are specific to BaseX can be found in the descriptions of the respective modules.

Original definitions of the error codes are found in the XQuery 3.0, XQuery 3.0 Functions, XQuery 1.0 Update, XQuery 1.0 Full Text, and EXPath HTTP Specifications.

Static Errors

- Namespace URI: `http://www.w3.org/2005/xqt-errors`
- Namespace prefix: `err`
- Codes: `XPST`, `XQST`

Code	Description	Examples
`XPST0003`	An error occurred while *parsing* the query string (i.e., before the query could be compiled and executed). This error is the most common one, and may be accompanied by a variety of different error messages.	`1+ for i in //* return $i`
`XPST0005`	An expression will never return any results, no matter what input is provided.	`doc('input')/..`
`XPST0008`	A variable or type name is used that has not been defined in the current scope.	`$a--- element(*, x)`
`XPST0017`	• The specified function is unknown,• it uses the wrong number of arguments, or, when calling Java functions:• there is more than one function with the same number of arguments.	`unknown() count(1,2,3)`
`XPST0051`	An unknown QName is used in a *sequence type* (e.g. in the target type of the `cast` expression).	`1 instance of x "test" cast as xs:itr`
`XPST0080`	`xs:NOTATION` or `xs:anyAtomicType` is used as target type of `cast` or `castable`.	`1 castable as xs:NOTATION`
`XPST0081`	• A QName uses a prefix that has not been bound to any namespace, or• a pragma or option declaration has not been prefixed.	`unknown:x (# pragma #) { 1 }`
`XQST0009`	The query imports a schema (schema import is not supported by BaseX).	`import schema "x"; ()`
`XQST0022`	Namespace values must be constant strings.	`<elem xmlns="{ 'dynamic' }"/>`
`XQST0031`	The specified XQuery version is not specified.	`xquery version "9.9"; ()`
`XQST0032`	The base URI was declared more than once.	`declare base-uri ...`
`XQST0033`	A namespace prefix was declared more than once.	`declare namespace a="a";declare namespace a="b"; ()`
`XQST0034`	A function was declared more than once.	`declare function local:a() { 1 };declare function local:a() { 2 }; local:a()`

XQST0038	The default collation was declared more than once.	`declare default collation ...`
XQST0039	Two or more parameters in a user-defined function have the same name.	`declare function local:fun($a, $a) { $a * $a };local:fun(1,2)`
XQDY0040	Two or more attributes in an element have the same node name.	`<elem a="1" a="12"/>`
XQDY0045	A user-defined function uses a reserved namespace.	`declare function fn:fun() { 1 }; ()`
XQST0047	A module was defined more than once.	`import module ...`
XQST0048	A module declaration does not match the namespace of the specified module.	`import module namespace invalid="uri"; 1`
XQST0049	A global variable was declared more than once.	`declare variable $a := 1;declare variable $a := 1; $a`
XQST0054	A global variable depends on itself. This may be triggered by a circular variable definition.	`declare variable $a := local:a();declare function local:a() { $a }; $a`
XQST0055	The mode for copying namespaces was declared more than once.	`declare copy-namespaces ...`
XQST0057	The namespace of a schema import may not be empty.	`import schema ""; ()`
XQST0059	The schema or module with the specified namespace cannot be found or processed.	`import module "unknown"; ()`
XQST0060	A user-defined function has no namespace.	`declare default function namespace "";declare function x() { 1 }; 1`
XQST0065	The ordering mode was declared more than once.	`declare ordering ...`
XQST0065	The default namespace mode for elements or functions was declared more than once.	`declare default element namespace ...`
XQST0067	The construction mode was declared more than once.	`declare construction ...`
XQST0068	The mode for handling boundary spaces was declared more than once.	`declare boundary-space ...`
XQST0069	The default order for empty sequences was declared more than once.	`declare default order empty ...`
XQST0070	A namespace declaration overwrites a reserved namespace.	`declare namespace xml=""; ()`
XQST0071	A namespace is declared more than once in an element constructor.	`<a xmlns="uri1" xmlns="uri2"/>`
XQST0075	The query contains a validate expression (validation is not supported by BaseX).	`validate strict { () }`
XQST0076	A `group by` or `order by` clause specifies an unknown collation.	`for $i in 1 to 10order by $i collation "unknown"return $i`
XQST0079	A pragma was specified without the expression that is to be evaluated.	`(# xml:a #) {}`
XQST0085	An empty namespace URI was specified.	`<pref:elem xmlns:pref=""/>`
XQST0087	An unknown encoding was specified. Note that the encoding declaration is currently ignored in BaseX.	`xquery version "1.0" encoding "a b"; ()`
XQST0088	An empty module namespace was specified.	`import module ""; ()`
XQST0089	Two variables in a `for` or `let` clause have the same name.	`for $a at $a in 1 return $i`

XQST0090	A character reference specifies an invalid character.	`"&#0;"`
XQST0093	A module depends on itself. This may be triggered by a circular module definition.	`import module ...`
XQST0094	`group by` references a variable that has not been declared before.	`for $a in 1 group by $b return $a`
XQST0097	A `decimal-format` property is invalid.	`declare default decimal-format digit = "xxx"; 1`
XQST0098	A single `decimal-format` character was assigned to multiple properties.	`declare default decimal-format digit = "%"; 1`
XQST0099	The context item was declared more than once.	`declare context item ...`
XQST0106	An annotation has been declared twice in a variable or function declaration.	`declare %updating %updating function ...`
XQST0108	Output declarations may only be specified in the main module.	Module: `declare output ...`
XQST0109	The specified serialization parameter is unknown.	`declare option output:unknown "..."; 1`
XQST0110	A serialization parameter was specified more than once in the output declarations.	`declare option output:indent "no";declare option output:indent "no"; 1`
XQST0111	A decimal format was declared more than once.	`declare decimal-format ...`
XQST0113	Context item values may only be in the main module.	Module: `declare context item := 1;`
XQST0114	A decimal-format property has been specified more than once.	`declare decimal-format EN NaN="!" NaN="?"; ()`

Type Errors

- Namespace URI: `http://www.w3.org/2005/xqt-errors`
- Namespace prefix: `err`
- Codes: `XPTY`, `XQTY`

Code	Description	Examples
XPTY0004	This error is raised if an expression has the wrong type, or cannot be cast into the specified type. It may be raised both statically (during query compilation) or dynamically (at runtime).	`1 + "A"` `abs("a")` `1 cast as xs:gYear`
XPTY0018	The result of the last step in a path expression contains both nodes and atomic values.	`doc('input.xml')/(*, 1)`
XPTY0019	The result of a step (other than the last step) in a path expression contains an atomic values.	`(1 to 10)/*`
XQTY0024	An attribute node cannot be bound to its parent element, as other nodes of a different type were specified before.	`<elem>text { attribute a { "val" } }</elem>`
XQTY0105	A function item has been specified as content of an element.	`<X>{ false#0 }</X>`

Dynamic Errors

- Namespace URI: `http://www.w3.org/2005/xqt-errors`
- Namespace prefix: `err`

- Codes: XPDY, XQDY

Code	Description	Examples
XPDY0002	• No value has been defined for an external variable, or• no context item has been set before the query was executed.	`declare variable $x external; $x descendant::*`
XPDY0050	• The operand type of a `treat` expression does not match the type of the argument, or• the root of the context item must be a document node.	`"string" treat as xs:int "string"[/]`
XQDY0025	Two or more attributes in a constructed element have the same node name.	`element x { attribute a { "" } attribute a { "" } }`
XQDY0026	The content of a computed processing instruction contains "?>".	`processing-instruction pi { "?>" }`
XQDY0041	The name of a processing instruction is invalid.	`processing-instruction { "1" } { "" }`
XQDY0044	The node name of an attribute uses reserved prefixes or namespaces.	`attribute xmlns { "etc" }`
XQDY0064	The name of a processing instruction equals "XML" (case insensitive).	`processing-instruction xml { "etc" }`
XQDY0072	The content of a computed comment contains "--" or ends with "-".	`comment { "one -- two" }`
XQDY0074	The name of a computed attribute or element is invalid, or uses an unbound prefix.	`element { "x y" } { "" }`
XQDY0095	A sequence with more than one item was bound to a `group by` clause.	`let $a := (1,2) group by $a return $a`
XQDY0096	The node name of an element uses reserved prefixes or namespaces.	`element { QName("uri", "xml:n") } {}`
XQDY0101	Invalid namespace declaration.	`namespace xmlns { 'x' }`
XQDY0102	Duplicate namespace declaration.	`element x { namespace a {'b'}, namespace a {'c'} }`

Functions Errors

- Namespace URI: `http://www.w3.org/2005/xqt-errors`
- Namespace prefix: `err`
- Codes: FOAR, FOCA, FOCH, FODC, FODF, FODT, FOER, FOFD, FONS, FORG, FORX, FOTY, FOUT

Code	Description	Examples
FOAR0001	A value was divided by zero.	`1 div 0`
FOAR0002	A numeric declaration or operation causes an over- or underflow.	`12345678901234567890 xs:double("-INF") idiv 1`
FOCA0002	• A float number cannot be converted to a decimal or integer value, or• a function argument cannot be converted to a valid QName.	`xs:int(xs:double("INF")) QName("", "el em")`
FOCA0003	A value is too large to be represented as integer.	`xs:integer(99e100)`
FOCA0005	`"NaN"` is supplied to duration operations.	`xs:yearMonthDuration("P1Y") * xs:double("NaN")`

FOCH0001	A codepoint was specified that does not represent a valid XML character.	`codepoints-to-string(0)`
FOCH0002	A unsupported collation was specified in a function.	`compare('a', 'a', 'unknown')`
FOCH0003	A unsupported normalization form was specified in a function.	`normalize-unicode('a', 'unknown')`
FODC0001	The argument specified in `fn:id()` or `fn:idref()` must have a document node as root.	`id("id0", <xml/>)`
FODC0002	The specified document resource cannot be retrieved.	`doc("unknown.xml")`
FODC0004	The specified collection cannot be retrieved.	`collection("unknown")`
FODC0005	The specified URI to a document resource is invalid.	`doc("<xml/>")`
FODC0006	The string passed to `fn:parse-xml()` is not well-formed.	`parse-xml("<x/")`
FODC0007	The base URI passed to `fn:parse-xml()` is invalid.	`parse-xml("<x/>", ":")`
FODF1280	The name of the decimal format passed to `fn:format-number()` is invalid.	`format-number(1, "0", "invalid")`
FODF1310	The picture string passed to `fn:format-number()` is invalid.	`format-number(1, "invalid")`
FODT0001	An arithmetic duration operation causes an over- or underflow.	`xs:date('2000-01-01') + xs:duration('P99999Y')`
FODT0002	A duration declaration or operation causes an over- or underflow.	`implicit-timezone() div 0`
FODT0003	An invalid timezone was specified.	`adjust-time-to-timezone(xs:time("01:01:01"), xs:dayTimeDuration("PT20H"))`
FOER0000	Error triggered by the `fn:error()` function.	`error()`
FOFD1340	The picture string passed to `fn:format-date()`, `fn:format-time()` or `fn:format-dateTime()` is invalid.	`format-date(current-date(), "[]")`
FOFD1350	The picture string passed to `fn:format-date()`, `fn:format-time()` or `fn:format-dateTime()` specifies an non-available component.	`format-time(current-time(), "[Y2]")`
FONS0004	A function has a QName as argument that specifies an unbound prefix.	`resolve-QName("x:e", <e/>)`
FORG0001	A value cannot be cast to the required target type.	`xs:integer("A")1 + <x>a</x>`
FORG0002	The URI passed to `fn:resolve-URI()` is invalid.	`resolve-URI(":")`
FORG0003	`fn:zero-or-one()` was called with more than one item.	`zero-or-one((1, 2))`
FORG0004	`fn:one-or-more()` was called with zero items.	`one-or-more(())`
FORG0005	`fn:exactly-one()` was called with zero or more than one item.	`exactly-one((1, 2))`
FORG0006	A wrong argument type was specified in a function call.	`sum((1, "string"))`
FORG0008	The arguments passed to `fn:dateTime()` have different timezones.	`dateTime(xs:date("2001-01-01+01:01"), current-time())`
FORX0001	A function specifies an invalid regular expression flag.	`matches('input', 'query', 'invalid')`

FORX0002	A function specifies an invalid regular expression.	`matches('input', '[')`
FORX0003	A regular expression matches an empty string.	`tokenize('input', '.?')`
FORX0004	The replacement string of a regular expression is invalid.	`replace("input", "match", "\")`
FOTY0012	An item has no typed value.	`count#1`
FOTY0013	Functions items cannot be atomized, have no defined equality, and have no string representation.	`data(false#0)`
FOTY0014	Function items have no string representation.	`string(map {})`
FOTY0015	Function items cannot be compared.	`deep-equal(false#0, true#0)`
FOUT1170	Function argument cannot be used to retrieve a text resource.	`unparsed-text(':')`
FOUT1190	Encoding to retrieve a text resource is invalid or not supported.	`unparsed-text('file.txt', 'InvalidEncoding')`

Serialization Errors

- Namespace URI: `http://www.w3.org/2005/xqt-errors`
- Namespace prefix: `err`
- Codes: SEPM, SERE, SESU

Code	Description	Examples	
SESU0007	The specified encoding is not supported.	`declare option output:encoding "xyz"; 1`	
SEPM0009	`omit-xml-declaration` is set to `yes`, and `standalone` has a value other than `omit`.		
SEPM0010	`method` is set to `xml`, `undeclare-prefixes` is set to `yes`, and `version` is set to `1.0`.		
SERE0014	`method` is set to `html`, and an invalid HTML character is found.		
SERE0015	`method` is set to `html`, and a closing bracket (>) appears inside a processing instruction.		
SEPM0016	A specified parameter is unknown or has an invalid value.	`declare option output:indent "nope"; 1`	

Update Errors

- Namespace URI: `http://www.w3.org/2005/xqt-errors`
- Namespace prefix: `err`
- Codes: FOUP, XUDY, XUST, XUTY

Code	Description	Examples
FOUP0001	The first argument of `fn:put()` must be a document node or element.	`fn:put(text { 1 }, 'file.txt')`
FOUP0002	The second argument of `fn:put()` is not a valid URI.	`fn:put(<a/>, '//')`

XUDY0009	The target node of a replace expression needs a parent in order to be replaced.	`replace node <target/> with <new/>`
XUDY0014	The expression updated by the `modify` clause was not created by the `copy` clause.	`let $a := doc('a') return copy $b := $a modify delete node $a/* return $b`
XUDY0015	In a `rename` expression, a target is renamed more than once.	`let $a := <xml/> return (rename node $a as 'a', rename node $a as 'b')`
XUDY0016	In a `replace` expression, a target is replaced more than once.	`let $a := <x>x</x>/node() return (replace node $a with <a/>, replace node $a with <b/>)`
XUDY0017	In a `replace value of` expression, a target is replaced more than once.	`let $a := <x/> return (replace value of node $a with 'a', replace value of node $a with 'a')`
XUDY0021	The resulting update expression contains duplicate attributes.	`copy $c := <x a='a'/> modify insert node attribute a {""} into $c return $c`
XUDY0023	The resulting update expression conflicts with existing namespaces.	`rename node <a:ns xmlns:a='uri'/> as QName('URI', 'a:ns')`
XUDY0024	New namespaces conflict with each other.	`copy $n := <x/> modify (insert node attribute { QName('uri1', 'a') } { "" } into $n, insert node attribute { QName('uri2', 'a') } { "" } into $n) return $n`
XUDY0027	Target of an update expression is an empty sequence.	`insert node <x/> into ()`
XUDY0029	The target of an update expression has no parent node.	`insert node <new/> before <target/>`
XUDY0030	Attributes cannot be inserted before or after the child of a document node.	`insert node <e a='a'/>/@a after document { <e/> }/*`
XUDY0031	Multiple calls to `fn:put()` address the same URI.	`for $i in 1 to 3 return put(<a/>, 'file.txt')`
XUST0001	No updating expression is allowed here.	`delete node /, "finished."`
XUST0002	An updating expression is expected in the `modify` clause or an updating function.	`copy $a := <x/> modify 1 return $a`
XUST0003	The revalidation mode was declared more than once.	`declare revalidation ...`
XUST0026	The query contains a revalidate expression (revalidation is not supported by BaseX).	`declare revalidation ...`
XUST0028	no return type may be specified in an updating function.	`declare updating function local:x() as item() { () }; ()`
XUTY0004	New attributes to be inserted must directly follow the root node.	`insert node (<a/>, attribute a {""}) into <a/>`
XUTY0005	A single element or document node is expected as target of an `insert` expression.	`insert node <new/> into attribute a { "" }`

XUTY0006	A single element, text, comment or processing instruction is expected as target of an `insert before/after` expression.	`insert node <new/> after attribute a { "" }`
XUTY0007	Only nodes can be deleted.	`delete node "string"`
XUTY0008	A single element, text, attribute, comment or processing instruction is expected as target of a `replace` expression.	`replace node document { <a/> } with <b/>`
XUTY0010	In a `replace` expression, in which no attributes are targeted, the replacing nodes must not be attributes as well.	`replace node <a><b/></a>/b with attribute size { 1 }`
XUTY0011	In the `replace` expression, in which attributes are targeted, the replacing nodes must be attributes as well.	`replace node <e a=""/>/@a with <a/>`
XUTY0012	In a `rename` expression, the target nodes must be an element, attribute or processing instruction.	`rename node text { 1 } as <x/>`
XUTY0013	An expression in the `copy` clause must return a single node.	`copy $c := (<a/>, <b/>) modify () return $c`
XUTY0022	An attribute must not be inserted into a document node.	`insert node <e a=""/>/@a into document {'a'}`

Full-Text Errors

- Namespace URI: `http://www.w3.org/2005/xqt-errors`
- Namespace prefix: `err`
- Codes: `FTDY`, `FTST`

Code	Description	Examples
FTDY0016	The specified weight value is out of range.	`'a' contains text 'a' weight { 1001 }`
FTDY0017	The `not in` operator contains a *string exclude*.	`'a' contains text 'a' not in (ftnot 'a')`
FTDY0020	The search term uses an invalid wildcard syntax.	`'a' contains text '.{}' using wildcards`
FTST0007	The full-text expression contains an ignore option (the `ignore option` is not supported by BaseX).	`'a' contains text 'a' without content 'x'`
FTST0008	The specified stop word file could not be opened or processed.	`'a' contains text 'a' using stop words at 'unknown.txt'`
FTST0009	The specified language is not supported.	`'a' contains text 'a' using language 'aaa'`
FTST0018	The specified thesaurus file could not be opened or processed.	`'a' contains text 'a' using thesaurus at 'aaa'`
FTST0019	A match option was specified more than once.	`'a' contains text 'a' using stemming using stemming`

BaseX Errors

- Namespace URI: `http://basex.org`
- Namespace prefix: `basex`

Code	Description	Examples

annotation	Annotation errors.	`%basex:xyz function() { 123 }`
doc	The argument specified via fn:doc must yield a single document.	`doc('db-collection')`
error	Generic error, which is e. g. raised by Java bindings.	`import module namespace qm='java:org.basex.query.func.QueryModuleTest`
function	Function items cannot be cached.	`db:output(true#0)`
http	The function was called outside an HTTP servlet context.	`session:get('abc')`
options	The specified database option is unknown.	`declare option db:xyz 'no'; 1`
overflow	Stack overflow.	`declare function local:a() { local:b() + 1 };declare function local:b() { local:a() + 2 };local:a()`
permission	The current user has insufficient permissions to open a database, update nodes, etc.	`db:open('admin')`
restxq	Errors related to RESTXQ.	`%restxq:GET('x')`
update	BaseX-specific update errors.	`<a/> update db:output('bla')`

Additional, module-specific error codes are listed in the descriptions of the query modules.

Part VI. XQuery Modules

Chapter 34. Admin Module

Read this entry online in the BaseX Wiki.

This XQuery Module contains functions for performing admin-centric operations such as managing database users and log data.

Conventions

Updated with Version 9.0:

All functions and errors in this module are assigned to the `http://basex.org/modules/admin` namespace, which is statically bound to the `admin` prefix.

Functions

admin:sessions

Signatures	`admin:sessions() as element(session)*`
Summary	Returns an element sequence with all currently opened database sessions, including the user name, address (IP:port) and an optionally opened database.The output of this function and the `SHOW SESSIONS` command is similar.
Examples	• `admin:sessions()` may e.g. return `<session user="admin" address="127.0.0.1:6286" database="factbook"/>`

admin:logs

Signatures	`admin:logs() as element(file)* admin:logs($date as xs:string) as element(entry)* admin:logs($date as xs:string, $merge as xs:boolean) as element(entry)*`
Summary	Returns Logging data compiled by the database or HTTP server: • If no argument is specified, a list of all log files will be returned, including the file size and date. • If a `$date` is specified, the contents of a single log file will be returned. • If `$merge` is set to true, related log entries will be merged. Please note that the merge might not be 100% successful, as log entries may be ambiguous.
Examples	• `admin:logs()` may return `<file size="834367"/>2015-01-23</file>` if a single log file exists. • `admin:logs() ! admin:logs(.)` lists the contents of all log files.

admin:write-log

Signatures	`admin:write-log($text as xs:string) as empty-sequence() admin:write-log($text as xs:string, $type as xs:string) as empty-sequence()`
Summary	Writes a string to the database logs, along with current user data (timestamp, user name). An optional log `$type` can be specified, which must consist of letters in upper case. If omitted, the log type is `INFO`.If the function is called from a database client, the IP will be logged. Otherwise, the string `SERVER` will be logged.
Errors	`type`: Log type must consist of uppercase letters.

admin:delete-logs

Signatures	`admin:delete-logs($date as xs:string) as empty-sequence()`
Summary	Deletes the log entries from the specified `$date`
Errors	`today`: Today's log file cannot be deleted.`delete`: An error occurred while deleting a log file.

Errors

Updated with Version 9.0:

Code	Description
`delete`	An error occurred while deleting a log file.
`today`	Today's log file cannot be deleted.
`type`	Log type must consist of uppercase letters.

Changelog

Version 9.0

- Updated: error codes updated; errors now use the module namespace

Version 8.3

- Updated: admin:write-log: optional log type added

Version 8.2

- Added: admin:delete-logs

Version 8.0

- Added: admin:write-log
- Deleted: admin:users (renamed to user:list-details)

Version 7.8.2

- Updated: admin:users: md5-encoded password added to output.
- Updated: admin:logs: represent name of log files as string value; `$merge` argument added.

The Module was introduced with Version 7.5.

Chapter 35. Archive Module

Read this entry online in the BaseX Wiki.

This XQuery Module contains functions to handle archives (including ePub, Open Office, JAR, and many other formats). New ZIP and GZIP archives can be created, existing archives can be updated, and the archive entries can be listed and extracted. The archive:extract-binary function includes an example for writing the contents of an archive to disk.

Conventions

Updated with Version 9.0:

All functions and errors in this module are assigned to the `http://basex.org/modules/archive` namespace, which is statically bound to the `archive` prefix.

Functions

archive:create

Signatures	`archive:create($entries as item(), $contents as item()*) as xs:base64Binary` `archive:create($entries as item(), $contents as item()*, $options as map(*)?) as xs:base64Binary`
Summary	Creates a new archive from the specified entries and contents.The `$entries` argument contains meta information required to create new entries. All items may either be of type `xs:string`, representing the entry name, or `element(archive:entry)`, containing the name as text node and additional, optional attributes: • `last-modified` : timestamp, specified as xs:dateTime (default: current time) • `compression-level` : 0-9, 0 = uncompressed (default: 8) • `encoding` : for textual entries (default: UTF-8) An example: `<archive:entry last-modified='2011-11-11T11:11:11' compression-level='8' encoding='US-ASCII'>hello.txt</archive:entry>` The actual `$contents` must be `xs:string` or `xs:base64Binary` items. The `$options` parameter contains archiving options: • `format` : allowed values are `zip` and `gzip`. `zip` is the default. • `algorithm` : allowed values are `deflate` and `stored` (for the `zip` format). `deflate` is the default.
Errors	`number`: the number of entries and contents differs.`format`: the specified option or its value is invalid or not supported.`descriptor`: entry descriptors contain invalid entry names, timestamps or compression levels.`encode`: the specified encoding is invalid or not supported, or the string conversion failed. Invalid XML characters will be ignored if the `CHECKSTRINGS` option is turned off.`single`: the chosen archive format only allows single entries.`error`: archive creation failed for some other reason.
Examples	The following one-liner creates an archive `archive.zip` with one file `file.txt`: `archive:create(<archive:entry>file.txt</archive:entry>, 'Hello World')`

The following function creates an archive `mp3.zip`, which contains all MP3 files of a local directory:

```
let $path  := 'audio/'
let $files := file:list($path, true(), '*.mp3')
let $zip   := archive:create(
  $files ! element archive:entry { . },
  $files ! file:read-binary($path || .))
return file:write-binary('mp3.zip', $zip)
```

archive:create-from

Signatures	`archive:create-from($path as xs:string) as xs:base64Binary` `archive:create-from($path as xs:string, $options as map(*)?) as xs:base64Binary` `archive:create-from($path as xs:string, $options as map(*)?, $entries as item()*) as xs:base64Binary`
Summary	This convenience function creates an archive from all files in the specified directory `$path`.The `$options` parameter contains archiving options, and the files to be archived can be limited via `$entries`. The format of the two last arguments is the same as for archive:create.
Errors	`file:no-dir`: the specified path does not point to a directory.`file:is-dir`: one of the specified entries points to a directory.`file:not-found`: a specified entry does not exist.`error`: archive creation failed for some other reason.

Examples	This example writes the files of a user's home directory to `archive.zip`:
	`let $zip := archive:create-from('/home/user/')`
	`return file:write-binary('archive.zip', $zip)`

archive:entries

Signatures	`archive:entries($archive as xs:base64Binary) as element(archive:entry)*`

Summary	Returns the entry descriptors of the specified `$archive`. A descriptor contains the following attributes, provided that they are available in the archive format:
	• `size` : original file size
	• `last-modified` : timestamp, formatted as xs:dateTime
	• `compressed-size` : compressed file size
	An example:
	`<archive:entry size="1840" last-modified="2009-03-20T03:30:32"`
	`compressed-size="672">`
	`doc/index.html`
	`</archive:entry>`

Errors	`error`: archive creation failed for some other reason.
Examples	Sums up the file sizes of all entries of a JAR file: `sum(archive:entries(file:read-binary('zip.zip'))/@size)`

archive:options

Signatures	`archive:options($archive as xs:base64Binary) as map(*)`

Summary	Returns the options of the specified `$archive` in the format specified by archive:create.
Errors	`format`: The packing format is not supported.`error`: archive creation failed for some other reason.
Examples	A standard ZIP archive will return the following options: `map { "format": "zip", "algorithm": "deflate" }`

archive:extract-text

Signatures	`archive:extract-text($archive as xs:base64Binary) as xs:string* archive:extract-text($archive as xs:base64Binary, $entries as item()*) as xs:string* archive:extract-text($archive as xs:base64Binary, $entries as item()*, $encoding as xs:string) as xs:string*`
Summary	Extracts entries of the specified `$archive` and returns them as texts.The returned entries can be limited via `$entries`. The format of the argument is the same as for archive:create (attributes will be ignored).The encoding of the input files can be specified via `$encoding`.
Errors	`encode`: the specified encoding is invalid or not supported, or the string conversion failed. Invalid XML characters will be ignored if the `CHECKSTRINGS` option is turned off.`error`: archive creation failed for some other reason.
Examples	The following expression extracts all `.txt` files from an archive: `let $archive := file:read-binary("documents.zip") for $entry in archive:entries($archive)[ends-with(., '.txt')] return archive:extract-text($archive, $entry)`

archive:extract-binary

Signatures	`archive:extract-binary($archive as xs:base64Binary) as xs:base64Binary* archive:extract-binary($archive as xs:base64Binary, $entries as item()*) as xs:base64Binary*`
Summary	Extracts entries of the specified `$archive` and returns them as binaries.The returned entries can be limited via `$entries`. The format of the argument is the same as for archive:create (attributes will be ignored).
Errors	`error`: archive creation failed for some other reason.
Examples	This example unzips all files of an archive to the current directory: `let $archive := file:read-binary('archive.zip') let $entries := archive:entries($archive) let $contents := archive:extract-binary($archive) return for-each-pair($entries, $contents, function($entry, $content) { file:create-dir(replace($entry, "[^/]+$", "")), file:write-binary($entry, $content) })`

archive:extract-to

Signatures	`archive:extract-to($path as xs:string, $archive as xs:base64Binary) as empty-sequence() archive:extract-to($path as xs:string, $archive as xs:base64Binary, $entries as item()*) as empty-sequence()`

Summary	This convenience function writes files of an `$archive` directly to the specified directory `$path`.The archive entries to be written can be restricted via `$entries`. The format of the argument is the same as for archive:create (attributes will be ignored).
Errors	`error`: archive creation failed for some other reason.
Examples	The following expression unzips all files of an archive to the current directory: `archive:extract-to('.', file:read-binary('archive.zip'))`

archive:update

Signatures	`archive:update($archive as xs:base64Binary, $entries as item()*, $contents as item()*) as xs:base64Binary`
Summary	Creates an updated version of the specified `$archive` with new or replaced entries.The format of `$entries` and `$contents` is the same as for archive:create.
Errors	`number`: the number of entries and contents differs.`descriptor`: entry descriptors contain invalid entry names, timestamps, compression levels or encodings.`encode`: the specified encoding is invalid or not supported, or the string conversion failed. Invalid XML characters will be ignored if the `CHECKSTRINGS` option is turned off.`modify`: the entries of the given archive cannot be modified.`error`: archive creation failed for some other reason.

Examples	This example replaces texts in a Word document:
	`declare variable $input  := "HelloWorld.docx";`
	`declare variable $output := "HelloUniverse.docx";`
	`declare variable $doc    := "word/document.xml";`
	
	`let $archive := file:read-binary($input)`
	`let $entry   :=`
	`  copy $c := fn:parse-xml(archive:extract-text($archive, $doc))`
	`  modify replace value of node $c//*[text() = "HELLO WORLD!"] with`
	` "HELLO UNIVERSE!"`
	`  return fn:serialize($c)`
	`let $updated := archive:update($archive, $doc, $entry)`
	`return file:write-binary($output, $updated)`

archive:delete

Signatures	`archive:delete($archive as xs:base64Binary, $entries as item()*) as xs:base64Binary`
Summary	Deletes entries from an `$archive`.The format of `$entries` is the same as for archive:create.
Errors	`modify`: the entries of the given archive cannot be modified.`error`: archive creation failed for some other reason.

Examples	This example deletes all HTML files in an archive and creates a new file:
	`let $zip := file:read-binary('old.zip')`
	`let $entries := archive:entries($zip)[matches(., '\.x?html?$', 'i')]`
	`return file:write-binary('new.zip', archive:delete($zip, $entries))`

Errors

Updated with Version 9.0:

Code	Description
`descriptor`	Entry descriptors contain invalid entry names, timestamps or compression levels.

`encode`	The specified encoding is invalid or not supported, or the string conversion failed. Invalid XML characters will be ignored if the `CHECKSTRINGS` option is turned off.
`error`	Archive processing failed for some other reason.
`format`	The packing format or the specified option is invalid or not supported.
`modify`	The entries of the given archive cannot be modified.
`number`	The number of specified entries and contents differs.
`single`	The chosen archive format only allows single entries.

Changelog

Version 9.0

- Updated: error codes updated; errors now use the module namespace

Version 8.5

- Updated: archive:options: map returned instead of element

Version 8.3

- Added: archive:create-from, archive:extract-to (replaces `archive:write`)

Version 7.7

- Added: archive:write

The module was introduced with Version 7.3.

Chapter 36. Array Module

Read this entry online in the BaseX Wiki.

This XQuery Module contains functions for manipulating arrays, which has been introduced with XQuery 3.1.

Conventions

All functions and errors in this module are assigned to the `http://www.w3.org/2005/xpath-functions/array` namespace, which is statically bound to the `array` prefix.

Functions

array:size

Signatures	`array:size($input as array(*)) as xs:integer`
Summary	Returns the number of members in `$array`. Note that because an array is an item, the `fn:count` function when applied to an array always returns `1`.
Examples	• `array:size(array { 1 to 10 })` returns `10`. • `array:size([1 to 10])` returns `1`, because the array contains a single sequence with 10 integers.

array:get

Signatures	`array:get($array as array(*), $position as xs:integer) as item()*`
Summary	Returns the `$array` member at the specified `$position`.
Errors	`FOAY0001`: `$position` is not in the range `1` to `array:size($array)` inclusive.
Examples	• `array:get(array { reverse(1 to 5) }, 5)` returns the value `1`.

array:append

Signatures	`array:append($array as array(*), $member as item()*) as array(*)`
Summary	Returns a copy of `$array` with a new `$member` attached.
Examples	• `array:append([], 'member1')` returns the array `["member1"]`.

array:subarray

Signatures	`array:subarray($array as array(*), $position as xs:integer) as array(*) array:subarray($array as array(*), $position as xs:integer, $length as xs:integer) as array(*)`
Summary	Constructs a new array with with `$length` members of `$array` beginning from the specified `$position`.The two-argument version of the function returns the same result as the three-argument version when called with `$length` equal to the value of `array:size($array) - $position + 1`.
Errors	`FOAY0001`: `$position` is less than one, or if `$position + $length` is greater than `array:size($array) + 1`.`FOAY0002`: `$length` is less than zero.
Examples	• `array:subarray(["a", "b", "c"], 2)` returns the array `["b", "c"]`.

array:put

Signatures	`array:put($array as array(*), $position as xs:integer, $member as item()*) as array(*)`

Summary	Returns a copy of `$array` with `$member` replaced at the specified `$position`. Equivalent to `$array => array:remove($position) => array:insert-before($position, $member)`.
Errors	`FOAY0001`: `$position` is not in the range `1` to `array:size($array)` inclusive.
Examples	• `array:put(["a", "b", "c"], 2, "d")` returns the array `["a", "d", "c"]`.

array:remove

Signatures	`array:remove($array as array(*), $positions as xs:integer*) as array(*)`
Summary	Returns a copy of `$array` without the member at the specified `$positions`.
Errors	`FOAY0001`: A position is not in the range `1` to `array:size($array)` inclusive.
Examples	• `array:append(["a"], 1)` returns the array `[]`.

array:insert-before

Signatures	`array:insert-before($array as array(*), $position as xs:integer, $member as item()*) as array(*)`
Summary	Returns a copy of `$array` with one new `$member` at the specified `$position`. Setting `$position` to the value `array:size($array) + 1` yields the same result as `array:append($array, $insert)`.
Errors	`FOAY0001`: `$position` is not in the range `1` to `array:size($array) + 1` inclusive.
Examples	• `array:insert-before(["a"], 1, "b")` returns the array `["b", "a"]`.

array:head

Signatures	`array:head($array as array(*)) as item()*`
Summary	Returns the first member of `$array`. This function is equivalent to the expression `$array(1)`.
Errors	`FOAY0001`: The array is empty.
Examples	• `array:head(["a", "b"])` returns `"a"`. • `array:head([["a", "b"], ["c", "d"]])` returns the array `["a", "b"]`.

array:tail

Signatures	`array:tail($array as array(*)) as array(*)`
Summary	Returns a new array with all members except the first from `$array`. This function is equivalent to the expression `array:remove($array, 1)`.
Errors	`FOAY0001`: The array is empty.
Examples	• `array:insert-before(["a"], 1, "b")` returns the array `["b", "a"]`.

array:reverse

Signatures	`array:reverse($array as array(*)) as array(*)`
Summary	Returns a new array with all members of `$array` in reverse order.
Examples	• `array:reverse(array { 1 to 3 })` returns the array `[3, 2, 1]`.

array:join

Signatures	`array:join($arrays as array(*)*) as array(*)`

Summary	Concatenates the contents of several `$arrays` into a single array.
Examples	• `array:join(())` returns the array `[]`. • `array:join((1 to 3) ! array { . })` returns the array `[1, 2, 3]`.

array:flatten

Signatures	`array:flatten($items as item()*) as item()*`
Summary	Recursively flattens all arrays that occur in the supplied `$items`.
Examples	• `array:flatten(["a","b"])` returns the sequence `"a", "b"`. • `array:flatten([1,[2,3],4])` returns the sequence `1, 2, 3, 4`.

array:for-each

Signatures	`array:for-each($array as array(*), $function as function(item()*) as item()*) as array(*)`
Summary	Returns a new array, in which each member is computed by applying `$function` to the corresponding member of `$array`.

Examples	The following query returns the array `[2, 3, 4, 5, 6]`:
	`array:for-each(`
	`  array { 1 to 5 },`
	`  function($i) { $i + 1}`
	`)`

array:filter

Signatures	`array:filter($array as array(*), $function as function(item()*) as xs:boolean) as array(*)`
Summary	Returns a new array with those members of `$array` for which `$function` returns `true`.

Examples	The following query returns the array `[0, 1, 3]`:
	`array:filter(`
	`  array { 0, 1, -2, 3, -4 },`
	`  function($i) { $i > 0 }`
	`)`

array:fold-left

Signatures	`array:fold-left($array as array(*), $zero as item()*, $function as function(item()*, item()*) as item()*) as item()*`
Summary	Evaluates the supplied `$function` cumulatively on successive members of the supplied `$array` from left to right and using `$zero` as first argument.

Examples	The following query returns `55` (the sum of the integers 1 to 10):
	`array:fold-left(`
	`  array { 1 to 10 },`
	`  0,`
	`  function($a, $b) { $a + $b }`
	`)`

array:fold-right

Signatures	`array:fold-right($array as array(*), $zero as item()*, $function as function(item()*, item()*) as item()*) as item()*`
Summary	Evaluates the supplied `$function` cumulatively on successive members of the supplied `$array` from right to left and using `$zero` as first argument.
Examples	The following query is equivalent to the expression `array:reverse(array { 1 to 5 })`: `array { array:fold-right( array { 1 to 5 }, (), function($a, $b) { $b, $a } ) }`

array:for-each-pair

Signatures	`array:for-each-pair($array1 as array(*), $array2 as array(*), $function as function(item()*) as item()*) as array(*)`
Summary	Returns a new array obtained by evaluating the supplied `$function` for each pair of members at the same position in `$array1` and `$array2`.
Examples	The following query returns the array `[5, 7, 9]`: `array:for-each-pair( array { 1 to 3 }, array { 4 to 6 }, function($a + $b) { $a + $b } )`

array:sort

Signatures	`array:sort($array as array(*)) as array(*)` `array:sort($array as array(*), $collation as xs:string?) as xs:anyAtomicType*) as array(*)` `array:sort($array as array(*), $collation as xs:string?, $key as function(item()*) as xs:anyAtomicType*) as array(*)`
Summary	Returns a new array with sorted `$array` members, using an optional `$collation`. If a `$key` function is supplied, it will be applied on all array members. The items of the resulting values will be sorted using the semantics of the `lt` expression.
Examples	• `array:sort(array { reverse(1 to 3) })` returns `[1, 2, 3]` • `array:sort([3,-2,1], (), abs#1)` returns `[1, -2, 3]` • `array:sort([1,2,3], (), function($x) { -$x })` returns `[3, 2, 1]` • `array:sort((1,'a'))` returns an error (strings and integers cannot be compared)

Errors

Code	Description
`FOAY0001`	The specified index extends beyonds the bounds of an array.
`FOAY0002`	The specified length is less than zero.

Changelog

Version 8.6

- Updated: Collation argument was inserted between first and second argument.

Version 8.5

- Added: array:put

Version 8.4

- Removed: array:serialize (use fn:serialize instead)

Introduced with Version 8.0.

Chapter 37. Binary Module

Read this entry online in the BaseX Wiki.

This XQuery Module contains functions to process binary data, including extracting subparts, searching, basic binary operations and conversion between binary and structured forms.

This module is based on the EXPath Binary Module.

Conventions

All functions and errors in this module are assigned to the `http://expath.org/ns/binary` namespace, which is statically bound to the `bin` prefix.

Constants and Conversions

bin:hex

Signatures	`bin:hex($in as xs:string?) as xs:base64Binary?`
Summary	Returns the binary form of the set of octets written as a sequence of (ASCII) hex digits ([0-9A-Fa-f]).`$in` will be effectively zero-padded from the left to generate an integral number of octets, i.e. an even number of hexadecimal digits. If `$in` is an empty string, then the result will be an `xs:base64Binary` with no embedded data. Byte order in the result follows (per-octet) character order in the string. If the value of `$in` is the empty sequence, the function returns an empty sequence.
Errors	`non-numeric-character`: the input cannot be parsed as a hexadecimal number.
Examples	`string(bin:hex('11223F4E'))` yields `ESI/Tg==`.`string(xs:hexBinary(bin:hex('FF')))` yields `FF`.

bin:bin

Signatures	`bin:bin($in as xs:string?) as xs:base64Binary?`
Summary	Returns the binary form of the set of octets written as a sequence of (8-wise) (ASCII) binary digits ([01]).`$in` will be effectively zero-padded from the left to generate an integral number of octets. If `$in` is an empty string, then the result will be an `xs:base64Binary` with no embedded data. Byte order in the result follows (per-octet) character order in the string. If the value of `$in` is the empty sequence, the function returns an empty sequence.
Errors	`non-numeric-character`: the input cannot be parsed as a binary number.
Examples	`string(bin:bin('1101000111010101'))` yields `0dU=`.`string(xs:hexBinary(bin:bin('1000111010101')))` yields `11D5`.

bin:octal

Signatures	`bin:octal($in as xs:string?) as xs:base64Binary?`
Summary	Returns the binary form of the set of octets written as a sequence of (ASCII) octal digits ([0-7]).`$in` will be effectively zero-padded from the left to generate an integral number of octets. If `$in` is an empty string, then the result will be an `xs:base64Binary` with no embedded data. Byte order in the result follows (per-octet) character order in the string. If the value of `$in` is the empty sequence, the function returns an empty sequence.
Errors	`non-numeric-character`: the input cannot be parsed as an octal number.
Examples	`string(xs:hexBinary(bin:octal('11223047')))` yields `252627`.

bin:to-octets

Signatures	`bin:to-octets($in as xs:base64Binary) as xs:integer*`
Summary	Returns binary data as a sequence of octets.If `$in` is a zero length binary data then the empty sequence is returned. Octets are returned as integers from 0 to 255.

bin:from-octets

Signatures	`bin:from-octets($in as xs:integer*) as xs:base64Binary`
Summary	Converts a sequence of octets into binary data.Octets are integers from 0 to 255. If the value of `$in` is the empty sequence, the function returns zero-sized binary data.
Errors	`octet-out-of-range`: one of the octets lies outside the range 0 - 255.

Basic Operations

bin:length

Signatures	`bin:length($in as xs:base64Binary) as xs:integer`
Summary	Returns the size of binary data in octets.

bin:part

Signatures	`bin:part($in as xs:base64Binary?, $offset as xs:integer) as xs:base64Binary? bin:part($in as xs:base64Binary?, $offset as xs:integer, $size as xs:integer) as xs:base64Binary?`
Summary	Returns a section of binary data starting at the `$offset` octet.If `$size` is specified, the size of the returned binary data is `$size` octets. If `$size` is absent, all remaining data from `$offset` is returned. The `$offset` is zero based. If the value of `$in` is the empty sequence, the function returns an empty sequence.
Errors	`negative-size`: the specified size is negative.`index-out-of-range`: the specified offset + size is out of range.
Examples	Test whether binary data starts with binary content consistent with a PDF file:`bin:part($data, 0, 4) eq bin:hex("25504446")`.

bin:join

Signatures	`bin:join($in as xs:base64Binary*) as xs:base64Binary`
Summary	Returns an `xs:base64Binary` created by concatenating the items in the sequence `$in`, in order. If the value of `$in` is the empty sequence, the function returns a binary item containing no data bytes.

bin:insert-before

Signatures	`bin:insert-before($in as xs:base64Binary?, $offset as xs:integer, $extra as xs:base64Binary?) as xs:base64Binary?`
Summary	Returns binary data consisting sequentially of the data from `$in` up to and including the `$offset - 1` octet, followed by all the data from `$extra`, and then the remaining data from `$in`.The `$offset` is zero based. If the value of `$in` is the empty sequence, the function returns an empty sequence.
Errors	`index-out-of-range`: the specified offset is out of range.

bin:pad-left

Signatures	`bin:pad-left($in as xs:base64Binary?, $size as xs:integer) as xs:base64Binary?` `bin:pad-left($in as xs:base64Binary?, $size as xs:integer, $octet as xs:integer) as xs:base64Binary?`
Summary	Returns an `xs:base64Binary` created by padding the input with `$size` octets in front of the input. If `$octet` is specified, the padding octets each have that value, otherwise they are zero.If the value of `$in` is the empty sequence, the function returns an empty sequence.
Errors	`negative-size`: the specified size is negative.`octet-out-of-range`: the specified octet lies outside the range 0-255.

bin:pad-right

Signatures	`bin:pad-right($in as xs:base64Binary?, $size as xs:integer) as xs:base64Binary?` `bin:pad-right($in as xs:base64Binary?, $size as xs:integer, $octet as xs:integer) as xs:base64Binary?`
Summary	Returns an `xs:base64Binary` created by padding the input with `$size` octets after the input. If `$octet` is specified, the padding octets each have that value, otherwise they are zero.If the value of `$in` is the empty sequence, the function returns an empty sequence.
Errors	`negative-size`: the specified size is negative.`octet-out-of-range`: the specified octet lies outside the range 0-255.

bin:find

Signatures	`bin:find($in as xs:base64Binary?, $offset as xs:integer, $search as xs:base64Binary) as xs:integer?`
Summary	Returns the first location of the binary search sequence in the input, or if not found, the empty sequence.The `$offset` and the returned location are zero based. If the value of `$in` is the empty sequence, the function returns an empty sequence.
Errors	`index-out-of-range`: the specified offset + size is out of range.

Text Decoding and Encoding

bin:decode-string

Signatures	`bin:decode-string($in as xs:base64Binary?, $encoding as xs:string) as xs:string?` `bin:decode-string($in as xs:base64Binary?, $encoding as xs:string, $offset as xs:integer) as xs:string?` `bin:decode-string($in as xs:base64Binary?, $encoding as xs:string, $offset as xs:integer, $size as xs:integer) as xs:string?`
Summary	Decodes binary data as a string in a given `$encoding`.If `$offset` and `$size` are provided, the `$size` octets from `$offset` are decoded. If `$offset` alone is provided, octets from `$offset` to the end are decoded.If the value of `$in` is the empty sequence, the function returns an empty sequence.
Errors	`negative-size`: the specified size is negative.`index-out-of-range`: the specified offset + size is out of range.`unknown-encoding`: the specified encoding is unknown.`conversion-error`: an error or malformed input occurred during decoding the string.
Examples	Tests whether the binary data starts with binary content consistent with a PDF file:`bin:decode-string($data, 'UTF-8', 0, 4) eq '%PDF'`.

bin:encode-string

Signatures	`bin:encode-string($in as xs:string?, $encoding as xs:string) as xs:base64Binary?`

Summary	Encodes a string into binary data using a given `$encoding`.If the value of `$in` is the empty sequence, the function returns an empty sequence.
Errors	`unknown-encoding`: the specified encoding is unknown.`conversion-error`: an error or malformed input occurred during encoding the string.

Packing and Unpacking of Numeric Values

The functions have an optional parameter $octet-order whose string value controls the order: Least-significant-first order is indicated by any of the values `least-significant-first`, `little-endian`, or `LE`. Most-significant-first order is indicated by any of the values `most-significant-first`, `big-endian`, or `BE`.

bin:pack-double

Signatures	`bin:pack-double($in as xs:double) as xs:base64Binary` `bin:pack-double($in as xs:double, $octet-order as xs:string) as xs:base64Binary`
Summary	Returns the 8-octet binary representation of a double value.Most-significant-octet-first number representation is assumed unless the `$octet-order` parameter is specified.
Errors	`unknown-significance-order`: the specified octet order is unknown.

bin:pack-float

Signatures	`bin:pack-float($in as xs:float) as xs:base64Binary` `bin:pack-float($in as xs:float, $octet-order as xs:string) as xs:base64Binary`
Summary	Returns the 4-octet binary representation of a float value.Most-significant-octet-first number representation is assumed unless the `$octet-order` parameter is specified.
Errors	`unknown-significance-order`: the specified octet order is unknown.

bin:pack-integer

Signatures	`bin:pack-integer($in as xs:integer, $size as xs:integer) as xs:base64Binary` `bin:pack-integer($in as xs:integer, $size as xs:integer, $octet-order as xs:string) as xs:base64Binary`
Summary	Returns the twos-complement binary representation of an integer value treated as `$size` octets long. Any 'excess' high-order bits are discarded.Most-significant-octet-first number representation is assumed unless the `$octet-order` parameter is specified. Specifying a `$size` of zero yields an empty binary data.
Errors	`unknown-significance-order`: the specified octet order is unknown.`negative-size`: the specified size is negative.

bin:unpack-double

Signatures	`bin:unpack-double($in as xs:base64Binary, $offset as xs:integer) as xs:double` `bin:unpack-double($in as xs:base64Binary, $offset as xs:integer, $octet-order as xs:string) as xs:double`
Summary	Extracts the double value stored at the particular offset in binary data.Most-significant-octet-first number representation is assumed unless the `$octet-order` parameter is specified. The `$offset` is zero based.
Errors	`index-out-of-range`: the specified offset is out of range.`unknown-significance-order`: the specified octet order is unknown.

bin:unpack-float

Signatures	`bin:unpack-float($in as xs:base64Binary, $offset as xs:integer) as xs:float` `bin:unpack-float($in as xs:base64Binary, $offset as xs:integer, $octet-order as xs:string) as xs:float`
Summary	Extracts the float value stored at the particular offset in binary data.Most-significant-octet-first number representation is assumed unless the `$octet-order` parameter is specified. The `$offset` is zero based.
Errors	`index-out-of-range`: the specified offset + size is out of range.`unknown-significance-order`: the specified octet order is unknown.

bin:unpack-integer

Signatures	`bin:unpack-integer($in as xs:base64Binary, $offset as xs:integer, $size as xs:integer) as xs:integer` `bin:unpack-integer($in as xs:base64Binary, $offset as xs:integer, $size as xs:integer, $octet-order as xs:string) as xs:integer`
Summary	Returns a signed integer value represented by the `$size` octets starting from `$offset` in the input binary representation. Necessary sign extension is performed (i.e. the result is negative if the high order bit is '1').Most-significant-octet-first number representation is assumed unless the `$octet-order` parameter is specified. The `$offset` is zero based. Specifying a `$size` of zero yields the integer `0`.
Errors	`negative-size`: the specified size is negative.`index-out-of-range`: the specified offset + size is out of range.`unknown-significance-order`: the specified octet order is unknown.

bin:unpack-unsigned-integer

Signatures	`bin:unpack-unsigned-integer($in as xs:base64Binary, $offset as xs:integer, $size as xs:integer) as xs:integer` `bin:unpack-unsigned-integer($in as xs:base64Binary, $offset as xs:integer, $size as xs:integer, $octet-order as xs:string) as xs:integer`
Summary	Returns an unsigned integer value represented by the `$size` octets starting from `$offset` in the input binary representation.Most-significant-octet-first number representation is assumed unless the `$octet-order` parameter is specified. The `$offset` is zero based. Specifying a `$size` of zero yields the integer `0`.
Errors	`negative-size`: the specified size is negative.`index-out-of-range`: the specified offset + size is out of range.`unknown-significance-order`: the specified octet order is unknown.

Bitwise Operations

bin:or

Signatures	`bin:or($a as xs:base64Binary?, $b as xs:base64Binary?) as xs:base64Binary?`
Summary	Returns the "bitwise or" of two binary arguments.If either argument is the empty sequence, an empty sequence is returned.
Errors	`differing-length-arguments`: the input arguments are of differing length.

bin:xor

Signatures	`bin:xor($a as xs:base64Binary?, $b as xs:base64Binary?) as xs:base64Binary?`

Summary	Returns the "bitwise xor" of two binary arguments.If either argument is the empty sequence, an empty sequence is returned.
Errors	`differing-length-arguments`: the input arguments are of differing length.

bin:and

Signatures	`bin:and($a as xs:base64Binary?, $b as xs:base64Binary?) as xs:base64Binary?`
Summary	Returns the "bitwise and" of two binary arguments.If either argument is the empty sequence, an empty sequence is returned.
Errors	`differing-length-arguments`: the input arguments are of differing length.

bin:not

Signatures	`bin:not($in as xs:base64Binary?) as xs:base64Binary?`
Summary	Returns the "bitwise not" of a binary argument.If the argument is the empty sequence, an empty sequence is returned.

bin:shift

Signatures	`bin:shift($in as xs:base64Binary?, $by as xs:integer) as xs:base64Binary?`
Summary	Shifts bits in binary data.If `$by` is zero, the result is identical to `$in`. If `$by` is positive then bits are shifted to the left. Otherwise, bits are shifted to the right. If the absolute value of `$by` is greater than the bit-length of `$in` then an all-zeros result is returned. The result always has the same size as `$in`. The shifting is logical: zeros are placed into discarded bits. If the value of `$in` is the empty sequence, the function returns an empty sequence.

Errors

Code	Description
`differing-length-arguments`	The arguments to a bitwise operation have different lengths.
`index-out-of-range`	An offset value is out of range.
`negative-size`	A size value is negative.
`octet-out-of-range`	An octet value lies outside the range 0-255.
`non-numeric-character`	Binary data cannot be parsed as number.
`unknown-encoding`	An encoding is not supported.
`conversion-error`	An error or malformed input during converting a string.
`unknown-significance-order`	An octet-order value is unknown.

Changelog

Introduced with Version 7.8.

Chapter 38. Client Module

Read this entry online in the BaseX Wiki.

This XQuery Module contains functions to access BaseX server instances from XQuery. With this module, you can execute database commands and evaluate XQuery expressions.

Please note that the client module should always be used to address independent BaseX server instances. You can create deadlocks if you evaluate a query with a server instance, and if you are addressing the same server instance in your query. See the following example:

```
(: Retrieve documents from database :)
let $client-id := client:connect('localhost', 1984, 'admin', 'admin')
let $docs := client:query($client-id, 'db:open("conflict")')
(: Create database with same name :)
return db:create('conflict', $docs, $docs ! db:path(.))
```

The read-only query cannot be processed, because the `conflict` database is currently write-locked by the main query. See Transaction Management for more background information.

Conventions

Updated with Version 9.0:

All functions and errors in this module are assigned to the `http://basex.org/modules/client` namespace, which is statically bound to the `client` prefix.

Functions

client:connect

Signatures	`client:connect($host as xs:string, $port as xs:integer, $user as xs:string, $password as xs:string) as xs:anyURI`
Summary	This function establishes a connection to a remote BaseX server, creates a new client session, and returns a session id. The parameter `$host` is the name of the database server, `$port` specifies the server port, and `$user` and `$password` represent the login data.
Errors	`connect`: an error occurs while creating the session (possible reasons: server not available, access denied).

client:execute

Signatures	`client:execute($id as xs:anyURI, $command as xs:string) as xs:string`
Summary	This function executes a command and returns the result as string. The parameter `$id` contains the session id returned by client:connect. The `$command` argument represents a single command, which will be executed by the server.
Errors	`error`: an I/O error occurs while transferring data from or to the server.`command`: an error occurs while executing a command.

Examples	The following query creates a new database `TEST` on a remote BaseX server:
	
	`client:connect('basex.server.org', 8080, 'admin', 'admin') !`
	`  client:execute(., 'create database TEST')`

client:info

Signatures	`client:info($id as xs:anyURI) as xs:string`
Summary	This function returns an information string, created by the last call of client:execute. `$id` specifies the session id.

client:query

Signatures	`client:query($id as xs:anyURI, $query as xs:string) as item()*` `client:query($id as xs:anyURI, $query as xs:string, $bindings as map(*)?) as item()*`
Summary	Evaluates a query and returns the result as sequence. The parameter `$id` contains the session id returned by client:connect, and `$query` represents the query string, which will be evaluated by the server.Variables and the context item can be declared via `$bindings`. The specified keys must be QNames or strings: • If a key is a QName, it will be directly adopted as variable name. • If a key is a string, it may be prefixed with a dollar sign. A namespace can be specified using the Clark Notation. If the specified string is empty, the value will be bound to the context item.
Errors	`error`: an I/O error occurs while transferring data from or to the server.`query`: an error occurs while evaluating a query, and if the original error cannot be extracted from the returned error string.`function`: function items (including maps and arrays) cannot be returned.

Examples	The following query sends a query on a local server instance, binds the integer `123` to the variable `$n` and returns `246`:
	`let $c := client:connect('localhost', 1984, 'admin', 'admin')`
	`return client:query($c, "declare variable $n external; $n * 2", map { 'n': 123 })`
	The following query performs a query on a first server, the results of which are passed on to a second server:
	`let $c1 := client:connect('basex1.server.org', 8080, 'jack', 'C0S19tt2X')`
	`let $c2 := client:connect('basex2.server.org', 8080, 'john', '465wFHe26')`
	`for $it in client:query($c1, '1 to 10')`
	`return client:query($c2, $it || '* 2')`

client:close

Signatures	`client:close($id as xs:anyURI) as empty-sequence()`
Summary	This function closes a client session. `$id` specifies the session id.Opened connections will automatically be closed after the XQuery expression has been evaluated, but it is recommendable to explicitly close them with this function if you open many connections.
Errors	`error`: an I/O error occurs while transferring data from or to the server.

Errors

Updated with Version 9.0:

Code	Description
`command`	An error occurred while executing a command.

`connect`	An error occurred while creating a new session (possible reasons: server not available, access denied).
`error`	An I/O error occurred while transferring data from or to the server.
`function`	Function items (including maps and arrays) cannot be returned.
`id`	The id with the specified session is unknown, or has already been closed.
`query`	An error occurred while evaluating a query. Will only be raised if the XQuery error cannot be extracted from the returned error string.

Changelog

Version 9.0

- Updated: error codes updated; errors now use the module namespace

Version 8.0

- Updated: Bound values may now contain no or more than one item in client:query.

Version 7.5

- Added: client:info

The module was introduced with Version 7.3.

Chapter 39. Conversion Module

Read this entry online in the BaseX Wiki.

This XQuery Module contains functions to convert data between different formats.

Conventions

Updated with Version 9.0:

All functions and errors in this module are assigned to the `http://basex.org/modules/convert` namespace, which is statically bound to the `convert` prefix.

Strings

convert:binary-to-string

Signatures	`convert:binary-to-string($bytes as xs:anyAtomicType) as xs:string` `convert:binary-to-string($bytes as xs:anyAtomicType, $encoding as xs:string) as xs:string` `convert:binary-to-string($bytes as xs:anyAtomicType, $encoding as xs:string, $fallback as xs:boolean) as xs:string`
Summary	Converts the specifed `$bytes` (`xs:base64Binary`, `xs:hexBinary`) to a string: • The UTF-8 default encoding can be overwritten with the optional `$encoding` argument. • By default, invalid characters will be rejected. If `$fallback` is set to true, these characters will be replaced with the Unicode replacement character `FFFD` (#).
Errors	`string`: The input is an invalid XML string, or the wrong encoding has been specified.`BXCO0002`: The specified encoding is invalid or not supported.
Examples	• `convert:binary-to-string(xs:hexBinary('48656c6c6f576f726c64'))` yields `HelloWorld`.

convert:string-to-base64

Signatures	`convert:string-to-base64($string as xs:string) as xs:base64Binary` `convert:string-to-base64($string as xs:string, $encoding as xs:string) as xs:base64Binary`
Summary	Converts the specified `$string` to an `xs:base64Binary` item. If the default encoding is chosen, conversion will be cheap, as strings and binaries are both internally represented as byte arrays.The UTF-8 default encoding can be overwritten with the optional `$encoding` argument.
Errors	`binary`: The input cannot be represented in the specified encoding.`encoding`: The specified encoding is invalid or not supported.
Examples	• `string(convert:string-to-base64('HelloWorld'))` yields `SGVsbG9Xb3JsZA==`.

convert:string-to-hex

Signatures	`convert:string-to-hex($string as xs:string) as xs:hexBinary` `convert:string-to-hex($string as xs:string, $encoding as xs:string) as xs:hexBinary`
Summary	Converts the specified `$string` to an `xs:hexBinary` item. If the default encoding is chosen, conversion will be cheap, as strings and binaries are both internally represented as byte arrays.The UTF-8 default encoding can be overwritten with the optional `$encoding` argument.

Errors	`binary`: The input cannot be represented in the specified encoding.`encoding`: The specified encoding is invalid or not supported.
Examples	• `string(convert:string-to-hex('HelloWorld'))` yields `48656C6C6F576F726C64`.

Binary Data

convert:integers-to-base64

Updated with Version 9.0: Renamed from `convert:bytes-to-base64`; argument type relaxed from `xs:byte` to `xs:integer`.

Signatures	`convert:integers-to-base64($integers as xs:integer*) as xs:base64Binary`
Summary	Converts the specified `$integers` to an item of type `xs:base64Binary`: • Only the first 8 bits of the supplied integers will be considered. • Conversion of byte sequences is particularly cheap, as items of binary type are internally represented as byte arrays.

convert:integers-to-hex

Updated with Version 9.0: Renamed from `convert:bytes-to-base64`; argument type relaxed from `xs:byte` to `xs:integer`.

Signatures	`convert:integers-to-hex($integers as xs:integer*) as xs:hexBinary`
Summary	Converts the specified `$integers` to an item of type `xs:hexBinary`: • Only the first 8 bits of the supplied integers will be considered. • Conversion of byte sequences is particularly cheap, as items of binary type are internally represented as byte arrays.

convert:binary-to-integers

Introduced with Version 9.0:

Signatures	`convert:binary-to-integer($binary as xs:anyAtomicType) as xs:integer*`
Summary	Returns the specified `$binary` (`xs:base64Binary`, `xs:hexBinary`) as a sequence of unsigned integers (octets).
Examples	• `convert:binary-to-integer(xs:hexBinary('FF'))` yields `255`.

convert:binary-to-bytes

Signatures	`convert:binary-to-bytes($binary as xs:anyAtomicType) as xs:byte*`
Summary	Returns the specified `$binary` (`xs:base64Binary`, `xs:hexBinary`) as a sequence of bytes. The conversion is very cheap and takes no additional memory, as items of binary type are internally represented as byte arrays.
Examples	• `convert:binary-to-bytes(xs:base64Binary('QmFzZVggaXMgY29vbA=='))` yields the sequence `(66, 97, 115, 101, 88, 32, 105, 115, 32, 99, 111, 111, 108)`. • `convert:binary-to-bytes(xs:hexBinary("4261736558"))` yields the sequence `(66 97 115 101 88)`.

Numbers

convert:integer-to-base

Signatures	`convert:integer-to-base($number as xs:integer, $base as xs:integer) as xs:string`
Summary	Converts `$number` to a string, using the specified `$base`, interpreting it as a 64-bit unsigned integer.The first base elements of the sequence `'0',..,'9','a',..,'z'` are used as digits.Valid bases are `2, .., 36`.
Errors	`base`: The specified base is not in the range 2-36.
Examples	• `convert:integer-to-base(-1, 16)` yields `'ffffffffffffffff'`. • `convert:integer-to-base(22, 5)` yields `'42'`.

convert:integer-from-base

Signatures	`convert:integer-from-base($string as xs:string, $base as xs:integer) as xs:integer`
Summary	Decodes an integer from `$string`, using the specified `$base`. The first base elements of the sequence `'0',..,'9','a',..,'z'` are allowed as digits; case does not matter. Valid bases are 2 - 36. If the supplied string contains more than 64 bits of information, the result will be truncated.
Errors	`base`: The specified base is not in the range 2-36.`integer`: The specified digit is not valid for the given range.
Examples	• `convert:integer-from-base('ffffffffffffffff', 16)` yields `-1`. • `convert:integer-from-base('CAFEBABE', 16)` yields `3405691582`. • `convert:integer-from-base('42', 5)` yields `22`. • `convert:integer-from-base(convert:integer-to-base(123, 7), 7)` yields `123`.

Dates and Durations

convert:integer-to-dateTime

Signatures	`convert:integer-to-dateTime($milliseconds as xs:integer) as xs:dateTime`
Summary	Converts the specified number of `$milliseconds` since 1 Jan 1970 to an item of type xs:dateTime.
Examples	• `convert:integer-to-dateTime(0)` yields `1970-01-01T00:00:00Z`. • `convert:integer-to-dateTime(1234567890123)` yields `2009-02-13T23:31:30.123Z`. • `convert:integer-to-dateTime(prof:current-ms())` returns the current miliseconds in the `xs:dateTime` format.

convert:dateTime-to-integer

Signatures	`convert:dateTime-to-integer($dateTime as xs:dateTime) as xs:integer`
Summary	Converts the specified `$dateTime` item to the number of milliseconds since 1 Jan 1970.

Examples	• `convert:dateTime-to-integer(xs:dateTime('1970-01-01T00:00:00Z'))` yields `0`.

convert:integer-to-dayTime

Signatures	`convert:integer-to-dayTime($milliseconds as xs:integer) as xs:dayTimeDuration`
Summary	Converts the specified number of `$milliseconds` to an item of type xs:dayTimeDuration.
Examples	• `convert:integer-to-dayTime(1234)` yields `PT1.234S`.

convert:dayTime-to-integer

Signatures	`convert:dayTime-to-integer($dayTime as xs:dayTimeDuration) as xs:integer`
Summary	Converts the specified `$dayTime` duration to milliseconds represented by an integer.
Examples	• `convert:dayTime-to-integer(xs:dayTimeDuration('PT1S'))` yields `1000`.

Errors

Updated with Version 9.0:

Code	Description
`base`	The specified base is not in the range 2-36.
`binary`	The input cannot be converted to a binary representation.
`encoding`	The specified encoding is invalid or not supported.
`integer`	The specified digit is not valid for the given range.
`string`	The input is an invalid XML string, or the wrong encoding has been specified.

Changelog

Version 9.0

- Added: convert:binary-to-integers.
- Updated: convert:integers-to-base64, convert:integers-to-hex: Renamed from `convert:bytes-to-base64`; argument type relaxed from `xs:byte` to `xs:integer`.
- Updated: error codes updated; errors now use the module namespace

Version 8.5

- Updated: convert:binary-to-string: `$fallback` argument added.

Version 7.5

- Added: convert:integer-to-dateTime, convert:dateTime-to-integer, convert:integer-to-dayTime, convert:dayTime-to-integer.

The module was introduced with Version 7.3. Some of the functions have been adopted from the obsolete Utility Module.

Chapter 40. Cryptographic Module

Read this entry online in the BaseX Wiki.

This XQuery Module contains functions to perform cryptographic operations in XQuery. The cryptographic module is based on an early draft of the EXPath Cryptographic Module and provides the following functionality: creation of message authentication codes (HMAC), encryption and decryption, and creation and validation of XML Digital Signatures.

Conventions

All functions in this module are assigned to the `http://expath.org/ns/crypto` namespace, which is statically bound to the `crypto` prefix. All errors are assigned to the `http://expath.org/ns/error` namespace, which is statically bound to the `experr` prefix.

Message Authentication

crypto:hmac

Signatures	`crypto:hmac($message as xs:string, $key as xs:anyAtomicType) as xs:base64Binary, $algorithm as xs:string crypto:hmac($message as xs:string, $key as xs:anyAtomicType) as xs:base64Binary, $algorithm as xs:string, $encoding as xs:string`
Summary	Creates a message authentication code via a cryptographic hash function and a secret `$key`. `$encoding` must either be `hex`, `base64` or the empty string and specifies the encoding of the returned authentication code. **Default is `base64` .** `$algorithm` describes the hash algorithm which is used for encryption. Currently supported are `md5`, `sha1`, `sha256`, `sha384`, `sha512`. **Default is `md5` .**
Errors	`CX0013`: the specified hashing algorithm is not supported.`CX0014`: the specified encoding method is not supported.`CX0019`: the specified secret key is invalid.

Example	**Returns the message authentication code (MAC) for a given string. Query:**
	`crypto:hmac('message','secretkey','md5','base64')`
	Result:
	`34D1E3818B347252A75A4F6D747B21C2`

Encryption & Decryption

The encryption and decryption functions underlie several limitations:

- Cryptographic algorithms are currently limited to `symmetric` algorithms only. This means that the same secret key is used for encryption and decryption.
- Available algorithms are `DES` and `AES`.
- Padding is fixed to `PKCS5Padding`.
- The result of an encryption using the same message, algorithm and key looks different each time it is executed. This is due to a random initialization vector (IV) which is appended to the message and simply increases security.
- As the IV has to be passed along with the encrypted message somehow, data which has been encrypted by the `crypto:encrypt` function in BaseX can only be decrypted by calling the `crypto:decrypt` function.

crypto:encrypt

Signatures	`crypto:encrypt($input as xs:string, $encryption as xs:string, $key as xs:string, $algorithm as xs:string) as xs:string`
Summary	Encrypts the given input string. `$encryption` must be `symmetric`, as asymmetric encryption is not supported so far. **Default is `symmetric` .** `$key` is the secret key which is used for both encryption and decryption of input data. Its length is fixed and depends on the chosen algorithm: `8 bytes for DES`, `16 bytes for AES`. `$algorithm` must either be DES or AES. Other algorithms are not supported so far, but, of course, can be added on demand. **Default is `DES` .**
Errors	`CX0016`: padding problems arise.`CX0017`: padding is incorrect.`CX0018`: the encryption type is not supported.`CX0019`: the secret key is invalid.`CX0020`: the block size is incorrect.`CX0021`: the specified encryption algorithm is not supported.
Example	**Encrypts input data. Query:** `crypto:encrypt('message', 'symmetric','keykeyke','DES')`

crypto:decrypt

Signatures	`crypto:decrypt($input as xs:string, $type as xs:string, $key as xs:string, $algorithm as xs:string) as xs:string`
Summary	Decrypts the encrypted `$input`. `$type` must be `symmetric`. An option for asymmetric encryption will most likely be added with another version of BaseX. **Default is `symmetric` .** `$key` is the secret key which is used for both encryption and decryption of input data. Its length is fixed and depends on the chosen algorithm: `8 bytes for DES`, `16 bytes for AES`. `$algorithm` must either be DES or AES. Other algorithms are not supported so far, but, of course, can be added on demand. **Default is `DES` .**
Errors	`CX0016`: padding problems arise.`CX0017`: padding is incorrect.`CX0018`: the encryption type is not supported.`CX0019`: the secret key is invalid.`CX0020`: the block size is incorrect.`CX0021`: the specified encryption algorithm is not supported.

Example	**Decrypts input data and returns the original string. Query:**
	`let $encrypted := crypto:encrypt('message', 'symmetric','keykeyke','DES') return crypto:decrypt($encrypted, 'symmetric','keykeyke','DES')`
	Result:
	`message`

XML Signatures

XML Signatures are used to sign data. In our case, the data which is signed is an XQuery node. The following example shows the basic structure of an XML signature.

XML Signature

```
<Signature>
  <SignedInfo>
    <CanonicalizationMethod/>
    <SignatureMethod/>
    <Reference>
      <Transforms/>
      <DigestMethod/>
      <DigestValue/>
```

```
    </Reference>
    <Reference/>
  </SignedInfo>
  <SignatureValue/>
  <KeyInfo/>
  <Object/>
</Signature>
```

- **SignedInfo** contains or references the signed data and lists algorithm information
- **Reference** references the signed node
- **Transforms** contains transformations (i.e. XPath expressions) that are applied to the input node in order to sign a subset
- **DigestValue** holds digest value of the transformed references
- **SignatureValue** contains the Base64 encoded value of the encrypted digest of the `SignedInfo` element
- **KeyInfo** provides information on the key that is used to validate the signature
- **Object** contains the node which is signed if the signature is of type `enveloping`

Signature Types

Depending on the signature type, the `signature` element is either placed as a child of the signed node (`enveloped` type), or directly contains the signed node (`enveloping` type). `Detached` signatures are so far not supported.

Digital Certificate

The `generate-signature` function allows to pass a `digital certificate`. This certificate holds parameters that allow to access key information stored in a Java key store which is then used to sign the input document. Passing a `digital certificate` simply helps re-using the same key pair to sign and validate data. The `digital certificate` is passed as a node and has the following form:

```
<digital-certificate>
  <keystore-type>JKS</keystore-type>
  <keystore-password>...</keystore-password>
  <key-alias>...</key-alias>
  <private-key-password>...</private-key-password>
  <keystore-uri>...</keystore-uri>
</digital-certificate>
```

crypto:generate-signature

Signatures	`crypto:generate-signature($input as node(), $canonicalization as xs:string, $digest as xs:string, $signature as xs:string, $prefix as xs:string, $type as xs:string) as node()` `crypto:generate-signature($input as node(), $canonicalization as xs:string, $digest as xs:string, $signature as xs:string, $prefix as xs:string, $type as xs:string, $xpath as xs:string, $certificate as node()) as node()` `crypto:generate-signature($input as node(), $canonicalization as xs:string, $digest as xs:string, $signature as xs:string, $prefix as xs:string, $type as xs:string, $ext as item()) as node()`
Summary	`$canonicalization` must either be `inclusive-with-comments`, `inclusive`, `exclusive-with-comments` or `exclusive`. **Default is `inclusive-with-comments`** . `$digest` must be one of the following: `SHA1`, `SHA256` or `SHA512`. **Default is `SHA1`** . `$signature` must either be `RSA_SHA1` or `DSA_SHA1`. **Default is `RSA_SHA1`** . `$prefix` may be empty and prefixes the `Signature` element accordingly. `$type` is the signature type. It must

	either be `enveloped` or `enveloping` (detached signatures are not supported so far). **Default is `enveloped`** . `$xpath` is an arbitrary XPath expression which specifies a subset of the document that is to be signed. `$certificate` is the digitial certificate used to sign the input document. `$ext` may either be an `$xpath` expression or a `$certificate`.
Errors	`CX0001`: the canonicalization algorithm is not supported.`CX0002`: the digest algorithm is not supported.`CX0003`: the signature algorithm is not supported.`CX0004`: the `$xpath-expression` is invalid.`CX0005`: the root name of `$digital-certificate` is not 'digital-certificate.`CX0007`: the key store is null.`CX0012`: the key cannot be found in the specified key store.`CX0023`: the certificate alias is invalid.`CX0024`: an invalid algorithm is specified.`CX0025`: an exception occurs while the signing the document.`CX0026`: an exception occurs during key store initialization.`CX0027`: an IO exception occurs.`CX0028`: the signature type is not supported.

Example	**Generates an XML Signature. Query:**
	`crypto:generate-signature(<a/>, '', '', '', '', '')`
	Result:
	`<a>`
	`  <Signature xmlns="http://www.w3.org/2000/09/xmldsig#">`
	`    <SignedInfo>`
	`      <CanonicalizationMethod Algorithm="http://www.w3.org/TR/2001/REC-xml-c14n-20010315#WithComments"/>`
	`      <SignatureMethod Algorithm="http://www.w3.org/2000/09/xmldsig#rsa-sha1"/>`
	`      <Reference URI="">`
	`        <Transforms>`
	`          <Transform Algorithm="http://www.w3.org/2000/09/xmldsig#enveloped-signature"/>`
	`        </Transforms>`
	`        <DigestMethod Algorithm="http://www.w3.org/2000/09/xmldsig#sha1"/>`
	`        <DigestValue>9hvH4qztnIYgYfJDRLnEMPJdoaY=</DigestValue>`
	`      </Reference>`
	`    </SignedInfo>`
	`    <SignatureValue>Pn/Jr44WBcdARff2UVYEiwYW1563XdqnU87nusAIaHgzd+U3SrjVJhPFLDe0DJfxVtYzLFaznTYE`
	`P3ddeoFmyA==</SignatureValue>`
	`    <KeyInfo>`
	`      <KeyValue>`
	`        <RSAKeyValue>`
	`          <Modulus>rtvpFSbCIE2BJePlVYLIRIjXl0R7ESr2+D+JOVKn7AM7VZbcbRDPeqRbjSkEz1HWC/N067tjB3qH`
	`4/4PPT9bGQ==</Modulus>`
	`          <Exponent>AQAB</Exponent>`
	`        </RSAKeyValue>`
	`      </KeyValue>`
	`    </KeyInfo>`
	`  </Signature>`
	`</a>`

crypto:validate-signature

Signatures	`crypto:validate-signature($input-doc as node()) as xs:boolean`
Summary	Checks if the given node contains a `Signature` element and whether the signature is valid. In this case `true` is returned. If the signature is invalid the function returns `false`.
Errors	`CX0015`: the signature element cannot be found.`CX9994`: an unspecified problem occurs during validation.`CX9996`: an IO exception occurs during validation.
Example	**Validates an XML Signature. Query:**

```
let $sig := crypto:generate-signature(<a/>, '', '', '', '', '')
return crypto:validate-signature($sig)
```

Result:

```
true
```

Errors

Code	Description
CX0001	The canonicalization algorithm is not supported.
CX0002	The digest algorithm is not supported.
CX0003	The signature algorithm is not supported.
CX0004	The XPath expression is invalid.
CX0005	The root element of argument $digital-certificate must have the name 'digital-certificate'.
CX0006	The child element of argument $digital-certificate having position $position must have the name $child-element-name.
CX0007	The keystore is null.
CX0008	I/O error while reading keystore.
CX0009	Permission denied to read keystore.
CX0010	The keystore URL is invalid.
CX0011	The keystore type is not supported.
CX0012	Cannot find key for alias in given keystore.
CX0013	The hashing algorithm is not supported.
CX0014	The encoding method is not supported.
CX0015	Cannot find Signature element.
CX0016	No such padding.
CX0017	Incorrect padding.
CX0018	The encryption type is not supported.
CX0019	The secret key is invalid.
CX0020	Illegal block size.
CX0021	The algorithm is not supported.
CX0023	An invalid certificate alias is specified. Added to the official specification.
CX0024	The algorithm is invalid. Added to the official specification.
CX0025	Signature cannot be processed. Added to the official specification.
CX0026	Keystore cannot be processed. Added to the official specification.
CX0027	An I/O Exception occurred. Added to the official specification.
CX0028	The specified signature type is not supported. Added to the official specification.

Changelog

Version 8.6

- Updated: crypto:hmac: The key can now be a string or a binary item.

The Module was introduced with Version 7.0.

Chapter 41. CSV Module

Read this entry online in the BaseX Wiki.

This XQuery Module contains a single function to parse CSV input. CSV (comma-separated values) is a popular representation for tabular data, exported e. g. from Excel.

Conventions

Updated with Version 9.0:

All functions and errors in this module are assigned to the `http://basex.org/modules/csv` namespace, which is statically bound to the `csv` prefix.

Conversion

XML: Direct, Attributes

If the `direct` or `attributes` format is chosen, a CSV string is converted to XML:

- The resulting XML document has a `<csv>` root element.
- Rows are represented via `<record>` elements.
- Fields are represented via `<entry>` elements. The value of a field is represented as text node.
- If the `header` option is set to `true`, the first text line is parsed as table header, and the `<entry>` elements are replaced with the field names:
  - Empty names are represented by a single underscore (_), and characters that are not valid in element names are replaced with underscores or (when invalid as first character of an element name) prefixed with an underscore.
  - If the `lax` option is set to `false`, invalid characters will be rewritten to an underscore and the character's four-digit Unicode, and underscores will be represented as two underscores (__). The resulting element names may be less readable, but can always be converted back to the original field names.
- If `format` is set to `attributes`, field names will be stored in name attributes.

A little advice: in the Database Creation dialog of the GUI, if you select CSV Parsing and switch to the *Parsing* tab, you can see the effects of some of the conversion options.

XQuery

This format has been introduced with *Version 9.0*. It is more flexible and light-weight than the old, discarded `map` format.

With the `xquery` format, CSV records are converted to a sequence of arrays:

- The resulting value will be a map with a `records` and an optional `names` key.
- Records are organized as a sequence of arrays. A single array contains the entries of a single record.
- The column names will be available if `header` option is set to `true`.

The CSV map can e.g. be accessed as follows:

- `$csv?records[5]` returns all entries of the 5th record (row)
- `$csv?records(2)` returns all entries of the 2nd field (column)

- `$csv?names?*` returns the names of all fields (if available)
- Return enumerated strings for all records:

```
for $record at $pos in $csv?records
return $pos || ". " || string-join($record?*, ', ')
```

The resulting representation consumes less memory than XML-based formats, and values can be directly accessed without conversion. Thus, it is recommendable for very large inputs and for efficient ad-hoc processing.

Options

In the following table, all available options are listed. The Excel column indicates what are the preferred options for data that is to be imported, or has been exported from Excel.

Option	Description	Allowed	Default	Excel
`separator`	Defines the character which separates the values of a single record.	`comma`, `semicolon`, `colon`, `tab`, `space` or a *single character*	`comma`	`semicolon`
`header`	Indicates if the first line of the parsed or serialized CSV data is a table header.	`yes`, `no`	`no`	
`format`	Specifies the format of the XML data: • With `direct` conversion, field names are represented as element names • With `attributes` conversion, field names are stored in `name` attributes • With `xquery` conversion, the input is converted to an XQuery map	`direct`, `attributes`, `map`	`direct`	
`lax`	Specifies if a lax approach is used to convert QNames to JSON names.	`yes`, `no`	`yes`	`no`
`quotes`	Specifies how quotes are parsed: • Parsing: If the option is enabled, quotes at the start and end of a value will be treated as control characters. Separators and newlines within the quotes will be adopted without change. • Serialization: If the option is enabled, the value will be wrapped with quotes. A quote character in the value will be encoded according to the rules of the `backslashes` option.	`yes`, `no`	`yes`	`yes`
`backslashes`	Specifies how quotes and other characters are escaped: • Parsing: If the option is enabled, `\r`, `n` and `\t` will be replaced with the corresponding control characters. All other escaped characters will be adopted as literals (e.g.: `\"` → `"`). If the option is disabled, two consecutive quotes will be replaced with a single quote (unless `quotes` is enabled and the quote is the first or last character of a value).	`yes`, `no`	`no`	`no`

• Serialization: If the option is enabled, `\r`, `n`, `\t`, `"` and the separator character will be encoded with a backslash. If the option is disabled, quotes will be duplicated.			

Functions

csv:parse

Signatures	`csv:parse($input as xs:string) as document-node(element(csv))` `csv:parse($input as xs:string, $options as map(*)?) as item()`
Summary	Converts the CSV data specified by `$input` to an XML document or a map. The `$options` argument can be used to control the way the input is converted.
Errors	`parse`: the input cannot be parsed.

csv:serialize

Signatures	`csv:serialize($input as item()?) as xs:string` `csv:serialize($input as item()?, $options as map(*)?) as xs:string`
Summary	Serializes the specified `$input` as CSV, using the specified `$options`, and returns the result as string. Values can also be serialized as CSV with the standard Serialization feature of XQuery: • The parameter `method` needs to be set to `csv`, and • the options presented in this article need to be assigned to the `csv` parameter.
Errors	`serialize`: the input cannot be serialized.

Examples

Example 1: Converts CSV data to XML, interpreting the first row as table header:

Input `addressbook.csv`:

```
Name,First Name,Address,City
Huber,Sepp,Hauptstraße 13,93547 Hintertupfing
```

Query:

```
let $text := file:read-text('addressbook.csv')
return csv:parse($text, map { 'header': true() })
```

Result:

```
<csv>
  <record>
    <Name>Huber</Name>
    <First_Name>Sepp</First_Name>
    <Address>Hauptstraße 13</Address>
    <City>93547 Hintertupfing</City>
  </record>
</csv>
```

Example 2: Converts some CSV data to XML and back, and checks if the input and output are equal. The expected result is `true`:

Query:

```
let $options := map { 'lax': false() }
let $input := file:read-text('some-data.csv')
let $output := $input => csv:parse($options) => csv:serialize($options)
return $input eq $output
```

Example 3: Converts CSV data to XQuery and returns distinct column values:

Query:

```
let $text := ``[Name,City
Jack,Chicago
Jack,Washington
John,New York
]``
let $options := map { 'format': 'xquery', 'header': true() }
let $csv := csv:parse($text, $options)
return (
  'Distinct values:',
  let $records := $csv('records')
  for $name at $pos in $csv('names')?*
  let $values := $records($pos)
  return (
    '* ' || $name || ': ' || string-join(distinct-values($values), ', ')
  )
)
```

Result:

```
Distinct values:
* Name: Jack, John
* City: Chicago, Washington, New York
```

Errors

Updated with Version 9.0:

Code	Description
`parse`	The input cannot be parsed.
`serialize`	The node cannot be serialized.

Changelog

Version 9.0

- Added: `xquery` option
- Removed: `map` option
- Updated: error codes updated; errors now use the module namespace

Version 8.6

- Updated: Options: improved Excel compatibility

Version 8.0

- Added: `backslashes` option

Version 7.8

- Updated: csv:parse now returns a document node instead of an element, or an XQuery map if `format` is set to `map`.
- Added: `format` and `lax` options

The module was introduced with Version 7.7.2.

Chapter 42. Database Module

Read this entry online in the BaseX Wiki.

This XQuery Module contains functions for processing databases from within XQuery. Existing databases can be opened and listed, its contents can be directly accessed, documents can be added to and removed, etc.

Conventions

Updated with Version 9.0:

All functions and errors in this module are assigned to the `http://basex.org/modules/db` namespace, which is statically bound to the `db` prefix.

Database Nodes

Database nodes are XML nodes which are either stored in a persistent database, or which contained in a so-called *database fragment*. All XML fragments can be converted to database fragments by e. g. applying the transform expression on an XML fragment:

```
copy $c := element hello { 'world' } modify () return $c
```

General Functions

db:system

Signatures	`db:system() as element(system)`
Summary	Returns general information on the database system the current values of all global and local Options. The `INFO` command returns similar output.

db:option

Introduced with Version 9.0:

Signatures	`db:option($name as xs:string) as xs:string`
Summary	Returns the current value (string, integer, boolean, map) of a global or local Option with the specified `$name`. The `GET` command works similar.
Examples	• `db:option('dbpath')` returns the database path string. • `db:option('serializer')` returns a map with the current serialization parameters. • `declare option db:chop 'true'; db:option('chop')` returns `true` (irrespective of the global value).

db:info

Signatures	`db:info($db as xs:string) as element(database)`
Summary	Returns meta information on the database `$db`. The output is similar to the `INFO DB` command.
Errors	`open`: the addressed database does not exist or could not be opened.

db:property

Signatures	`db:property($db as xs:string, $name as xs:string) as xs:anyAtomicType`

Summary	Returns the value (string, boolean, integer) of a property with the specified `$name` in the database `$db`. The available properties are the ones returned by db:info.
Errors	`property`: the specified property is unknown.
Examples	• `db:property('db', 'size')` returns the number of bytes occupied by the database `db`. • `db:property('xmark', 'textindex')` indicates if the `xmark` database has a text index. • `db:property('discogs', 'uptodate')` indicates if the database statistics and index structures of the `discogs` database are up-to-date.

db:list

Signatures	`db:list() as xs:string*` `db:list($db as xs:string) as xs:string*` `db:list($db as xs:string, $path as xs:string) as xs:string*`
Summary	The result of this function is dependent on the number of arguments: • Without arguments, the names of all databases are returned that are accessible to the current user. • If a database `$db` is specified, all documents and raw files of the specified database are returned. • The list of returned resources can be restricted by the `$path` argument.
Errors	`open`: the addressed database does not exist or could not be opened.
Examples	• `db:list("docs")` returns the names of all documents of a database named `docs`.

db:list-details

Signatures	`db:list-details() as element(database)*` `db:list-details($db as xs:string) as element(resource)*` `db:list-details($db as xs:string, $path as xs:string) as element(resource)*`
Summary	Without arguments, an element is returned for each database that is accessible to the current user: • An element has a value, which is the name of the database, and several attributes, which contain the number of stored resources, the modification date, the database size on disk (measured in bytes), and a path to the original database input. If a database `$db` is specified, an element for each documents and raw file of the specified database is returned: • An element has a value, which is the name of the resource, and several attributes, which contain the content type, the modification date, the raw flag (which indicates if the resource is binary or XML), and the size of a resource. • The value of the size attribute depends on the resource type: for documents, it represents the number of nodes; for binary data, it represents the file size (measured in bytes). • Returned databases resources can be further restricted by the `$path` argument.
Errors	`open`: the addressed database does not exist or could not be opened.
Examples	• `db:list-details("shop")` returns the names plus additional info on all resources of a database named `shop`.

db:backups

Signatures	`db:backups() as element(backup)*` `db:backups($db as xs:string) as element(backup)*`

Summary	Returns an element sequence containing all available database backups.If a database `$db` is specified, the sequence will be restricted to the backups matching this database.
Examples	• `db:backups("factbook")` returns all backups that have been made from the `factbook` database.

Read Operations

db:open

Signatures	`db:open($db as xs:string) as document-node()* db:open($db as xs:string, $path as xs:string) as document-node()*`
Summary	Opens the database `$db` and returns all document nodes.The document nodes to be returned can be filtered with the `$path` argument.
Errors	`open`: the addressed database does not exist or could not be opened.
Examples	• `db:open("docs")` returns all documents from the database named `docs`. • `db:open("db", "one")` returns all documents from the database named `db` located in the path `one`. • `for $i in 1 to 3 return db:open("db" || $i)//item` returns all item elements from the databases `db1`, `db2` and `db3`.

db:open-pre

Signatures	`db:open-pre($db as xs:string, $pre as xs:integer) as node()`
Summary	Opens the database `$db` and returns the node with the specified `$pre` value.The PRE value provides very fast access to an existing database node, but it will change whenever a node with a smaller *pre* values is added to or deleted from a database.
Errors	`open`: the addressed database does not exist or could not be opened.`range`: the specified pre value does not exist in the database.
Examples	• `db:open-pre("docs", 0)` returns the first database node from the database named `docs`.

db:open-id

Signatures	`db:open-id($db as xs:string, $id as xs:integer) as node()`
Summary	Opens the database `$db` and returns the node with the specified `$id` value.Each database node has a *persistent* ID value. Access to the node id can be sped up by turning on the `UPDINDEX` option.
Errors	`open`: the addressed database does not exist or could not be opened.`range`: the specified id value does not exist in the database.

db:node-pre

Signatures	`db:node-pre($nodes as node()*) as xs:integer*`
Summary	Returns the *pre* values of the nodes supplied by `$nodes`, which must all be database nodes.The PRE value provides very fast access to an existing database node, but it will change whenever a node with a smaller *pre* values is added to or deleted from a database.
Errors	`node`: `$nodes` contains a node which is not stored in a database.
Examples	• `db:node-pre(doc("input"))` returns `0` if the database `input` contains a single document.

db:node-id

Signatures	`db:node-id($nodes as node()*) as xs:integer*`

Summary	Returns the *id* values of the nodes supplied by `$nodes`, which must all be database nodes.Each database node has a *persistent* ID value. Access to the node id can be sped up by turning on the `UPDINDEX` option.
Errors	`node`: `$nodes` contains a node which is not stored in a database.

db:retrieve

Signatures	`db:retrieve($db as xs:string, $path as xs:string) as xs:base64Binary`
Summary	Returns a binary resource addressed by the database `$db` and `$path` as streamable `xs:base64Binary`.
Errors	`open`: the addressed database does not exist or could not be opened.`mainmem`: the database is not *persistent* (stored on disk).
Examples	• `db:retrieve("DB", "music/01.mp3")` returns the specified audio file as raw data. • `stream:materialize(db:retrieve("DB", "music/01.mp3"))` materializes the streamable result in main-memory before returning it. • `convert:binary-to-string(db:retrieve("DB", "info.txt"), 'UTF-8')` converts a binary database resource as UTF-8 text and returns a string.

db:export

Signatures	`db:export($db as xs:string, $path as xs:string) as empty-sequence()` `db:export($db as xs:string, $path as xs:string, $params as item()) as empty-sequence()`

Summary	Exports the specified database `$db` to the specified file `$path`. Existing files will be overwritten. The `$params` argument contains serialization parameters (see Serialization for more details), which can either be specified
	• as children of an `<output:serialization-parameters/>` element, as defined for the fn:serialize() function; e.g.:
	`<output:serialization-parameters>`
	`  <output:method value='xml'/>`
	`  <output:cdata-section-elements value="div"/>`
	`  ...`
	`</output:serialization-parameters>`
	• as map, which contains all key/value pairs:
	`map { "method": "xml", "cdata-section-elements": "div", ... }`

Errors	`open`: the addressed database does not exist or could not be opened.

Examples	Export all files as text:
	`db:export("DB", "/home/john/xml/texts", map { 'method': 'text' })`
	The following query can be used to export parts of the database:
	`let $target := '/home/john/xml/target'`
	`for $doc in db:open('DB', 'collection')`
	`let $path := $target \|\| db:path($doc)`
	`return (`
	`  file:create-dir(file:parent($path)),`

```
  file:write($path, $doc)
)
```

Value Indexes

db:text

Signatures	`db:text($db as xs:string, $string as item()) as text()*`
Summary	Returns all text nodes of the database `$db` that have `$string` as their string value and that are stored in the text index.
Errors	`open`: the addressed database does not exist or could not be opened.`no-index`: the index is not available.
Examples	• `db:text("DB", "QUERY")/..` returns the parents of all text nodes of the database `DB` that match the string `QUERY`.

db:text-range

Signatures	`db:text-range($db as xs:string, $min as xs:string, $max as xs:string) as text()*`
Summary	Returns all text nodes of the database `$db` that are located in between the `$min` and `$max` strings and that are stored in the text index.
Errors	`open`: the addressed database does not exist or could not be opened.`no-index`: the index is not available.
Examples	• `db:text-range("DB", "2000", "2001")` returns all text nodes of the database `DB` that are found in between `2000` and `2001`.

db:attribute

Signatures	`db:attribute($db as xs:string, $string as item()) as attribute()* db:attribute($db as xs:string, $string as item(), $name as xs:string) as attribute()*`
Summary	Returns all attribute nodes of the database `$db` that have `$string` as string value and that are stored in the attribute index.If `$name` is specified, the resulting attribute nodes are filtered by their attribute name.
Errors	`open`: the addressed database does not exist or could not be opened.`no-index`: the index is not available.
Examples	• `db:attribute("DB", "QUERY", "id")/..` returns the parents of all `id` attribute nodes of the database `DB` that have `QUERY` as string value.

db:attribute-range

Signatures	`db:attribute-range($db as xs:string, $min as xs:string, $max as xs:string) as attribute()* db:attribute-range($db as xs:string, $min as xs:string, $max as xs:string, $name as xs:string) as attribute()*`
Summary	Returns all attributes of the database `$db`, the string values of which are larger than or equal to `$min` and smaller than or equal to `$max` and that are stored in the attribute index.
Errors	`open`: the addressed database does not exist or could not be opened.`no-index`: the index is not available.
Examples	• `db:attribute-range("DB", "id456", "id473", 'id')` returns all `@id` attributes of the database `DB` that have a string value in between `id456` and `id473`.

db:token

Signatures	`db:token($db as xs:string, $token as item()) as attribute()*` `db:token($db as xs:string, $token as item(), $name as xs:string) as attribute()*`
Summary	Returns all attribute nodes of the database `$db`, the value of which contains the specified `$token`.If `$name` is specified, the resulting attribute nodes are filtered by their attribute name.
Errors	`open`: the addressed database does not exist or could not be opened.`no-index`: the index is not available.
Examples	• `db:token("DB", "row", "class")/parent::div` returns all `div` nodes of database `DB` with a `class` attribute that contains the token `row`.

Updates

Important note: All functions in this section are *updating functions*: they will not be immediately executed, but queued on the Pending Update List, which will be processed after the actual query has been evaluated. This means that the order in which the functions are specified in the query does usually not reflect the order in which the code will be evaluated.

db:create

Signatures	`db:create($db as xs:string) as empty-sequence()` `db:create($db as xs:string, $inputs as item()*) as empty-sequence()` `db:create($db as xs:string, $inputs as item()*, $paths as xs:string*) as empty-sequence()` `db:create($db as xs:string, $inputs as item()*, $paths as xs:string*, $options as map(*)?) as empty-sequence()`

Summary	Creates a new database with name `$db` and adds initial documents specified via `$inputs` to the specified `$paths`:
	• `$inputs` may be strings or nodes:
	  • nodes may be of any type except for attributes
	  • strings can be a URI pointing to a file/directory or an XML string (which is detected by the leading < character)
	  • a path must be specified if the input is not a file or directory reference
	• The parsing and indexing behavior can be controlled via `$options`:
	  • allowed options are ADDCACHE and the indexing, full-text indexing, parsing and XML parsing options, all in lower case
	  • parsing options will only impact string input (URIs, XML strings), because nodes have already been parsed.
	• An existing database will be overwritten.
	• Database creation takes place after most other update operations (see Pending Update List). As a consequence, a newly created database cannot be addressed in the same query.

Errors	`lock`: a database is opened by another process.`name`: the specified name is not a valid database name.`conflict`: the same database was addressed more than once.`args`: the number of specified inputs and paths differs.
Examples	• `db:create("DB")` creates the empty database `DB`. • `db:create("DB", "/home/dir/doc.xml")` creates the database `DB` and adds the document `/home/dir/doc.xml` as initial content.

- `db:create("DB", <a/>, "doc.xml")` creates the database `DB` and adds the document with content `<a/>` under the name `doc.xml`.
- `db:create("DB", "/home/dir/", "docs/dir")` creates the database `DB` and adds the documents in `/home/dir` to the database under the path `docs/dir`.
- `db:create("DB", file:list('.'), (), map { 'ftindex': true() })` adds all files of the current working directory to a new database, preserving relative filesystem paths and creating a full-text index.

db:drop

Signatures	`db:drop($db as xs:string) as empty-sequence()`
Summary	Drops the database `$db` and all connected resources.
Errors	`open`: the addressed database does not exist or could not be opened.`lock`: a database is opened by another process.`conflict`: the same database was addressed more than once.
Examples	• `db:drop("DB")` drops the database `DB`.

db:add

Signatures	`db:add($db as xs:string, $input as item()) as empty-sequence()` `db:add($db as xs:string, $input as item(), $path as xs:string) as empty-sequence()` `db:add($db as xs:string, $input as item(), $path as xs:string, $options as map(*)?) as empty-sequence()`

Summary	Adds documents specified by `$input` to the database `$db` with the specified `$path`:
	• A document with the same path may occur more than once in a database. If you want to enforce single instances, use db:replace instead.
	• See db:create for more details on the input argument.
	• The parsing behavior can be controlled via `$options`:
	  • allowed options are `ADDCACHE` and the parsing and XML parsing options, all in lower case
	  • parsing options will only impact string input (URIs, XML strings), because nodes have already been parsed

Errors	`open`: the addressed database does not exist or could not be opened.
Examples	• `db:add("DB", "/home/dir/doc.xml")` adds the file `/home/dir/doc.xml` to the database `DB`. • `db:add("DB", <a/>, "doc.xml")` adds a document node to the database `DB` under the name `doc.xml`. • `db:add("DB", "/home/dir", "docs/dir", map { 'addcache': true() })` adds all documents in `/home/dir` to the database `DB` under the path `docs/dir`. In order to reduce memory consumption, the files will be cached before being added to the database.

db:delete

Signatures	`db:delete($db as xs:string, $path as xs:string) as empty-sequence()`
Summary	Deletes resource(s), specified by `$path`, from the database `$db`.
Errors	`open`: the addressed database does not exist or could not be opened.`path`: the specified path is invalid.
Examples	• `db:delete("DB", "docs/dir/doc.xml")` deletes the resource `docs/dir/doc.xml` from `DB`.

- `db:delete("DB", "docs/dir")` deletes all resources from `DB` in the specified path `docs/dir`.

db:copy

Signatures	`db:copy($db as xs:string, $name as xs:string) as empty-sequence()`
Summary	Creates a copy of the database `$db`, which will be called `$name`.
Errors	`open`: the addressed database does not exist or could not be opened.`lock`: a database is opened by another process.`name`: invalid database name.`conflict`: the same database was addressed more than once.

db:alter

Signatures	`db:alter($db as xs:string, $name as xs:string) as empty-sequence()`
Summary	Renames the database `$db` to `$name`.
Errors	`open`: the addressed database does not exist or could not be opened.`lock`: a database is opened by another process.`name`: invalid database name.`conflict`: the same database was addressed more than once.

db:create-backup

Signatures	`db:create-backup($db as xs:string) as empty-sequence()`
Summary	Creates a backup of the database `$db`.
Errors	`open`: the addressed database does not exist or could not be opened.`name`: invalid database name.`conflict`: the same database was addressed more than once.
Examples	• `db:create-backup("DB")` creates a backup of the database `DB`.

db:drop-backup

Signatures	`db:drop-backup($name as xs:string) as empty-sequence()`
Summary	Drops all backups of the database with the specified `$name`. If the given `$name` points to a specific backup file, only this specific backup file is deleted.
Errors	`backup`: No backup file found.`name`: invalid database name.`conflict`: the same database was addressed more than once.
Examples	• `db:drop-backup("DB")` drops all backups of the database `DB`. • `db:drop-backup("DB-2014-03-13-17-36-44")` drops the specific backup file `DB-2014-03-13-17-36-44.zip` of the database `DB`.

db:restore

Signatures	`db:restore($name as xs:string) as empty-sequence()`
Summary	Restores the database with the specified `$name`. The `$name` may include the timestamp of the backup file.
Errors	`lock`: a database is opened by another process.`name`: invalid database name.`no-backup`: No backup found.`conflict`: the same database was addressed more than once.
Examples	• `db:restore("DB")` restores the database `DB`. • `db:restore("DB-2014-03-13-18-05-45")` restores the database `DB` from the backup file with the given timestamp.

db:optimize

Signatures	`db:optimize($db as xs:string) as empty-sequence()` `db:optimize($db as xs:string, $all as xs:boolean) as empty-sequence()` `db:optimize($db as xs:string, $all as xs:boolean, $options as map(*)?) as empty-sequence()`
Summary	Optimizes the meta data and indexes of the database `$db`.If `$all` is `true`, the complete database will be rebuilt.The `$options` argument can be used to control indexing. The syntax is identical to the db:create function: Allowed options are all indexing and full-text options. `UPDINDEX` is only supported if `$all` is `true`.
Errors	`open`: the addressed database does not exist or could not be opened.
Examples	• `db:optimize("DB")` optimizes the database structures of the database `DB`. • `db:optimize("DB", true(), map { 'ftindex': true() })` optimizes all database structures of the database `DB` and creates a full-text index.

db:rename

Signatures	`db:rename($db as xs:string, $source as xs:string, $target as xs:string) as empty-sequence()`
Summary	Moves all resources(s) of database `$db`, which are found in the supplied `$source` path, to the supplied `$target` path. The paths may point to single resources or directories. No updates will take place if a non-existing source path is supplied.
Errors	`open`: the addressed database does not exist or could not be opened.`path`: the specified source or target path, or one of its descendants, is invalid.
Examples	• `db:rename("DB", "docs/dir/doc.xml", "docs/dir/newdoc.xml")` renames the resource `docs/dir/doc.xml` to `docs/dir/newdoc.xml` in the database `DB`. • `db:rename("DB", "docs/dir", "docs/newdir")` moves all resources in the database `DB` from `docs/dir` to {Code|docs/newdir}}.

db:replace

Signatures	`db:replace($db as xs:string, $path as xs:string, $input as item()) as empty-sequence()` `db:replace($db as xs:string, $path as xs:string, $input as item(), $options as map(*)?) as empty-sequence()`

Summary	Replaces a resource, specified by `$path`, in the database `$db` with the contents of `$input`, or adds it as a new resource:
	• See db:create for more details on the input argument.
	• The parsing behavior can be controlled via `$options`:
	  • allowed options are `ADDCACHE` and the parsing and XML parsing options, all in lower case
	  • parsing options will only impact string input (URIs, XML strings), because nodes have already been parsed
	• For historical reasons, the order of the 2nd and 3rd argument is different to db:add and db:create

Errors	`open`: the addressed database does not exist or could not be opened.`target`: the path points to a directory.
Examples	• `db:replace("DB", "docs/dir/doc.xml", "/home/dir/doc.xml")` replaces the content of the document `docs/dir/doc.xml` in the database `DB` with the content of the file `/home/dir/doc.xml`.

- `db:replace("DB", "docs/dir/doc.xml", "<a/>")` replaces the content of the document `docs/dir/doc.xml` in the database `DB` with `<a/>`.
- `db:replace("DB", "docs/dir/doc.xml", document { <a/> })` replaces the content of the document `docs/dir/doc.xml` in the database `DB` with the specified document node.

The following query can be used to import files from a directory to a database:

```
let $source := '/home/john/xml/source'
for $file in file:list($source, true())
let $path := $source || $file
where not(file:is-dir($path))
return db:replace('db', $file, doc($path))
```

db:store

Signatures	`db:store($db as xs:string, $path as xs:string, $input as item()) as empty-sequence()`
Summary	Replaces a binary resource specified by `$input` in the database `$db` and the location specified by `$path`, or adds it as new resource.
Errors	`open`: the addressed database does not exist or could not be opened.`mainmem`: the database is not *persistent* (stored on disk).

Examples	• `db:store("DB", "video/sample.mov", file:read-binary('video.mov'))` stores the addressed video file at the specified location.
	• With the following query, you can copy full directories:
	`let $db := 'db'`
	`let $src-path := 'src/'`
	`let $trg-path := 'trg/'`
	`for $src in db:list($db, $src-path)`
	`where db:is-raw($db, $src)`
	`let $trg := $trg-path \|\| substring-after($src, $src-path)`
	`return db:store($db, $trg, db:retrieve($db, $src))`

db:flush

Signatures	`db:flush($db as xs:string) as empty-sequence()`
Summary	Explicitly flushes the buffers of the database `$db`. This command is only useful if `AUTOFLUSH` has been set to `false`.
Errors	`open`: the addressed database does not exist or could not be opened.

Helper Functions

db:name

Signatures	`db:name($node as node()) as xs:string`
Summary	Returns the name of the database in which the specified database node `$node` is stored.
Errors	`node`: `$nodes` contains a node which is not stored in a database.

db:path

Signatures	`db:path($node as node()) as xs:string`

Summary	Returns the path of the database document in which the specified database node `$node` is stored.
Errors	`node`: `$nodes` contains a node which is not stored in a database.

db:exists

Signatures	`db:exists($db as xs:string) as xs:boolean db:exists($db as xs:string, $path as xs:string) as xs:boolean`
Summary	Checks if the database `$db` or the resource specified by `$path` exists. `false` is returned if a database directory has been addressed.
Examples	• `db:exists("DB")` returns `true` if the database `DB` exists. • `db:exists("DB", "resource")` returns `true` if `resource` is an XML document or a raw file.

db:is-raw

Signatures	`db:is-raw($db as xs:string, $path as xs:string) as xs:boolean`
Summary	Checks if the specified resource in the database `$db` and the path `$path` exists, and if it is a binary resource.
Errors	`open`: the addressed database does not exist or could not be opened.
Examples	• `db:is-raw("DB", "music/01.mp3")` returns `true`.

db:is-xml

Signatures	`db:is-xml($db as xs:string, $path as xs:string) as xs:boolean`
Errors	`open`: the addressed database does not exist or could not be opened.
Summary	Checks if the specified resource in the database `$db` and the path `$path` exists, and if it is an XML document.
Examples	• `db:is-xml("DB", "dir/doc.xml")` returns `true`.

db:content-type

Signatures	`db:content-type($db as xs:string, $path as xs:string) as xs:string`
Summary	Retrieves the content type of a resource in the database `$db` and the path `$path`.The file extension is used to recognize the content-type of a resource stored in the database. Content-type `application/xml` will be returned for any XML document stored in the database, regardless of its file name extension.
Errors	`open`: the addressed database does not exist or could not be opened.
Examples	• `db:content-type("DB", "docs/doc01.pdf")` returns `application/pdf`. • `db:content-type("DB", "docs/doc01.xml")` returns `application/xml`. • `db:content-type("DB", "docs/doc01")` returns `application/xml`, if `db:is-xml("DB", "docs/doc01")` returns `true`.

Errors

Updated with Version 9.0:

Code	Description
`args`	The number of specified inputs and paths differs.

`conflict`	Multiple update operations point to the same target.
`lock`	A database cannot be updated because it is opened by another process.
`mainmem`	The addressed database is not *persistent* (stored on disk).
`name`	The name of the specified database is invalid.
`no-backup`	No backup exists for a database.
`node`	The referenced XML node is no database node, i.e. it is neither stored in a database nor represented as database fragment.
`no-index`	The database lacks an index structure required by the called function.
`open`	The addressed database does not exist or could not be opened.
`path`	The specified database path is invalid.
`property`	A database property is unknown.
`range`	The addressed database id or pre value is out of range.
`target`	Path points to an invalid target.

Changelog

Version 9.0

- Added: db:option
- Updated: db:output renamed to update:output, db:output-cache renamed to update:output-cache
- Updated: error codes updated; errors now use the module namespace

Version 8.6

- Added: db:property

Version 8.4

- Updated: db:create, db:add, db:replace: support for `ADDCACHE` option.
- Added: db:token

Version 8.3

- Updated: db:list-details: attributes with name of database and date of backup added to results.
- Updated: db:backups now include attributes with name of database and date of backup.
- Updated: Value Indexes: raise error if no index exists.

Version 8.2

- Added: db:output-cache
- Removed: db:event

Version 7.9

- Updated: parsing options added to db:create, db:add and db:replace.
- Updated: allow `UPDINDEX` if `$all` is `true`.

Version 7.8.2

- Added: db:alter, db:copy, db:create-backup, db:drop-backup, db:restore

Version 7.8

- Removed: db:fulltext (use ft:search instead)

Version 7.7

- Added: db:export, db:name, db:path
- Updated: `$options` argument added to db:create and db:optimize.
- Updated: the functions no longer accept Database Nodes as reference. Instead, the name of a database must now be specified.

Version 7.6

- Updated: db:create: allow more than one input and path.

Version 7.5

- Updated: db:add: input nodes will be automatically converted to document nodes
- Added: db:backups
- Added: db:create
- Added: db:drop

Version 7.3

- Added: db:flush

Version 7.2.1

- Added: db:text-range, db:attribute-range, db:output

Version 7.1

- Added: db:list-details, db:content-type
- Updated: db:info, db:system, db:retrieve

Version 7.0

- Added: db:retrieve, db:store, db:exists, db:is-raw, db:is-xml
- Updated: db:list, db:open, db:add

Chapter 43. Fetch Module

Read this entry online in the BaseX Wiki.

This XQuery Module provides simple functions to fetch the content of resources identified by URIs. Resources can be stored locally or remotely and e.g. use the `file://` or `http://` scheme. If more control over HTTP requests is required, the HTTP Module can be used. With the HTML Module, retrieved HTML documents can be converted to XML.

Conventions

Updated with Version 9.0:

All functions and errors in this module are assigned to the `http://basex.org/modules/fetch` namespace, which is statically bound to the `fetch` prefix.

URI arguments can point be URLs or point to local files. Relative file paths will be resolved against the *current working directory* (for more details, have a look at the File Module).

Functions

fetch:binary

Signatures	`fetch:binary($uri as xs:string) as xs:base64Binary`
Summary	Fetches the resource referred to by the given URI and returns it as lazy `xs:base64Binary` item.
Errors	`open`: the URI could not be resolved, or the resource could not be retrieved.
Examples	• `fetch:binary("http://images.trulia.com/blogimg/c/5/f/4/679932_1298401950553_o.jpg")` returns the addressed image. • `lazy:cache(fetch:binary("http://en.wikipedia.org"))` enforces the fetch operation (otherwise, it will be delayed until requested first).

fetch:text

Signatures	`fetch:text($uri as xs:string) as xs:string` `fetch:text($uri as xs:string, $encoding as xs:string) as xs:string` `fetch:text($uri as xs:string, $encoding as xs:string, $fallback as xs:boolean) as xs:string`
Summary	Fetches the resource referred to by the given `$uri` and returns it as lazy `xs:string` item: • The UTF-8 default encoding can be overwritten with the optional `$encoding` argument. • By default, invalid characters will be rejected. If `$fallback` is set to true, these characters will be replaced with the Unicode replacement character `FFFD` (#).
Errors	`open`: the URI could not be resolved, or the resource could not be retrieved.`encoding`: the specified encoding is not supported, or unknown.
Examples	• `fetch:text("http://en.wikipedia.org")` returns a string representation of the English Wikipedia main HTML page. • `fetch:text("http://www.bbc.com","US-ASCII",true())` returns the BBC homepage in US-ASCII with all non-US-ASCII characters replaced with #. • `lazy:cache(fetch:text("http://en.wikipedia.org"))` enforces the fetch operation (otherwise, it will be delayed until requested first).

fetch:xml

Signatures	`fetch:xml($uri as xs:string) as document-node()` `fetch:xml($uri as xs:string, $options as map(*)?) as document-node()`
Summary	Fetches the resource referred to by the given `$uri` and returns it as XML document node.In contrast to `fn:doc`, each function call returns a different document node. As a consequence, document instances created by this function will not be kept in memory until the end of query evaluation.The `$options` argument can be used to change the parsing behavior. Allowed options are all parsing and XML parsing options in lower case.
Errors	`open`: the URI could not be resolved, or the resource could not be retrieved.

Examples	• Retrieve an XML representation of the English Wikipedia main HTML page, chop all whitespace nodes:
	`fetch:xml("http://en.wikipedia.org", map { 'chop': true() })`
	• Return a document located in the current base directory:
	`fetch:xml(file:base-dir() || "example.xml")`

fetch:xml-binary

Introduced with Version 9.0:

Signatures	`fetch:xml-binary($data as xs:base64Binary) as document-node()` `fetch:xml-binary($data as xs:base64Binary, $options as map(*)?) as document-node()`
Summary	Parses binary `$data` and returns it as XML document node.In contrast to fn:parse-xml, which expects an XQuery string, the input of this function can be arbitrarily encoded. The encoding will be derived from the XML declaration or (in case of UTF16 or UTF32) from the first bytes of the input.The `$options` argument can be used to change the parsing behavior. Allowed options are all parsing and XML parsing options in lower case.

Examples	• Retrieves file input as binary data and parses it as XML:
	`fetch:xml-binary(file:read-binary('doc.xml'))`
	• Encodes a string as CP1252 and parses it as XML. The input and the string `touché` will be correctly decoded because of the XML declaration:
	`fetch:xml-binary(convert:string-to-base64(`
	`  "<?xml version='1.0' encoding='CP1252'?><xml>touché</xml>",`
	`  "CP1252"`
	`))`
	• Encodes a string as UTF16 and parses it as XML. The document will be correctly decoded, as the first bytes of the data indicate that the input must be UTF16:
	`fetch:xml-binary(convert:string-to-base64("<xml/>", "UTF16"))`

fetch:content-type

Signatures	`fetch:content-type($uri as xs:string) as xs:string`
Summary	Returns the content-type (also called mime-type) of the resource specified by `$uri`:

	• If a remote resource is addressed, the request header will be evaluated. • If the addressed resource is locally stored, the content-type will be guessed based on the file extension.
Errors	`open`: the URI could not be resolved, or the resource could not be retrieved.
Examples	• `fetch:content-type("http://docs.basex.org/skins/vector/images/wiki.png")` returns `image/png`.

Errors

Updated with Version 9.0:

Code	Description
`encoding`	The specified encoding is not supported, or unknown.
`open`	The URI could not be resolved, or the resource could not be retrieved.

Changelog

Version 9.0

- Added: fetch:xml-binary
- Updated: error codes updated; errors now use the module namespace

Version 8.5

- Updated: fetch:text: `$fallback` argument added.

Version 8.0

- Added: fetch:xml

The module was introduced with Version 7.6.

Chapter 44. File Module

Read this entry online in the BaseX Wiki.

This XQuery Module contains functions related to file system operations, such as listing, reading, or writing files.

This module is based on the EXPath File Module.

Conventions

All functions and errors in this module are assigned to the `http://expath.org/ns/file` namespace, which is statically bound to the `file` prefix.

For serialization parameters, the `http://www.w3.org/2010/xslt-xquery-serialization` namespace is used, which is statically bound to the `output` prefix.

The error `invalid-path` is raised if a path is invalid.

File Paths

- All file paths are resolved against the *current working directory* (the directory from which BaseX or, more generally, the Java Virtual Machine, was started). This directory can be retrieved via file:base-dir.
- A path can be specified as local filesystem path or as file URI.
- Returned strings that refer to existing directories are suffixed with a directory separator.

Read Operations

file:list

Signatures	`file:list($dir as xs:string) as xs:string*` `file:list($dir as xs:string, $recursive as xs:boolean) as xs:string*` `file:list($dir as xs:string, $recursive as xs:boolean, $pattern as xs:string) as xs:string*`
Summary	Lists all files and directories found in the specified `$dir`. The returned paths are relative to the provided path.The optional parameter `$recursive` specifies whether sub-directories will be traversed, too.The optional parameter `$pattern` defines a file name pattern in the Glob Syntax. If present, only those files and directories are returned that correspond to the pattern. Several patterns can be separated with a comma (`,`).
Errors	`not-found`: the specified file does not exist.`no-dir`: the specified path does not point to a directory.`io-error`: the operation fails for some other reason.

file:children

Signatures	`file:children($dir as xs:string) as xs:string*`
Summary	Returns the full paths to all files and directories found in the specified `$dir`.The inverse function is file:parent. The related function file:list returns relative file paths.
Errors	`not-found`: the specified file does not exist.`no-dir`: the specified path does not point to a directory.`io-error`: the operation fails for some other reason.

file:read-binary

Signatures	`file:read-binary($path as xs:string) as xs:base64Binary` `file:read-binary($path as xs:string, $offset as xs:integer) as xs:base64Binary` `file:read-binary($path as xs:string, $offset as xs:integer, $length as xs:integer) as xs:base64Binary`

Summary	Reads the binary content of the file specified by `$path` and returns it as lazy `xs:base64Binary` item.The optional parameters `$offset` and `$length` can be used to read chunks of a file.
Errors	`not-found`: the specified file does not exist.`is-dir`: the specified path is a directory.`out-of-range`: the offset or length is negative, or the chosen values would exceed the file bounds.`io-error`: the operation fails for some other reason.
Examples	• `lazy:cache(file:read-binary("config.data"))` enforces the file access (otherwise, it will be delayed until requested first).

file:read-text

Signatures	`file:read-text($path as xs:string) as xs:string file:read-text($path as xs:string, $encoding as xs:string) as xs:string file:read-text($path as xs:string, $encoding as xs:string, $fallback as xs:boolean) as xs:string`
Summary	Reads the textual contents of the file specified by `$path` and returns it as lazy `xs:string` item: • The UTF-8 default encoding can be overwritten with the optional `$encoding` argument. • By default, invalid characters will be rejected. If `$fallback` is set to true, these characters will be replaced with the Unicode replacement character `FFFD` (#).
Errors	`not-found`: the specified file does not exist.`is-dir`: the specified path is a directory.`unknown-encoding`: the specified encoding is not supported, or unknown.`io-error`: the operation fails for some other reason.
Examples	• `lazy:cache(file:read-text("ids.txt"))` enforces the file access (otherwise, it will be delayed until requested first).

file:read-text-lines

Updated with Version 9.0: file:read-text-lines: `$offset` and `$length` arguments added.

Signatures	`file:read-text-lines($path as xs:string) as xs:string file:read-text-lines($path as xs:string, $encoding as xs:string) as xs:string* file:read-text-lines($path as xs:string, $encoding as xs:string, $fallback as xs:boolean) as xs:string* file:read-text-lines($path as xs:string, $encoding as xs:string, $fallback as xs:boolean, $offset as xs:integer) as xs:string* file:read-text-lines($path as xs:string, $encoding as xs:string, $fallback as xs:boolean, $offset as xs:integer, $length as xs:integer) as xs:string*`
Summary	Reads the textual contents of the file specified by `$path` and returns it as a sequence of `xs:string` items: • The UTF-8 default encoding can be overwritten with the optional `$encoding` argument. • By default, invalid characters will be rejected. If `$fallback` is set to true, these characters will be replaced with the Unicode replacement character `FFFD` (#). The lines to be read can be restricted with the optional parameters `$offset` and `$length`.
Errors	`not-found`: the specified file does not exist.`is-dir`: the specified path is a directory.`unknown-encoding`: the specified encoding is not supported, or unknown.`io-error`: the operation fails for some other reason.

Write Operations

file:create-dir

Signatures	`file:create-dir($dir as xs:string) as empty-sequence()`

Summary	Creates the directory specified by `$dir`, including all non-existing parent directories.
Errors	`exists`: a file with the same path already exists.`io-error`: the operation fails for some other reason.

file:create-temp-dir

Signatures	`file:create-temp-dir($prefix as xs:string, $suffix as xs:string) as xs:string file:create-temp-dir($prefix as xs:string, $suffix as xs:string, $dir as xs:string) as xs:string`
Summary	Creates a new temporary directory that did not exist before this function was called, and returns its full file path. The directory name begins and ends with the specified `$prefix` and `$suffix`. If no directory is specified via `$dir`, the directory will be placed in the system's default temporary directory. The operation will create all non-existing parent directories.
Errors	`no-dir`: the specified directory points to a file.`io-error`: the directory could not be created.

file:create-temp-file

Signatures	`file:create-temp-file($prefix as xs:string, $suffix as xs:string) as xs:string file:create-temp-file($prefix as xs:string, $suffix as xs:string, $dir as xs:string) as xs:string`
Summary	Creates a new temporary file that did not exist before this function was called, and returns its full file path. The file name begins and ends with the specified `$prefix` and `$suffix`. If no directory is specified via `$dir`, the file will be placed in the system's default temporary directory. The operation will create all non-existing parent directories.
Errors	`no-dir`: the specified directory points to a file.`io-error`: the directory could not be created.

file:delete

Signatures	`file:delete($path as xs:string) as empty-sequence() file:delete($path as xs:string, $recursive as xs:boolean) as empty-sequence()`
Summary	Recursively deletes a file or directory specified by `$path`.The optional parameter `$recursive` specifies whether sub-directories will be deleted, too.
Errors	`not-found`: the specified path does not exist.`io-error`: the operation fails for some other reason.

file:write

Signatures	`file:write($path as xs:string, $items as item()*) as empty-sequence() file:write($path as xs:string, $items as item()*, $params as item()) as empty-sequence()`

Summary	Writes a serialized sequence of items to the specified file. If the file already exists, it will be overwritten.The `$params` argument contains serialization parameters (see Serialization for more details), which can either be specified
	• as children of an `<output:serialization-parameters/>` element, as defined for the fn:serialize() function; e.g.:
	`<output:serialization-parameters>`
	`  <output:method value='xml'/>`
	`  <output:cdata-section-elements value="div"/>`
	`  ...`

```
</output:serialization-parameters>
```

- as map, which contains all key/value pairs:

```
map { "method": "xml", "cdata-section-elements": "div", ... }
```

Errors	`no-dir`: the parent of specified path is no directory.`is-dir`: the specified path is a directory.`io-error`: the operation fails for some other reason.

file:write-binary

Signatures	`file:write-binary($path as xs:string, $value as xs:anyAtomicType) as empty-sequence()` `file:write-binary($path as xs:string, $value as xs:anyAtomicType, $offset as xs:integer) as empty-sequence()`
Summary	Writes a binary item (xs:base64Binary, xs:hexBinary) to the specified file. If the file already exists, it will be overwritten.If `$offset` is specified, data will be written at this file position. An existing file may be resized by that operation.
Errors	`no-dir`: the parent of specified path is no directory.`is-dir`: the specified path is a directory.`out-of-range`: the offset is negative, or it exceeds the current file size.`io-error`: the operation fails for some other reason.

file:write-text

Signatures	`file:write-text($path as xs:string, $value as xs:string) as empty-sequence()` `file:write-text($path as xs:string, $value as xs:string, $encoding as xs:string) as empty-sequence()`
Summary	Writes a string to the specified file. If the file already exists, it will be overwritten.The optional parameter `$encoding` defines the output encoding (default: UTF-8).
Errors	`no-dir`: the parent of specified path is no directory.`is-dir`: the specified path is a directory.`unknown-encoding`: the specified encoding is not supported, or unknown.`io-error`: the operation fails for some other reason.

file:write-text-lines

Signatures	`file:write-text-lines($path as xs:string, $values as xs:string*) as empty-sequence()` `file:write-text-lines($path as xs:string, $values as xs:string*, $encoding as xs:string) as empty-sequence()`
Summary	Writes a sequence of strings to the specified file, each followed by the system specific newline character. If the file already exists, it will be overwritten.The optional parameter `$encoding` defines the output encoding (default: UTF-8).
Errors	`no-dir`: the parent of specified path is no directory.`is-dir`: the specified path is a directory.`unknown-encoding`: the specified encoding is not supported, or unknown.`io-error`: the operation fails for some other reason.

file:append

Signatures	`file:append($path as xs:string, $items as item()*) as empty-sequence()` `file:append($path as xs:string, $items as item()*, $params as item()) as empty-sequence()`
Summary	Appends a serialized sequence of items to the specified file. If the file does not exists, a new file is created.
Errors	`no-dir`: the parent of specified path is no directory.`is-dir`: the specified path is a directory.`io-error`: the operation fails for some other reason.

file:append-binary

Signatures	`file:append-binary($path as xs:string, $value as xs:anyAtomicType) as empty-sequence()`
Summary	Appends a binary item (xs:base64Binary, xs:hexBinary) to the specified file. If the file does not exists, a new one is created.
Errors	`no-dir`: the parent of specified path is no directory.`is-dir`: the specified path is a directory.`io-error`: the operation fails for some other reason.

file:append-text

Signatures	`file:append-text($path as xs:string, $value as xs:string) as empty-sequence() file:append-text($path as xs:string, $value as xs:string, $encoding as xs:string) as empty-sequence()`
Summary	Appends a string to a file specified by `$path`. If the specified file does not exists, a new file is created.The optional parameter `$encoding` defines the output encoding (default: UTF-8).
Errors	`no-dir`: the parent of specified path is no directory.`is-dir`: the specified path is a directory.`unknown-encoding`: the specified encoding is not supported, or unknown.`io-error`: the operation fails for some other reason.

file:append-text-lines

Signatures	`file:append-text-lines($path as xs:string, $values as xs:string*) as empty-sequence() file:append-text-lines($path as xs:string, $values as xs:string*, $encoding as xs:string) as empty-sequence()`
Summary	Appends a sequence of strings to the specified file, each followed by the system specific newline character. If the specified file does not exists, a new file is created.The optional parameter `$encoding` defines the output encoding (default: UTF-8).
Errors	`no-dir`: the parent of specified path is no directory.`is-dir`: the specified path is a directory.`unknown-encoding`: the specified encoding is not supported, or unknown.`io-error`: the operation fails for some other reason.

file:copy

Signatures	`file:copy($source as xs:string, $target as xs:string) as empty-sequence()`
Summary	Copies a file or directory specified by `$source` to the file or directory specified by `$target`. If the target file already exists, it will be overwritten. No operation will be performed if the source and target path are equal.
Errors	`not-found`: the specified source does not exist.`exists`: the specified source is a directory and the target is a file.`no-dir`: the parent of the specified target is no directory.`io-error`: the operation fails for some other reason.

file:move

Signatures	`file:move($source as xs:string, $target as xs:string) as empty-sequence()`
Summary	Moves or renames the file or directory specified by `$source` to the path specified by `$target`. If the target file already exists, it will be overwritten. No operation will be performed if the source and target path are equal.
Errors	`not-found`: the specified source does not exist.`exists`: the specified source is a directory and the target is a file.`no-dir`: the parent of the specified target is no directory.`io-error`: the operation fails for some other reason.

File Properties

file:exists

Signatures	`file:exists($path as xs:string) as xs:boolean`
Summary	Returns an `xs:boolean` indicating whether a file or directory specified by `$path` exists in the file system.

file:is-dir

Signatures	`file:is-dir($path as xs:string) as xs:boolean`
Summary	Returns an `xs:boolean` indicating whether the argument `$path` points to an existing directory.

file:is-absolute

Signatures	`file:is-absolute($path as xs:string) as xs:boolean`
Summary	Returns an `xs:boolean` indicating whether the argument `$path` is absolute.The behavior of this function depends on the operating system: On Windows, an absolute path starts with the drive letter and a colon, whereas on Linux it starts with a slash.

file:is-file

Signatures	`file:is-file($path as xs:string) as xs:boolean`
Summary	Returns an `xs:boolean` indicating whether the argument `$path` points to an existing file.

file:last-modified

Signatures	`file:last-modified($path as xs:string) as xs:dateTime`
Summary	Retrieves the timestamp of the last modification of the file or directory specified by `$path`.
Errors	`not-found`: the specified path does not exist.

file:size

Signatures	`file:size($file as xs:string) as xs:integer`
Summary	Returns the size, in bytes, of the file specified by `$path`, or `0` for directories.
Errors	`not-found`: the specified file does not exist.

Path Functions

file:name

Signatures	`file:name($path as xs:string) as xs:string`
Summary	Returns the name of a file or directory specified by `$path`. An empty string is returned if the path points to the root directory.

file:parent

Signatures	`file:parent($path as xs:string) as xs:string?`
Summary	Returns the absolute path to the parent directory of a file or directory specified by `$path`. An empty sequence is returned if the path points to a root directory.The inverse function is file:children.

Examples	• `file:parent(static-base-uri())` returns the directory of the current XQuery module.

file:path-to-native

Signatures	`file:path-to-native($path as xs:string) as xs:string`
Summary	Transforms the `$path` argument to its native representation on the operating system.
Errors	`not-found`: the specified file does not exist.`io-error`: the specified path cannot be transformed to its native representation.

file:resolve-path

Signatures	`file:resolve-path($path as xs:string) as xs:string` `file:resolve-path($path as xs:string, $base as xs:string) as xs:string`
Summary	Transforms the `$path` argument to an absolute operating system path.If the path is relative, and if an absolute `$base` path is specified, it will be resolved against this path.
Errors	`is-relative`: the specified base path is relative.
Examples	The following examples apply to Windows: • `file:resolve-path('file.txt', 'C:/Temp/')` returns `C:/Temp/file.txt`. • `file:resolve-path('file.txt', 'C:/Temp')` returns `C:/file.txt`. • `file:resolve-path('file.txt', 'Temp')` raises an error.

file:path-to-uri

Signatures	`file:path-to-uri($path as xs:string) as xs:string`
Summary	Transforms the path specified by `$path` into a URI with the `file://` scheme.

System Properties

file:dir-separator

Signatures	`file:dir-separator() as xs:string`
Summary	Returns the directory separator used by the operating system, such as `/` or `\`.

file:path-separator

Signatures	`file:path-separator() as xs:string`
Summary	Returns the path separator used by the operating system, such as `;` or `:`.

file:line-separator

Signatures	`file:line-separator() as xs:string`
Summary	Returns the line separator used by the operating system, such as `
`, `
` or `
`.

file:temp-dir

Signatures	`file:temp-dir() as xs:string`
Summary	Returns the system's default temporary-file directory.

file:current-dir

Signatures	`file:current-dir() as xs:string`
Summary	Returns the current working directory. - This function returns the same result as the function call `file:resolve-path("")`

file:base-dir

Signatures	`file:base-dir() as xs:string?`
Summary	Returns the parent directory of the static base URI. If the Base URI property is undefined, the empty sequence is returned. - If a static base URI exists, and if points to a local file path, this function returns the same result as the expression `file:parent(static-base-uri())`.

Errors

Code	Description
`exists`	A file with the same path already exists.
`invalid-path`	A specified path is invalid.
`io-error`	The operation fails for some other reason specific to the operating system.
`is-dir`	The specified path is a directory.
`is-relative`	The specified path is relative (and must be absolute).
`no-dir`	The specified path does not point to a directory.
`not-found`	A specified path does not exist.
`out-of-range`	The specified offset or length is negative, or the chosen values would exceed the file bounds.
`unknown-encoding`	The specified encoding is not supported, or unknown.

Changelog

Version 9.0

- Updated: file:read-text-lines: `$offset` and `$length` arguments added.

Version 8.5

- Updated: file:read-text, file:read-text-lines: `$fallback` argument added.

Version 8.2

- Added: file:is-absolute
- Updated: file:resolve-path: base argument added

Version 8.0

- Added: file:current-dir, file:base-dir, file:children

Version 7.8

- Added: file:parent, file:name
- Updated: error codes; file:read-binary, file:write-binary: `$offset` and `$length` arguments added.

- Deleted: file:base-name, file:dir-name

Version 7.7

- Added: file:create-temp-dir, file:create-temp-file, file:temp-dir
- Updated: all returned strings that refer to existing directories will be suffixed with a directory separator.

Version 7.3

- Added: file:append-text, file:write-text, file:append-text-lines, file:write-text-lines, file:line-separator
- Aligned with latest specification: $file:directory-separator → file:dir-separator, $file:path-separator → file:path-separator, file:is-directory → file:is-dir, file:create-directory → file:create-dir
- Updated: file:write-binary, file:append-binary: output limited to a single value

Version 7.2.1

- Updated: file:delete: `$recursive` parameter added to prevent sub-directories from being accidentally deleted.
- Fixed: file:list now returns relative instead of absolute paths.

Chapter 45. Full-Text Module

Read this entry online in the BaseX Wiki.

This XQuery Module extends the W3C Full Text Recommendation with some useful functions: The index can be directly accessed, fulltext results can be marked with additional elements, or the relevant parts can be extracted. Moreover, the score value, which is generated by the `contains text` expression, can be explicitly requested from items.

Conventions

Updated with Version 9.0:

All functions and errors in this module are assigned to the `http://basex.org/modules/ft` namespace, which is statically bound to the `ft` prefix.

Functions

ft:search

Signatures	`ft:search($db as xs:string, $terms as item()*) as text()*` `ft:search($db as xs:string, $terms as item()*, $options as map(*)?) as text()*`

Summary	Returns all text nodes from the full-text index of the database `$db` that contain the specified `$terms`.The options used for tokenizing the input and building the full-text will also be applied to the search terms. As an example, if the index terms have been stemmed, the search string will be stemmed as well. The `$options` argument can be used to control full-text processing. The following options are supported (the introduction on Full-Text processing gives you equivalent expressions in the XQuery Full-Text notation):
	• `mode` : determines the mode how tokens are searched. Allowed values are `any`, `any word`, `all`, `all words`, and `phrase`. `any` is the default search mode.
	• `fuzzy` : turns fuzzy querying on or off. Allowed values are `true` and `false`. By default, fuzzy querying is turned off.
	• `wildcards` : turns wildcard querying on or off. Allowed values are `true` and `false`. By default, wildcard querying is turned off.
	• `ordered` : requires that all tokens occur in the order in which they are specified. Allowed values are `true` and `false`. The default is `false`.
	• `content` : specifies that the matched tokens need to occur at the beginning or end of a searched string, or need to cover the entire string. Allowed values are `start`, `end`, and `entire`. By default, the option is turned off.
	• `scope` : defines the scope in which tokens must be located. The option has following sub options:
	  • `same` : can be set to `true` or `false`. It specifies if tokens need to occur in the same or different units.
	  • `unit` : can be `sentence` or `paragraph`. It specifies the unit for finding tokens.
	• `window` : sets up a window in which all tokens must be located. By default, the option is turned off. It has following sub options:
	  • `size` : specifies the size of the window in terms of *units*.

	• `unit` : can be `sentences`, `sentences` or `paragraphs`. The default is `words`.
	• `distance` : specifies the distance in which tokens must occur. By default, the option is turned off. It has following sub options:
	  • `min` : specifies the minimum distance in terms of *units*. The default is `0`.
	  • `max` : specifies the maximum distance in terms of *units*. The default is .
	  • `unit` : can be `words`, `sentences` or `paragraphs`. The default is `words`.

Errors	`db:open`: The addressed database does not exist or could not be opened.`db:no-index`: the index is not available.`options`: the fuzzy and wildcard option cannot be both specified.

Examples	• `ft:search("DB", "QUERY")` : Return all text nodes of the database `DB` that contain the term `QUERY`.
	• Return all text nodes of the database `DB` that contain the numbers `2010` and `2020`:`ft:search("DB", ("2010", "2020"), map { 'mode': 'all' })`
	• Return text nodes that contain the terms `A` and `B` in a distance of at most 5 words:
	`ft:search("db", ("A", "B"), map { "mode": "all words", "distance": map { "max": "5", "unit": "words" } })`
	• Iterate over three databases and return all elements containing terms similar to `Hello World` in the text nodes:
	`let $terms := "Hello Worlds" let $fuzzy := true() for $db in 1 to 3 let $dbname := 'DB' || $db return ft:search($dbname, $terms, map { 'fuzzy': $fuzzy })/..`

ft:contains

Signatures	`ft:contains($input as item()*, $terms as item()*) as xs:boolean` `ft:contains($input as item()*, $terms as item()*, $options as map(*)?) as xs:boolean`
Summary	Checks if the specified `$input` items contain the specified `$terms`.The function does the same as the Full-Text expression `contains text`, but options can be specified more dynamically. The `$options` are the same as for ft:search, and the following ones in addition: • `case` : determines how character case is processed. Allowed values are `insensitive`, `sensitive`, `upper` and `lower`. By default, search is case insensitive. • `diacritics` : determines how diacritical characters are processed. Allowed values are `insensitive` and `sensitive`. By default, search is diacritical insensitive. • `stemming` : determines is tokens are stemmed. Allowed values are `true` and `false`. By default, stemming is turned off. • `language` : determines the language. This option is relevant for stemming tokens. All language codes are supported. The default language is `en`.

Errors	`options`: specified options are conflicting.

Examples	• Checks if `jack` or `john` occurs in the input string `John Doe`:
	`ft:contains("John Doe", ("jack", "john"), map { "mode": "any" })`
	• Calls the function with stemming turned on and off:
	`(true(), false()) ! ft:contains("Häuser", "Haus", map { 'stemming': ., 'language':'de' })`

ft:mark

Signatures	`ft:mark($nodes as node()*) as node()* ft:mark($nodes as node()*, $name as xs:string) as node()*`
Summary	Puts a marker element around the resulting `$nodes` of a full-text index request.The default name of the marker element is `mark`. An alternative name can be chosen via the optional `$name` argument.Please note that: • the full-text expression that computes the token positions must be specified as argument of the `ft:mark()` function, as all position information is lost in subsequent processing steps. You may need to specify more than one full-text expression if you want to use the function in a FLWOR expression, as shown in Example 2. • the XML node to be transformed must be an internal "database" node. The `transform` expression can be used to apply the method to a main-memory fragment, as shown in Example 3.

Examples	**Example 1**: The following query returns `<XML><mark>hello</mark> world</XML>`, if one text node of the database `DB` has the value "hello world":
	`ft:mark(db:open('DB')//*[text() contains text 'hello'])`
	Example 2: The following expression loops through the first ten full-text results and marks the results in a second expression:
	`let $start := 1`
	`let $end   := 10`
	`let $term  := 'welcome'`
	`for $ft in (db:open('DB')//*[text() contains text { $term }])[position() = $start to $end]`
	`return element hit {`
	`  ft:mark($ft[text() contains text { $term }])`
	`}`
	Example 3: The following expression returns `<p><b>word</b></p>`:
	`copy $p := <p>word</p>`
	`modify ()`
	`return ft:mark($p[text() contains text 'word'], 'b')`

ft:extract

Signatures	`ft:extract($nodes as node()*) as node()* ft:extract($nodes as node()*, $name as xs:string) as node()* ft:extract($nodes as node()*, $name as xs:string, $length as xs:integer) as node()*`
Summary	Extracts and returns relevant parts of full-text results. It puts a marker element around the resulting `$nodes` of a full-text index request and chops irrelevant sections of the result.The default element

	name of the marker element is `mark`. An alternative element name can be chosen via the optional `$name` argument.The default length of the returned text is `150` characters. An alternative length can be specified via the optional `$length` argument. Note that the effective text length may differ from the specified text due to formatting and readibility issues.For more details on this function, please have a look at ft:mark.
Examples	• The following query may return `<XML>...<b>hello</b>...<XML>` if a text node of the database `DB` contains the string "hello world": `ft:extract(db:open('DB')//*[text() contains text 'hello'], 'b', 1)`

ft:count

Signatures	`ft:count($nodes as node()*) as xs:integer`
Summary	Returns the number of occurrences of the search terms specified in a full-text expression.
Examples	• `ft:count(//*[text() contains text 'QUERY'])` returns the `xs:integer` value `2` if a document contains two occurrences of the string "QUERY".

ft:score

Signatures	`ft:score($item as item()*) as xs:double*`
Summary	Returns the score values (0.0 - 1.0) that have been attached to the specified items. `0` is returned a value if no score was attached.
Examples	• `ft:score('a' contains text 'a')` returns the `xs:double` value `1`.

ft:tokens

Signatures	`ft:tokens($db as xs:string) as element(value)*` `ft:tokens($db as xs:string, $prefix as xs:string) as element(value)*`
Summary	Returns all full-text tokens stored in the index of the database `$db`, along with their numbers of occurrences.If `$prefix` is specified, the returned nodes will be refined to the strings starting with that prefix. The prefix will be tokenized according to the full-text used for creating the index.
Errors	`db:open`: The addressed database does not exist or could not be opened.`db:no-index`: the full-text index is not available.

Examples	Returns the number of occurrences for a single, specific index entry:
	
	`let $term := ft:tokenize($term)`
	`return number(ft:tokens('db', $term)[. = $term]/@count)`

ft:tokenize

Signatures	`ft:tokenize($input as xs:string) as xs:string*` `ft:tokenize($input as xs:string, $options as map(*)?) as xs:string*`
Summary	Tokenizes the given `$input` string, using the current default full-text options or the `$options` specified as second argument. The following options are available: • `case` : determines how character case is processed. Allowed values are `insensitive`, `sensitive`, `upper` and `lower`. By default, search is case insensitive. • `diacritics` : determines how diacritical characters are processed. Allowed values are `insensitive` and `sensitive`. By default, search is diacritical insensitive. • `stemming` : determines is tokens are stemmed. Allowed values are `true` and `false`. By default, stemming is turned off.

	• `language` : determines the language. This option is relevant for stemming tokens. All language codes are supported. The default language is `en`. The `$options` argument can be used to control full-text processing.
Examples	• `ft:tokenize("No Doubt")` returns the two strings `no` and `doubt`. • `ft:tokenize("École", map { 'diacritics': 'sensitive' })` returns the string `école`. • `declare ft-option using stemming; ft:tokenize("GIFTS")` returns a single string `gift`.

ft:normalize

Signatures	`ft:normalize($input as xs:string) as xs:string*` `ft:normalize($input as xs:string, $options as map(*)?) as xs:string*`
Summary	Normalizes the given `$input` string, using the current default full-text options or the `$options` specified as second argument. The function expects the same arguments as ft:tokenize.
Examples	• `ft:tokenize("Häuser am Meer", map { 'case': 'sensitive' })` returns the string `Hauser am Meer`.

Errors

Updated with Version 9.0:

Code	Description
`options`	Both wildcards and fuzzy search have been specified as search options.

Changelog

Version 9.0

- Updated: error codes updated; errors now use the module namespace

Version 8.0

- Added: ft:contains, ft:normalize
- Updated: Options added to ft:tokenize

Version 7.8

- Added: ft:contains
- Updated: Options added to ft:search

Version 7.7

- Updated: the functions no longer accept Database Nodes as reference. Instead, the name of a database must now be specified.

Version 7.2

- Updated: ft:search (second argument generalized, third parameter added)

Version 7.1

- Added: ft:tokens, ft:tokenize

Chapter 46. Geo Module

Read this entry online in the BaseX Wiki.

This XQuery Module contains functions that may be applied to geometry data conforming to the Open Geospatial Consortium (OGC) Simple Feature (SF) data model. It is based on the EXPath Geo Module and uses the JTS library.

Geometries included in GML 2 are: Point, LineString, LinearRing, Polygon, MultiPoint, MultiLineString, MultiPolygon, and MultiGeometry. All nodes queried by BaseX should be a valid geometry. The only geometry type which is not supported by BaseX right now is MultiGeometry. Moreover, the module provides no support for GML 3.

Conventions

- This module is included in the complete distributions of BaseX (zip, exe, war).
- All functions are assigned to the `http://expath.org/ns/geo` namespace, which must be dynamically imported:

```
import module namespace geo = "http://expath.org/ns/geo";
...
```

- All errors are assigned to the `http://expath.org/ns/error` namespace, which is statically bound to the `experr` prefix.

General Functions

geo:dimension

Signatures	`geo:dimension($geometry as element(*)) as xs:integer`
Summary	Returns the dimension of the given geometry `$geometry`.
Errors	`GEO0001`: the given element is not recognized as a valid geometry.`GEO0002`: the given element cannot be read by reader for some reason.

Example	`import module namespace geo = "http://expath.org/ns/geo";`
	`declare namespace gml='http://www.opengis.net/gml';`
	`geo:dimension(<gml:Point><gml:coordinates>1,2</gml:coordinates></gml:Point>)`

geo:geometry-type

Signatures	`geo:geometry-type($geometry as element(*)) as xs:QName`
Summary	Returns the name of the geometry type of given geometry `$geometry`, if the geometry is not recognized with an error massage.
Errors	`GEO0001`: the given element is not recognized as a valid geometry.`GEO0002`: the given element cannot be read by reader for some reason.

Example	`import module namespace geo = "http://expath.org/ns/geo";`
	`declare namespace gml='http://www.opengis.net/gml';`
	`geo:geometry-type(<gml:Point><gml:coordinates>1,2</gml:coordinates></gml:Point>)`

geo:srid

Signatures	`geo:srid($geometry as element(*)) as xs:integer`

Summary	Returns the ID of the Spatial Reference System used by the given geometry `$geometry`. Spatial Reference System information is supported in the simple way defined in the SFS. A Spatial Reference System ID (SRID) is present in each Geometry object. Geometry provides basic accessor operations for this field, but no others. The SRID is represented as an integer (based on the OpenGIS Simple Features Specifications For SQL). Here is a difference between the EXPath Geo Module and the implementation in BaseX, since the specification return the URI.
Errors	`GEO0001`: the given element is not recognized as a valid geometry.`GEO0002`: the given element cannot be read by reader for some reason.
Examples	

```
import module namespace geo='http://expath.org/ns/geo';
declare namespace gml='http://www.opengis.net/gml';
geo:srid(
  <gml:Polygon>
    <outerboundaryIs>
      <gml:LinearRing>
        <coordinates>-150,50 -150,60 -125,60 -125,50 -150,50</
coordinates>
      </gml:LinearRing>
    </outerboundaryIs>
  </gml:Polygon>
)
```

geo:envelope

Signatures	`geo:envelope($geometry as element(*)) as element(*)`
Summary	Returns the gml:Envelope of the given geometry `$geometry`. The envelope is the minimum bounding box of this geometry. If this Geometry is the empty geometry, returns an empty Point. If the Geometry is a point, returns a non-empty Point. Otherwise, returns a Polygon whose points are (minx, miny), (maxx, miny), (maxx, maxy), (minx, maxy), (minx, miny).
Errors	`GEO0001`: the given element is not recognized as a valid geometry.`GEO0002`: the given element cannot be read by reader for some reason.`GEO0005`: the output object cannot be written as an element by writer for some reason.
Example	

```
import module namespace geo = "http://expath.org/ns/geo";
declare namespace gml='http://www.opengis.net/gml';
geo:envelope(
  <gml:LinearRing>
    <gml:coordinates>1,1 20,1 20,20 1,20 1,1</gml:coordinates>
  </gml:LinearRing>
)
```

geo:as-text

Signatures	`geo:as-text($geometry as element(*)) as xs:string`
Summary	Returns the WKT (Well-known Text) representation of the given geometry `$geometry`. The envelope is the minimum bounding box of this geometry
Errors	`GEO0001`: the given element is not recognized as a valid geometry.`GEO0002`: the given element cannot be read by reader for some reason.
Example	

```
import module namespace geo = "http://expath.org/ns/geo";
declare namespace gml='http://www.opengis.net/gml';
geo:as-text(<gml:Point><gml:coordinates>1,2</gml:coordinates></
gml:Point>)
```

geo:as-binary

Signatures	`geo:as-binary($geometry as element(*)) as xs:base64Binary`

Summary	Returns the WKB (Well-known Binary) representation of the given geometry `$geometry`.
Errors	`GEO0001`: the given element is not recognized as a valid geometry.`GEO0002`: the given element cannot be read by reader for some reason.

Example	`import module namespace geo = "http://expath.org/ns/geo";`
	`declare namespace gml='http://www.opengis.net/gml';`
	`geo:as-text(<gml:Point><gml:coordinates>1,2</gml:coordinates></gml:Point>)`

geo:is-simple

Signatures	`geo:is-simple($geometry as element(*)) as xs:boolean`
Summary	Returns whether the given geometry is simple `$geometry` and does not have has no anomalous geometric points (ie. the geometry does not self-intersect and does not pass through the same point more than once (may be a ring)).
Errors	`GEO0001`: the given element is not recognized as a valid geometry.`GEO0002`: the given element cannot be read by reader for some reason.

Example	`import module namespace geo = "http://expath.org/ns/geo";`
	`declare namespace gml='http://www.opengis.net/gml';`
	`geo:is-simple(`
	`  <gml:MultiLineString>`
	`  <gml:LineString><gml:coordinates>1,1 0,0 2,1</gml:coordinates></gml:LineString>`
	`  <gml:LineString><gml:coordinates>2,1 3,3 4,4</gml:coordinates></gml:LineString>`
	`  </gml:MultiLineString>`
	`)`

geo:boundary

Signatures	`geo:boundary($geometry as element(*)) as element(*)?`
Summary	Returns the boundary of the given geometry `$geometry`, in GML 2. The return value is a sequence of either gml:Point or gml:LinearRing elements as a GeometryCollection object. For a Point or MultiPoint, the boundary is the empty geometry, nothing is returned.
Errors	`GEO0001`: the given element is not recognized as a valid geometry.`GEO0002`: the given element cannot be read by reader for some reason.`GEO0005`: the output object cannot be written as an element by writer for some reason.

Example	`import module namespace geo = "http://expath.org/ns/geo";`
	`declare namespace gml='http://www.opengis.net/gml';`
	`geo:boundary(`
	`  <gml:LineString>`
	`  <gml:coordinates>1,1 0,0 2,1</gml:coordinates>`
	`  </gml:LineString>`
	`)`

geo:num-geometries

Signatures	`geo:num-geometries($geometry as element(*)) as xs:integer`
Summary	Returns the number of geometry in a geometry-collection `$geometry`, in GML. For the geometries which are not a collection, it returns the instant value 1. This function is implemented wider than the specification and accepts all types of geometries, while the specification limits it to the collection types (MultiPoint, MultiPolygon, ...).
Errors	`GEO0001`: the given element(s) is not recognized as a valid geometry (QName).`GEO0002`: the given element cannot be read by reader for some reason.

Example	

```
import module namespace geo = "http://expath.org/ns/geo";
declare namespace gml='http://www.opengis.net/gml';
geo:num-geometries(
  <gml:MultiLineString>
    <gml:LineString><gml:coordinates>1,1 0,0 2,1</gml:coordinates></
gml:LineString>
    <gml:LineString><gml:coordinates>2,1 3,3 4,4</gml:coordinates></
gml:LineString>
  </gml:MultiLineString>
)
```

geo:geometry-n

Signatures	`geo:geometry-n($geometry as element(*), $geoNumber as xs:integer) as element(*)`
Summary	Returns the Nth geometry in geometry-collection `$geometry`, in GML. For the geometries which are not a collection, it returns the geometry if geoNumber `$geoNumber` is 1. This function is implemented wider than the specification and accepts all types of geometries, while the specification limits it to the collection types (MultiPoint, MultiPolygon, ...).
Errors	`GEO0001`: the given element(s) is not recognized as a valid geometry (QName).`GEO0002`: the given element cannot be read by reader for some reason.`GEO0004`: the the input index of geometry is out of range.`GEO0005`: the output object cannot be written as an element by writer for some reason.
Example	

```
import module namespace geo = "http://expath.org/ns/geo";
declare namespace gml='http://www.opengis.net/gml';
let $line :=
  <gml:MultiLineString>
    <gml:LineString><gml:coordinates>1,1 0,0 2,1</gml:coordinates></
gml:LineString>
    <gml:LineString><gml:coordinates>2,1 3,3 4,4</gml:coordinates></
gml:LineString>
  </gml:MultiLineString>
return geo:geometry-n($line, 1)
```

geo:length

Signatures	`geo:length($geometry as element(*)) as xs:double`
Summary	Returns the length of the geometry `$geometry`. If the geometry is a point, zero value will be returned.
Errors	`GEO0001`: the given element(s) is not recognized as a valid geometry (QName).`GEO0002`: the given element cannot be read by reader for some reason.
Example	

```
import module namespace geo = "http://expath.org/ns/geo";
declare namespace gml='http://www.opengis.net/gml';
let $polygon :=
  <gml:Polygon>
    <gml:outerBoundaryIs>
      <gml:LinearRing>
        <gml:coordinates>1,1 2,1 2,2 1,2 1,1</gml:coordinates>
      </gml:LinearRing>
    </gml:outerBoundaryIs>
  </gml:Polygon>
return geo:length($polygon)
```

geo:num-points

Signatures	`geo:num-points($geometry as element(*)) as xs:integer`

Summary	Returns integer value of number of the points in the given geometry`$geometry`. It can be used not only for Lines, also any other geometry types, like MultiPolygon. For Point geometry it will return 1. This is an implementation different from the EXPath geo specification, as it limits the input geometry type only to lines.
Errors	`GEO0001`: the given element(s) is not recognized as a valid geometry (QName).`GEO0002`: the given element cannot be read by reader for some reason.

Example	`import module namespace geo = "http://expath.org/ns/geo";`
	`declare namespace gml='http://www.opengis.net/gml';`
	`geo:num-points(`
	`  <gml:LineString><gml:coordinates>2,1 3,3 4,4</gml:coordinates></`
	`gml:LineString>`
	`)`

geo:area

Signatures	`geo:area($geometry as element(*)) as xs:double`
Summary	Returns the area of the given geometry `$geometry`. For points and line the return value will be zero.
Errors	`GEO0001`: the given element(s) is not recognized as a valid geometry (QName).`GEO0002`: the given element cannot be read by reader for some reason.

Example	`import module namespace geo = "http://expath.org/ns/geo";`
	`declare namespace gml='http://www.opengis.net/gml';`
	`let $polygon :=`
	`  <gml:Polygon>`
	`  <gml:outerBoundaryIs>`
	`  <gml:LinearRing>`
	`  <gml:coordinates>1,1 2,1 2,2 1,2 1,1</gml:coordinates>`
	`  </gml:LinearRing>`
	`  </gml:outerBoundaryIs>`
	`  </gml:Polygon>`
	`return geo:area($polygon)`

geo:centroid

Signatures	`geo:centroid($geometry as element(*)) as element(*)`
Summary	Returns the mathematical centroid of the given geometry `$geometry`, as a gml:Point. Based on the definition, this point is not always on the surface of the geometry `$geometry`.
Errors	`GEO0001`: the given element(s) is not recognized as a valid geometry (QName).`GEO0002`: the given element cannot be read by reader for some reason.`GEO0005`: the output object cannot be written as an element by writer for some reason.

Example	`import module namespace geo = "http://expath.org/ns/geo";`
	`declare namespace gml='http://www.opengis.net/gml';`
	`let $point :=`
	`  <gml:MultiPoint>`
	`  <gml:Point><gml:coordinates>1,1</gml:coordinates></gml:Point>`
	`  <gml:Point><gml:coordinates>10,10</gml:coordinates></gml:Point>`
	`  <gml:Point><gml:coordinates>2,2</gml:coordinates></gml:Point>`
	`  </gml:MultiPoint>`
	`return geo:centroid($point)`

geo:point-on-surface

Signatures	`geo:point-on-surface($geometry as element(*)) as element(*)`

Summary	Returns an interior point on the given geometry `$geometry`, as a gml:Point. It is guaranteed to be on surface. Otherwise, the point may lie on the boundary of the geometry.
Errors	`GEO0001`: the given element(s) is not recognized as a valid geometry (QName).`GEO0002`: the given element cannot be read by reader for some reason.`GEO0005`: the output object cannot be written as an element by writer for some reason.
Example	

```
import module namespace geo = "http://expath.org/ns/geo";
declare namespace gml='http://www.opengis.net/gml';
geo:point-on-surface(
  <gml:Polygon>
    <gml:outerBoundaryIs>
      <gml:LinearRing>
        <gml:coordinates>1,1 2,1 2,2 1,2 1,1</gml:coordinates>
      </gml:LinearRing>
    </gml:outerBoundaryIs>
  </gml:Polygon>
)
```

Spatial Predicate Functions

geo:equals

Signatures	`geo:equals($geometry1 as element(*), $geometry2 as element(*)) as xs:boolean`
Summary	Returns whether geometry1 `$geometry1` is spatially equal to $geometry2 `$geometry2`.
Errors	`GEO0001`: the given element(s) is not recognized as a valid geometry (QName).`GEO0002`: the given element cannot be read by reader for some reason.
Example	

```
import module namespace geo = "http://expath.org/ns/geo";
declare namespace gml='http://www.opengis.net/gml';
geo:equals(
  <gml:LineString><gml:coordinates>1,1 55,99 2,1</gml:coordinates></
gml:LineString>,
  <gml:LineString><gml:coordinates>1,1 1,1 55,99 2,1</gml:coordinates></
gml:LineString>
)
```

geo:disjoint

Signatures	`geo:disjoint($geometry1 as element(*), $geometry2 as element(*)) as xs:boolean`
Summary	Returns whether geometry1 `$geometry1` is spatially disjoint from $geometry2 `$geometry2` (they have no point in common, they do not intersect each other, and the DE-9IM Intersection Matrix for the two geometries is FF*FF****).
Errors	`GEO0001`: the given element(s) is not recognized as a valid geometry (QName).`GEO0002`: the given element cannot be read by reader for some reason.
Example	

```
import module namespace geo = "http://expath.org/ns/geo";
declare namespace gml='http://www.opengis.net/gml';
let $lines :=
  <gml:MultiLineString>
    <gml:LineString><gml:coordinates>1,1 0,0 2,1</gml:coordinates></
gml:LineString>
    <gml:LineString><gml:coordinates>2,1 3,3 4,4</gml:coordinates></
gml:LineString>
  </gml:MultiLineString>
let $line :=
```

```
  <gml:LineString><gml:coordinates>0,0 2,1 3,3</gml:coordinates></
gml:LineString>
return geo:disjoint($lines, $line)
```

geo:intersects

Signatures	`geo:intersects($geometry1 as element(*), $geometry2 as element(*)) as xs:boolean`
Summary	Returns whether geometry1 `$geometry1` is spatially intersects $geometry2 `$geometry2`. This is true if disjoint function of the two geometries returns false.
Errors	`GEO0001`: the given element(s) is not recognized as a valid geometry (QName).`GEO0002`: the given element cannot be read by reader for some reason.
Example	

```
import module namespace geo = "http://expath.org/ns/geo";
declare namespace gml='http://www.opengis.net/gml';
let $lines :=
  <gml:MultiLineString>
    <gml:LineString><gml:coordinates>1,1 0,0 2,1</gml:coordinates></
gml:LineString>
    <gml:LineString><gml:coordinates>2,1 3,3 4,4</gml:coordinates></
gml:LineString>
  </gml:MultiLineString>
let $line :=
  <gml:LineString><gml:coordinates>0,0 2,1 3,3</gml:coordinates></
gml:LineString>
return geo:intersects($lines, $line)
```

geo:touches

Signatures	`geo:touches($geometry1 as element(*), $geometry2 as element(*)) as xs:boolean`
Summary	Returns whether geometry1 `$geometry1` is spatially touches $geometry2 `$geometry2`.
Errors	`GEO0001`: the given element(s) is not recognized as a valid geometry (QName).`GEO0002`: the given element cannot be read by reader for some reason.
Example	

```
import module namespace geo = "http://expath.org/ns/geo";
declare namespace gml='http://www.opengis.net/gml';
let $line :=
  <gml:LinearRing><gml:coordinates>1,1 2,1 5,3 1,1</gml:coordinates></
gml:LinearRing>
let $polygon :=
  <gml:Polygon>
    <gml:outerBoundaryIs>
      <gml:LinearRing><gml:coordinates>1,1 2,1 5,3 1,1</
gml:coordinates></gml:LinearRing>
    </gml:outerBoundaryIs>
  </gml:Polygon>
return geo:touches($line, $polygon)
```

geo:crosses

Signatures	`geo:crosses($geometry1 as element(*), $geometry2 as element(*)) as xs:boolean`
Summary	Returns whether geometry1 `$geometry1` is spatially crosses $geometry2 `$geometry2`. It means, if the geometries have some but not all interior points in common. Returns true if the DE-9IM intersection matrix for the two geometries is: `T*T******` (for P/L, P/A, and L/A situations) `T*****T**` (for L/P, A/P, and A/L situations) `0********` (for L/L situations).

Errors	`GEO0001`: the given element(s) is not recognized as a valid geometry (QName).`GEO0002`: the given element cannot be read by reader for some reason.
Example	

```
import module namespace geo = "http://expath.org/ns/geo";
declare namespace gml='http://www.opengis.net/gml';
let $line :=
  <gml:LinearRing><gml:coordinates>1,1 2,1 5,3 1,1</gml:coordinates></
gml:LinearRing>
let $polygon :=
  <gml:Polygon>
    <gml:outerBoundaryIs>
      <gml:LinearRing><gml:coordinates>1,1 2,1 5,3 1,1</
gml:coordinates></gml:LinearRing>
    </gml:outerBoundaryIs>
  </gml:Polygon>
return geo:crosses($line, $polygon)
```

geo:within

Signatures	`geo:within($geometry1 as element(*), $geometry2 as element(*)) as xs:boolean`
Summary	Returns whether geometry1 `$geometry1` is spatially within $geometry2 `$geometry2`.
Errors	`GEO0001`: the given element(s) is not recognized as a valid geometry (QName).`GEO0002`: the given element cannot be read by reader for some reason.
Example	

```
import module namespace geo = "http://expath.org/ns/geo";
declare namespace gml='http://www.opengis.net/gml';
let $line :=
  <gml:LinearRing><gml:coordinates>1,1 2,1 5,3 1,1</gml:coordinates></
gml:LinearRing>
let $polygon :=
  <gml:Polygon>
    <gml:outerBoundaryIs>
      <gml:LinearRing><gml:coordinates>1,1 2,1 5,3 1,1</
gml:coordinates></gml:LinearRing>
    </gml:outerBoundaryIs>
  </gml:Polygon>
return geo:within($line, $polygon)
```

geo:contains

Signatures	`geo:contains($geometry1 as element(*), $geometry2 as element(*)) as xs:boolean`
Summary	Returns whether geometry1 `$geometry1` spatially contains $geometry2 `$geometry2`. Returns true if within function of these two geometries also returns true.
Errors	`GEO0001`: the given element(s) is not recognized as a valid geometry (QName).`GEO0002`: the given element cannot be read by reader for some reason.
Example	

```
import module namespace geo = "http://expath.org/ns/geo";
declare namespace gml='http://www.opengis.net/gml';
let $point :=
  <gml:Point><gml:coordinates>1,1</gml:coordinates></gml:Point>
let $polygon :=
  <gml:Polygon>
    <gml:outerBoundaryIs>
      <gml:LinearRing><gml:coordinates>1,1 2,1 5,3 1,1</
gml:coordinates></gml:LinearRing>
    </gml:outerBoundaryIs>
  </gml:Polygon>
```

```
return geo:contains($polygon, $point)
```

geo:overlaps

Signatures	`geo:overlaps($geometry1 as element(*), $geometry2 as element(*)) as xs:boolean`
Summary	Returns whether geometry1 `$geometry1` is spatially overlaps $geometry2 `$geometry2`.
Errors	`GEO0001`: the given element(s) is not recognized as a valid geometry (QName).`GEO0002`: the given element cannot be read by reader for some reason.
Example	

```
import module namespace geo = "http://expath.org/ns/geo";
declare namespace gml='http://www.opengis.net/gml';
let $polygon1 :=
  <gml:Polygon>
    <gml:outerBoundaryIs>
      <gml:LinearRing>
        <gml:coordinates>1,1 20,1 20,20 30,20 30,30 1,30 1,1</
gml:coordinates>
      </gml:LinearRing>
    </gml:outerBoundaryIs>
    <gml:innerBoundaryIs>
      <gml:LinearRing>
        <gml:coordinates>2,2 3,2 3,3 2,3 2,2</gml:coordinates>
      </gml:LinearRing>
    </gml:innerBoundaryIs>
    <gml:innerBoundaryIs>
      <gml:LinearRing>
        <gml:coordinates>10,10 19,10 19,19 10,19 10,10</gml:coordinates>
      </gml:LinearRing>
    </gml:innerBoundaryIs>
  </gml:Polygon>
let $polygon2 :=
  <gml:Polygon>
    <gml:outerBoundaryIs>
      <gml:LinearRing>
        <gml:coordinates>1,1 2,1 5,3 1,1</gml:coordinates>
      </gml:LinearRing>
    </gml:outerBoundaryIs>
  </gml:Polygon>
return geo:overlaps($polygon1, $polygon2)
```

geo:relate

Signatures	`geo:relate($geometry1 as element(*), $geometry2 as element(*), $intersectionMatrix as xs:string) as xs:boolean`
Summary	Returns whether relationships between the boundaries, interiors and exteriors of geometry1 `$geometry1` and geometry2 `$geometry2` match the pattern specified in intersectionMatrix `$geometry2`, which should have the length of 9 charachters.The values in the DE-9IM can be T, F, *, 0, 1, 2 . - T means the intersection gives a non-empty result. - F means the intersection gives an empty result. - * means any result. - 0, 1, 2 gives the expected dimension of the result (point, curve, surface)
Errors	`GEO0001`: the given element(s) is not recognized as a valid geometry (QName).`GEO0002`: the given element cannot be read by reader for some reason.`GEO0006`: the given matrix is invalid.
Example	

```
import module namespace geo = "http://expath.org/ns/geo";
declare namespace gml='http://www.opengis.net/gml';
let $point :=
  <gml:Point><gml:coordinates>18,11</gml:coordinates></gml:Point>
let $polygon :=
```

```
  <gml:Polygon>
    <gml:outerBoundaryIs>
      <gml:LinearRing>
        <gml:coordinates>10,10 20,10 30,40 20,40 10,10</gml:coordinates>
      </gml:LinearRing>
    </gml:outerBoundaryIs>
  </gml:Polygon>
return geo:relate($point, $polygon)
```

Analysis Functions

geo:distance

Signatures	`geo:distance($geometry1 as element(*), $geometry2 as element(*)) as xs:double`
Summary	Returns the shortest distance, in the units of the spatial reference system of geometry1 `$geometry1`, between the geometries, where that distance is the distance between a point on each of the geometries.
Errors	`GEO0001`: the given element(s) is not recognized as a valid geometry (QName).`GEO0002`: the given element cannot be read by reader for some reason.
Example	

```
import module namespace geo = "http://expath.org/ns/geo";
declare namespace gml='http://www.opengis.net/gml';
let $line :=
  <gml:LinearRing>
    <gml:coordinates>10,400 20,200 30,100 20,100 10,400</
gml:coordinates>
  </gml:LinearRing>
let $polygon :=
  <gml:Polygon>
    <gml:outerBoundaryIs>
      <gml:LinearRing>
        <gml:coordinates>10,10 20,10 30,40 20,40 10,10</gml:coordinates>
      </gml:LinearRing>
    </gml:outerBoundaryIs>
  </gml:Polygon>
return geo:distance($line, $polygon)
```

geo:buffer

Signatures	`geo:buffer($geometry as element(*), $distance as xs:double) as element(*)`
Summary	Returns polygonal geometry representing the buffer by distance `$distance` of geometry `$geometry` a buffer area around this geometry having the given width, in the spatial reference system of geometry. The buffer of a Geometry is the Minkowski sum or difference of the geometry with a disc of radius abs(distance). The buffer is constructed using 8 segments per quadrant to represent curves.
Errors	`GEO0001`: the given element(s) is not recognized as a valid geometry (QName).`GEO0002`: the given element cannot be read by reader for some reason.`GEO0005`: the output object cannot be written as an element by writer for some reason.
Example	

```
import module namespace geo = "http://expath.org/ns/geo";
declare namespace gml='http://www.opengis.net/gml';
let $polygon :=
  <gml:Polygon>
    <gml:outerBoundaryIs>
      <gml:LinearRing>
        <gml:coordinates>10,10 20,10 30,40 20,40 10,10</gml:coordinates>
```

```
      </gml:LinearRing>
    </gml:outerBoundaryIs>
  </gml:Polygon>
return geo:buffer($polygon, 3)
```

geo:convex-hull

Signatures	`geo:convex-hull($geometry as element(*)) as element(*)`
Summary	Returns the convex hull geometry of the given geometry `$geometry` in GML, or the empty sequence. Actually returns the object of smallest dimension possible.
Errors	`GEO0001`: the given element(s) is not recognized as a valid geometry (QName).`GEO0002`: the given element cannot be read by reader for some reason.`GEO0005`: the output object cannot be written as an element by writer for some reason.

Example	`import module namespace geo = "http://expath.org/ns/geo";`
	`declare namespace gml='http://www.opengis.net/gml';`
	`geo:convex-hull(`
	`  <gml:LinearRing>`
	`  <gml:coordinates>10,400 20,200 30,100 20,100 10,400</`
	`gml:coordinates>`
	`  </gml:LinearRing>`
	`)`

geo:intersection

Signatures	`geo:intersection($geometry1 as element(*), $geometry2 as element(*)) as element(*)?`
Summary	Returns the intersection geometry of geometry1 `$geometry1` with geometry2 `$geometry2`, in GML or empty sequence if there is no intersection of these geometries.
Errors	`GEO0001`: the given element(s) is not recognized as a valid geometry (QName).`GEO0002`: the given element cannot be read by reader for some reason.`GEO0005`: the output object cannot be written as an element by writer for some reason.

Example	`import module namespace geo = "http://expath.org/ns/geo";`
	`declare namespace gml='http://www.opengis.net/gml';`
	`let $line :=`
	`  <gml:LinearRing>`
	`  <gml:coordinates>10,400 20,200 30,100 20,100 10,400</`
	`gml:coordinates>`
	`  </gml:LinearRing>`
	`let $point :=`
	`  <gml:Point><gml:coordinates>1.00,1.00</gml:coordinates></gml:Point>`
	`return geo:intersection($line, $point)`

geo:union

Signatures	`geo:union($geometry1 as element(*), $geometry2 as element(*)) as element(*)`
Summary	Returns the union geometry of geometry1 `$geometry1` with geometry2 `$geometry2`, in GML.
Errors	`GEO0001`: the given element(s) is not recognized as a valid geometry (QName).`GEO0002`: the given element cannot be read by reader for some reason.`GEO0005`: the output object cannot be written as an element by writer for some reason.

Example	`import module namespace geo = "http://expath.org/ns/geo";`
	`declare namespace gml='http://www.opengis.net/gml';`
	`let $line :=`
	`  <gml:LinearRing>`

```
    <gml:coordinates>10,400 20,200 30,100 20,100 10,400</
gml:coordinates>
  </gml:LinearRing>
let $point :=
  <gml:Point><gml:coordinates>1.00,1.00</gml:coordinates></gml:Point>
return geo:union($line, $point)
```

geo:difference

Signatures	`geo:difference($geometry1 as element(*), $geometry2 as element(*)) as element(*)?`
Summary	Returns the difference geometry of geometry1 `$geometry1` with geometry2 `$geometry2`, in GML, or empty sequence if the difference is empty, as a set of point in geometry1 `$geometry1` and not included in geometry2 `$geometry2`.
Errors	`GEO0001`: the given element(s) is not recognized as a valid geometry (QName).`GEO0002`: the given element cannot be read by reader for some reason.`GEO0005`: the output object cannot be written as an element by writer for some reason.
Example	

```
import module namespace geo = "http://expath.org/ns/geo";
declare namespace gml='http://www.opengis.net/gml';
let $point :=
  <gml:Point><gml:coordinates>1.00,1.00</gml:coordinates></gml:Point>
let $line :=
  <gml:LineString><gml:coordinates>2,1 3,3 4,4</gml:coordinates></
gml:LineString>
return geo:difference($point, $line)
```

geo:sym-difference

Signatures	`geo:sym-difference($geometry1 as element(*), $geometry2 as element(*)) as element(*)?`
Summary	Returns the symmetric difference geometry of geometry1 `$geometry1` with geometry2 `$geometry2`, in GML, or empty sequence if the difference is empty, as a set of point in one of the geometries and not included in the other.
Errors	`GEO0001`: the given element(s) is not recognized as a valid geometry (QName).`GEO0002`: the given element cannot be read by reader for some reason.`GEO0005`: the output object cannot be written as an element by writer for some reason.
Example	

```
import module namespace geo = "http://expath.org/ns/geo";
declare namespace gml='http://www.opengis.net/gml';
let $point :=
  <gml:Point><gml:coordinates>1.00,1.00</gml:coordinates></gml:Point>
let $line :=
  <gml:LineString><gml:coordinates>2,1 3,3 4,4</gml:coordinates></
gml:LineString>
return geo:sym-difference($point, $line)
```

Functions Specific to Geometry Type

geo:x

Signatures	`geo:x($point as element(*)) as xs:double`
Summary	Returns the x coordinate of point `$point`. A point has to have an x coordinate.
Errors	`GEO0001`: the given element(s) is not recognized as a valid geometry (QName).`GEO0002`: the given element cannot be read by reader for some reason.
Example	

```
import module namespace geo = "http://expath.org/ns/geo";
declare namespace gml='http://www.opengis.net/gml';
geo:x(<gml:Point><gml:coordinates>1.00,1.00</gml:coordinates></
gml:Point>)
```

geo:y

Signatures	`geo:y($point as element(*)) as xs:double?`
Summary	Returns the y coordinate of point `$point`. If the point does not have the y coordinate, 0 will be returned.
Errors	`GEO0001`: the given element(s) is not recognized as a valid geometry (QName).`GEO0002`: the given element cannot be read by reader for some reason.

Example	`import module namespace geo = "http://expath.org/ns/geo";`
	`declare namespace gml='http://www.opengis.net/gml';`
	`geo:y(<gml:Point><gml:coordinates>1.00,2.00</gml:coordinates></`
	`gml:Point>)`

geo:z

Signatures	`geo:z($point as element(*)) as xs:double?`
Summary	Returns the z coordinate of point `$point`. If the point does not have the y coordinate, 0 will be returned.
Errors	`GEO0001`: the given element(s) is not recognized as a valid geometry (QName).`GEO0002`: the given element cannot be read by reader for some reason.

Example	`import module namespace geo = "http://expath.org/ns/geo";`
	`declare namespace gml='http://www.opengis.net/gml';`
	`geo:z(<gml:Point><gml:coordinates>1.00,1.00,3.00</gml:coordinates></`
	`gml:Point>)`

geo:start-point

Signatures	`geo:start-point($line as element(*)) as element(*)`
Summary	Returns the starting point of the given line `$line`. `$line` has to be a single line, LineString or LinearRing.
Errors	`GEO0001`: the given element(s) is not recognized as a valid geometry (QName).`GEO0002`: the given element cannot be read by reader for some reason.`GEO0003`: the given element has to be a line. Other geometries are not accepted.

Example	`import module namespace geo = "http://expath.org/ns/geo";`
	`declare namespace gml='http://www.opengis.net/gml';`
	`geo:start-point(`
	`  <gml:LineString><gml:coordinates>2,1 3,3 4,4</gml:coordinates></`
	`gml:LineString>`
	`)`

geo:end-point

Signatures	`geo:end-point($line as element(*)) as element(*)`
Summary	Returns the ending point of the given line `$line`. `$line` has to be a single line, LineString or LinearRing.
Errors	`GEO0001`: the given element(s) is not recognized as a valid geometry (QName).`GEO0002`: the given element cannot be read by reader for some reason.`GEO0003`: the given element has to be a line. Other geometries are not accepted.

Example	`import module namespace geo = "http://expath.org/ns/geo";`
	`declare namespace gml='http://www.opengis.net/gml';`
	`geo:end-point(`
	`  <gml:LineString><gml:coordinates>2,1 3,3 4,4</gml:coordinates></`
	`gml:LineString>`
	`)`

geo:is-closed

Signatures	`geo:is-closed($line as element(*)) as xs:boolean`
Summary	Returns a boolean value that shows the line `$line` is a closed loop (start point and end point are the same) or not. `$line` has to be a line, as a geometry, LineString or LinearRing, and MultiLineString.
Errors	`GEO0001`: the given element(s) is not recognized as a valid geometry (QName).`GEO0002`: the given element cannot be read by reader for some reason.`GEO0003`: the given element has to be a line. Other geometries are not accepted.

Example	`import module namespace geo = "http://expath.org/ns/geo";`
	`declare namespace gml='http://www.opengis.net/gml';`
	`geo:is-closed(`
	`  <gml:LineString>`
	`  <gml:coordinates>2,1 3,3 4,4</gml:coordinates>`
	`  </gml:LineString>`
	`)`

geo:is-ring

Signatures	`geo:is-ring($line as element(*)) as xs:boolean`
Summary	Returns a boolean value that shows the line `$line` is a ring (closed loop and single) or not. `$line` has to be a single line, as a geometry, LineString or LinearRing.
Errors	`GEO0001`: the given element(s) is not recognized as a valid geometry (QName).`GEO0002`: the given element cannot be read by reader for some reason.`GEO0003`: the given element has to be a line. Other geometries are not accepted.

Example	`import module namespace geo = "http://expath.org/ns/geo";`
	`declare namespace gml='http://www.opengis.net/gml';`
	`geo:is-ring(`
	`  <gml:LineString>`
	`  <gml:coordinates>2,1 3,3 4,4</gml:coordinates>`
	`  </gml:LineString>`
	`)`

geo:point-n

Signatures	`geo:point-n($line as element(*)) as element(*)`
Summary	Returns the Nth point in the given line `$geometry`. `$line` has to be a single line, as a geometry, LineString or LinearRing.
Errors	`GEO0001`: the given element(s) is not recognized as a valid geometry (QName).`GEO0002`: the given element cannot be read by reader for some reason.`GEO0003`: the given element has to be a line. Other geometries are not accepted.`GEO0004`: the the input index of geometry is out of range.`GEO0005`: the output object cannot be written as an element by writer for some reason.

Example	`import module namespace geo = "http://expath.org/ns/geo";`
	`declare namespace gml='http://www.opengis.net/gml';`
	`let $line :=`
	`  <gml:LineString>`

```
    <gml:coordinates>2,1 3,3 4,4</gml:coordinates>
  </gml:LineString>
return geo:point-n($line, 1)
```

geo:exterior-ring

Signatures	`geo:exterior-ring($polygon as element(*)) as element(*)`
Summary	Returns the outer ring of the given polygon `$geometry`, as a gml:LineString.
Errors	`GEO0001`: the given element(s) is not recognized as a valid geometry (QName).`GEO0002`: the given element cannot be read by reader for some reason.`GEO0003`: the given element has to be a polygon. Other geometries are not accepted.`GEO0005`: the output object cannot be written as an element by writer for some reason.
Example	

```
import module namespace geo = "http://expath.org/ns/geo";
declare namespace gml='http://www.opengis.net/gml';
let $polygon :=
  <gml:Polygon>
    <gml:outerBoundaryIs>
      <gml:LinearRing>
        <gml:coordinates>10,10 20,10 30,40 20,40 10,10</gml:coordinates>
      </gml:LinearRing>
    </gml:outerBoundaryIs>
  </gml:Polygon>
return geo:exterior-ring($polygon)
```

geo:num-interior-ring

Signatures	`geo:num-interior-ring($polygon as element(*)) as xs:integer`
Summary	Returns the number of interior rings in the given polygon `$geometry`.
Errors	`GEO0001`: the given element(s) is not recognized as a valid geometry (QName).`GEO0002`: the given element cannot be read by reader for some reason.`GEO0003`: the given element has to be a polygon. Other geometries are not accepted.
Example	

```
import module namespace geo = "http://expath.org/ns/geo";
declare namespace gml='http://www.opengis.net/gml';
geo:num-interior-ring(
  <gml:Polygon>
    <gml:outerBoundaryIs>
      <gml:LinearRing>
        <gml:coordinates>1,1 20,1 20,20 30,20 30,30 1,30 1,1</
gml:coordinates>
      </gml:LinearRing>
    </gml:outerBoundaryIs>
    <gml:innerBoundaryIs>
      <gml:LinearRing>
        <gml:coordinates>2,2 3,2 3,3 2,3 2,2</gml:coordinates>
      </gml:LinearRing>
    </gml:innerBoundaryIs>
    <gml:innerBoundaryIs>
      <gml:LinearRing>
        <gml:coordinates>10,10 19,10 19,19 10,19 10,10</gml:coordinates>
      </gml:LinearRing>
    </gml:innerBoundaryIs>
  </gml:Polygon>
)
```

geo:interior-ring-n

Signatures	`geo:interior-ring-n($polygon as element(*)) as element(*)`

Summary	Returns the outer ring of the given polygon `$geometry`, as a gml:LineString.
Errors	`GEO0001`: the given element(s) is not recognized as a valid geometry (QName).`GEO0002`: the given element cannot be read by reader for some reason.`GEO0003`: the given element has to be a polygon. Other geometries are not accepted.`GEO0004`: the the input index of geometry is out of range.`GEO0005`: the output object cannot be written as an element by writer for some reason.
Example	

```
import module namespace geo = "http://expath.org/ns/geo";
declare namespace gml='http://www.opengis.net/gml';
let $polygon :=
  <gml:Polygon>
    <gml:outerBoundaryIs>
       <gml:LinearRing>
         <gml:coordinates>1,1 20,1 20,20 30,20 30,30 1,30 1,1</
gml:coordinates>
       </gml:LinearRing>
    </gml:outerBoundaryIs>
    <gml:innerBoundaryIs>
       <gml:LinearRing>
         <gml:coordinates>2,2 3,2 3,3 2,3 2,2</gml:coordinates>
       </gml:LinearRing>
    </gml:innerBoundaryIs>
    <gml:innerBoundaryIs>
       <gml:LinearRing>
         <gml:coordinates>10,10 19,10 19,19 10,19 10,10</
gml:coordinates>
       </gml:LinearRing>
    </gml:innerBoundaryIs>
  </gml:Polygon>
return geo:interior-ring-n($polygon, 1)
```

Errors

Code	Description
`GEO0001`	Unrecognized Geo type.
`GEO0002`	The input GML node cannot be read by GMLreader.
`GEO0003`	Input geometry is not an appropriate geometry for this function.
`GEO0004`	The input index is out of range.
`GEO0005`	The result geometry can not be written by GMLwriter.
`GEO0006`	The input matrix is invalid.

Changelog

The module was introduced with Version 7.6.

Chapter 47. Hashing Module

Read this entry online in the BaseX Wiki.

This XQuery Module provides functions that perform different hash operations.

Conventions

Updated with Version 9.0:

All functions and errors in this module are assigned to the `http://basex.org/modules/hash` namespace, which is statically bound to the `hash` prefix.

Functions

hash:md5

Signatures	`hash:md5($value as xs:anyAtomicType) as xs:base64Binary`
Summary	Computes the MD5 hash of the given `$value`, which may be of type xs:string, xs:base64Binary, or xs:hexBinary.
Examples	• `string(xs:hexBinary(hash:md5("BaseX")))` returns `0D65185C9E296311C0A2200179E479A2`. • `string(hash:md5(xs:base64Binary("")))` returns `1B2M2Y8AsgTpgAmY7PhCfg==`.

hash:sha1

Signatures	`hash:sha1($value as xs:anyAtomicType) as xs:base64Binary`
Summary	Computes the SHA-1 hash of the given `$value`, which may be of type xs:string, xs:base64Binary, or xs:hexBinary.
Examples	• `string(xs:hexBinary(hash:sha1("BaseX")))` returns `3AD5958F0F27D5AFFDCA2957560F121D0597A4ED`. • `string(hash:sha1(xs:base64Binary("")))` returns `2jmj7l5rSw0yVb/vlWAYkK/YBwk=`.

hash:sha256

Signatures	`hash:sha256($value as xs:anyAtomicType) as xs:base64Binary`
Summary	Computes the SHA-256 hash of the given `$value`, which may be of type xs:string, xs:base64Binary, or xs:hexBinary.
Examples	• `string(xs:hexBinary(hash:sha256("BaseX")))` returns `15D570763DEB75D728BB69643392873B835CCCC94A2F1E881909DA47662821A3`. • `string(hash:sha256(xs:base64Binary("")))` returns `47DEQpj8HBSa+/TImW+5JCeuQeRkm5NMpJWZG3hSuFU=`.

hash:hash

Signatures	`hash:hash($value as xs:anyAtomicType, $algorithm as xs:string) as xs:base64Binary`

Summary	Computes the hash of the given `$value`, using the specified `$algorithm`. The specified values may be of type xs:string, xs:base64Binary, or xs:hexBinary.The following three algorihms are supported: `MD5`, `SHA-1`, and `SHA-256`.
Errors	`algorithm`: the specified hashing algorithm is unknown.
Examples	• `string(xs:hexBinary(hash:hash("", "MD5")))` returns `D41D8CD98F00B204E9800998ECF8427E`. • `string(hash:hash("", ""))` raises an error, because no algorithm was specified.

Errors

Updated with Version 9.0:

Code	Description
`algorithm`	The specified hash algorithm is unknown.

Changelog

Version 9.0

- Updated: error codes updated; errors now use the module namespace

The module was introduced with Version 7.3.

Chapter 48. Higher-Order Functions Module

Read this entry online in the BaseX Wiki.

This XQuery Module adds some useful higher-order functions, additional to the Higher-Order Functions provided by the official specification.

Conventions

All functions in this module are assigned to the `http://basex.org/modules/hof` namespace, which is statically bound to the `hof` prefix.

Loops

hof:fold-left1

Signatures	`hof:fold-left1($seq as item()+, $f as function(item()*, item()) as item()*) as item()*`
Summary	Works the same as fn:fold-left, but does not need a seed, because the sequence must be non-empty.
Examples	• `hof:fold-left1(1 to 10, function($a, $b) { $a + $b })` returns `55`. • `hof:fold-left1((), function($a, $b) { $a + $b })` throws `XPTY0004`, because `$seq` has to be non-empty.

hof:until

Signatures	`hof:until($pred as function(item()*) as xs:boolean, $f as function(item()*) as item()*, $start as item()*) as item()*`
Summary	Applies the predicate function `$pred` to `$start`. If the result is `false`, `$f` is invoked with the start value – or, subsequently, with the result of this function – until the predicate function returns `true()`.
Examples	• Doubles a numeric value until a maximum is reached: • Calculates the square-root of a number by iteratively improving an initial guess: • Returns `OK`, as the predicate is evaluated first:

```
hof:until(
  function($output) { $output ge 1000 },
  function($input ) { 2 * $input },
  1
)
```

```
let $sqrt := function($input as xs:double) as xs:double {
  hof:until(
    function($result) { abs($result * $result - $input) < 0.00001 },
    function($guess) { ($guess + $input div $guess) div 2 },
    $input
  )
}
return $sqrt(25)
```

```
hof:until(
  function($_) { true() },
  function($_) { error() },
  'OK'
)
```

hof:scan-left

Signatures	`hof:scan-left($seq as item()*, $start as item()*, $f as function(item()*, item()) as item()*) as item()*`

Summary	This function is similar to fn:fold-left, but it returns a list of successive reduced values from the left. It is equivalent to:
	
	`declare function hof:scan-left($seq, $acc, $f) {`
	`  if(empty($seq)) then $acc else (`
	`  $acc,`
	`  hof:scan-left(tail($seq), $f($acc, head($seq)), $f)`
	`  )`
	`};`

Examples	• Returns triangular numbers: `hof:scan-left(1 to 10, 0, function($a, $b) { $a + $b })`

hof:take-while

Signatures	`hof:take-while($seq as item()*, $pred as function(item()) as xs:boolean) as item()*`

Summary	The function returns items of `$seq` as long as the predicate `$pred` is satisfied. It is equivalent to:
	
	`declare function hof:take-while($seq, $pred) {`
	`  if(empty($seq) or not($pred(head($seq)))) then () else (`
	`  head($seq),`
	`  hof:take-while(tail($seq), $pred)`
	`  )`
	`};`

Examples	• Computes at most 100 random integers, but stops if an integer is smaller than 10:
	
	`hof:take-while(`
	`  (1 to 100) ! random:integer(50),`
	`  function($x) { $x >= 10 }`
	`)`

Sorting

hof:top-k-by

Signatures	`hof:top-k-by($seq as item()*, $sort-key as function(item()) as item(), $k as xs:integer) as item()*`

Summary	Returns the `$k` items in `$seq` that are greatest when sorted by the result of `$f` applied to the item. The function is a much more efficient implementation of the following scheme:
	
	`(for $x in $seq`
	` order by $sort-key($x) descending`
	` return $x`

	`)[position() <= $k]`
Examples	• `hof:top-k-by(1 to 1000, hof:id#1, 5)` returns `1000 999 998 997 996` • `hof:top-k-by(1 to 1000, function($x) { -$x }, 3)` returns `1 2 3` • `hof:top-k-by(<x a='1' b='2' c='3'/>/@*, xs:integer#1, 2)/node-name()` returns `c b`

hof:top-k-with

Signatures	`hof:top-k-with($seq as item()*, $lt as function(item(), item()) as xs:boolean, $k as xs:integer) as item()*`
Summary	Returns the `$k` items in `$seq` that are greatest when sorted in the order of the *less-than* predicate `$lt`. The function is a general version of `hof:top-k-by($seq, $sort-key, $k)`.
Examples	• `hof:top-k-with(1 to 1000, function($a, $b) { $a lt $b }, 5)` returns `1000 999 998 997 996` • `hof:top-k-with(-5 to 5, function($a, $b) { abs($a) gt abs($b) }, 5)` returns `0 1 -1 2 -2`

IDs

hof:id

Signatures	`hof:id($expr as item()*) as item()*`
Summary	Returns its argument unchanged. This function isn't useful on its own, but can be used as argument to other higher-order functions.

Examples	• `hof:id(1 to 5)` returns `1 2 3 4 5`
	• With higher-order functions:
	`let $sort := sort(?, (), hof:id#1)`
	`let $reverse-sort := sort(?, (), function($x) { -$x })`
	`return (`
	`  $sort((1, 5, 3, 2, 4)),`
	`  '|',`
	`  $reverse-sort((1, 5, 3, 2, 4))`
	`)`
	returns: `1 2 3 4 5 | 5 4 3 2 1`

hof:const

Signatures	`hof:const($expr as item()*, $ignored as item()*) as item()*`
Summary	Returns its first argument unchanged and ignores the second. This function isn't useful on its own, but can be used as argument to other higher-order functions, e.g. when a function combining two values is expected and one only wants to retain the left one.

Examples	• `hof:const(42, 1337)` returns `42`.
	• With higher-order functions:
	`let $zip-sum := function($f, $seq1, $seq2) {`
	`  sum(for-each-pair($seq1, $seq2, $f))`
	`}`
	`let $sum-all  := $zip-sum(function($a, $b) { $a + $b }, ?, ?)`

```
let $sum-left := $zip-sum(hof:const#2, ?, ?)
return (
  $sum-all((1, 1, 1, 1, 1), 1 to 5),
  $sum-left((1, 1, 1, 1, 1), 1 to 5)
)
```

- Another use-case: When inserting a key into a map, `$f` decides how to combine the new value with a possibly existing old one. `hof:const` here means ignoring the old value, so that's normal insertion.

```
let $insert-with := function($f, $map, $k, $v) {
  let $old := $map($k)
  let $new := if($old) then $f($v, $old) else $v
  return map:merge(($map, map:entry($k, $new)))
}
let $map := map { 'foo': 1 }
let $add := $insert-with(function($a, $b) { $a + $b }, ?, ?, ?)
let $ins := $insert-with(hof:const#2, ?, ?, ?)
return (
  $add($map, 'foo', 2)('foo'),
  $ins($map, 'foo', 42)('foo')
)
```

returns `3 42`

Changelog

Version 8.1

- Added: hof:scan-left, hof:take-while

Version 7.2

- Added: hof:top-k-by, hof:top-k-with
- Removed: hof:iterate

Version 7.0

- module added

Chapter 49. HTML Module

Read this entry online in the BaseX Wiki.

This XQuery Module provides functions for converting HTML to XML. Conversion will only take place if TagSoup is included in the classpath (see HTML Parsing for more details).

Conventions

Updated with Version 9.0:

All functions and errors in this module are assigned to the `http://basex.org/modules/html` namespace, which is statically bound to the `html` prefix.

Functions

html:parser

Signatures	`html:parser() as xs:string`
Summary	Returns the name of the applied HTML parser (currently: `TagSoup`). If an *empty string* is returned, TagSoup was not found in the classpath, and the input will be treated as well-formed XML.

html:parse

Signatures	`html:parse($input as xs:anyAtomicType) as document-node()` `html:parse($input as xs:anyAtomicType, $options as map(*)?) as document-node()`
Summary	Converts the HTML document specified by `$input` to XML, and returns a document node: • The input may either be a string or a binary item (xs:hexBinary, xs:base64Binary). • If the input is passed on in its binary representation, the HTML parser will try to automatically choose the correct encoding. The `$options` argument can be used to set TagSoup Options.
Errors	`parse`: the input cannot be converted to XML.

Examples

Basic Example

The following query converts the specified string to an XML document node.

Query

```
html:parse("<html>")
```

Result

```
<html xmlns="http://www.w3.org/1999/xhtml"/>
```

Specifying Options

The next query creates an XML document with namespaces:

Query

```
html:parse("<a href='ok.html'/>", map { 'nons': false() })
```

Result

```
<html xmlns="http://www.w3.org/1999/xhtml">
  <body>
    <a shape="rect" href="ok.html"/>
  </body>
</html>
```

Parsing Binary Input

If the input encoding is unknown, the data to be processed can be passed on in its binary representation. The HTML parser will automatically try to detect the correct encoding:

Query

```
html:parse(fetch:binary("http://en.wikipedia.org"))
```

Result

```
<html xmlns="http://www.w3.org/1999/xhtml" class="client-nojs" dir="ltr" lang="en">
  <head>
    <title>Wikipedia, the free encyclopedia</title>
    <meta charset="UTF-8"/>
    ...
```

Errors

Updated with Version 9.0:

Code	Description
`parse`	The input cannot be converted to XML.

Changelog

Version 9.0

- Updated: error codes updated; errors now use the module namespace

The module was introduced with Version 7.6.

Chapter 50. HTTP Module

Read this entry online in the BaseX Wiki.

This XQuery Module contains a single function to send HTTP requests and handle HTTP responses. The function `send-request` is based on the EXPath HTTP Client Module. It gives full control over the available request and response parameters. For simple GET requests, the Fetch Module may be sufficient.

With *Version 9.0*, if `<http:header name="Accept-Encoding" value="gzip"/>` is specified and if the addressed web server provides support for the `gzip` compression algorithm, the response will automatically be decompressed.

Conventions

All functions in this module are assigned to the `http://expath.org/ns/http-client` namespace, which is statically bound to the `http` prefix. All errors are assigned to the `http://expath.org/ns/error` namespace, which is statically bound to the `exerr` prefix.

Functions

http:send-request

Signatures	`http:send-request($request as element(http:request)?, $href as xs:string?, $bodies as item()*) as item()+ http:send-request($request as element(http:request)) as item()+ http:send-request($request as element(http:request)?, $href as xs:string?) as item()+`
Summary	Sends an HTTP request and interprets the corresponding response. `$request` contains the parameters of the HTTP request such as HTTP method and headers. In addition to this it can also contain the URI to which the request will be sent and the body of the HTTP method. If the URI is not given with the parameter `$href`, its value in `$request` is used instead.The structure of `http:request` element follows the EXPath specification. Both basic and digest authentication is supported.
Errors	`HC0001`: an HTTP error occurred.`HC0002`: error parsing the entity content as XML or HTML.`HC0003`: with a multipart response, the override-media-type must be either a multipart media type or application/octet-stream.`HC0004`: the src attribute on the body element is mutually exclusive with all other attribute (except the media-type).`HC0005`: the request element is not valid.`HC0006`: a timeout occurred waiting for the response.

Examples

Status Only

Simple GET request. As the attribute `status-only` is set to true, only the response element is returned.

Query:

```
http:send-request(<http:request method='get' status-only='true'/>, 'http://
basex.org')
```

Result:

```
<http:response status="200" message="OK">
  <http:header name="Date" value="Mon, 14 Mar 2011 20:55:53 GMT"/>
  <http:header name="Content-Length" value="12671"/>
  <http:header name="Expires" value="Mon, 14 Mar 2011 20:57:23 GMT"/>
```

```
  <http:header name="Set-Cookie"
 value="fe_typo_user=d10c9552f9a784d1a73f8b6ebdf5ce63; path=/"/>
  <http:header name="Connection" value="close"/>
  <http:header name="Content-Type" value="text/html; charset=utf-8"/>
  <http:header name="Server" value="Apache/2.2.16"/>
  <http:header name="X-Powered-By" value="PHP/5.3.5"/>
  <http:header name="Cache-Control" value="max-age=90"/>
  <http:body media-type="text/html; charset=utf-8"/>
</http:response>
```

Google Homepage

Retrieve the Google search home page with a timeout of 10 seconds. In order to parse HTML, TagSoup must be contained in the class path.

Query:

```
http:send-request(<http:request method='get' href='http://www.google.com'
 timeout='10'/>)
```

Result:

```
<http:response status="200" message="OK">
  <http:header name="Date" value="Mon, 14 Mar 2011 22:03:25 GMT"/>
  <http:header name="Transfer-Encoding" value="chunked"/>
  <http:header name="Expires" value="-1"/>
  <http:header name="X-XSS-Protection" value="1; mode=block"/>
  <http:header name="Set-Cookie" value="...; expires=Tue, 13-Sep-2011 22:03:25 GMT;
 path=/; domain=.google.ch; HttpOnly"/>
  <http:header name="Content-Type" value="text/html; charset=ISO-8859-1"/>
  <http:header name="Server" value="gws"/>
  <http:header name="Cache-Control" value="private, max-age=0"/>
  <http:body media-type="text/html; charset=ISO-8859-1"/>
</http:response>
<html xmlns="http://www.w3.org/1999/xhtml">
  <head>
    <meta http-equiv="content-type" content="text/html; charset=ISO-8859-1"/>
    <title>Google</title>
    <script>window.google={kEI:"rZB-
    ...
    </script>
    </center>
  </body>
</html>
```

The response content type can also be overwritten in order to retrieve HTML pages and other textual data as plain string (using `text/plain`) or in its binary representation (using `application/octet-stream`). With the `http:header` element, a custom user agent can be set. See the following example:

Query:

```
let $binary :=  http:send-request(
  <http:request method='get'
     override-media-type='application/octet-stream'
     href='http://www.google.com'>
    <http:header name="User-Agent" value="Opera"/>
  </http:request>
)[2]
return try {
  html:parse($binary)
} catch * {
  'Conversion to XML failed: ' || $err:description
```

```
}
```

SVG Data

Content-type ending with +xml, e.g. image/svg+xml.

Query:

```
http:send-request(<http:request method='get'/>, 'http://upload.wikimedia.org/
wikipedia/commons/6/6b/Bitmap_VS_SVG.svg')
```

Result:

```
<http:response status="200" message="OK">
  <http:header name="ETag" value="W/"11b6d-4ba15ed4""/>
  <http:header name="Age" value="9260"/>
  <http:header name="Date" value="Mon, 14 Mar 2011 19:17:10 GMT"/>
  <http:header name="Content-Length" value="72557"/>
  <http:header name="Last-Modified" value="Wed, 17 Mar 2010 22:59:32 GMT"/>
  <http:header name="Content-Type" value="image/svg+xml"/>
  <http:header name="X-Cache-Lookup" value="MISS from
 knsq22.knams.wikimedia.org:80"/>
  <http:header name="Connection" value="keep-alive"/>
  <http:header name="Server" value="Sun-Java-System-Web-Server/7.0"/>
  <http:header name="X-Cache" value="MISS from knsq22.knams.wikimedia.org"/>
  <http:body media-type="image/svg+xml"/>
</http:response>
<svg xmlns="http://www.w3.org/2000/svg" xmlns:xlink="http://www.w3.org/1999/xlink"
 version="1.1" width="1063" height="638">
  <defs>
    <linearGradient id="lg0">
      <stop stop-color="#3333ff" offset="0"/>
      <stop stop-color="#3f3fff" stop-opacity="0" offset="1"/>
    </linearGradient>
    ...
</svg>
```

POST Request

POST request to the BaseX REST Service, specifying a username and password.

Query:

```
let $request :=
  <http:request href='http://localhost:8984/rest'
    method='post' username='admin' password='admin' send-authorization='true'>
    <http:body media-type='application/xml'>
      <query xmlns="http://basex.org/rest">
        <text><![CDATA[
          <html>{
            for $i in 1 to 3
            return <div>Section {$i }</div>
          }</html>
        ]]></text>
      </query>
    </http:body>
  </http:request>
return http:send-request($request)
```

Result:

```
<http:response xmlns:http="http://expath.org/ns/http-client" status="200"
 message="OK">
```

```
  <http:header name="Content-Length" value="135"/>
  <http:header name="Content-Type" value="application/xml"/>
  <http:header name="Server" value="Jetty(6.1.26)"/>
  <http:body media-type="application/xml"/>
</http:response>
<html>
  <div>Section 1</div>
  <div>Section 2</div>
  <div>Section 3</div>
</html>
```

Errors

Code	Description
`HC0001`	An HTTP error occurred.
`HC0002`	Error parsing the entity content as XML or HTML.
`HC0003`	With a multipart response, the override-media-type must be either a multipart media type or application/octet-stream.
`HC0004`	The src attribute on the body element is mutually exclusive with all other attribute (except the media-type).
`HC0005`	The request element is not valid.
`HC0006`	A timeout occurred waiting for the response.

Changelog

Version 9.0

- Updated: support for gzipped content encoding

Version 8.0

- Added: digest authentication

Version 7.6

- Updated: http:send-request: `HC0002` is raised if the input cannot be parsed or converted to the final data type.
- Updated: errors are using `text/plain` as media-type.

Chapter 51. Index Module

Read this entry online in the BaseX Wiki.

This XQuery Module provides functions for displaying information stored in the database index structures.

Conventions

All functions and errors in this module are assigned to the `http://basex.org/modules/index` namespace, which is statically bound to the `index` prefix.

Functions

index:facets

Signatures	`index:facets($db as xs:string) as xs:string` `index:facets($db as xs:string, $type as xs:string) as xs:string`
Summary	Returns information about all facets and facet values of the database `$db` in document structure format.If `$type` is specified as `flat`, the function returns this information in a flat summarized version. The returned data is derived from the Path Index.
Errors	`db:open`: The addressed database does not exist or could not be opened.
Examples	• `index:facets("DB")` returns information about facets and facet values on the database `DB` in document structure. • `index:facets("DB", "flat")` returns information about facets and facet values on the database `DB` in a summarized flat structure.

index:texts

Signatures	`index:texts($db as xs:string) as element(value)*` `index:texts($db as xs:string, $prefix as xs:string) as element(value)*` `index:texts($db as xs:string, $start as xs:string, $ascending as xs:boolean) as element(value)*`
Summary	Returns all strings stored in the Text Index of the database `$db`, along with their number of occurrences.If `$prefix` is specified, the returned entries will be refined to the ones starting with that prefix.If `$start` and `$ascending` are specified, all nodes will be returned after or before the specified start entry.
Errors	`db:open`: The addressed database does not exist or could not be opened.`db:no-index`: the index is not available.

index:attributes

Signatures	`index:attributes($db as xs:string) as element(value)*` `index:attributes($db as xs:string, $prefix as xs:string) as element(value)*` `index:attributes($db as xs:string, $start as xs:string, $ascending as xs:boolean) as element(value)*`
Summary	Returns all strings stored in the Attribute Index of the database `$db`, along with their number of occurrences.If `$prefix` is specified, the returned entries will be refined to the ones starting with that prefix.If `$start` and `$ascending` are specified, all nodes will be returned after or before the specified start entry.
Errors	`db:open`: The addressed database does not exist or could not be opened.`db:no-index`: the index is not available.

index:tokens

Signatures	`index:tokens($db as xs:string) as element(value)*`
Summary	Returns all strings stored in the Token Index of the database `$db`, along with their number of occurrences.
Errors	`db:open`: The addressed database does not exist or could not be opened.`db:no-index`: the index is not available.

index:element-names

Signatures	`index:element-names($db as xs:string) as element(value)*`
Summary	Returns all element names stored in the Name Index of the database `$db`, along with their number of occurrences.
Errors	`db:open`: The addressed database does not exist or could not be opened.

index:attribute-names

Signatures	`index:attribute-names($db as xs:string) as element(value)*`
Summary	Returns all attribute names stored in the Name Index of the database `$db`, along with their number of occurrences.
Errors	`db:open`: The addressed database does not exist or could not be opened.

Changelog

Version 8.4

- Added: index:token

Version 7.7

- Updated: the functions no longer accept Database Nodes as reference. Instead, the name of a database must now be specified.

Version 7.3

- Updated: index:texts, index:attributes: signature with three arguments added.

The module was introduced with Version 7.1.

Chapter 52. Inspection Module

Read this entry online in the BaseX Wiki.

This XQuery Module contains functions for extracting internal information about modules and functions and generating documentation.

Conventions

All functions and errors in this module are assigned to the `http://basex.org/modules/inspect` namespace, which is statically bound to the `inspect` prefix. xqDoc document instances are assigned to the `http://www.xqdoc.org/1.0` namespace, which is statically bound to the `xqdoc` prefix.

Reflection

inspect:functions

Signatures	`inspect:functions() as function(*)* inspect:functions($uri as xs:string) as function(*)*`
Summary	Returns function items for all user-defined functions (both public and private) that are known in the current query context. If a `$uri` is specified, the addressed module will be compiled, and its functions will be added to the query context and returned to the user. A relative URI will be resolved against the static base URI of the query.

Examples	Invokes the declared functions and returns their values:
	`declare %private function local:one() { 12 };`
	`declare %private function local:two() { 34 };`
	`for $f in inspect:functions() return $f()`
	Compiles all functions in `code.xqm` and invokes the function named `run`:
	`let $uri := 'code.xqm'`
	`let $name := "run"`
	`for $f in inspect:functions($uri)`
	`where local-name-from-QName(function-name($f)) = $name`
	`return $f()`

inspect:function-annotations

Signatures	`inspect:function-annotations($function as function(*)?) as map(xs:QName, xs:anyAtomicType*)`
Summary	Returns the annotations of the specified `$function` in a map.

Examples	• Returns an empty map:
	`inspect:function-annotations(true#0)`
	• Returns a map with a single key `Q{http://www.w3.org/2012/xquery}private` and an empty sequence as value:
	`declare %private function local:f() { 'well hidden' };`
	`inspect:function-annotations(local:f#0)`

inspect:static-context

Signatures	`inspect:static-context($function as function(*)?, $name as xs:string) as item()*`
Summary	Returns a component of the static context of a `$function` with the specified `$name`. If no function is supplied, the current static context is considered.The following components can be requested: • `base-uri` : Static base URI. • `namespaces` : Prefix/URI map with all statically known namespaces. • `element-namespace` : Default element/type namespace URI, or an empty sequence if it is absent. • `function-namespace` : Default function namespace URI, or an empty sequence if it is absent. • `collation` : URI of the default collation. • `ordering` : Ordering mode (`ordered`/`unordered`) • `construction` : Construction mode (`preserve`/`strip`) • `default-order-empty` : Default order for empty sequences (`greatest`/`least`) • `boundary-space` : Boundary-space policy (`preserve`/`strip`) • `copy-namespaces` : Copy-namespaces mode (`inherit`/`no-inherit`, `preserve`/`no-preserve`) • `decimal-formats` : Nested map with all statically known decimal formats

Examples	• Returns the static base URI (same as `static-base-uri()`):
	`inspect:static-context((), 'base-uri')`
	• Returns a map with all namespaces that are statically known in the module of the specified function:
	`import module namespace data = 'data.xqm';`
	`inspect:static-context(data:get#1, 'namespaces')`

Errors	`unknown`: The specified component does not exist.

Documentation

inspect:function

Signatures	`inspect:function($function as function(*)) as element(function)`
Summary	Inspects the specified `$function` and returns an element that describes its structure. The output of this function is similar to eXist-db's inspect:inspect-function function.

Examples	The query `inspect:function(count#1)` yields:
	`<function name="count" uri="http://www.w3.org/2005/xpath-functions" external="false">`
	`  <argument type="item()" occurrence="*"/>`

```
  <return type="xs:integer"/>
</function>
```

The function…

```
(:~
 : This function simply returns the specified integer.
 : @param $number  number to return
 : @return         specified number
 :)
declare %private function local:same($number as xs:integer) as
 xs:integer {
  $number
};
```

…is represented by `inspect:function(local:same#1)` as…

```
<function name="local:same" uri="http://www.w3.org/2005/xquery-local-
functions" external="false">
  <argument type="xs:integer" name="number">number to return</argument>
  <annotation name="private" uri="http://www.w3.org/2012/xquery"/>
  <description>This function simply returns the specified integer.</
description>
  <return type="xs:integer">specified number</return>
</function>
```

inspect:context

Signatures	`inspect:context() as element(context)`
Summary	Generates an element that describes all variables and functions in the current query context.

Examples	Evaluate all user-defined functions with zero arguments in the query context:
	
	`inspect:context()/function ! function-lookup(QName(@uri, @name), 0) ! .()`
	
	Return the names of all private functions in the current context:
	
	`for $f in inspect:context()/function`
	`where $f/annotation/@name = 'private'`
	`return $f/@name/string()`

inspect:module

Signatures	`inspect:module($uri as xs:string) as element(module)`
Summary	Retrieves the resource located at the specified `$uri`, parses it as XQuery module, and generates an element that describes the module's structure. A relative URI will be resolved against the static base URI of the query.
Examples	An example is shown below.

inspect:xqdoc

Signatures	`inspect:xqdoc($uri as xs:string) as element(xqdoc:xqdoc)`
Summary	Retrieves the resource located at the specified `$uri`, parses it as XQuery module, and generates an xqDoc element. A relative URI will be resolved against the static base URI of the query.xqDoc provides a simple vendor-neutral solution for generating documentation from XQuery modules. The

	documentation conventions have been inspired by the JavaDoc standard. Documentation comments begin with `(:~` and end with `:)`, and tags start with `@`. xqDoc comments can be specified for main and library modules and variable and function declarations. We have slightly extended the xqDoc conventions to do justice to more recent versions of XQuery (Schema: xqdoc-1.1.30052013.xsd): • an `<xqdoc:annotations/>` node is added to each variable or function that uses annotations. The xqdoc:annotation child nodes may have additional `xqdoc:literal` elements with `type` attributes (xs:string, xs:integer, xs:decimal, xs:double) and values. • a single `<xqdoc:namespaces/>` node is added to the root element, which summarizes all prefixes and namespace URIs used or declared in the module. • name and type elements are added to variables.
Examples	An example is shown below.

Examples

This is the `sample.xqm` library module:

```
(:~
 : This module provides some sample functions to demonstrate
 : the features of the Inspection Module.
 :
 : @author   BaseX Team
 : @see      http://docs.basex.org/wiki/XQDoc_Module
 : @version  1.0
 :)
module namespace samples = 'http://basex.org/modules/samples';

(:~ This is a sample string. :)
declare variable $samples:test-string as xs:string := 'this is a string';

(:~
 : This function simply returns the specified integer.
 : @param   $number number to return
 : @return  specified number
 :)
declare %private function samples:same($number as xs:integer) as xs:integer {
  $number
};
```

If `inspect:module('sample.xqm')` is run, the following output will be generated:

```
<module prefix="samples" uri="http://basex.org/modules/samples">
  <description>This module provides some sample functions to demonstrate
the features of the Inspection Module.</description>
  <author>BaseX Team</author>
  <see>http://docs.basex.org/wiki/XQDoc_Module</see>
  <version>1.0</version>
  <variable name="samples:test-string" uri="http://basex.org/modules/samples"
 type="xs:string" external="false">
    <description>This is a sample string.</description>
  </variable>
  <function name="samples:same" uri="http://basex.org/modules/samples"
 external="false">
    <argument name="number" type="xs:integer">number to return</argument>
    <annotation name="private" uri="http://www.w3.org/2012/xquery"/>
    <description>This function simply returns the specified integer.</description>
    <return type="xs:integer">specified number</return>
  </function>
</module>
```

The output looks as follows if `inspect:xqdoc('sample.xqm')` is called:

```
<xqdoc:xqdoc xmlns:xqdoc="http://www.xqdoc.org/1.0">
  <xqdoc:control>
    <xqdoc:date>2013-06-01T16:59:33.654+02:00</xqdoc:date>
    <xqdoc:version>1.1</xqdoc:version>
  </xqdoc:control>
  <xqdoc:module type="library">
    <xqdoc:uri>http://basex.org/modules/samples</xqdoc:uri>
    <xqdoc:name>sample.xqm</xqdoc:name>
    <xqdoc:comment>
      <xqdoc:description>This module provides some sample functions to demonstrate
the features of the Inspection Module.</xqdoc:description>
      <xqdoc:author>BaseX Team</xqdoc:author>
      <xqdoc:see>http://docs.basex.org/wiki/XQDoc_Module</xqdoc:see>
      <xqdoc:version>1.0</xqdoc:version>
    </xqdoc:comment>
  </xqdoc:module>
  <xqdoc:namespaces>
    <xqdoc:namespace prefix="samples" uri="http://basex.org/modules/samples"/>
  </xqdoc:namespaces>
  <xqdoc:imports/>
  <xqdoc:variables>
    <xqdoc:variable>
      <xqdoc:name>samples:test-string</xqdoc:name>
      <xqdoc:comment>
        <xqdoc:description>This is a sample string.</xqdoc:description>
      </xqdoc:comment>
      <xqdoc:type>xs:string</xqdoc:type>
    </xqdoc:variable>
  </xqdoc:variables>
  <xqdoc:functions>
    <xqdoc:function arity="1">
      <xqdoc:comment>
        <xqdoc:description>This function simply returns the specified integer.</
xqdoc:description>
        <xqdoc:param>$number number to return</xqdoc:param>
        <xqdoc:return>specified number</xqdoc:return>
      </xqdoc:comment>
      <xqdoc:name>samples:same</xqdoc:name>
      <xqdoc:annotations>
        <xqdoc:annotation name="private"/>
      </xqdoc:annotations>
      <xqdoc:signature>declare %private function samples:same($number as
 xs:integer) as xs:integer</xqdoc:signature>
      <xqdoc:parameters>
        <xqdoc:parameter>
          <xqdoc:name>number</xqdoc:name>
          <xqdoc:type>xs:integer</xqdoc:type>
        </xqdoc:parameter>
      </xqdoc:parameters>
      <xqdoc:return>
        <xqdoc:type>xs:integer</xqdoc:type>
      </xqdoc:return>
    </xqdoc:function>
  </xqdoc:functions>
</xqdoc:xqdoc>
```

Errors

Code	Description
`unknown`	The specified component does not exist.

Changelog

Version 8.5

- Added: inspect:function-annotations, inspect:static-context
- Updated: `external` attribute added to variables and functions
- Updated: Relative URIs will always be resolved against the static base URI of the query

Version 7.9

- Updated: a query URI can now be specified with inspect:functions.

This module was introduced with Version 7.7.

Chapter 53. Jobs Module

Read this entry online in the BaseX Wiki.

This XQuery Module provides functions for organizing scheduled, queued, running and cached jobs. Jobs can be commands, queries, client or HTTP requests.

Conventions

All functions in this module are assigned to the `http://basex.org/modules/jobs` namespace, which is statically bound to the `jobs` prefix. Errors will be bound to the same prefix.

Services

Introduced with Version 9.0:

Jobs can additionally be registered as persistent services. An additional `service` option has been added to the options list of jobs:eval and jobs:invoke:

```
(: register job, which will be run every day at 1 am :)
jobs:eval('db:drop("tmp")', (), map { 'id':'cleanup', 'start':'01:00:00',
 'interval':'P1D', 'service': true() }),

(: list registered services :)
jobs:services(),
(: result: <job base-uri="..." id="cleanup" interval="P1D"
 start="01:00:00">db:drop("tmp")</job> :)

(: unregister job :)
jobs:stop('cleanup', map { 'service': true() })
```

Some more notes:

- All registered jobs will be scheduled for evaluation when the BaseX server or BaseX HTTP server is started.
- If a job service is outdated (e.g. because a supplied end time has been exceeded), it will be removed from the jobs file at startup time.
- Job services can be updated: If a new job is registered, and if there is already a job with the same id, the old entry will be replaced.
- The job definitions are stored in a `jobs.xml` file in the database directory. It can also be edited manually.

Basic Functions

jobs:current

Signatures	`jobs:current() as xs:string`
Summary	Returns the id of the current job.

jobs:list

Signatures	`jobs:list() as xs:string*`

Summary	Returns the ids of all jobs that are currently registered. The list includes scheduled, queued, running, stopped, and finished jobs with cached results.
Examples	`jobs:list()` returns the same job id as jobs:current if no other job is registered.

jobs:list-details

Signatures	`jobs:list-details() as element(job)* jobs:list-details($id as xs:string) as element(job)*`
Summary	Returns information on all jobs that are currently registered, or on a job with the specified `$id` (or an empty sequence if this job is not found). The list includes scheduled, queued, running jobs, and cached jobs. A string representation of the job, or its URI, will be returned as value. The returned elements have additional attributes: • `id` : job id • `type` : type of the job (command, query, REST, RESTXQ, etc.) • `state` : current state of the job (scheduled, queued, running, or cached) • `user` : the user who started the job • `duration` : evaluation time (for running and cached jobs) • `start` : dateTime string with next start (for jobs that will be executed repeatedly)
Examples	`jobs:list-details()` returns information on the currently running job and possibly others: `<job id="job1" type="XQuery" state="running" user="admin" duration="PT0.001S"> XQUERY jobs:list-details() </job>`

Signatures	`jobs:services() as element(job)*`
Summary	Returns a list of all jobs that have been persistently registered as Services.
Errors	`services`: Registered services cannot be parsed.

jobs:finished

Signatures	`jobs:finished($id as xs:string) as xs:boolean`
Summary	Indicates if the evaluation of an already running job with the specified `$id` has finished. As the ids of finished jobs will usually be discarded, unless caching is enabled, the function will also return `true` for unknown jobs. • `false` indicates that the job id is scheduled, queued, or currently running. • `true` will be returned if the job has either finished, or if the id is unknown (because the ids of all finished jobs will not be cached).

Execution

Asynchronous query execution is recommendable if a client does not, or cannot, wait until a request is fully processed. This is e. g. the case with web browsers, which will usually cancel a request after a specific timeout. In such cases, you can use asynchronous execution to trigger another server-side process, which will start the time-consuming process, and fetch the result later on as soon as it is available.

jobs:eval

Signatures	`jobs:eval($query as xs:string) as xs:string` `jobs:eval($query as xs:string, $bindings as map(*)?) as xs:string` `jobs:eval($query as xs:string, $bindings as map(*)?, $options as map(*)?) as xs:string`

Summary	Schedules the evaluation of the supplied `$query` and returns a query id. The query will be queued, and the result will optionally be cached. Queries can be updating. Variables and context items can be declared via `$bindings` (see xquery:eval for more details). The following `$options` can be supplied:
	• `cache` : indicates if the query result will be cached or ignored (default: `false`):
	  • The result will be cached in main-memory until it is fetched via jobs:result, or until `CACHETIMEOUT` is exceeded.
	  • If the query raises an error, it will be cached and returned instead.
	• `start` : a dayTimeDuration, time or dateTime can be specified to delay the execution of the query:
	  • If a dayTimeDuration is specified, the query will be queued after the specified duration has passed. Examples for valid values are: `P1D` (1 day), `PT5M` (5 minutes), `PT0.1S` (100 ms). An error will be raised if a negative value is specified.
	  • If a time is specified, the query will be executed at this time of the day. Examples for valid times are: `02:00:00` (2am local time), `12:00:00Z` (noon, UTC). If the time lies in the past, the query will be executed the next day.
	  • If a dateTime is specified, the query will be executed at this date. Examples for valid values are: `2018-12-31T23:59:59` (New Year's Eve 2018, close to midnight). An error will be raised if the specified time lies in the past.
	• `interval` : a dayTimeDuration string can be specified to execute the query periodically. An error is raised if the specified interval is less than one second (`PT1S`). If the next scheduled call is due, and if a query with the same id is still running, it will be skipped.
	• `end` : scheduling can be stopped after a given time or duration. The string format is the same as for `start`. An error is raised if the resulting end time is smaller than the start time.
	• `base-uri` : sets the base-uri property for the query. This URI will be used when resolving relative URIs, such as with `fn:doc`.
	• `id` : sets a custom job id. The id must not start with the standard `job` prefix, and it can only be assigned if no job with the same name exists.
	• `service` : additionally registers the job as service.

Errors	`overflow`: Query execution is rejected, because too many jobs are queued or being executed. `CACHETIMEOUT` can be decreased if the default setting is too restrictive.`range`: A specified time or duration is out of range.`id`: The specified id is invalid or has already been assigned.`options`: The specified options are conflicting.

Examples	• Cache query result. The returned id can be used to pick up the result with jobs:result:
	`jobs:eval("1+3", (), map { 'cache': true() })`
	• A happy birthday mail will be sent at the given date:
	`jobs:eval("import module namespace mail='mail'; mail:send('Happy birthday!')",`

```
  (), map { 'start': '2018-09-01T06:00:00' })}}
```

- The following RESTXQ functions can be called to execute a query at 2 am every day. An id will be returned by the first function, which can be used to stop the scheduler via the second function:

```
declare %rest:POST("{$query}") %rest:path('/start-scheduling') function
 local:start($query) {
  jobs:eval($query, (), map { 'start': '02:00:00', 'interval': 'P1D' })
};
declare %rest:path('/stop-scheduling/{$id}') function local:stop($id) {
  jobs:stop($id)
};
```

- Query execution is scheduled for every second, and for 10 seconds in total. As the query itself will take 1.5 seconds, it will only be executed every second time:

```
jobs:eval("prof:sleep(1500)", (), map { 'interval': 'PT1S', 'end':
 'PT10S' })
```

- The following expression, if stored as a file, calls and evaluates itself every 5 seconds:

```
jobs:eval(
  file:read-text(static-base-uri()),
  map { },
  map { 'start': 'PT5S' }
)
```

jobs:invoke

Introduced with Version 9.0:

Signatures	`jobs:invoke($uri as xs:string) as xs:string` `jobs:invoke($uri as xs:string, $bindings as map(*)?) as xs:string` `jobs:invoke($uri as xs:string, $bindings as map(*)?, $options as map(*)?) as xs:string`
Summary	Schedules the evaluation of the XQuery expression located at `$uri` and returns a query id. For further details, see jobs:eval.
Errors	`overflow`: Query execution is rejected, because too many jobs are queued or being executed. `CACHETIMEOUT` can be decreased if the default setting is too restrictive.`range`: A specified time or duration is out of range.`id`: The specified id is invalid or has already been assigned.`options`: The specified options are conflicting.
Examples	Run XQuery expression that may perform some cleanups: `jobs:invoke("cleanup.xq", (), ())`

jobs:result

Signatures	`jobs:result($id as xs:string) as item()*`
Summary	Returns the cached result of a job with the specified job `$id`: • Results can only be retrieved once. After retrieval, the cached result will be dropped. • If the original job has raised an error, the cached error will be raised instead.
Errors	`running`: the job is still running.`unknown`: the supplied id is unknown: The id is unknown, or the result has already been retrieved.

Examples

- The following RESTXQ function will either return the result of a previously started job or raise an error:

```
declare %rest:path('/result/{$id}') function local:result($id) {
  jobs:result($id)
};
```

- The following query demonstrates how the results of an asynchronously executed query can be returned within the same query:

```
let $query := jobs:eval('(1 to 10000000)[. = 1]', map{}, map{ 'cache':
 true() })
return (
  jobs:wait($query),
  jobs:result($query)
)
```

Please note that queries of this kind can cause deadlocks. For example, if both the original query and the query to be executed asynchronously perform updates on the same database, the second query would only be run after the first one has been executed, and the first query will wait forever. This is why you should avoid this pattern in practice and resort to xquery:fork-join if you want to do things in parallel.

jobs:stop

Signatures	`jobs:stop($id as xs:string) as empty-sequence()`
Summary	Triggers the cancelation of a job with the specified `$id`, drops the cached result of a query, or cancels a scheduled job. Unknown ids are ignored. All jobs are gracefully stopped; it is up to the process to decide when it is safe to shut down. The following `$options` can be supplied: • `service` : additionally removes the job from the job services list.
Examples	`jobs:list()[. != jobs:current()] ! jobs:stop(.)` stops and discards all jobs except for the current one.

jobs:wait

Signatures	`jobs:wait($id as xs:string) as empty-sequence()`
Summary	Waits for the completion of a job with the specified `$id`: • The function will terminate immediately if the job id is unknown. This is the case if a future job has not been queued yet, or if the id has already been discarded after job evaluation. • If the function is called with the id of a queued job, or repeatedly executed job, it may stall and never terminate.
Errors	`self`: The current job is addressed.

Errors

Code	Description
`options`	The specified options are conflicting.
`id`	The specified id is invalid or has already been assigned.
`overflow`	Too many queries or query results are queued.
`range`	A specified time or duration is out of range.
`running`	A query is still running.

`self`	The current job cannot be addressed.
`service`	Registered services cannot be parsed, added or removed.
`unknown`	The supplied query id is unknown or not available anymore.

Changelog

Version 9.0

- Added: jobs:invoke, Services

Version 8.6

- Updated: jobs:eval: `id` option added.

The module was introduced with Version 8.5.

Chapter 54. JSON Module

Read this entry online in the BaseX Wiki.

This XQuery Module contains functions to parse and serialize JSON data JSON (JavaScript Object Notation) is a popular data exchange format for applications written in JavaScript. As there are notable differences between JSON and XML, or XQuery data types, no mapping exists that guarantees a lossless, bidirectional conversion between JSON and XML. For this reason, we offer various mappings, all of which are suited to different use cases.

Conventions

Updated with Version 9.0:

All functions and errors in this module are assigned to the `http://basex.org/modules/json` namespace, which is statically bound to the `json` prefix.

Conversion Formats

A little advice: in the Database Creation dialog of the GUI, if you select JSON Parsing and switch to the *Parsing* tab, you can see the effects of some of the conversion options.

Direct

The `direct` conversion format allows a lossless conversion from JSON to XML and back. The transformation is based on the following rules:

- The resulting document has a `<json>` root node.
- Object pairs are represented via elements. The name of a pair is rewritten to an element name:
  - Empty names are represented by a single underscore (_). Existing underscores are rewritten to two underscores (__), and characters that are not valid in element names are rewritten to an underscore and the character's four-digit Unicode.
  - If the `lax` option is set to `true`, invalid characters are simply replaced with underscores or (when invalid as first character of an element name) prefixed with an underscore. The resulting names are better readable, but cannot always be converted back to their original form.
- Array entries are also represented via elements. _ is used as element name.
- Object and array values are stored in text nodes.
- The types of values are represented via `type` attributes:
  - The existing types are *string*, *number*, *boolean*, *null*, *object*, and *array*.
  - As most values are strings, the *string* type is by default omitted.

Attributes

The `attributes` format is lossless, too. The transformation based on the following rules:

- The resulting document has a `<json>` root node.
- Object pairs are represented via `<pair>` elements. The name of a pair is stored in a `name` attribute.
- Array entries are represented via `<item>` elements.
- Object and array values are stored in text nodes.
- The types of values are represented via `type` attributes:

- The existing types are *string*, *number*, *boolean*, *null*, *object*, and *array*.
- As most values are strings, the *string* type is by default omitted.

Basic

The `basic` format is another lossless format. It converts a JSON document to an XML node and vice versa. The conversion rules are the same as for fn:json-to-xml.

JsonML

The `jsonml` format is designed to convert XML to JSON and back, using the JsonML dialect. JsonML allows the transformation of arbitrary XML documents, but namespaces, comments and processing instructions will be discarded in the transformation process. More details are found in the official JsonML documentation.

XQuery

The `xquery` format is lossless, too. It converts JSON data to an XQuery value (a map, array, string, number, boolean, or empty sequence) and vice versa. The conversion rules are the same as for fn:parse-json.

The resulting representation consumes less memory than XML-based formats, and values can be directly accessed without conversion. Thus, it is recommendable for very large inputs and for efficient ad-hoc processing.

Before *Version 9.0*, the format was called `map` (it has been renamed because the resulting value may also be a string, number, boolean, or an empty sequence).

Options

The following options are available (the *Direction* column indicates if an option applies to parsing, serialization, or both operations):

Option	Description	Allowed	Default	Direction
`format`	Specifies the format for converting JSON data.	`direct`, `attributes`, `jsonml`, `xquery`	`direct`	*parse*, *serialize*
`liberal`	Determines if minor deviations from RFC 7159 will be ignored.	`yes`, `no`	`no`	*parse*
`merge`	This option is considered when `direct` or `attributes` conversion is used: • If a name has the same type throughout the data, the `type` attribute will be omitted. Instead, the name will be listed in additional, type-specific attributes in the root node. • The attributes are named by their type in plural (*numbers*, *booleans*, *nulls*, *objects* and *arrays*), and the attribute value contains all names with that type, separated by whitespaces.	`yes`, `no`	`no`	*parse*, *serialize*
`strings`	Indicates if `type` attributes will be added for strings.	`yes`, `no`	`yes`	*parse*, *serialize*
`lax`	Specifies if a lax approach is used to convert QNames to JSON names.	`yes`, `no`	`no`	*parse*, *serialize*
`escape`	Indicates if escaped characters are expanded (for example, `\n` becomes a single `x0A` character, while `\u20AC` becomes the character).	`yes`, `no`	`yes`	*parse*

`escape`	Indicates if characters are escaped whenever the JSON syntax requires it. This option can be set to `no` if strings are already in escaped form and no further escaping is permitted.	`yes`, `no`	`yes`	*serialize*
`indent`	Indicates if whitespace should be added to the output with the aim of improving human legibility. If the parameter is set as in the query prolog, it overrides the `indent` serialization parameter.	`yes`, `no`	`yes`	*serialize*

Functions

json:parse

Signatures	`json:parse($input as xs:string) as element(json)` `json:parse($input as xs:string, $options as map(*)?) as item()`
Summary	Converts the JSON data specified by `$input` to an XQuery value. If the input can be successfully parsed, it can be serialized back to the original JSON representation. The `$options` argument can be used to control the way the input is converted.
Errors	`parse`: the specified input cannot be parsed as JSON document.`options`: the specified options are conflicting.

json:serialize

Signatures	`json:serialize($input as item()?) as xs:string` `json:serialize($input as item()?, $options as map(*)?) as xs:string`
Summary	Serializes the specified `$input` as JSON, using the specified `$options`, and returns the result as string: • The input is expected to conform to the results that are created by json:parse(). • Non-conforming items will be serialized as specified in the json output method of the official recommendation. Values can also be serialized as JSON with the standard Serialization feature of XQuery: • The parameter `method` needs to be set to `json`, and • the options presented in this article need to be assigned to the `json` parameter.
Errors	`serialize`: the specified node cannot be serialized as JSON document.

Examples

BaseX Format

Example 1: Adds all JSON documents in a directory to a database

Query:

```
let $database := "database"
for $name in file:list('.', false(), '*.json')
let $file := file:read-text($name)
let $json := json:parse($file)
return db:add($database, $json, $name)
```

Example 2: Converts a simple JSON string to XML and back

Query:

```
json:parse('{}')
```

Result:

```
<json type="object"/>
```

Query:

```
(: serialize result as plain text :)
declare option output:method 'text';
json:serialize(<json type="object"/>)
```

Result:

```
{ }
```

Example 3: Converts a JSON string with simple objects and arrays

Query:

```
json:parse('{
  "title": "Talk On Travel Pool",
  "link": "http://www.flickr.com/groups/talkontravel/pool/",
  "description": "Travel and vacation photos from around the world.",
  "modified": "2014-02-02T11:10:27Z",
  "generator": "http://www.flickr.com/"
}')
```

Result:

```
<json type="object">
  <title>Talk On Travel Pool</title>
  <link>http://www.flickr.com/groups/talkontravel/pool/</link>
  <description>Travel and vacation photos from around the world.</description>
  <modified>2014-02-02T11:10:27Z</modified>
  <generator>http://www.flickr.com/</generator>
</json>
```

Example 4: Converts a JSON string with different data types

Query:

```
let $options := map { 'merge': true() }
return json:parse('{
  "first_name": "John",
  "last_name": "Smith",
  "age": 25,
  "address": {
    "street": "21 2nd Street",
    "city": "New York",
    "code": 10021
  },
  "phone": [
    {
      "type": "home",
      "number": "212 555-1234"
```

```
    },
    {
      "type": "mobile",
      "number": 1327724623
    }
  ]
}', $options)
```

Result:

```
<json numbers="age code" arrays="phone" objects="json address value">
  <first__name>John</first__name>
  <last__name>Smith</last__name>
  <age>25</age>
  <address>
    <street>21 2nd Street</street>
    <city>New York</city>
    <code>10021</code>
  </address>
  <phone>
    <_>
      <type>home</type>
      <number>212 555-1234</number>
    </_>
    <_>
      <type>mobile</type>
      <number type="number">1327724623</number>
    </_>
  </phone>
</json>
```

JsonML Format

Example 1: Converts all XML documents in a database to the JsonML format and writes them to disk

Query:

```
for $doc in collection('json')
let $name := document-uri($doc)
let $json := json:serialize($doc, map { 'format': 'jsonml' })
return file:write($name, $json)
```

Example 2: Converts an XML document with elements and text

Query:

```
json:serialize(doc('flickr.xml'), map { 'format': 'jsonml' })
```

flickr.xml:

```
<flickr>
  <title>Talk On Travel Pool</title>
  <link>http://www.flickr.com/groups/talkontravel/pool/</link>
  <description>Travel and vacation photos from around the world.</description>
  <modified>2014-02-02T11:10:27Z</modified>
  <generator>http://www.flickr.com/</generator>
</flickr>
```

Result:

```
```

```
["flickr",
  ["title",
    "Talk On Travel Pool"],
  ["link",
    "http://www.flickr.com/groups/talkontravel/pool/"],
  ["description",
    "Travel and vacation photos from around the world."],
  ["modified",
    "2014-02-02T11:10:27Z"],
  ["generator",
    "http://www.flickr.com/"]]
```

Example 3: Converts a document with nested elements and attributes to JsonML

Query:

```
json:serialize(doc('input.xml'), map { 'format': 'jsonml' })
```

input.xml:

```
<address id='1'>
  <!-- comments will be discarded -->
  <last_name>Smith</last_name>
  <age>25</age>
  <address xmlns='will be dropped as well'>
    <street>21 2nd Street</street>
    <city>New York</city>
    <code>10021</code>
  </address>
  <phone type='home'>212 555-1234</phone>
</address>
```

Result:

```
["address", {"id":"1"},
  ["last_name",
    "Smith"],
  ["age",
    "25"],
  ["address",
    ["street",
      "21 2nd Street"],
    ["city",
      "New York"],
    ["code",
      "10021"]],
  ["phone", {"type":"home"},
    "212 555-1234"]]
```

XQuery Format

Example 1: Converts a JSON string to XQuery

Query:

```
let $input := '{
  "Title": "Drinks",
  "Author": [ "Jim Daniels", "Jack Beam" ]
}'
let $data := json:parse($input, map { 'format': 'xquery' })
return map:for-each($data, function($k, $v) {
```

```
  $k || ': ' || string-join($v, ', ')
})
```

Result:

```
Author: Jim Daniels, Jack Beam
Title: Drinks
```

Example 2: Converts XQuery data to JSON

Query:

```
for $item in (
  true(),
  'ABC',
  array { 1 to 5 },
  map { "Key": "Value" }
)
return json:serialize(
  $item,
  map { 'format': 'xquery', 'indent': 'no' }
)
```

Result:

```
true
"ABC"
[1,2,3,4,5]
{"Key":"Value"}
```

Errors

Updated with Version 9.0:

Code	Description
`options`	The specified options are conflicting.
`parse`	The specified input cannot be parsed as JSON document.
`serialize`	The specified node cannot be serialized as JSON document.

Changelog

Version 9.0

- Updated: `map` format renamed to `xquery`.
- Updated: error codes updated; errors now use the module namespace

Version 8.4

- Updated: `unescape` changed to `escape`.

Version 8.2

- Added: Conversion format `basic`.

Version 8.0

- Updated: Serialization aligned with the `json` output method of the official specification.

- Added: `liberal` option.
- Removed: `spec` option.

Version 7.8

- Removed: `json:parse-ml`, `json:serialize-ml`.
- Updated: `json:parse` now returns a document node instead of an element, or an XQuery map if `format` is set to `.map`.

Version 7.7.2

- Updated: `$options` argument added to json:parse and json:serialize.
- Updated: json:parse-ml and json:serialize-ml are now *deprecated*.

The module was introduced with Version 7.0.

Chapter 55. Lazy Module

Read this entry online in the BaseX Wiki.

This XQuery Module contains functions for handling *lazy* items.

In contrast to standard XQuery items, a lazy item contains a reference to the actual data, and the data itself will only be retrieved if it is requested. Hence, possible errors will be postponed, and no memory will be occupied by a lazy item as long as its content has not been requested yet.

The following BaseX functions return lazy items:

- Lazy Base64 binaries:
  - `db:retrieve`
  - `fetch:binary`
  - `file:read-binary`
- Lazy strings:
  - `fetch:text`
  - `file:read-text`

Some functions are capable of consuming the contents of lazy items in a *streamable* fashion: data will not be cached, but instead passed on to another target (file, the calling expression, etc.). The following streaming functions are currently available:

- Archive Module (most functions)
- Conversion Module: `convert:binary-to-bytes`, `convert:binary-to-string`
- Database Module: `db:store`
- File Module: `file:write-binary`, `file:write-text` (if no encoding is specified)
- Hashing Module (all functions)

The XQuery expression below serves as an example on how large files can be downloaded and written to a file with constant memory consumption:

```
file:write-binary('output.data', fetch:binary('http://files.basex.org/xml/
xmark111mb.zip'))
```

If lazy items are serialized, they will be streamed as well.

Conventions

All functions and errors in this module are assigned to the `http://basex.org/modules/lazy` namespace, which is statically bound to the `lazy` prefix.

Functions

lazy:cache

Signatures	`lazy:cache($item as item()) as item()`

Summary	Caches the contents of a lazy `$item`: • contents of lazy items will be retrieved and cached in the item. • non-lazy items or lazy items with cached contents will simply be passed through. Caching of a lazy items is advisable if the the targeted contents will not be available anymore at a later stage.

Example	In the following example, a file will be deleted before its content is returned. To avoid a “file not found” error when serializing the result, the content must be cached:
	`let $file := 'data.txt'`
	`let $text := lazy:cache(file:read-text($file))`
	`return (file:delete($file), $text)`

lazy:is-lazy

Signatures	`lazy:is-lazy($item as item()) as xs:boolean`
Summary	Checks whether the specified `$item` is lazy.

lazy:is-cached

Signatures	`lazy:is-cached($item as item()) as xs:boolean`
Summary	Checks whether the contents of the specified `$item` are cached. The function will always return `true` for non-lazy items.

Changelog

Version 9.0

- Updated: Renamed from Streaming Module to Lazy Module.
- Added: lazy:is-cached

Version 8.0

- Updated: stream:materialize extended to sequences.

This module was introduced with Version 7.7.

Chapter 56. Map Module

Read this entry online in the BaseX Wiki.

This XQuery Module contains functions for manipulating maps. Maps have been introduced with XQuery 3.1 and are described in detail in the XQuery Functions and Operators 3.1 specification.

Conventions

All functions in this module are assigned to the `http://www.w3.org/2005/xpath-functions/map` namespace, which is statically bound to the `map` prefix.

Functions

Some examples use the *map* `$week` defined as:

```
declare variable $week := map {
  0: "Sun", 1: "Mon", 2: "Tue", 3: "Wed", 4: "Thu", 5: "Fri", 6: "Sat"
};
```

map:contains

Signatures	`map:contains($map as map(*), $key as xs:anyAtomicType) as xs:boolean`
Summary	Returns true if the supplied `$map` contains an entry with a key equal to the supplied value of `$key`; otherwise it returns false. No error is raised if the map contains keys that are not comparable with the supplied `$key`. If the supplied key is `xs:untypedAtomic`, it is compared as an instance of `xs:string`. If the supplied key is the `xs:float` or `xs:double` value `NaN`, the function returns true if there is an entry whose key is `NaN`, or false otherwise.
Examples	• `map:contains($week, 2)` returns `true()`. • `map:contains($week, 9)` returns `false()`. • `map:contains(map {}, "xyz")` returns `false()`. • `map:contains(map { "xyz": 23 }, "xyz")` returns `true()`.

map:entry

Signatures	`map:entry($key as xs:anyAtomicType, $value as item()*) as map(*)`

Summary	Creates a new *map* containing a single entry. The key of the entry in the new map is `$key`, and its associated value is `$value`. The function `map:entry` is intended primarily for use in conjunction with the function `map:merge`. For example, a map containing seven entries may be constructed like this:
	
	`map:merge((`
	`  map:entry("Sun", "Sunday"),`
	`  map:entry("Mon", "Monday"),`
	`  map:entry("Tue", "Tuesday"),`
	`  map:entry("Wed", "Wednesday"),`
	`  map:entry("Thu", "Thursday"),`
	`  map:entry("Fri", "Friday"),`
	`  map:entry("Sat", "Saturday")`
	`))`

	Unlike the `map { ... }` expression, this technique can be used to construct a map with a variable number of entries, for example: `map:merge(for $b in //book return map:entry($b/isbn, $b))`
Examples	`map:entry("M", "Monday")` creates `map { "M": "Monday" }`.

map:find

Signatures	`map:find($input as item()*, $key as xs:anyAtomicType) as array(*)`
Summary	Returns all values of maps in the supplied `$input` with the specified `$key`. The found values will be returned in an array. Arbitrary input will be processed recursively as follows: • In a sequence, each item will be processed in order. • In an array, all array members will be processed as sequence. • In a map, all entries whose keys match the specified key. Moreover, all values of the map will be processed as sequence.
Examples	• `map:find(map { 1:2 }, 1)` returns `[ 2 ]`. • `map:find(map { 1: map { 2: map { 3: 4 } } }, 3)` returns `[ 4 ]`. • `map:find((1, 'b', true#0), 1)` returns an empty array.

map:for-each

Signatures	`map:for-each($map as map(*), $function as function(xs:anyAtomicType, item()*) as item()*) as item()*`
Summary	Applies the specified `$function` to every key/value pair of the supplied `$map` and returns the results as a sequence.

Examples	The following query adds the keys and values of all map entries and returns `(3,7)`:
	`map:for-each(`
	`  map { 1: 2, 3: 4 },`
	`  function($key, $value) { $key + $value }`
	`)`

map:get

Signatures	`map:get($map as map(*), $key as xs:anyAtomicType) as item()*`
Summary	Returns the value associated with a supplied key in a given map. This function attempts to find an entry within the `$map` that has a key equal to the supplied value of `$key`. If there is such an entry, the function returns the associated value; otherwise it returns an empty sequence. No error is raised if the map contains keys that are not comparable with the supplied `$key`. If the supplied key is `xs:untypedAtomic`, it is converted to `xs:string`. A return value of `()` from `map:get` could indicate that the key is present in the map with an associated value of `()`, or it could indicate that the key is not present in the map. The two cases can be distinguished by calling `map:contains`. Invoking the *map* as a function item has the same effect as calling `get`: that is, when `$map` is a map, the expression `$map($K)` is equivalent to `get($map, $K)`. Similarly, the expression `get(get(get($map, 'employee'), 'name'), 'first')` can be written as `$map('employee')('name')('first')`.
Examples	• `map:get($week, 4)` returns `"Thu"`. • `map:get($week, 9)` returns `()`. *(When the key is not present, the function returns an empty sequence.).*

- `map:get(map:entry(7,()), 7)` returns `()`. *(An empty sequence as the result can also signify that the key is present and the associated value is an empty sequence.).*

map:keys

Signatures	`map:keys($map as map(*)) as xs:anyAtomicType*`
Summary	Returns a sequence containing all the key values present in a map. The function takes the supplied `$map` and returns the keys that are present in the map as a sequence of atomic values. The order may differ from the order in which entries were inserted in the map.
Examples	• `map:keys(map { 1: "yes", 2: "no" })` returns `(1,2)`.

map:merge

Signatures	`map:merge($maps as map(*)*) as map(*)` `map:merge($maps as map(*)*, $options as map(*)) as map(*)`
Summary	Constructs and returns a new map. The *map* is formed by combining the contents of the supplied `$maps`. The maps are combined as follows: 1. There is one entry in the new map for each distinct key present in the union of the input maps. 2. The `$options` argument defines how duplicate keys are handled. Currently, a single option `duplicates` exists, and its allowed values are `use-first`, `use-last`, `combine` and `reject`.

Examples	• `map:merge(())` creates an empty map.
	• `map:merge((map:entry(0, "no"), map:entry(1, "yes")))` creates `map { 0: "no", 1: "yes" }`.
	• The following function adds a seventh entry to an existing map:
	`map:merge(($week, map { 7: "---" }))`
	• In the following example, the values of all maps are combined, resulting in a map with a single key (`map { "key": (1, 2, 3) }`):
	`map:merge( for $i in 1 to 3 return map { 'key': $i }, map { 'duplicates': 'combine' } )`

map:put

Signatures	`map:put($map as map(*), $key as xs:anyAtomicType, $value as item()*) as map(*)`
Summary	Creates a new *map*, containing the entries of the supplied `$map` and a new entry composed by `$key` and `$value`. The semantics of this function are equivalent to `map:merge((map { $key, $value }, $map))`

map:remove

Signatures	`map:remove($map as map(*), $keys as xs:anyAtomicType*) as map(*)`
Summary	Constructs a new map by removing entries from an existing map. The entries in the new map correspond to the entries of `$map`, excluding entries supplied via `$keys`. No failure occurs if the input map contains no entry with the supplied keys; the input map is returned unchanged.

Examples	• `map:remove($week, 4)` creates `map { 0: "Sun", 1: "Mon", 2: "Tue", 3: "Wed", 5: "Fri", 6: "Sat" }`. • `map:remove($week, 23)` creates `map { 0: "Sun", 1: "Mon", 2: "Tue", 3: "Wed", 4: "Thu", 5: "Fri", 6: "Sat" }`.

map:size

Signatures	`map:size($map as map(*)) as xs:integer`
Summary	Returns a the number of entries in the supplied map. The function takes the supplied `$map` and returns the number of entries that are present in the map.
Examples	• `map:size(map:merge(()))` returns `0`. • `map:size(map { "true": 1, "false": 0 })` returns `2`.

Changelog

Version 8.6

- Added: map:find
- Updated: map:merge: Signature extended with options argument. By default, value of first key is now adopted.

Version 8.4

- Removed: map:serialize (use fn:serialize instead)

Version 8.0

- Added: map:for-each, map:merge, map:put
- Removed: support for collations (in accordance with the XQuery 3.1 spec).
- Removed: `map:new` (replaced with `map:merge`)
- Updated: aligned with latest specification: compare keys of type `xs:untypedAtomic` as `xs:string` instances, store `xs:float` or `xs:double` value `NaN`.
- Introduction on maps is now found in the article on XQuery 3.1.

Version 7.8

- Updated: map syntax `map { 'key': 'value' }`
- Added: map:serialize

Version 7.7.1

- Updated: alternative map syntax without `map` keyword and `:` as key/value delimiter (e.g.: `{ 'key': 'value' }`)

Chapter 57. Math Module

Read this entry online in the BaseX Wiki.

The math XQuery Module defines functions to perform mathematical operations, such as `pi`, `asin` and `acos`. Most functions are specified in the Functions and Operators Specification of the upcoming XQuery 3.0 Recommendation, and some additional ones have been added in this module.

Conventions

All functions in this module are assigned to the `http://www.w3.org/2005/xpath-functions/math` namespace, which is statically bound to the `math` prefix.

W3 Functions

math:pi

Signatures	`math:pi() as xs:double`
Summary	Returns the `xs:double` value of the mathematical constant π whose lexical representation is 3.141592653589793.
Examples	• `2*math:pi()` returns `6.283185307179586e0`. • `60 * (math:pi() div 180)` converts an angle of 60 degrees to radians.

math:sqrt

Signatures	`math:sqrt($arg as xs:double?) as xs:double?`
Summary	Returns the square root of `$arg`.If `$arg` is the empty sequence, the empty sequence is returned.Otherwise the result is the `xs:double` value of the mathematical square root of `$arg`.

math:sin

Signatures	`math:sin($arg as xs:double?) as xs:double?`
Summary	Returns the sine of the `$arg`, expressed in radians.If `$arg` is the empty sequence, the empty sequence is returned.Otherwise the result is the sine of `$arg`, treated as an angle in radians.

math:cos

Signatures	`math:cos($arg as xs:double?) as xs:double?`
Summary	Returns the cosine of `$arg`, expressed in radians.If `$arg` is the empty sequence, the empty sequence is returned.Otherwise the result is the cosine of `$arg`, treated as an angle in radians.

math:tan

Signatures	`math:tan($arg as xs:double?) as xs:double?`
Summary	Returns the tangent of `$arg`, expressed in radians.If `$arg` is the empty sequence, the empty sequence is returned.Otherwise the result is the tangent of `$arg`, treated as an angle in radians.

math:asin

Signatures	`math:asin($arg as xs:double?) as xs:double?`

Summary	Returns the arc sine of `$arg`.If `$arg` is the empty sequence, the empty sequence is returned.Otherwise the result is the arc sine of `$arg`, returned as an angle in radians in the range $-\pi/2$ to $+\pi/2$.

math:acos

Signatures	`math:acos($arg as xs:double?) as xs:double?`
Summary	Returns the arc cosine of `$arg`.If `$arg` is the empty sequence, the empty sequence is returned.Otherwise the result is the arc cosine of `$arg`, returned as an angle in radians in the range 0 to $+\pi$.

math:atan

Signatures	`math:atan($arg as xs:double?) as xs:double?`
Summary	Returns the arc tangent of `$arg`.If `$arg` is the empty sequence, the empty sequence is returned.Otherwise the result is the arc tangent of `$arg`, returned as an angle in radians in the range $-\pi/2$ to $+\pi/2$.

math:atan2

Signatures	`math:atan2($arg1 as xs:double?, $arg2 as xs:double) as xs:double?`
Summary	Returns the arc tangent of `$arg1` divided by `$arg2`, the result being in the range $-\pi/2$ to $+\pi/2$ radians.If `$arg1` is the empty sequence, the empty sequence is returned.Otherwise the result is the arc tangent of `$arg1` divided by `$arg2`, returned as an angle in radians in the range $-\pi$ to $+\pi$.

math:pow

Signatures	`math:pow($arg1 as xs:double?, $arg2 as xs:double) as xs:double?`
Summary	Returns `$arg1` raised to the power of `$arg2`.If `$arg1` is the empty sequence, the empty sequence is returned.Otherwise the result is the `$arg1` raised to the power of `$arg2`.
Examples	• `math:pow(2, 3)` returns `8`.

math:exp

Signatures	`math:exp($arg as xs:double?) as xs:double?`
Summary	Returns *e* raised to the power of `$arg`.If `$arg` is the empty sequence, the empty sequence is returned.Otherwise the result is the value of *e* raised to the power of `$arg`.
Examples	• `math:exp(1)` returns *e*.

math:log

Signatures	`math:log($arg as xs:double?) as xs:double?`
Summary	Returns the natural logarithm of `$arg`.If `$arg` is the empty sequence, the empty sequence is returned.Otherwise the result is the natural logarithm (base *e*) of `$arg`.
Examples	• `math:log(math:e())` returns `1`.

math:log10

Signatures	`math:log10($arg as xs:double?) as xs:double?`
Summary	Returns the base 10 logarithm of `$arg`.If `$arg` is the empty sequence, the empty sequence is returned.Otherwise the result is the base 10 logarithm of `$arg`.
Examples	• `math:log(100)` returns `2`.

Additional Functions

math:e

Signatures	`math:e() as xs:double`
Summary	Returns the `xs:double` value of the mathematical constant *e* whose lexical representation is 2.718281828459045.
Examples	• `5*math:e()` returns `13.591409142295225`.

math:sinh

Signatures	`math:sinh($arg as xs:double?) as xs:double?`
Summary	Returns the hyperbolic sine of `$arg`.If `$arg` is the empty sequence, the empty sequence is returned.Otherwise the result is the hyperbolic sine of `$arg`.
Examples	• `math:sinh(0)` returns `0`.

math:cosh

Signatures	`math:cosh($arg as xs:double?) as xs:double?`
Summary	Returns the hyperbolic cosine of `$arg`.If `$arg` is the empty sequence, the empty sequence is returned.Otherwise the result is the hyperbolic cosine of `$arg`.
Examples	• `math:cosh(0)` returns `1`.

math:tanh

Signatures	`math:tanh($arg as xs:double?) as xs:double?`
Summary	Returns the hyperbolic tangent of `$arg`.If `$arg` is the empty sequence, the empty sequence is returned.Otherwise the result is the hyperbolic tangent of `$arg`.
Examples	• `math:tanh(100)` returns `1`.

math:crc32

Signatures	`math:crc32($str as xs:string) as xs:hexBinary`
Summary	Calculates the CRC32 check sum of the given string `$str`.
Examples	• `math:crc32("")` returns `'00000000'`. • `math:crc32("BaseX")` returns `'4C06FC7F'`.

Changelog

Version 7.5

- Moved: math:random and math:uuid have been move to Random Module.

Version 7.3

- Added: math:crc32 and math:uuid have been adopted from the obsolete Utility Module.

Chapter 58. Output Module

Read this entry online in the BaseX Wiki.

This XQuery Module contains functions for simplifying formatted data output.

Conventions

Updated with Version 9.0:

All functions and errors in this module are assigned to the `http://basex.org/modules/out` namespace, which is statically bound to the `out` prefix.

Functions

out:cr

Intrduced with Version 9.0:

Signatures	`out:cr() as xs:string`
Summary	Returns a single carriage return character (`
`).

out:nl

Signatures	`out:nl() as xs:string`
Summary	Returns a single newline character (`
`).

out:tab

Signatures	`out:tab() as xs:string`
Summary	Returns a single tabulator character (` `).

out:format

Signatures	`out:format($format as xs:string, $item1 as item(), ...) as xs:string`
Summary	Returns a formatted string. `$item1` and all following items are applied to the `$format` string, according to Java's printf syntax.
Errors	`format`: The specified format is not valid.
Examples	• `out:format("%b", true())` returns `true`. • `out:format("%06d", 256)` returns `000256`. • `out:format("%e", 1234.5678)` returns `1.234568e+03`.

Errors

Updated with Version 9.0:

Code	Description
`format`	The specified format is not valid.

Changelog

Version 9.0

- Added: out:cr
- Updated: error codes updated; errors now use the module namespace

Introduced with Version 7.3. Functions have been adopted from the obsolete Utility Module.

Chapter 59. Process Module

Read this entry online in the BaseX Wiki.

This XQuery Module provides functions for executing system commands from XQuery.

Conventions

Updated with Version 9.0:

All functions and errors in this module are assigned to the `http://basex.org/modules/proc` namespace, which is statically bound to the `proc` prefix.

Functions

proc:system

Updated with Version 9.0: new `input` option; revised error handling.

Signatures	`proc:system($cmd as xs:string) as xs:string` `proc:system($cmd as xs:string, $args as xs:string*) as xs:string` `proc:system($cmd as xs:string, $args as xs:string*, $options as map(xs:string, xs:string)) as xs:string`
Summary	Executes the specified command in a separate process and returns the result as string. `$cmd` is the name of the command, arguments to the command may be specified via `$args`. The `$options` parameter contains process options: • `encoding` : convert result to the specified encoding. If no encoding is supplied, the system's default encoding is used. • `timeout` : abort process execution after the specified number of seconds. • `dir` : process command in the specified directory. • `input` : standard string input (`stdin`) to be passed on to the command.
Errors	`encoding`: the specified encoding does not exist or is not supported.`timeout`: the specified timeout was exceeded.`error`: the command could not be executed, or an I/O exception was raised.`code...`: If the commands returns an exit code different to 0, an error will be raised. Its code will consist of the letters `code` and four digits with the exit code.

Examples	• `proc:system('date')` returns the current date on a Linux system.
	• Analyses the given input and counts the number of lines, words and characters (provided that `wc` is available on the system):
	`proc:system( 'wc', (), map { 'input': 'A B' || out:nl() || 'C' } )`
	• The following example returns "Command not found" (unless `xyz` is a valid command on the system):
	`try { proc:system('xyz') } catch proc:error { 'Command not found: ' || $err:description`

```
}
```

proc:execute

Signatures	`proc:execute($cmd as xs:string) as element(result)` `proc:execute($cmd as xs:string, $args as xs:string*) as element(result)` `proc:execute($cmd as xs:string, $args as xs:string*, $options as map(xs:string, xs:string)) as element(result)`

Summary	Executes the specified command in a separate process and returns the result as element:
	• `$cmd` is the name of the command, and arguments to the command may be specified via `$args`.
	• The same `$options` are allowed as for proc:system.
	• Instead of the `proc:error` error, the error message and process code will be assigned to the returned elements.
	• Instead of the `proc:code...` error, the error message will be assigned to the returned element (no process code will be returned).
	The result has the following structure:
	`<result>`
	`  <output>...output...</output>`
	`  <error>...error message...</error>`
	`  <code>...process code...</code>`
	`</result>`

Errors	`encoding`: the specified encoding does not exist or is not supported.`timeout`: the specified timeout was exceeded.
Examples	• `proc:execute('dir', '\')` returns the files of the root directory of a Windows system. • `proc:execute('ls', ('-l', '-a'))` executes the `ls -la` command on Unix systems.

proc:fork

Introduced with Version 9.0:

Signatures	`proc:fork($cmd as xs:string) as element(result)` `proc:fork($cmd as xs:string, $args as xs:string*) as element(result)` `proc:fork($cmd as xs:string, $args as xs:string*, $options as map(xs:string, xs:string)) as element(result)`
Summary	Executes the specified command and ignores the result. `$cmd` is the name of the command, and arguments to the command may be specified via `$args`. The same `$options` are allowed as for proc:system (but the encoding will be ignored).
Errors	`encoding`: the specified encoding does not exist or is not supported.
Examples	• `proc:fork('sleep', '5')` : sleep for 5 seconds (no one should notice).

proc:property

Signatures	`proc:property($name as xs:string) as xs:string?`
Summary	Returns the system property, specified by `$name`, or a context parameter of the `web.xml` file with that name (see Web Applications). An empty sequence is returned if the property does not exist. For environment variables of the operating system, please use fn:environment-variable.

Examples	• `map:merge(proc:property-names() ! map:entry(., proc:property(.)))` returns a map with all system properties.

proc:property-names

Signatures	`proc:property-names() as xs:string*`
Summary	Returns the names of all Java system properties and context parameters of the `web.xml` file (see Web Applications). For environment variables of the operating system, please use fn:available-environment-variables.
Examples	• `proc:property('java.runtime.version')` returns the version of the Java runtime engine.

Errors

Updated with Version 9.0:

Code	Description
`code...`	The result of a command call with an exit code different to 0.
`code9999`	A command could not be executed.
`encoding`	The specified encoding does not exist or is not supported.
`timeout`	The specified timeout was exceeded.

Changelog

Version 9.0

- Added: proc:fork
- Updated: error codes; errors now use the module namespace
- Updated: new `input` option; revised error handling

Version 8.6

- Updated: proc:system, proc:exec: `encoding` option moved to options argument, `timeout` and `dir` options added.

Version 8.3

- Added: proc:property, proc:property-names.

The module was introduced with Version 7.3.

Chapter 60. Profiling Module

Read this entry online in the BaseX Wiki.

This XQuery Module contains various functions to test and profile code, and to dump information to standard output.

Conventions

All functions and errors in this module are assigned to the `http://basex.org/modules/prof` namespace, which is statically bound to the `prof` prefix.

Performance Functions

prof:track

Introduced with Version 9.0:

Signatures	`prof:track($expression as item()) as item()*` `prof:track($expression as item(), $options as map(*)?) as item()*`
Summary	Measures the execution time and memory consumption required for evaluating the specified `$expression` and returns a map with the results. The following `$options` are available: • `memory` : Include memory consumption in result (unit: bytes; default: true). • `time` : Include execution time in result (unit: milliseconds; default: true). • `value` : Include value in result (default: true). Helpful notes: • If you are not interested in some of the returned results, you should disable them to save time and memory. • Profiling might change the execution behavior of your code: An expression that might be executed iteratively will be cached by the profiling function. • If a value has a compact internal representation, memory consumption will be very low, even if the serialized result may consume much more memory. • Please note that memory profiling is only approximative, so it can be quite misleading. If the memory option is enabled, main-memory will be garbage-collected before and after evaluation to improve the quality of the measurement.
Properties	The function is *non-deterministic*: evaluation order will be preserved by the compiler.

Examples	• Return a human-readable representation of the memory consumption caused by fetching an XML document (`fetch:xml` is used, as `fn:doc` may already be evaluated at compilation time):
	`prof:track(fetch:xml('factbook.xml'))?memory`
	`=> prof:human()`
	• The function call `prof:track((1 to 1000000)[. mod 2 = 0], map { 'time': false() })` will return something similar to:
	`map {`
	`  "memory": 21548400,`
	`  "value": (2, 4, 6, 8, 10, ...)`

```
}
```

prof:time

Updated with Version 9.0: `$cache` argument removed.

Signatures	`prof:time($expr as item()) as item()*` `prof:time($expr as item(), $label as xs:string) as item()*`
Summary	Measures the time needed to evaluate `$expr` and outputs a string to standard error or, if the GUI is used, to the Info View. An optional `$label` may be specified to tag the profiling result. See prof:track for further notes.
Properties	The function is *non-deterministic*: evaluation order will be preserved by the compiler.
Examples	• `prof:time(prof:sleep(1000))` outputs something similar to `1000.99 ms`.

prof:memory

Updated with Version 9.0: Renamed (old name: `prof:mem`); `$cache` argument removed.

Signatures	`prof:memory($expr as item()) as item()*` `prof:memory($expr as item(), $label as xs:string) as item()*`
Summary	Measures the memory allocated by evaluating `$expr` and outputs a string to standard error or, if the GUI is used, to the Info View. An optional `$label` may be specified to tag the profiling result. See prof:track for further notes.
Properties	The function is *non-deterministic*: evaluation order will be preserved by the compiler.
Examples	• `prof:memory((1 to 100000) ! <a/>)` will output something similar to `5620 kB`.

prof:current-ms

Signatures	`prof:current-ms() as xs:integer`
Summary	Returns the number of milliseconds passed since 1970/01/01 UTC. The granularity of the value depends on the underlying operating system and may be larger. For example, many operating systems measure time in units of tens of milliseconds.
Properties	In contrast to `fn:current-time()`, the function is *non-deterministic* and returns different values every time it is called. Its evaluation order will be preserved by the compiler.
Examples	• `convert:integer-to-dateTime(prof:current-ms())` returns the current miliseconds in the `xs:dateTime` format.

prof:current-ns

Signatures	`prof:current-ns() as xs:integer`
Summary	Returns the current value of the most precise available system timer in nanoseconds.
Properties	In contrast to `fn:current-time()`, the function is *non-deterministic* and returns different values every time it is called. Its evaluation order will be preserved by the compiler.
Examples	Measures the time of an expression:

```
let $ns1 := prof:current-ns()
return (
  (: process to measure :)
  (1 to 1000000)[. = 0],
  let $ns2 := prof:current-ns()
  let $ms := (($ns2 - $ns1) idiv 10000) div 100)
  return $ms || ' ms'
)
```

Debugging Functions

prof:dump

Signatures	`prof:dump($expr as item()) as empty-sequence()` `prof:dump($expr as item(), $label as xs:string) as empty-sequence()`
Summary	Dumps a serialized representation of `$expr` to `STDERR`, optionally prefixed with `$label`, and returns an empty sequence. If the GUI is used, the dumped result is shown in the Info View.
Properties	In contrast to `fn:trace()`, the consumed expression will not be passed on.

prof:variables

Signatures	`prof:variables() as empty-sequence()`
Summary	Prints a list of all current local and global variable assignments to standard error or, if the GUI is used, to the Info View.As every query is optimized before being evaluated, not all of the original variables may be visible in the output. Moreover, many variables of function calls will disappear because functions are inlined. Function inlining can be turned off by setting the INLINELIMIT option to `0`.
Properties	The function is *non-deterministic*: evaluation order will be preserved by the compiler.
Examples	• `for $x in 1 to 2 return prof:variables()` will dump the values of `$x` to standard error.

prof:type

Signatures	`prof:type($expr as item()*) as item()*`
Summary	Similar to `fn:trace($expr, $msg)`, but instead of a user-defined message, it emits the compile-time type and estimated result size of its argument.

Helper Functions

prof:void

Signatures	`prof:void($value as item()*) as empty-sequence()`
Summary	Swallows all items of the specified `$value` and returns an empty sequence. This function is helpful if some code needs to be evaluated and if the actual result is irrelevant.
Properties	The function is *non-deterministic*: evaluation order will be preserved by the compiler.
Examples	• `prof:void(fetch:binary('http://my.rest.service'))` performs an HTTP request and ignores the result.

prof:sleep

Signatures	`prof:sleep($ms as xs:integer) as empty-sequence()`
Summary	Sleeps for the specified number of milliseconds.
Properties	The function is *non-deterministic*: evaluation order will be preserved by the compiler.

prof:human

Signatures	`prof:human($number as xs:integer) as xs:string`
Summary	Returns a human-readable representation of the specified `$number`.
Example	• `prof:human(16384)` returns `16K`.

Changelog

Version 9.0

- Added: prof:track
- Updated: renamed prof:mem to prof:memory

Version 8.5

- Added: prof:type (moved from XQuery Module)

Version 8.1

- Added: prof:variables

Version 7.7

- Added: prof:void

Version 7.6

- Added: prof:human

Version 7.5

- Added: prof:dump, prof:current-ms, prof:current-ns

This module was introduced with Version 7.3.

Chapter 61. Random Module

Read this entry online in the BaseX Wiki.

This XQuery Module contains functions for computing random values. All functions except for random:seeded-double and random:seeded-integer are non-deterministic, i.#e., they return different values for each call.

Conventions

Updated with Version 9.0:

All functions and errors in this module are assigned to the `http://basex.org/modules/random` namespace, which is statically bound to the `random` prefix.

Functions

random:double

Signatures	`random:double() as xs:double`
Summary	Returns a double value between 0.0 (inclusive) and 1.0 (exclusive).

random:integer

Signatures	`random:integer() as xs:integer` `random:integer($max as xs:integer) as xs:integer`
Summary	Returns an integer value, either in the whole integer range or between 0 (inclusive) and the given maximum (exclusive)
Errors	`bounds`: the maximum value is out of bounds.

random:seeded-double

Signatures	`random:seeded-double($seed as xs:integer, $num as xs:integer) as xs:double*`
Summary	Returns a sequence with `$num` double values between 0.0 (inclusive) and 1.0 (exclusive). The random values are created using the initial seed given in `$seed`.

random:seeded-integer

Signatures	`random:seeded-integer($seed as xs:integer, $num as xs:integer) as xs:integer*` `random:seeded-integer($seed as xs:integer, $num as xs:integer, $max as xs:integer) as xs:integer*`
Summary	Returns a sequence with `$num` integer values, either in the whole integer range or between 0 (inclusive) and the given maximum (exclusive). The random values are created using the initial seed given in `$seed`.
Errors	`bounds`: the maximum value is out of bounds.`negative`: the number of values to be returned is negative.

random:gaussian

Signatures	`random:gaussian($num as xs:integer) as xs:double*`
Summary	Returns a sequence with `$num` double values. The random values are Gaussian (i.e. normally) distributed with the mean 0.0. and the derivation 1.0.

random:seeded-permutation

Signatures	`random:seeded-permutation($seed as xs:integer, $items as item()*) as item()*`
Summary	Returns a random permutation of the specified `$items`. The random order is created using the initial seed given in `$seed`.

random:uuid

Signatures	`random:uuid() as xs:string`
Summary	Creates a random universally unique identifier (UUID), represented as 128-bit value.
Examples	• `random:uuid() eq random:uuid()` will (most probably) return the boolean value `false`.

Errors

Updated with Version 9.0:

Code	Description
`bounds`	The specified maximum value is out of bounds.
`negative`	The specified number of values to be returned is negative.

Changelog

Version 9.0

- Updated: error codes updated; errors now use the module namespace

Version 8.5

- Added: random:seeded-permutation

Version 8.0

- Updated: random:integer, random:seeded-integer raise error for invalid input.

The module was introduced with Version 7.5. It includes some functionality which was previously located in the Math Module.

Chapter 62. Repository Module

Read this entry online in the BaseX Wiki.

This XQuery Module contains functions for installing, listing and deleting modules contained in the Repository.

Conventions

Updated with Version 9.0:

All functions and errors in this module are assigned to the `http://basex.org/modules/repo` namespace, which is statically bound to the `repo` prefix.

Functions

repo:install

Signatures	`repo:install($path as xs:string) as empty-sequence()`
Summary	Installs a package or replaces an existing package. The parameter `$path` indicates the path to the package.
Errors	`not-found`: a package does not exist.`descriptor`: the package descriptor is invalid.`installed`: the module contained in the package to be installed is already installed as part of another package.`parse`: an error occurred while parsing the package.`version`: the package version is not supported.

repo:delete

Signatures	`repo:delete($pkg as xs:string) as empty-sequence()`
Summary	Deletes a package. The parameter `$pkg` indicates the package name, optionally suffixed with a dash and the package version.
Errors	`not-found`: a package does not exist.`delete`: the package cannot be deleted.

repo:list

Signatures	`repo:list() as element(package)*`
Summary	Lists the names and versions of all currently installed packages.

Errors

Updated with Version 9.0:

Code	Description
`delete`	The package cannot be deleted because of dependencies, or because files are missing.
`descriptor`	The package descriptor is invalid.
`installed`	The module contained in the package to be installed is already installed as part of another package.
`not-found`	A package does not exist.
`parse`	An error occurred while parsing the package.
`version`	The package version is not supported.

Changelog

Version 9.0

- Updated: error codes updated; errors now use the module namespace

Version 7.2.1

- Updated: repo:install: existing packages will be replaced
- Updated: repo:delete: remove specific version of a package

Version 7.2

- Updated: repo:list now returns nodes

The module was introduced with Version 7.1.

Chapter 63. Request Module

Read this entry online in the BaseX Wiki.

This XQuery Module contains functions for retrieving information on an HTTP request that has triggered the query. It is mainly useful in the context of Web Applications.

The module is related to Adam Retter's EXQuery Request Module draft.

Conventions

- The `basex-api` package must be included in the classpath. This is always the case if you use one of the complete distributions (zip, exe, war) of BaseX.
- All functions are assigned to the `http://exquery.org/ns/request` namespace. The module must be imported in the query prolog:

```
import module namespace request = "http://exquery.org/ns/request";
...
```

- If any of the functions is called outside the servlet context, `basex:http` is raised.

The following example illustrated what components a URI may consist of (the example is derived from RFC 3986):

```
  foo://example.com:8042/over/there?name=ferret
  \_/   \_________/ \__/\_________/ \_________/
   |         |       |       |          |
scheme   hostname  port    path      query
```

General Functions

request:method

Signatures	`request:method() as xs:string`
Summary	Returns the Method of the HTTP request.

request:attribute

Signatures	`request:attribute($name as xs:string) as xs:string`
Summary	Returns the value of an attribute of the HTTP request. If the attribute does not exist, an empty sequence is returned.
Example	• `request:attribute("javax.servlet.error.request_uri")` returns the original URI of a caught error. • `request:attribute("javax.servlet.error.message")` returns the error message of a caught error.

URI Functions

request:scheme

Signatures	`request:scheme() as xs:string`
Summary	Returns the Scheme component of the URI of an HTTP request.
Example	For the example given in the introduction, this function would return `foo`.

request:hostname

Signatures	`request:hostname() as xs:string`
Summary	Returns the Hostname component of the URI of an HTTP request.
Example	For the example given in the introduction, this function would return `example.com`.

request:port

Signatures	`request:port() as xs:integer`
Summary	Returns the Port component of the URI of an HTTP request, or a default port if it has not been explicitly specified in the URI.
Example	For the example given in the introduction, this function would return `8042`.

request:path

Signatures	`request:path() as xs:string`
Summary	Returns the Path component of the URI of an HTTP request.
Example	For the example given in the introduction, this function would return `/over/there`.

request:query

Signatures	`request:query() as xs:string?`
Summary	Returns the Query component of the URI of an HTTP request. If no query has been specified, an empty sequence is returned.
Example	For the example given in the introduction, this function would return `name=ferret`.

request:uri

Signatures	`request:uri() as xs:anyURI`
Summary	Returns the complete URI of an HTTP request as it has been specified by the client.
Example	For the example given in the introduction, this method would return `foo://example.com:8042/over/there?name=ferret`.

request:context-path

Signatures	`request:context-path() as xs:string`
Summary	Returns the context of the request. For servlets in the default (root) context, this method returns an empty string.

Connection Functions

request:address

Signatures	`request:address() as xs:string`
Summary	Returns the IP address of the server.

request:remote-hostname

Signatures	`request:remote-hostname() as xs:string`
Summary	Returns the fully qualified hostname of the client that sent the request.

request:remote-address

Signatures	`request:remote-address() as xs:string`
Summary	Returns the IP address of the client that sent the request.

request:remote-port

Signatures	`request:remote-port() as xs:string`
Summary	Returns the TCP port of the client socket that triggered the request.

Parameter Functions

request:parameter-names

Signatures	`request:parameter-names() as xs:string*`
Summary	Returns the names of all query and form field parameters available from the HTTP request. With RESTXQ, this function can be used to access parameters that have not been statically bound by %rest:query-param.
Example	For the example given in the introduction, this function would return `name`.

request:parameter

Signatures	`request:parameter($name as xs:string) as xs:string*` `request:parameter($name as xs:string, $default as xs:string) as xs:string*`
Summary	Returns the value of the named query or form field parameter in an HTTP request. If the parameter does not exist, an empty sequence or the optionally specified default value is returned instead. If both query and form field parameters with the same name exist, the form field values will be attached to the query values.
Example	For the example given in the introduction, the function call `request:parameter('name')` would return `ferret`.

Header Functions

request:header-names

Signatures	`request:header-names() as xs:string*`
Summary	Returns the names of all headers available from the HTTP request. If RESTXQ is used, this function can be used to access headers that have not been statically bound by %rest:header-param.

request:header

Signatures	`request:header($name as xs:string) as xs:string?` `request:header($name as xs:string, $default as xs:string) as xs:string`
Summary	Returns the value of the named header in an HTTP request. If the header does not exist, an empty sequence or the optionally specified default value is returned instead.

Cookie Functions

request:cookie-names

Signatures	`request:cookie-names() as xs:string*`

Summary	Returns the names of all cookies in the HTTP headers available from the HTTP request. If RESTXQ is used, this function can be used to access cookies that have not been statically bound by %rest:cookie-param.

request:cookie

Signatures	`request:cookie($name as xs:string) as xs:string*` `request:cookie($name as xs:string, $default as xs:string) as xs:string`
Summary	Returns the value of the named Cookie in an HTTP request. If there is no such cookie, an empty sequence or the optionally specified default value is returned instead.

Changelog

Version 7.9

- Updated: The returned values of request:parameter-names, request:parameter now also include form field parameters.

Version 7.8

- Added: request:context-path

Version 7.7

- Added: request:attribute

This module was introduced with Version 7.5.

Chapter 64. RESTXQ Module

Read this entry online in the BaseX Wiki.

This XQuery Module contains helper functions for the RESTXQ API, some of which are defined in the RESTXQ Draft.

Conventions

- The `basex-api` package must be included in the classpath. This is always the case if you use one of the complete distributions (zip, exe, war) of BaseX.
- All functions are assigned to the `http://exquery.org/ns/restxq` namespace. The module must be imported in the query prolog:

```
import module namespace rest = "http://exquery.org/ns/restxq";
...
```

- The `http://wadl.dev.java.net/2009/02` namespace is bound to the `wadl` prefix.
- If any of the functions is called outside the servlet context, `basex:http` is raised.

General Functions

rest:base-uri

Signatures	`rest:base-uri() as xs:anyURI`
Summary	Returns the implementation-defined base URI of the resource function.

rest:uri

Signatures	`rest:uri() as xs:anyURI`
Summary	Returns the complete URI that addresses the Resource Function. This is the result of rest:base-uri appended with the path from the path annotation of the resource function.

rest:wadl

Signatures	`rest:wadl() as element(wadl:application)`
Summary	Returns a WADL description of all available REST services.

rest:init

Signatures	`rest:init() as empty-sequence()`
Summary	Initializes the RESTXQ module cache. This function should be called after RESTXQ modules have been replaced while the web server is running, and if `PARSERESTXQ` is not set to `0`.

Changelog

Version 8.6

- Added: rest:init

This module was introduced with Version 7.7.

Chapter 65. Session Module

Read this entry online in the BaseX Wiki.

This XQuery Module contains functions for accessing and modifying server-side session information. This module is mainly useful in the context of Web Applications.

Conventions

Updated with Version 9.0:

- The `basex-api` package must be included in the classpath. This is always the case if you use one of the complete distributions (zip, exe, war) of BaseX.
- All functions and errors are assigned to the `http://basex.org/modules/session` namespace. The module must be imported in the query prolog:

```
import module namespace session = "http://basex.org/modules/session";
...
```

- If any of the functions is called outside the servlet context, `basex:http` is raised.
- As sessions are side-effecting operations, all functions are flagged as *non-deterministic*. As a result, the functions will not be reordered by the compiler.

Functions

session:id

Signatures	`session:id() as xs:string`
Summary	Returns the session ID of a servlet request.
Examples	Running the server-side XQuery file `id.xq` via `http://localhost:8984/id.xq`:

```
import module namespace session = "http://basex.org/modules/session";
'Session ID: ' || session:id()
```

session:created

Signatures	`session:created() as xs:dateTime`
Summary	Returns the creation time of a session.

session:accessed

Signatures	`session:accessed() as xs:dateTime`
Summary	Returns the last access time of a session.

session:names

Signatures	`session:names() as xs:string*`
Summary	Returns the names of all variables bound to the current session.
Examples	Running the server-side XQuery file `names.xq` via `http://localhost:8984/names.xq`:

```
import module namespace session = "http://basex.org/modules/session";
session:names() ! element variable { . }
```

session:get

Signatures	`session:get($name as xs:string) as item()* session:get($name as xs:string, $default as item()*) as item()*`
Summary	Returns the value of `$name` bound to the current session. If the specified variable is unknown, an empty sequence or the optionally specified default value is returned instead.
Errors	`get`: the value of a session variable could not be retrieved.
Examples	Running the server-side XQuery file `get.xq` via `http://localhost:8984/get.xq?key=user`:

```
import module namespace session = "http://basex.org/modules/session";
'Value of ' || $key || ': ' || session:get($key)
```

session:set

Signatures	`session:set($name as xs:string, $value as item()*) as empty-sequence()`
Summary	Binds the specified name/value pair to a session.
Errors	`set`: a function item was specified as value of a session variable.
Examples	Running the server-side XQuery file `set.xq` via `http://localhost:8984/set.xq?key=user&value=john`:

```
import module namespace session = "http://basex.org/modules/session";
session:set($key, $value), 'Variable was set.'
```

session:delete

Signatures	`session:delete($name as xs:string) as empty-sequence()`
Summary	Deletes a session value bound to `$name`.
Examples	Running the server-side XQuery file `delete.xq` via `http://localhost:8984/delete.xq?key=user`:

```
import module namespace session = "http://basex.org/modules/session";
session:delete($key), 'Variable was deleted.'
```

session:close

Signatures	`session:close() as empty-sequence()`
Summary	Unregisters a session and all data associated with it.

Errors

Updated with Version 9.0:

Code	Description
`get`	The stored attribute is no XQuery value.
`set`	Function items cannot be stored.

Changelog

Version 9.0

- Updated: error codes updated; errors now use the module namespace

Version 8.0

- Updated: Allow sequences as session values.

This module was introduced with Version 7.5.

Chapter 66. Sessions Module

Read this entry online in the BaseX Wiki.

This XQuery Module can only be called from users with *Admin* permissions. It contains functions for accessing and modifying all registered server-side sessions. This module is mainly useful in the context of Web Applications.

Conventions

Updated with Version 9.0:

- The `basex-api` package must be included in the classpath. This is always the case if you use one of the complete distributions (zip, exe, war) of BaseX.
- All functions and errors are assigned to the `http://basex.org/modules/sessions` namespace. The module must be imported in the query prolog:

```
import module namespace sessions = "http://basex.org/modules/sessions";
...
```

- If any of the functions is called outside the servlet context, `basex:http` is raised.
- If the requested session is not found, `not-found` is raised.
- As sessions are side-effecting operations, all functions are flagged as *non-deterministic*. This means that the functions will not be reordered by the compiler.

Functions

sessions:ids

Signatures	`sessions:ids() as xs:string`
Summary	Returns the IDs of all registered sessions.

sessions:created

Signatures	`sessions:created($id as xs:string) as xs:dateTime`
Summary	Returns the creation time of the session specified by `$id`.

sessions:accessed

Signatures	`sessions:accessed($id as xs:string) as xs:dateTime`
Summary	Returns the last access time of the session specified by `$id`.

sessions:names

Signatures	`sessions:names($id as xs:string) as xs:string*`
Summary	Returns the names of all variables bound to the session specified by `$id`.

sessions:get

Signatures	`sessions:get($id as xs:string, $key as xs:string) as item()*` `sessions:get($id as xs:string, $key as xs:string, $default as item()*) as item()*`

Summary	Returns the value of a variable bound to the session specified by `$id`. If the variable does not exist, or if the key is unknown, an empty sequence or the optionally specified default value is returned instead.
Errors	`get`: the value of a session variable could not be retrieved.

sessions:set

Signatures	`sessions:set($id as xs:string, $key as xs:string, $value as item()*) as empty-sequence()`
Summary	Binds the specified key/value pair to the session specified by `$id`.
Errors	`set`: a function item was specified as value of a session variable.

sessions:delete

Signatures	`sessions:delete($id as xs:string, $key as xs:string) as empty-sequence()`
Summary	Deletes a variable bound to the session specified by `$id`.

sessions:close

Signatures	`sessions:close($id as xs:string) as empty-sequence()`
Summary	Unregisters the session specified by `$id`.

Errors

Updated with Version 9.0:

Code	Description
`get`	The stored attribute is no XQuery value.
`set`	Function items cannot be stored.
`not-found`	The specified session was not found.

Changelog

Version 9.0

- Updated: error codes updated; errors now use the module namespace

Version 8.4

- Updated: Allow sequences as session values.

This module was introduced with Version 7.5.

Chapter 67. SQL Module

Read this entry online in the BaseX Wiki.

This XQuery Module contains functions to access relational databases from XQuery using SQL. With this module, you can execute query, update and prepared statements, and the result sets are returned as sequences of XML elements representing tuples. Each element has children representing the columns returned by the SQL statement.

This module uses JDBC to connect to a SQL server. Hence, your JDBC driver will need to be added to the classpath, too. If you work with the full distributions of BaseX, you can copy the driver into the `lib` directory. To connect to MySQL, for example, download the Connector/J Driver and extract the archive into this directory.

Conventions

Updated with Version 9.0:

All functions and errors in this module are assigned to the `http://basex.org/modules/sql` namespace, which is statically bound to the `sql` prefix.

Functions

sql:init

Signatures	`sql:init($class as xs:string) as empty-sequence()`
Summary	This function initializes a JDBC driver specified via `$class`. This step might be superfluous if the SQL database is not embedded.
Errors	`init`: the specified driver is not found.

sql:connect

Signatures	`sql:connect($url as xs:string) as xs:anyURI` `sql:connect($url as xs:string, $user as xs:string, $password as xs:string) as xs:anyURI` `sql:connect($url as xs:string, $user as xs:string, $password as xs:string, $options as map(*)?) as xs:anyURI`
Summary	This function establishes a connection to a relational database and returns a connection id. The parameter `$url` is the URL of the database and shall be of the form: `jdbc:<driver name>:[//<server>[/<database>]]`. If the parameters `$user` and `$password` are specified, they are used as credentials for connecting to the database. The `$options` parameter can be used to set connection options.
Errors	`error`: an SQL exception occurred when connecting to the database.
Examples	Connects to an SQL Server and sets autocommit to `true`: `sql:connect('dbc:sqlserver://DBServer', map { 'autocommit': true() })`

sql:execute

Updated with Version 9.0: Return update count for updating statements. `$options` argument added.

Signatures	`sql:execute($id as xs:anyURI, $statement as xs:string) as item()*` `sql:execute($id as xs:anyURI, $statement as xs:string, $options as map(*)?) as item()*`
Summary	This function executes an SQL `$statement`, using the connection with the specified `$id`. The returned result depends on the kind of statement:

	• If an update statement was executed, the number of updated rows will be returned as integer. • Otherwise, an XML representation of all results will be returned. With `$options`, the following parameter can be set: • `timeout` : query execution will be interrupted after the specified number of seconds.
Errors	`error`: an error occurred while executing SQL.`id`: the specified connection does not exist.`timeout`: query execution exceeded timeout.

sql:execute-prepared

Updated with Version 9.0: Return update count for updating statements.

Signatures	`sql:execute-prepared($id as xs:anyURI, $params as element(sql:parameters)) as item()* sql:execute-prepared($id as xs:anyURI, $params as element(sql:parameters), $options as map(*)?) as item()*`
Summary	This function executes a prepared statement with the specified `$id`. The output format is identical to sql:execute. The optional parameter `$params` is an element `<sql:parameters/>` representing the parameters for a prepared statement along with their types and values. The following schema shall be used: `element sql:parameters { element sql:parameter { attribute type { "int" | "string" | "boolean" | "date" | "double" | "float" | "short" | "time" | "timestamp" | "sqlxml" }, attribute null { "true" | "false" }?, text }+ }?` With `$options`, the following parameter can be set: • `timeout` : query execution will be interrupted after the specified number of seconds.
Errors	`attribute`: an attribute different from `type` and `null` is set for a `<sql:parameter/>` element.`error`: an error occurred while executing SQL.`id`: the specified connection does not exist.`parameters`: no parameter type specified.`timeout`: query execution exceeded timeout.`type`: the value of a parameter cannot be converted to the specified format.

sql:prepare

Signatures	`sql:prepare($id as xs:anyURI, $statement as xs:string) as xs:anyURI`
Summary	This function prepares an SQL `$statement`, using the specified connection `$id`, and returns the id reference to this statement. The statement is a string with one or more '?' placeholders. If the value of a field has to be set to `NULL`, then the attribute `null` of the `<sql:parameter/>` element must be `true`.
Errors	`error`: an error occurred while executing SQL.`id`: the specified connection does not exist.

sql:commit

Signatures	`sql:commit($id as xs:anyURI) as empty-sequence()`
Summary	This function commits the changes made to a relational database, using the specified connection `$id`.
Errors	`error`: an error occurred while executing SQL.`id`: the specified connection does not exist.

sql:rollback

Signatures	`sql:rollback($id as xs:anyURI) as empty-sequence()`
Summary	This function rolls back the changes made to a relational database, using the specified connection `$id`.
Errors	`error`: an error occurred while executing SQL.`id`: the specified connection does not exist.

sql:close

Signatures	`sql:close($id as xs:anyURI) as empty-sequence()`
Summary	This function closes a database connection with the specified `$id`.Opened connections will automatically be closed after the XQuery expression has been evaluated, but in order to save memory, it is always recommendable to close connections that are not used anymore.
Errors	`error`: an error occurred while executing SQL.`id`: the specified connection does not exist.

Examples

Direct queries

A simple select statement can be executed as follows:

```
let $id := sql:connect("jdbc:postgresql://localhost:5432/coffeehouse")
return sql:execute($id, "SELECT * FROM coffees WHERE price < 10")
```

The result may look like:

```
<sql:row xmlns:sql="http://basex.org/modules/sql">
  <sql:column name="cof_name">French_Roast</sql:column>
  <sql:column name="sup_id">49</sql:column>
  <sql:column name="price">9.5</sql:column>
  <sql:column name="sales">15</sql:column>
  <sql:column name="total">30</sql:column>
</sql:row>
<sql:row xmlns:sql="http://basex.org/modules/sql">
  <sql:column name="cof_name">French_Roast_Decaf</sql:column>
  <sql:column name="sup_id">49</sql:column>
  <sql:column name="price">7.5</sql:column>
  <sql:column name="sales">10</sql:column>
  <sql:column name="total">14</sql:column>
</sql:row>
```

Prepared Statements

A prepared select statement can be executed in the following way:

```
(: Establish a connection :)
let $conn := sql:connect("jdbc:postgresql://localhost:5432/coffeehouse")
(: Obtain a handle to a prepared statement :)
let $prep := sql:prepare($conn, "SELECT * FROM coffees WHERE price < ? AND cof_name
 = ?")
(: Values and types of prepared statement parameters :)
let $params := <sql:parameters>
                 <sql:parameter type='double'>10</sql:parameter>
                 <sql:parameter type='string'>French_Roast</sql:parameter>
               </sql:parameters>
(: Execute prepared statement :)
return sql:execute-prepared($prep, $params)
```

SQLite

The following expression demonstrates how SQLite can be addressed using the Xerial SQLite JDBC driver:

```
(: Initialize driver :)
sql:init("org.sqlite.JDBC"),
(: Establish a connection :)
let $conn := sql:connect("jdbc:sqlite:database.db")
return (
  (: Create a new table :)
  sql:execute($conn, "drop table if exists person"),
  sql:execute($conn, "create table person (id integer, name string)"),
  (: Run 10 updates :)
  for $i in 1 to 10
  let $q := "insert into person values(" || $i || ", '" || $i || "')"
  return sql:execute($conn, $q),
  (: Return table contents :)
  sql:execute($conn, "select * from person")
)
```

Errors

Updated with Version 9.0:

Code	Description
`attribute`	An attribute different from `type` and `null` is set for a `<sql:parameter/>` element.
`error`	An SQL exception occurred.
`id`	A connection does not exist.
`init`	A database driver is not found.
`parameters`	No parameter type specified.
`timeout`	Query execution exceeded timeout.
`type`	The value of a parameter cannot be converted to the specified format.

Changelog

Version 9.0

- Updated: sql:execute, sql:execute-prepared: Return update count for updating statements. `$options` argument added.
- Updated: Connection ids are URIs now.
- Updated: error codes updated; errors now use the module namespace

Version 7.5

- Updated: prepared statements are now executed via sql:execute-prepared

The module was introduced with Version 7.0.

Chapter 68. Strings Module

Read this entry online in the BaseX Wiki.

This XQuery Module contains functions for string computations.

Conventions

All functions and errors in this module and errors are assigned to the `http://basex.org/modules/strings` namespace, which is statically bound to the `strings` prefix.

Functions

strings:levenshtein

Signatures	`strings:levenshtein($string1 as xs:string, $string2 as xs:string) as xs:double`
Summary	Computes the Damerau-Levenshtein Distance for two strings and returns a double value (`0.0` - `1.0`). The returned value is computed as follows: • `1.0` – distance / max(length of strings) • `1.0` is returned if the strings are equal; `0.0` is returned if the strings are too different.

Examples	• `strings:levenshtein("flower", "flower")` returns `1`
	• `strings:levenshtein("flower", "lewes")` returns `0.5`
	• In the following query, the input is first normalized (words are stemmed, converted to lower case, and diacritics are removed). It returns `1`:
	`let $norm := ft:normalize(?, map { 'stemming': true() })`
	`return strings:levenshtein($norm("HOUSES"), $norm("house"))`

strings:soundex

Signatures	`strings:soundex($string as xs:string) as xs:string`
Summary	Computes the Soundex value for the specified string. The algorithm can be used to find and index English words with similar pronouncation.
Examples	• `strings:soundex("Michael")` returns `M240` • `strings:soundex("OBrien") = strings:soundex("O'Brien")` returns `true`

strings:cologne-phonetic

Signatures	`strings:cologne-phonetic($string as xs:string) as xs:string`
Summary	Computes the Kölner Phonetik value for the specified string. Similar to Soundex, the algorithm is used to find similarly pronounced words, but for the German language. As the first returned digit can be `0`, the value is returned as string.
Examples	• `strings:cologne-phonetic("Michael")` returns `645` • `every $s in ("Mayr", "Maier", "Meier") satisfies strings:cologne-phonetic($s) = "67"` returns `true`

Changelog

The Module was introduced with Version 8.3.

Chapter 69. Unit Module

Read this entry online in the BaseX Wiki.

This XQuery Module contains annotations and functions for performing XQUnit tests.

Introduction

The more complex a software application grows, the more error-prone it gets. This is why testing frameworks have been developed, which provide a standardized, automated way of testing software. The XUnit frameworks (such as SUnit or JUnit) allow testing of atomic units of a program, such as single functions and algorithms.

This module borrows heavily from the existing frameworks: it provides various annotations for testing XQuery functions. Unit functions are provided to assert the validity of arbitrary conditions expressed in XQuery and to raise errors whenever a condition is not satisfied. Some additional functions exist to run all unit tests of the current module or a set of specified library modules.

Usage

Tests are started via the TEST command. It compiles all XQuery modules in a given file or directory and runs all functions that are annotated with `%unit:test`. A test report is generated and returned, which resembles the format returned by other xUnit testing frameworks, such as the Maven Surefire Plugin (see below).

Conventions

All annotations, functions and errors in this module are assigned to the `http://basex.org/modules/unit` namespace, which is statically bound to the `unit` prefix.

Annotations

%unit:test

Syntax	`%unit:test` `%unit:test("expected", CODE)`
Summary	With this annotation, a function can be marked as unit test. It will be evaluated if a test report is created for the module in which this function is located.`error` can be supplied as additional string argument. It is followed by `CODE`, which must be a valid EQName string. If the function expression does not raise that error, the test will fail.

Examples	• The following test does will be successful, as it does nothing (and, hence, nothing wrong):
	`declare %unit:test function local:void() { () };`
	• The following test will be successful, as the function body will raise `err:XPTY0004`:
	`declare %unit:test('expected', "err:XPTY0004") function local:add() {`
	`  123 + 'strings and integers cannot be added'`
	`};`

%unit:before

Syntax	`%unit:before` `%unit:before(FUNCTION)`
Summary	A function decorated with this annotation will be evaluated **before each** unit test.`FUNCTION` can be supplied as additional argument. It must be a valid EQName string. If specified, the function will only be evaluated before a function with the given name is tested. This extension is e. g. helpful if the results of updates need to be tested.

Examples	• The first function will be evaluated before the actual test: `declare %updating %unit:before("local:check") function local:before-check() { db:create('test-db') }; declare %updating %unit:test function local:check() { unit:assert(db:exists('test-db')) };`

%unit:after

Syntax	`%unit:after` `%unit:after(FUNCTION)`
Summary	A function decorated with this annotation will be evaluated **after each** unit test.`FUNCTION` can be supplied as additional argument. It must be a valid EQName string. If specified, the function will only be evaluated after a function with the given name is tested.

%unit:before-module

Syntax	`%unit:before-module`
Summary	If a function is decorated with this annotation, it will be evaluated **before all** unit tests in the current module.

%unit:after-module

Syntax	`%unit:after-module`
Summary	If a function is decorated with this annotation, it will be evaluated **after all** unit tests in the current module.

%unit:ignore

Syntax	`%unit:ignore` `%unit:ignore(MESSAGE)`
Summary	If a function is decorated with this annotation, it will temporarily be ignored by the test suite runner.

Functions

unit:assert

Signatures	`unit:assert($test as item()*) as empty-sequence()` `unit:assert($test as item()*, $info as item()) as empty-sequence()`
Summary	Asserts that the effective boolean value of the specified `$test` is true and returns an empty sequence. Otherwise, raises an error. The *effective boolean value* of an expression can be explicitly computed by using the `fn:boolean` function.The default failure message can be overridden with the `$info` argument.
Errors	`fail`: the assertion failed, or an error was raised.

unit:assert-equals

Signatures	`unit:assert-equals($returned as item()*, $expected as item()*) as empty-sequence()` `unit:assert-equals($returned as item()*, $expected as item()*, $info as item()) as empty-sequence()`
Summary	Asserts that the specified arguments are equal according to the rules of the `fn:deep-equal` function. Otherwise, raises an error.The default failure message can be overridden with the `$info` argument.

Errors	`fail`: the assertion failed, or an error was raised.

unit:fail

Signatures	`unit:fail() as empty-sequence()` `unit:fail($info as item()) as empty-sequence()`
Summary	Raises a unit error. The default failure message can be overridden with the `$info` argument.
Errors	`fail`: default error raised by this function.

Example

The following XQUnit module `tests.xqm` contains all available unit annotations:

Query

```
module namespace test = 'http://basex.org/modules/xqunit-tests';

(:~ Initializing function, which is called once before all tests. :)
declare %unit:before-module function test:before-all-tests() {
  ()
};

(:~ Initializing function, which is called once after all tests. :)
declare %unit:after-module function test:after-all-tests() {
  ()
};

(:~ Initializing function, which is called before each test. :)
declare %unit:before function test:before() {
  ()
};

(:~ Initializing function, which is called after each test. :)
declare %unit:after function test:after() {
  ()
};

(:~ Function demonstrating a successful test. :)
declare %unit:test function test:assert-success() {
  unit:assert(<a/>)
};

(:~ Function demonstrating a failure using unit:assert. :)
declare %unit:test function test:assert-failure() {
  unit:assert((), 'Empty sequence.')
};

(:~ Function demonstrating a failure using unit:assert-equals. :)
declare %unit:test function test:assert-equals-failure() {
  unit:assert-equals(4 + 5, 6)
};

(:~ Function demonstrating an unexpected success. :)
declare %unit:test("expected", "err:FORG0001") function test:unexpected-success() {
  ()
};

(:~ Function demonstrating an expected failure. :)
declare %unit:test("expected", "err:FORG0001") function test:expected-failure() {
  1 + <a/>
```

```
};

(:~ Function demonstrating the creation of a failure. :)
declare %unit:test function test:failure() {
  unit:fail("Failure!")
};

(:~ Function demonstrating an error. :)
declare %unit:test function test:error() {
  1 + <a/>
};

(:~ Skipping a test. :)
declare %unit:test %unit:ignore("Skipped!") function test:skipped() {
  ()
};
```

By running `TEST tests.xqm`, the following report will be generated (timings may differ):

Result

```
<testsuites time="PT0.256S">
  <testsuite name="file:///C:/Users/user/Desktop/test.xqm" time="PT0.212S"
 tests="8" failures="4" errors="1" skipped="1">
    <testcase name="assert-success" time="PT0.016S"/>
    <testcase name="assert-failure" time="PT0.005S">
      <failure line="30" column="15">
        <info>Empty sequence.</info>
      </failure>
    </testcase>
    <testcase name="assert-equals-failure" time="PT0.006S">
      <failure line="35" column="22">
        <returned item="1" type="xs:integer">9</returned>
        <expected item="1" type="xs:integer">6</expected>
        <info>Item 1: 6 expected, 9 returned.</info>
      </failure>
    </testcase>
    <testcase name="unexpected-success" time="PT0.006S">
      <failure>
        <expected>FORG0001</expected>
      </failure>
    </testcase>
    <testcase name="expected-failure" time="PT0.004S"/>
    <testcase name="failure" time="PT0.004S">
      <failure line="50" column="13">
        <info>Failure!</info>
      </failure>
    </testcase>
    <testcase name="error" time="PT0.004S">
      <error line="55" column="6" type="FORG0001">
        <info>Cannot cast to xs:double: "".</info>
      </error>
    </testcase>
    <testcase name="skipped" skipped="Skipped!" time="PT0S"/>
  </testsuite>
</testsuites>
```

Errors

Updated with Version 9.0:

Code	Description

`fail`	An assertion failed, or an error was raised.
`no-args`	A test function must have no arguments.
`private`	A test function must not be private.

Changelog

Version 9.0

- Updated: error codes updated; errors now use the module namespace

Version 8.0.2

- Updated: (expected) errors are compared by QNames instead of local names (including namespaces).

Version 8.0

- Deleted: `UNIT0006` (ignore results returned by functions).
- Added: unit:fail, 0-argument signature.
- Updated: the info argument of functions can now be an arbitrary item.
- Updated: infos are now represented in an `info` child element.
- Updated: unit:before and unit:after can be extended by a filter argument.

Version 7.9

- Added: TEST command
- Removed: unit:test, unit:test-uris

Version 7.8

- Added: unit:assert-equals
- Updated: enhanced test report output

This module was introduced with Version 7.7.

Chapter 70. Update Module

Read this entry online in the BaseX Wiki.

This XQuery Module provides additional functions for performing updates and returning results in updating expressions.

Conventions

All functions in this module are assigned to the `http://basex.org/modules/update` namespace, which is statically bound to the `update` prefix.

Except for update:output-cache, all functions are *updating* and thus comply to the XQuery Update constraints.

Updates

update:apply

Signatures	`update:apply($function as function(*), $arguments as array(*))) as empty-sequence()`
Summary	The updating variant of fn:apply applies the specified updating `$function` to the specified `$arguments`.

Examples	• Creates a new database with an initial document and adds a document to an existing database.
	
	`declare %updating function local:update(`
	`  $database  as xs:string,`
	`  $path  as xs:string,`
	`  $function  as %updating function(item(), xs:string) as empty-sequence()`
	`) as empty-sequence() {`
	`  update:apply($function, [ $database, $path ])`
	`};`
	`local:update('new-db', 'doc.xml', db:create#2),`
	`local:update('existing-db', 'doc.xml', db:add#2)`

update:for-each

Signatures	`update:for-each($seq as item()*, $function as function(item()) as item()*)) as empty-sequence()`
Summary	The updating variant of fn:for-each applies the specified updating `$function` to every item of `$seq`.

Examples	• Creates two databases:
	
	`let $names := ('db1', 'db2')`
	`return update:for-each($names, db:create#1)`

update:for-each-pair

Signatures	`update:for-each-pair($seq1 as item()*, $function as function(item()) as item()*)) as empty-sequence()`
Summary	The updating variant of fn:for-each-pair applies the specified updating `$function` to the successive pairs of items of `$seq1` and `$seq2`. Evaluation is stopped if one sequence yields no more items.

Examples

- Renames nodes in an XML snippets:

```
copy $xml := <xml><a/><b/></xml>
modify update:for-each-pair(
  ('a', 'b'),
  ('d', 'e'),
  function($source, $target) {
    for $e in $xml/*[name() = $source]
    return rename node $e as $target
  }
)
return $xml
```

update:map-for-each

Signatures	`update:map-for-each($map as map(*), $function as function(xs:anyAtomicType, item()*) as item()*) as item()*`
Summary	The updating variant of map:for-each applies the specified `$function` to every key/value pair of the supplied `$map` and returns the results as a sequence.

Examples

- Inserts attributes into a document:

```
copy $doc := <xml/>
modify update:map-for-each(
  map {
    'id': 'id0',
    'value': 456
  },
  function($key, $value) {
    insert node attribute { $key } { $value } into $doc
  }
)
return $doc
```

Output

update:output

Updated with Version 9.0: formerly `db:output`.

Signatures	`update:output($result as item()*) as empty-sequence()`
Summary	This function is a helper function for returning results in an updating expression. The argument of the function will be evaluated, and the resulting items will be cached and returned after the updates on the *pending update list* have been processed. As nodes may be updated, they will be copied before being cached.

Examples

- `update:output("Prices have been deleted."), delete node //price` deletes all `price` elements in a database and returns an info message.

update:output-cache

Updated with Version 9.0: formerly `db:output-cache`.

Signatures	`update:output-cache() as item()*`
Summary	Returns the items that have been cached by update:output. It can be used to check which items will eventually be returned as result of an updating function.This function is *non-deterministic*: It will return different results before and after items have been cached. It is e. g. useful when writing unit tests.

Changelog

This module was introduced with Version 9.0.

Chapter 71. User Module

Read this entry online in the BaseX Wiki.

This XQuery Module contains functions for creating and administering database users. The User Management article gives more information on database users and permissions.

Conventions

All functions and errors in this module are assigned to the `http://basex.org/modules/user` namespace, which is statically bound to the `user` prefix.

Read Operations

user:current

Signatures	`user:current() as xs:string`
Summary	Returns the name of the currently logged in user.
Examples	• If the GUI or the standalone mode is used, `user:current()` always returns `admin`.

user:list

Signatures	`user:list() as xs:string*`
Summary	Returns the names of all registered users that are visible to the current user.
Examples	• After a fresh installation, `user:list()` will only return `admin`.

user:list-details

Signatures	`user:list-details() as element(user)* user:list-details($name as xs:string) as element(user)*`
Summary	Returns an element sequence, containing all registered users that are visible to the current user.In addition to the SHOW USERS command, encoded password strings and database permissions will be output. A user `$name` can be specified to filter the results in advance.
Examples	• After a fresh installation, `user:list-details()` returns output similar to the following one:
Errors	`unknown`: The specified user name is unknown.

```
<user name="admin" permission="admin">
  <password algorithm="digest">
    <hash>304bdfb0383c16f070a897fc1eb25cb4</hash>
  </password>
  <password algorithm="salted-sha256">
    <salt>871602799292195</salt>

 <hash>a065ca66fa3d6da5762c227587f1c8258c6dc08ee867e44a605a72da115dcb41</
hash>
  </password>
</user>
```

user:exists

Signatures	`user:exists($name as xs:string) as xs:boolean`
Summary	Checks if a user with the specified `$name` exists.

Examples	• `user:exists('admin')` will always yield true.
Errors	`name`: The specified user name is invalid.

user:check

Signatures	`user:check($name as xs:string, $password as xs:string) as xs:empty-sequence()`
Summary	Checks if the specified user and password is correct. Raises errors otherwise.
Examples	• `user:check('admin', 'admin')` will raise an error if the admin password was changed.
Errors	`name`: The specified user name is invalid.`unknown`: The specified user does not exist.`password`: The specified password is wrong.

user:info

Signatures	`user:info() as element(info)`
Summary	Returns an `info` element, which can be used to organize application-specific data. By default, the element has no contents. It can be modified via user:update-info.
Examples	• After a fresh installation, `user:info()` returns `<info/>`.

Updates

Important note: All functions in this section are *updating functions*: they will not be immediately executed, but queued on the Pending Update List, which will be processed after the actual query has been evaluated. This means that the order in which the functions are specified in the query does usually not reflect the order in which the code will be evaluated.

user:create

Signatures	`user:create($name as xs:string, $password as xs:string) as empty-sequence()` `user:create($name as xs:string, $password as xs:string, $permissions as xs:string*) as empty-sequence()` `user:create($name as xs:string, $password as xs:string, $permissions as xs:string*, $patterns as xs:string*) as empty-sequence()`
Summary	Creates a new user with the specified `$name`, `$password`, and `$permissions`. Local permissions are granted with non-empty glob `$patterns`. The default global permission (*none*) can be overwritten with an empty pattern or by omitting the last argument. Existing users will be overwritten.
Examples	• `user:create('John', '7e$j#!1', 'admin')` creates a new user 'John' with admin permissions. • `user:create('Jack', 'top!secret', 'read', 'index*')` creates a new user 'Jack' with no permissions, but write permissions for databases starting with the letters 'index'.
Errors	`name`: The specified user name is invalid.`permission`: The specified permission is invalid.`admin`: The "admin" user cannot be modified.`logged-in`: The specified user is currently logged in.`update`: The operation can only be performed once per user or database pattern.

user:grant

Signatures	`user:grant($name as xs:string, $permissions as xs:string*) as empty-sequence()` `user:grant($name as xs:string, $permissions as xs:string*, $patterns as xs:string*) as empty-sequence()`
Summary	Grants global or local `$permissions` to a user with the specified `$name`. Local permissions are granted with non-empty glob `$patterns`.

Examples	• `user:grant('John', 'create')` grants create permissions to the user 'John'. • `user:grant('John', ('read','write'), ('index*','unit*'))` allows John to read all databases starting with the letters 'index', and to write to all databases starting with 'unit'.
Errors	`unknown`: The specified user name is unknown.`name`: The specified user name is invalid.`pattern`: The specified database pattern is invalid.`permission`: The specified permission is invalid.`admin`: The "admin" user cannot be modified.`local`: A local permission can only be 'none', 'read' or 'write'.`logged-in`: The specified user is currently logged in.`update`: The operation can only be performed once per user or database pattern.

user:drop

Signatures	`user:drop($name as xs:string) as empty-sequence()` `user:drop($name as xs:string, $patterns as xs:string*) as empty-sequence()`
Summary	Drops a user with the specified `$name`. If non-empty glob `$patterns` are specified, only the database patterns will be dropped.
Examples	• `user:drop('John')` drops the user 'John'. • `user:grant('John', 'unit*')` removes the 'unit*' database pattern. If John accesses any of these database, his global permission will be checked again.
Errors	`unknown`: The specified user name is unknown.`name`: The specified user name is invalid.`pattern`: The specified database pattern is invalid.`admin`: The "admin" user cannot be modified.`logged-in`: The specified user is currently logged in.`update`: The operation can only be performed once per user or database pattern.`conflict`: A user cannot be both altered and dropped.

user:alter

Signatures	`user:alter($name as xs:string, $newname as xs:string) as empty-sequence()`
Summary	Renames a user with the specified `$name` to `$newname`.
Examples	• `user:rename('John', 'Jack')` renames the user 'John' to 'Jack'.
Errors	`unknown`: The specified user name is unknown.`name`: The specified user name is invalid.`admin`: The "admin" user cannot be modified.`logged-in`: The specified user is currently logged in.`update`: The operation can only be performed once per user or database pattern.`conflict`: A user cannot be both altered and dropped.

user:password

Signatures	`user:password($name as xs:string, $password as xs:string) as empty-sequence()`
Summary	Changes the `password` of a user with the specified `$name`.
Examples	• `user:password('John', )` *assigns user 'John' an empty password string.*
Errors	`unknown`: The specified user name is unknown.`name`: The specified user name is invalid.`update`: The operation can only be performed once per user or database pattern.

user:update-info

Signatures	`user:update-info($info as element(info)) as empty-sequence()`
Summary	Updates the `info` element with `$info`. This node can be used to organize application-specific data (groups, enhanced user info, etc.).
Examples	• Store initial groups information:

```
user:update-info(element info {
  for $group in ('editor', 'author', 'writer')
  return element group { $group }
})
```

- Assign a group to a new user:

```
let $user := 'john', $pw := '8hKJ@%.c/!0O', $group := 'editor'
return (
  user:create($user, $pw),
  user:update-info(user:info() update
    insert node <user name='{ $user }' group='{ $group }'/> into .
  )
)
```

Errors

Code	Description
`admin`	The "admin" user cannot be modified.
`conflict`	A user cannot be both altered and dropped.
`equal`	Name of old and new user is equal.
`local`	A local permission can only be 'none', 'read' or 'write'.
`logged-in`	The specified user is currently logged in.
`name`	The specified user name is invalid.
`password`	The specified password is wrong.
`pattern`	The specified database name is invalid.
`permission`	The specified permission is invalid.
`unknown`	The specified user does not exist.
`update`	The operation can only be performed once per user or database pattern.

Changelog

Version 8.6

- Added: user:check, user:info, user:update-info.
- Updated: user:list, user:list-details: If called by non-admins, will only return the current user.

Version 8.4

- Updated: user:create, user:grant, user:drop: extended support for database patterns.

Version 8.1

- Added: user:current.

The Module was introduced with Version 8.0.

Chapter 72. Validation Module

Read this entry online in the BaseX Wiki.

This XQuery Module contains functions to perform validations against DTDs, XML Schema and RelaxNG. For Schematron validation, check out Vincent Lizzi's Schematron XQuery Module for BaseX.

Conventions

Updated with Version 9.0:

All functions and errors in this module are assigned to the `http://basex.org/modules/validate` namespace, which is statically bound to the `validate` prefix.

DTD Validation

Checks whether an XML document validates against a DTD. The input document can be specified as:

- `xs:string` , representing a URI (relative URIs will always be resolved against the static base URI of the query),
- `xs:string` , representing the resource in its string representation, or
- `node()` , representing the resource itself.

If no DTD is supplied in a function, the XML document is expected to contain an embedded DTD doctype declaration.

validate:dtd

Signatures	`validate:dtd($input as item()) as empty-sequence()` `validate:dtd($input as item(), $schema as xs:string?) as empty-sequence()`
Summary	Validates the XML `$input` document against a `$schema` and returns an empty sequence or an error.
Errors	`error`: the validation fails.`init`: the validation process cannot be started.`not-found`: no DTD validator is available.
Examples	• `validate:dtd('doc.xml', 'doc.dtd')` validates the document `doc.xml` against the specified DTD file `doc.dtd`. • The following example validates an invalid document against a DTD, which is specified as string: `try { let $doc := <invalid/> let $schema := '<!ELEMENT root (#PCDATA)>' return validate:dtd($doc, $schema) } catch validate:error { 'DTD Validation failed.' }`

validate:dtd-info

Signatures	`validate:dtd-info($input as item()) as xs:string* validate:dtd-info($input as item(), $schema as xs:string?) as xs:string*`

Summary	Validates the XML `$input` document against a `$schema` and returns warnings, errors and fatal errors in a string sequence.
Errors	`init`: the validation process cannot be started.`not-found`: no DTD validator is available.
Examples	• `validate:dtd-info(<invalid/>, '<!ELEMENT root (#PCDATA)>')` returns:`2:11: Element type "invalid" must be declared.`.

validate:dtd-report

width='100%'

Signatures	`validate:dtd-report($input as item()) as element(report)` `validate:dtd-report($input as item(), $schema as xs:string?) as element(report)`
Summary	Validates the XML `$input` document against a `$schema` and returns warnings, errors and fatal errors as XML.
Errors	`init`: the validation process cannot be started.`not-found`: no DTD validator is available.

Examples	• `validate:dtd-report(<invalid/>, '<!ELEMENT root (#PCDATA)>')` returns:
	`<report>`
	`  <status>invalid</status>`
	`  <message level="Error" line="2" column="11">Element type "invalid"`
	`must be declared.</message>`
	`</report>`

XML Schema Validation

Checks whether an XML document validates against an XML Schema. The input document and the schema can be specified as:

- `xs:string` , containing the path to the resource,
- `xs:string` , containing the resource in its string representation, or
- `node()` , containing the resource itself.

If no schema is given, the input is expected to contain an `xsi:(noNamespace)schemaLocation` attribute, as defined in W3C XML Schema.

Different XML Schema implementations can be applied for validation:

- By default, the Java implementation of XML Schema 1.0 is used (it is based on an old version of Apache Xerces).
- If Xerces2 exists in the classpath, it will be used instead. If you want to manually add Xerces2, you should download the Xerces2 Java ..... (XML Schema 1.1) (Beta) archive and copy at least four libraries (`cupv10k-runtime.jar`, `org.eclipse.wst.xml.xpath2.processor_1.1.0.jar`, `xercesImpl.jar`, `xml-apis.jar`) to the `lib` directory of the full distribution of BaseX.
- The Saxon Enterprise Edition (`saxon9ee.jar`) is detected as well.

The XML Schema version can be specified as well (the supplied string must be `1.0` or `1.1`). Please note that Version 1.1 is only available if Saxon EE or Xerces2 is added to the classpath.

validate:xsd

Signatures	`validate:xsd($input as item()) as empty-sequence()` `validate:xsd($input as item(), $schema as item()?) as empty-`

	`sequence() validate:xsd($input as item(), $schema as item()?, $version as xs:string) as empty-sequence()`
Summary	Validates the XML `$input` document against a `$schema`, using the specified `$version` of XML Schema.
Errors	`error`: the validation fails.`init`: the validation process cannot be started.`not-found`: no XML Schema validator is available.`version`: no validator is found for the specified version.

Examples	• `validate:xsd('doc.xml', 'doc.xsd')` validates the document `doc.xml` against the specified schema `doc.xsd`.
	• The following example demonstrates how a document can be validated against a schema without resorting to local or remote URIs:
	`let $doc := <simple:root xmlns:simple='http://basex.org/simple'/>`
	`let $schema :=`
	`  <xs:schema xmlns:xs='http://www.w3.org/2001/XMLSchema'`
	`targetNamespace='http://basex.org/simple'>`
	`  <xs:element name='root'/>`
	`  </xs:schema>`
	`return validate:xsd($doc, $schema)`

validate:xsd-info

Signatures	`validate:xsd-info($input as item()) as xs:string* validate:xsd-info($input as item(), $schema as item()?) as xs:string* validate:xsd-info($input as item(), $schema as item()?, $version as xs:string) as xs:string*`
Summary	Validates the XML `$input` document against a `$schema`, using the specified `$version` of XML Schema, and returns warnings, errors and fatal errors in a string sequence.
Errors	`init`: the validation process cannot be started.`not-found`: no XML Schema validator is available.`version`: no validator is found for the specified version.

validate:xsd-report

Signatures	`validate:xsd-report($input as item()) as element(report) validate:xsd-report($input as item(), $schema as xs:string?) as element(report) validate:xsd-report($input as item(), $schema as xs:string?, $version as xs:string) as element(report)`
Summary	Validates the XML `$input` document against a `$schema`, using the specified `$version` of XML Schema, and returns warnings, errors and fatal errors as XML.
Errors	`init`: the validation process cannot be started.`not-found`: no XML Schema validator is available.`version`: no validator is found for the specified version.

RelaxNG Validation

Checks whether an XML document validates against a RelaxNG schema. The input document and the schema can be specified as:

- `xs:string` , containing the path to the resource,
- `xs:string` , containing the resource in its string representation, or
- `node()` , containing the resource itself.

RelaxNG validation will be available if Jing exists in the classpath. The latest version, `jing-20091111.jar`, is included in the full distributions of BaseX. As Jing additionally supports NVDL validation, you can also use the functions to validate the input against NVDL schemas.

validate:rng

Signatures	`validate:rng($input as item(), $schema as item()) as empty-sequence()` `validate:rng($input as item(), $schema as item(), $compact as xs:boolean) as empty-sequence()`
Summary	Validates the XML `$input` document against a `$schema`, using the XML or `$compact` notation.
Errors	`error`: the validation fails.`init`: the validation process cannot be started.`not-found`: the RelaxNG validator is not available.
Examples	• `validate:rng('doc.xml', 'doc.rng')` validates the document `doc.xml` against the specified schema `doc.rng`.

validate:rng-info

Signatures	`validate:rng-info($input as item(), $schema as item()) as xs:string*` `validate:rng-info($input as item(), $schema as item(), $compact as xs:boolean) as xs:string*`
Summary	Validates the XML `$input` document against a `$schema`, using the XML or `$compact` notation, and returns warnings, errors and fatal errors in a string sequence.
Errors	`init`: the validation process cannot be started.`not-found`: the RelaxNG validator is not available.

validate:rng-report

Signatures	`validate:rng-report($input as item(), $schema as xs:string) as element(report)` `validate:rng-report($input as item(), $schema as xs:string, $compact as xs:boolean) as element(report)`
Summary	Validates the XML `$input` document against a `$schema`, using the XML or `$compact` notation, and returns warnings, errors and fatal errors as XML.
Errors	`init`: the validation process cannot be started.`not-found`: The RelaxNG validator is not available.

Errors

Updated with Version 9.0:

Code	Description
`error`	The document cannot be validated against the specified schema.
`init`	The validation cannot be started.
`not-found`	No validator is available.
`version`	No validator is found for the specified version.

Changelog

Version 9.0

- Updated: error codes updated; errors now use the module namespace

Version 8.5

- Updated: Relative URIs will always be resolved against the static base URI of the query

Version 8.3

- Added: validate:rng, validate:rng-info
- Added: dtd-report, xsd-report, validate:rng-report

Version 7.6

- Added: validate:xsd-info, validate:dtd-info

The module was introduced with Version 7.3.

Chapter 73. Web Module

Read this entry online in the BaseX Wiki.

This XQuery Module provides convenience functions for building web applications with RESTXQ.

Conventions

Updated with Version 9.0:

All functions and errors in this module are assigned to the `http://basex.org/modules/web` namespace, which is statically bound to the `web` prefix.

Functions

web:content-type

Signatures	`web:content-type($path as xs:string) as xs:string`
Summary	Returns the content type of a path by analyzing its file suffix. `application/octet-stream` is returned if the file suffix is unknown.
Examples	• `web:content-type("sample.mp3")` returns `audio/mpeg`

web:create-url

Signatures	`web:create-url($url as xs:string, $parameters as map(*)) as xs:string`
Summary	Creates a new URL from the specified `$url` string and the `$parameters` specified in a map. The keys and and values of the map entries will be converted to strings, URL-encoded (see web:encode-url), and appended to the url as query parameters. If a map entry has more than a single item, all of them will be appended as single parameters.
Examples	• `web:create-url('http://find.me', map { 'q': 'dog' })` returns `http://find.me?q=dog` • `web:create-url('search', map { 'year': (2000,2001), 'title':() })` returns `search?year=2000&year=2001`

web:encode-url

Signatures	`web:encode-url($string as xs:string) as xs:string`
Summary	Encodes a string to a URL. Spaces are rewritten to `+`; `*`, `-`, `.` and _ are adopted; and all other non-ASCII characters and special characters are percent-encoded.
Examples	• `web:encode-url("this is a test!.html")` returns `this+is+a+test%21.html`.

web:decode-url

Signatures	`web:decode-url($string as xs:string) as xs:string`
Summary	Decodes a URL to the original string. Percent-encoded characters are decoded to their UTF8 codepoints, and + characters are rewritten to spaces.
Examples	• `web:decode-url("%E6%97%A5%E6%9C%AC%E8%AA%9E")` returns ###.
Errors	`invalid`: the string contains invalid XML characters.

web:redirect

Signatures	`web:redirect($location as xs:string) as element(rest:response)` `web:redirect($location as xs:string, $parameters as map(*)) as element(rest:response)`
Summary	Creates a RESTXQ redirection to the specified location. The returned response will only work if no other items are returned by the RESTXQ function.If `$parameters` are specified, they will be appended as query parameters to the URL as described for web:create-url.

Examples	• The query `web:redirect('/a/b')` returns the following result (which will be interpreted as redirection if RESTXQ is used):
	
	`<rest:response xmlns:rest="http://exquery.org/ns/restxq">`
	`  <http:response xmlns:http="http://expath.org/ns/http-client"`
	`status="302">`
	`  <http:header name="location" value="/a/b"/>`
	`  </http:response>`
	`</rest:response>`
	
	• The first RESTXQ function creates an initial database, and redirects to a second function that will access this database:
	
	`declare %updating %rest:path('/app/init') function local:init() {`
	`  db:create('app', <root/>, 'root.xml'),`
	`  db:output(web:redirect('/app/main'))`
	`};`
	
	`declare %rest:path('/app/main') function local:update() {`
	`  'Stored documents: ' || count(db:open('app'))`
	`};`

web:response-header

Updated with Version 9.0: third argument added; default parameters removed.

Signatures	`web:response-header() as element(rest:response)` `web:response-header($output as map(*)?) as element(rest:response)` `web:response-header($output as map(*)?, $headers as map(*)?) as element(rest:response)` `web:response-header($output as map(*)?, $headers as map(*)?, $atts as map(*)?) as element(rest:response)`
Summary	Creates a RESTXQ response header. Serialization parameters and header values can be supplied via the `$output` and `$headers` arguments, and status and message attributes can be attached to the top element with the `$atts` argument. • `media-type` : `application/octet-stream` Header options can be supplied via the `$headers` argument. Empty string values can be specified to invalidate default values. By default, the following header options will be returned: • `Cache-Control` : `max-age=3600,public`

Examples	• The function call `web:response-header()` returns:
	
	`<rest:response xmlns:rest="http://exquery.org/ns/restxq">`
	`  <http:response xmlns:http="http://expath.org/ns/http-client"/>`
	`  <output:serialization-parameters xmlns:output="http://www.w3.org/2010/xslt-xquery-serialization"/>`
	`</rest:response>`

- The following expression returns a media-type for binary data, a caching directive, and the OK status:

```
web:response-header(
  map { 'media-type': 'application/octet-stream' },
  map { 'Cache-Control': 'max-age=3600,public' },
  map { 'status': 200, 'message': 'OK' }
)
```

- The following RESTXQ function returns the contents of a file to the client with correct media type:

```
declare %rest:path('media/{$file}') function local:get($file) {
  let $path := 'path/to/' || $file
  return (
    web:response-header(map { 'media-type': web:content-type($path) }),
    file:read-binary($path)
  )
};
```

Errors

Updated with Version 9.0:

Code	Description
`invalid`	A string contains invalid XML characters.

Changelog

Version 9.0

- Updated: web:response-header: third argument added; default parameters removed.
- Updated: error codes updated; errors now use the module namespace

Version 8.4

- Updated: web:response-header: serialization method `raw` was removed (now obsolete).

Version 8.2

- Added: web:encode-url, web:decode-url.

The module was introduced with Version 8.1.

Chapter 74. XQuery Module

Read this entry online in the BaseX Wiki.

This XQuery Module contains functions for evaluating XQuery strings and modules at runtime.

Conventions

Updated with Version 9.0:

All functions and errors in this module are assigned to the `http://basex.org/modules/xquery` namespace, which is statically bound to the `xquery` prefix.

Functions

xquery:eval

Updated with Version 9.0: `pass` option added.

Signatures	`xquery:eval($query as xs:string) as item()*` `xquery:eval($query as xs:string, $bindings as map(*)?) as item()*` `xquery:eval($query as xs:string, $bindings as map(*)?, $options as map(*)?) as item()*`
Summary	Evaluates the supplied `$query` string as XQuery expression and returns the resulting items.The evaluated query has its own query context. If a returned node is stored in a database, a main-memory copy will be returned as result, because the referenced database is closed after query execution and will not be accessible anymore.Variables and context items can be declared via `$bindings`. The specified keys must be QNames or strings: • If a key is a QName, it will be directly adopted as variable name. • It a key is a string, it may be prefixed with a dollar sign. Namespace can be specified using the Clark Notation. • If the specified string is empty, the value will be bound to the context item. The `$options` parameter contains evaluation options: • `permission` : the query will be evaluated with the specified permissions (see User Management). • `timeout` : query execution will be interrupted after the specified number of seconds. • `memory` : query execution will be interrupted if the specified number of megabytes will be exceeded. This check works best if only one process is running at the same time. Moreover, please note that this option enforces garbage collection, so it will take some additional time, and it requires GC to be enabled in your JVM. • `base-uri` : set base-uri property for the query. This URI will be used when resolving relative URIs by functions such as `fn:doc`. • `pass` : passes on the original error info (line and column number, optional file uri). By default, this option is `false`.
Errors	`update`: the query contains updating expressions.`permission`: insufficient permissions for evaluating the query.`timeout`: query execution exceeded timeout.`limit`: query execution exceeded memory limit.`nested`: nested query evaluation is not allowed.Any other error that may occur while evaluating the query.

Examples

- `xquery:eval("1+3")` returns 4.
- You can bind the context and e.g. operate on a certain database only:

```
xquery:eval("//country", map { '': db:open('factbook') })
```

- The following expressions use strings as keys. All of them return 'XML':

```
xquery:eval(".", map { '': 'XML' }),

xquery:eval("declare variable $xml external; $xml", map { 'xml':
 'XML' }),

xquery:eval(
  "declare namespace pref='URI';
   declare variable $pref:xml external;
   $pref:xml",
  map { '{URI}xml': 'XML' }
)
```

- The following expressions use QNames as keys. All of them return 'XML':

```
declare namespace pref = 'URI';

xquery:eval("declare variable $xml external; $xml", map
 { xs:QName('xml'): 'XML' }),

let $query := "declare namespace pref='URI';
               declare variable $pref:xml external;
               $pref:xml"
let $vars := map { xs:QName('pref:xml'): 'XML' }
return xquery:eval($query, $vars)
```

xquery:eval-update

Updated with Version 9.0: Renamed (old name: xquery:update)

Signatures	`xquery:eval-update($query as xs:string) as item()*` `xquery:eval-update($query as xs:string, $bindings as map(*)?) as item()*` `xquery:eval-update($query as xs:string, $bindings as map(*)?, $options as map(*)?) as item()`
Summary	Evaluates `$query` as updating XQuery expression at runtime.All updates will be added to the Pending Update List of the main query and performed after the evaluation of the main query.The rules of the `$bindings` and `$options` parameters are the same as for xquery:eval.
Errors	`update`: the query contains no updating expressions.`permission`: insufficient permissions for evaluating the query.`timeout`: query execution exceeded timeout.`limit`: query execution exceeded memory limit.`nested`: nested query evaluation is not allowed.Any other error that may occur while evaluating the query.

xquery:invoke

Signatures	`xquery:invoke($uri as xs:string) as item()*` `xquery:invoke($uri as xs:string, $bindings as map(*)?) as item()*` `xquery:invoke($uri as xs:string, $bindings as map(*)?, $options as map(*)?) as item()*`
Summary	Evaluates the XQuery module located at `$uri` at runtime and returns the resulting items. A relative URI will be resolved against the static base URI of the query.The rules of the `$bindings` and `$options` parameters are the same as for xquery:eval.

Errors	`update`: the expression contains updating expressions.`permission`: insufficient permissions for evaluating the query.`timeout`: query execution exceeded timeout.`nested`: nested query evaluation is not allowed.Any other error that may occur while evaluating the query.

xquery:invoke-update

Signatures	`xquery:invoke-update($uri as xs:string) as item()* xquery:invoke-update($uri as xs:string, $bindings as map(*)?) as item()* xquery:invoke-update($uri as xs:string, $bindings as map(*)?, $options as map(*)?) as item()*`
Summary	Evaluates the updating XQuery module located at `$uri` at runtime. A relative URI will be resolved against the static base URI of the query.The rules of the `$bindings` and `$options` parameters are the same as for xquery:eval.
Errors	`update`: the expression contains no updating expressions.`permission`: insufficient permissions for evaluating the query.`timeout`: query execution exceeded timeout.`nested`: nested query evaluation is not allowed.Any other error that may occur while evaluating the query.

xquery:parse

Updated with Version 9.0: `base-uri` option added.

Signatures	`xquery:parse($query as xs:string) as item()? xquery:parse($query as xs:string, $options as map(*)?) as item()?`
Summary	Parses the specified `$query` string as XQuery module and returns the resulting query plan. The `$options` parameter influences the output: • `compile` : additionally compiles the query after parsing it. By default, this option is `false`. • `plan` : returns an XML representation of the internal query plan. By default, this option is `true`. The naming of the expressions in the query plan may change over time • `pass` : passes on the original error info (line and column number, optional file uri). By default, this option is `false`. • `base-uri` : set base-uri property for the query. This URI will be used when resolving relative URIs by functions such as `fn:doc`.
Errors	Any error that may occur while parsing the query.

Examples	• `xquery:parse("1 + 3")` returns:
	`<MainModule updating="false">`
	`  <QueryPlan compiled="false">`
	`  <Arith op="+">`
	`  <Int value="1" type="xs:integer"/>`
	`  <Int value="3" type="xs:integer"/>`
	`  </Arith>`
	`  </QueryPlan>`
	`</MainModule>`

xquery:parse-uri

Updated with Version 9.0: `base-uri` option added.

Signatures	`xquery:parse-uri($uri as xs:string) as item()? xquery:parse-uri($uri as xs:string, $options as map(*)?) as item()?`

Summary	Parses the XQuery module located at `$uri` and returns the resulting query plan. A relative URI will be resolved against the static base URI of the query. The rules for the `$options` parameter are the same as for xquery:parse.
Errors	Any error that may occur while parsing the query.

Parallelized Execution

Parallel query execution is recommendable if you have various calls that require a lot of time, but cannot be sped up by rewriting the code. This is e. g. the case if external URLs are called. If you are parallelizing local data reads (such as the access to a database), single-threaded queries will usually be faster, because parallelized access to disk data often results in randomized access patterns, which can hardly be optimized by the caching strategies of HD, SSD or operating system.

xquery:fork-join

Signatures	`xquery:fork-join($functions as function(*)*) as item()*`
Summary	This function executes the supplied (non-updating) functions in parallel.

Examples	• The following function sleeps in parallel; it will be finished in 1 second if your system has at least 2 cores:
	`let $f := function() { prof:sleep(1000) }`
	`return xquery:fork-join(($f, $f))`
	• In the following query, up to four URLs will be requested in parallel:
	`let $funcs :=`
	`  for $segment in 1 to 4`
	`  let $url := 'http://url.com/path' || $segment`
	`  return function() { http:send-request((), $url) }`
	`return xquery:fork-join($funcs)`

Errors	`error`: an unexpected error occurred.

Errors

Updated with Version 9.0:

Code	Description
`permission`	Insufficient permissions for evaluating the query.
`update`	updating expression found or expected.
`timeout`	Query execution exceeded timeout.
`memory`	Query execution exceeded memory limit.
`nested`	Nested query evaluation is not allowed.
`error`	An unexpected error occurred.

Changelog

Version 9.0

- Added: xquery:invoke-update
- Updated: xquery:eval: `pass` option added
- Updated: xquery:parse, xquery:parse-uri: `base-uri` option added

- Updated: xquery:update renamed to xquery:eval-update
- Updated: error codes updated; errors now use the module namespace

Version 8.5

- Added: xquery:fork-join
- Updated: xquery:eval: `base-uri` option added
- Updated: Relative URIs will always be resolved against the static base URI of the query
- Deleted: xquery:type (moved to Profiling Module

Version 8.4

- Added: xquery:parse-uri
- Updated: xquery:parse: `pass` option added

Version 8.0

- Added: xquery:update, xquery:parse
- Deleted: xquery:evaluate (opened databases will now be closed by main query)

Version 7.8.2

- Added: `$options` argument

Version 7.8

- Added: xquery:evaluate
- Updated: used variables must be explicitly declared in the query string.

This module was introduced with Version 7.3. Functions have been adopted from the obsolete Utility Module.

Chapter 75. XSLT Module

Read this entry online in the BaseX Wiki.

This XQuery Module contains functions and variables to perform XSLT transformations. By default, this module uses Java's XSLT 1.0 Xalan implementation to transform documents. XSLT 2.0 is used instead if Version 9.x of the Saxon XSLT Processor (`saxon9he.jar`, `saxon9pe.jar`, `saxon9ee.jar`) is found in the classpath. A custom transformer can be specified by overwriting the system property `javax.xml.transform.TransformerFactory`, as shown in the following Java example:

```
System.setProperty(
  "javax.xml.transform.TransformerFactory",
  "org.custom.xslt.TransformerFactoryImpl");

Context ctx = new Context();
String result = new XQuery("xslt:transform('...', '...')").execute(ctx);
...
ctx.close();
```

Conventions

Updated with Version 9.0:

All functions and errors in this module are assigned to the `http://basex.org/modules/xslt` namespace, which is statically bound to the `xslt` prefix.

Functions

xslt:processor

Signatures	`xslt:processor() as xs:string`
Summary	Returns the name of the applied XSLT processor, or the path to a custom implementation (currently: "Java", "Saxon EE", "Saxon PE", or "Saxon HE").

xslt:version

Signatures	`xslt:version() as xs:string`
Summary	Returns the supported XSLT version (currently: "1.0" or "2.0"). "Unknown" is returned if a custom implementation was chosen.

xslt:transform

Updated with Version 9.0: `$options` argument added.

Signatures	`xslt:transform($input as item(), $stylesheet as item()) as node()` `xslt:transform($input as item(), $stylesheet as item(), $params as map(*)?) as node()` `xslt:transform($input as item(), $stylesheet as item(), $params as map(*)?, $options as map(*)?) as node()`
Summary	Transforms the document specified by `$input`, using the XSLT template specified by `$stylesheet`, and returns the result as node. `$input` and `$stylesheet` can be specified as • `xs:string` , containing the stylesheet URI, • `xs:string` , containing the document in its string representation, or • `node()` , containing the document itself.

	The `$params` argument can be used to bind variables to a stylesheet. Only strings are supported when using Saxon (XSLT 2.0). The following `$options` are available: • `cache` : cache XSLT transformer (speeds up repeated transformations, but increases memory consumption)
Error	`error`: an error occurred during the transformation process.

xslt:transform-text

Updated with Version 9.0: `$options` argument added.

Signatures	`xslt:transform-text($input as item(), $stylesheet as item()) as xs:string xslt:transform-text($input as item(), $stylesheet as item(), $params as map(*)?) as xs:string xslt:transform-text($input as item(), $stylesheet as item(), $params as map(*)?, $options as map(*)?) as xs:string`
Summary	Transforms the document specified by `$input`, using the XSLT template specified by `$stylesheet`, and returns the result as string. The semantics of `$params` and `$options` is the same as for xslt:transform.
Error	`error`: an error occurred during the transformation process.

Examples

Example 1: Basic XSL transformation with dummy document and without parameters

Query:

```
xslt:transform-text(<dummy/>, 'basic.xslt')
```

basic.xslt

```
<xsl:stylesheet version='1.0' xmlns:xsl='http://www.w3.org/1999/XSL/Transform'>
  <xsl:template match="/">123</xsl:template>
</xsl:stylesheet>
```

Result:

```
123
```

Example 2: XSLT transformation of an input document

Query:

```
(: Outputs the result as html. :)
declare option output:method 'html';
(: Turn whitespace chopping off. :)
declare option db:chop 'no';

let $in :=
  <books>
    <book>
      <title>XSLT Programmer's Reference</title>
      <author>Michael H. Kay</author>
    </book>
    <book>
      <title>XSLT</title>
      <author>Doug Tidwell</author>
      <author>Simon St. Laurent</author>
      <author>Robert Romano</author>
```

```
    </book>
  </books>
let $style :=
  <xsl:stylesheet version='2.0' xmlns:xsl='http://www.w3.org/1999/XSL/Transform'>
  <xsl:output method='xml'/>
    <xsl:template match="/">
<html>
  <body>
    <div>
      <xsl:for-each select='books/book'>
      • <b><xsl:apply-templates select='title'/></b>: <xsl:value-of
 select='author'/><br/>
      </xsl:for-each>
    </div>
  </body>
</html>
    </xsl:template>
  </xsl:stylesheet>

return xslt:transform($in, $style)
```

Result:

```
<html>
  <body>
    <div>
      • <b>XSLT Programmer’s Reference</b>: Michael H. Kay<br>
      • <b>XSLT</b>: Doug Tidwell<br>
    </div>
  </body>
</html>
```

Example 3: Assigning a variable to an XSLT stylesheet

Query:

```
let $in := <dummy/>
let $style := doc('variable.xsl')
return xslt:transform($in, $style, map { "v": 1 })
```

variable.xsl

```
<xsl:stylesheet version='1.0'
    xmlns:xsl='http://www.w3.org/1999/XSL/Transform'>
  <xsl:param name='v'/>
    <xsl:template match='/'>
      <v><xsl:value-of select='$v'/></v>
    </xsl:template>
</xsl:stylesheet>
```

Result:

```
<v>1</v>
<v>1</v>
```

Errors

Updated with Version 9.0:

Code	Description

`error`	An error occurred during the transformation process.

Changelog

Version 9.0

- Updated: xslt:transform, xslt:transform-text: `$options` argument added.
- Updated: error codes updated; errors now use the module namespace

Version 7.6

- Added: xslt:transform-text
- Updated: xslt:transform returned error code

Version 7.3

- Updated: $xslt:processor → xslt:processor, $xslt:version → xslt:version

Chapter 76. ZIP Module

Read this entry online in the BaseX Wiki.

This XQuery Module contains functions to handle ZIP archives. The contents of ZIP files can be extracted and listed, and new archives can be created. The module is based on the EXPath ZIP Module. Please note that the ZIP module is not being actively maintained but is still distributed for compatibility with older applications. We recommend you use the Archive Module wherever possible.

Conventions

All functions in this module are assigned to the `http://expath.org/ns/zip` namespace, which is statically bound to the `zip` prefix. All errors are assigned to the `http://expath.org/ns/error` namespace, which is statically bound to the `experr` prefix.

Functions

zip:binary-entry

Signatures	`zip:binary-entry($uri as xs:string, $path as xs:string) as xs:base64Binary`
Summary	Extracts the binary file at `$path` within the ZIP file located at `$uri` and returns it as an `xs:base64Binary` item.
Errors	`ZIP0001`: the specified path does not exist.`ZIP0003`: the operation fails for some other reason.

zip:text-entry

Signatures	`zip:text-entry($uri as xs:string, $path as xs:string) as xs:string` `zip:text-entry($uri as xs:string, $path as xs:string, $encoding as xs:string) as xs:string`
Summary	Extracts the text file at `$path` within the ZIP file located at `$uri` and returns it as an `xs:string` item.An optional encoding can be specified via `$encoding`.
Errors	`ZIP0001`: the specified path does not exist.`ZIP0003`: the operation fails for some other reason.

zip:xml-entry

Signatures	`zip:xml-entry($uri as xs:string, $path as xs:string) as document-node()`
Summary	Extracts the XML file at `$path` within the ZIP file located at `$uri` and returns it as a document node.
Errors	`ZIP0001`: the specified path does not exist.`ZIP0003`: the operation fails for some other reason.

zip:html-entry

Signatures	`zip:html-entry($uri as xs:string, $path as xs:string) as document-node()`
Summary	Extracts the HTML file at `$path` within the ZIP file located at `$uri` and returns it as a document node. The file is converted to XML first if Tagsoup is found in the classpath.
Errors	`ZIP0001`: the specified path does not exist.`ZIP0003`: the operation fails for some other reason.

zip:entries

Signatures	`zip:entries($uri as xs:string) as element(zip:file)`

Summary	Generates an ZIP XML Representation of the hierarchical structure of the ZIP file located at `$uri` and returns it as an element node. The file contents are not returned by this function.
Errors	`ZIP0001`: the specified path does not exist.`ZIP0003`: the operation fails for some other reason.
Examples	If the ZIP archive `archive.zip` is empty, `zip:entries('archive.zip')` returns: `<zip:file xmlns:zip="http://expath.org/ns/zip" href="archive.zip"/>`

zip:zip-file

Signatures	`zip:zip-file($zip as element(zip:file)) as empty-sequence()`
Summary	Creates a new ZIP archive with the characteristics described by `$zip`, the ZIP XML Representation.
Errors	`ZIP0001`: an addressed file does not exist.`ZIP0002`: entries in the ZIP archive description are unknown, missing, or invalid.`ZIP0003`: the operation fails for some other reason.

Examples	The following function creates a file `archive.zip` with the file `file.txt` inside:
	`zip:zip-file(`
	`  <file xmlns="http://expath.org/ns/zip" href="archive.zip">`
	`  <entry src="file.txt"/>`
	`  </file>)`
	The following function creates a file `archive.zip`. It contains one file `readme` with the content `"thanks"`:
	`zip:zip-file(`
	`  <file xmlns="http://expath.org/ns/zip" href="archive.zip">`
	`  <entry name="readme">thanks</entry>`
	`  </file>)`

zip:update-entries

Signatures	`zip:update-entries($zip as element(zip:file), $output as xs:string) as empty-sequence()`
Summary	Updates an existing ZIP archive or creates a modifed copy, based on the characteristics described by `$zip`, the ZIP XML Representation. The `$output` argument is the URI where the modified ZIP file is copied to.
Errors	`ZIP0001`: an addressed file does not exist.`ZIP0002`: entries in the ZIP archive description are unknown, missing, or invalid.`ZIP0003`: the operation fails for some other reason.

Examples	The following function creates a copy `new.zip` of the existing `archive.zip` file:
	`zip:update-entries(zip:entries('archive.zip'), 'new.zip')`
	The following function deletes all PNG files from `archive.zip`:
	`declare namespace zip = "http://expath.org/ns/zip";`
	`copy $doc := zip:entries('archive.zip')`
	`modify delete node $doc//zip:entry[ends-with(lower-case(@name), '.png')]`
	`return zip:update-entries($doc, 'archive.zip')`

Errors

Code	Description
`ZIP0001`	A specified path does not exist.

`ZIP0002`	Entries in the ZIP archive description are unknown, missing, or invalid.
`ZIP0003`	An operation fails for some other reason.

Part VII. Developing

Chapter 77. Developing

Read this entry online in the BaseX Wiki.

This page is one of the Main Sections of the documentation. It provides useful information for developers. Here you can find information on various alternatives to integrate BaseX into your own project.

Integrate & Contribute

- Eclipse : Compile and run BaseX from within Eclipse
- Git : Learn how to work with Git
- Maven : Embed BaseX into your own projects
- Releases : Official releases, snapshots, old versions
- Translations : Contribute a new translation to BaseX!

Project (Code, Features, Questions)

- The Source Code can be browsed online
- The Issue Tracker contains feature requests and bug reports
- For questions on the project, please write to our mailing list

Web Technology

- RESTXQ : Write web services with XQuery
- REST : Access and update databases via HTTP requests
- WebDAV : Access databases from your filesystem
- XForms : Build browser forms with XML technologies

APIs

- Clients : Communicate with BaseX using C#, PHP, Python, Perl, C, ...
- Java Examples : Code examples for developing with BaseX
- XQJ API , implemented by Charles Foster (closed source, restricted to XQuery 3.0)
- XQuery for Scala API , based on XQJ and written by Dino Fancellu

Extensions

- Docker : Isolate BaseX in a docker container
- Service/daemon : Install BaseX server as a service
- Android : Running BaseX with Android

Chapter 78. Developing with Eclipse

Read this entry online in the BaseX Wiki.

This page is part of the Developer Section. It describes how to get the BaseX sources compiled and running on your system.

Another article in the documentation describes how to use BaseX as a query processor in Eclipse.

Prerequisites

BaseX is developed with the Eclipse environment (other IDEs like IntelliJ IDEA can be used as well). The Eclipse IDE for Java Developers includes the EGit plugin (for Git) and the m2e plugin (for Maven).

Other Eclipse plugins we use are:

Name	Description	Update URL	Eclipse Marketplace
eclipse-cs	Enforces Checkstyle coding standards.	`http://eclipse-cs.sf.net/update/`	install
FindBugs	Analyze project at byte code level	`http://findbugs.cs.umd.edu/eclipse`	install
UCDetector	Unnecessary code detector	`http://ucdetector.sourceforge.net/update`	install
EclEmma	Code coverage tool.	`http://update.eclemma.org/`	install

Check Out

Our Git Tutorial explains how BaseX can be checked out from the GitHub Repository and embedded in Eclipse with EGit. The article also demonstrates how git can be used on command-line.

The basex repository contains the following sub-directories:

1. `basex-core` is the main project
2. `basex-api` contains the BaseX APIs (XML:DB, bindings in other languages) and HTTP Services (REST, RESTXQ, WebDAV)
3. `basex-examples` includes some examples code for BaseX
4. `basex-tests` contains several unit and stress tests

If the "Problems" View contains errors or warnings, you may need to switch to Java 7 (*Windows → Preferences → Installed JREs*). With the Maven plugin from Eclipse, it sometimes requires several attempts to get all dependencies updated. This loop can be avoided if the sources are precompiled via Maven on command-line.

Start in Eclipse

1. Press *Run → Run…*
2. Create a new "Java Application" launch configuration
3. Select "basex" as "Project"
4. Choose a "Main class" (e.g., `org.basex.BaseXGUI` for the graphical user interface)

5. Launch the project via *Run*

Alternative

You may as well use the standalone version of Maven to compile and run the project, use other IDEs such as IntelliJ IDEA.

Chapter 79. Git

Read this entry online in the BaseX Wiki.

This page is part of the Developer Section. It describes how to use git to manage the BaseX sources.

Using Git to contribute to BaseX

Our team uses git and GitHub to manage the source code. All team members have read/write access to the repository, and external contributors are welcome to fork the project.

Git makes it easy to retain a full copy of the repository for yourself. To get started and running, simply *fork* BaseX:

1. Head over to https://github.com and create an account
2. Fork https://github.com/BaseXdb/basex, so you have a version on your own
3. The forked project can then be cloned on your local machine, and changes can be pushed back to your remote repository

Using Git & Eclipse







Clone

- In the **Package Explorer** to the left, use right-click and choose **Import...**
- Select **Projects from Git** and click **Next >**
- Choose the **Clone** option to create a local copy of the remote repository. This copy will include the full project history
- Copy & Paste the GitHub URI in the Location field. If you want to use SSH, make sure you provided GitHub with your public key to allow write-access. If in doubt, use the https URI and authenticate yourself with your GitHub credentials. The read-only URI of the repository is `https://github.com/BaseXdb/basex.git`.
- Select the master branch (or arbitrary branches you like)
- Now choose a location where the local repository is stored: Create <workspace>/**repos/BaseX** and click "**Finish**".

Create the project

- Select our newly cloned repository and click Next
- Select "**Import Existing Projects**" and depending on your Eclipse version enable automatic sharing. More recent versions will not offer this feature as sharing is enabled by default.
- Click next to select the Project to import
- Check "basex" to checkout and click finish









- You are now ready to contribute.

EGit & SSH

The Eclipse git plugin uses the JSch library, which had problems with RSA SSH keys in Linux and possibly other platforms. If the problem persists, the path to the native SSH executable can be assigned to the Template:Cpde variable. According to this change in EGit, the plugin will try to use a native SSH implementation instead of JSch.

Using Git on Command-Line

Note: this is not intended to be a complete git reference; it's purpose is to quickly introduce BaseX developers to the most commonly used git commands in the context of the BaseX project.

Preparation

1. Create a GitHub user account: here (your github user name will be referenced as $username)
2. Set up SSH access to GitHub as described here
3. Create a fork of one of the BaseXdb projects (it will be referenced as $project)
4. Choose a directory where the project will be created and make it your working directory (e. g. /home/user/myprojects)

Clone Repository

```
$ git clone git@github.com:$username/
$project.git
Cloning into $project...
Enter passphrase for key '/home/
user/.ssh/id_rsa':
...

$ ls -d -1 $PWD/*
/home/user/myprojects/$project
```

Note that git automatically creates a directory where the repository content will be checked out.

List Remote Repositories

```
$ git remote -v
origin  git@github.com:$username/
$project.git (fetch)
origin  git@github.com:$username/
$project.git (push)
```

Currently, there is only one remote repository; it is automatically registered during the clone operation. Git remembers this repository as the default repository for push/pull operations.







List Local Changes

After some files have been changed locally, the changes can be seen as follows:

```
$ git diff
diff --git a/readme.txt b/readme.txt
index fabaeaa..cd09568 100644
--- a/readme.txt
+++ b/readme.txt
@@ -49,6 +49,10 @@ ADDING CHECKSTYLE
 ----------------------------------------------------
   - Enter the URL: http://eclipse-
cs.sourceforge.net/update
   - Follow the installation procedure
 and restart Eclipse

+USING GIT
 ----------------------------------------------------

  Any kind of feedback is welcome;
 please check out the online
 documentation at
```

Commit to Local Repository

Note: this commit operation does **not** commit into the remote repository!

First, it is needed to select the modified files which should be committed:

```
$ git add readme.txt
```

Then perform the actual commit:

```
$ git commit
[master 0fde1fb] Added TODO in section
 "USING GIT"
 1 files changed, 4 insertions(+), 0
 deletions(-)
```

Before executing the actual commit, git will open the default shell editor (determined using the $EDITOR variable, usually vi) to enter a message describing the commit changes.

Alternative way is to commit all changed files, i. e. it is not needed to explicitly add the changed files:

```
$ git commit -a
[master 0fde1fb] Added TODO in section
 "USING GIT"
 1 files changed, 4 insertions(+), 0
 deletions(-)
```

Pushing Changes to Remote Repository

```
$ git push
Enter passphrase for key '/home/
user/.ssh/id_rsa':
Everything up-to-date
```

Pulling Changes from Remote Repository

```
$ git pull
Enter passphrase for key '/home/
user/.ssh/id_rsa':
Already up-to-date.
```

Add Upstream Repository

The upstream repository is the one from which the BaseX releases are made and the one from which the personal repository was forked.

```
$ git remote add upstream
 git@github.com:BaseXdb/$project.git

$ git remote -v
origin  git@github.com:$username/
$project.git (fetch)
origin  git@github.com:$username/
$project.git (push)
upstream        git@github.com:BaseXdb/
$project.git (fetch)
upstream        git@github.com:BaseXdb/
$project.git (push)
```

Pulling Changes from Upstream to Local Repository

When some changes are made in the upstream repository, they can be pulled to the local repository as follows:

```
$ git pull upstream master
Enter passphrase for key '/home/
user/.ssh/id_rsa':
From github.com:BaseXdb/$project
 * branch            master     ->
 FETCH_HEAD
Already up-to-date.
```

The changes can then be pushed in the personal repository:

```
$ git push
```

Check out the links at the end of the page for more git options.

Developing a new feature or bug fix

It is always a good idea to create a new branch for a new feature or a big fix you are working on. So first, let's make sure you have the most up-to-date source code. We assume, that you added BaseX as upstream repository as described above and you are currently in the *master* branch:

```
$ git pull upstream master
```

Now, we create a new branch, based on the master branch

```
$ git checkout -b new-feature
Switched to a new branch 'new-feature'
```

Your are now automatically switched to the *new-feature* branch. Now you can make all your changes in one or several commits. You can commit all changes using

```
$ git commit -a
```

Now, you want to push these changes to the repository on GitHub. Remember, that up to now your changes just reside on your local drive, so now you want to push it to your remote fork of BaseX. Simply do:

```
$ git push origin new-feature
Counting objects: 318, done.
Delta compression using up to 4 threads.
Compressing objects: 100% (107/107), done.
Writing objects: 100% (154/154), 22.96 KiB | 0 bytes/s, done.
Total 154 (delta 93), reused 81 (delta 26)
To git@github.com:$username/basex.git
 * [new branch]      new-feature -> new-feature
```

You can now use your web browser and go to your fork of BaseX. You will see the following message:



You can now click the "Compare & pull request" button. You can now review the changes you are going to push.

Please review them carefully. Also, please give a meaningful comment so we can quickly determine what your changes are doing. After clicking the "Create Pull request" button you are done and we will review your changes and either merge the pull request or get back to you.

Links

- GitHub: git Installation Guide
- Comprehensive Getting Starting Guide on GitHub
- The git book
- Gitcasts.com – Video Guides

Chapter 80. Maven

Read this entry online in the BaseX Wiki.

This page is part of the Developer Section. It demonstrates how Maven is used to compile and run BaseX, and embed it into other projects.

Using Maven

If you have cloned our repository and installed Maven on your machine, you can run the following commands from all local repository directories:

- `mvn compile` : the BaseX source files are compiled.
- `mvn package` : JAR archives are created in the `target` class directory, and all relevant libraries are created in the `lib` directory. Packaging is useful if you want to use the start scripts.
- `mvn install` : the JAR archive is installed to the local repository, and made available to other Maven projects. This is particularly useful if you are compiling a beta version of BaseX, for which no archives exist in the repositories.

By adding the flag `-DskipTests` you can skip the JUnit tests and speed up packaging. You may as well use Eclipse and m2eclipse to compile the BaseX sources.

There are several alternatives for starting BaseX:

- type in `java -cp target/classes org.basex.BaseX` in the `basex-core` directory to start BaseX on the command-line mode,
- type in `mvn jetty:run` in the `basex-api` directory to start BaseX with Jetty and the HTTP servers,
- run one of the Start Scripts contained in the `etc` directory

Artifacts

You can easily embed BaseX into your own Maven projects by adding the following XML snippets to your `pom.xml` file:

```
<repositories>
  <repository>
    <id>basex</id>
    <name>BaseX Maven Repository</name>
    <url>http://files.basex.org/maven</url>
  </repository>
</repositories>
```

BaseX Main Package

```
<dependency>
  <groupId>org.basex</groupId>
  <artifactId>basex</artifactId>
  <version>7.6</version>
</dependency>
```

APIs and Services

...including APIs and the REST, RESTXQ and WebDAV services:

```
<dependency>
  <groupId>org.basex</groupId>
  <artifactId>basex-api</artifactId>
```

```
  <version>7.6</version>
</dependency>
```

XQJ API

The XQJ API is hosted at http://xqj.net:

```
<repository>
  <id>xqj</id>
  <name>XQJ Maven Repository</name>
  <url>http://xqj.net/maven</url>
</repository>
...
<dependency>
  <groupId>net.xqj</groupId>
  <artifactId>basex-xqj</artifactId>
  <version>1.2.0</version>
</dependency>
<dependency>
  <groupId>com.xqj2</groupId>
  <artifactId>xqj2</artifactId>
  <version>0.1.0</version>
</dependency>
<dependency>
  <groupId>javax.xml.xquery</groupId>
  <artifactId>xqj-api</artifactId>
  <version>1.0</version>
</dependency>
```

Chapter 81. Releases

Read this entry online in the BaseX Wiki.

This page is part of the Developer Section. It lists the official locations of major and minor BaseX versions:

Official Releases

Our releases, packaged for various platforms, are linked from our homepage. They are updated every 2-8 weeks:

- `http://basex.org/download`

Our file server contains links to older releases as well (but we recommend everyone to stay up-to-date, as you'll get faster feedback working with the latest version):

- `http://files.basex.org/releases`

Stable Snapshots

If you are a developer, we recommend you to regularly download one of our stable snapshots, which are packaged and uploaded several times a week:

- `http://files.basex.org/releases/latest/`

Note that the offered snapshot files are replaced as soon as newer versions are available.

Code Base

If you always want to be on the cutting edge, you are invited to watch and clone our GitHub repository:

- `https://github.com/BaseXdb/basex`

We do our best to keep our main repository stable as well.

Maven Artifacts

The official releases and the current snapshots of both our core and our API packages are also deployed as Maven artifacts on our file server at regular intervals:

- `http://files.basex.org/maven/org/basex/`

Linux

BaseX can also be found in some Linux distributions, such as Debian, Ubuntu and archlinux (Suse and other distributions will follow soon):

- Debian: http://packages.debian.org/sid/basex
- Ubuntu: http://launchpad.net/ubuntu/+source/basex
- Arch Linux: http://aur.archlinux.org/packages.php?ID=38645

Chapter 82. Translations

Read this entry online in the BaseX Wiki.

This page is part of the Developer Section. It describes how to translate BaseX into other (natural) languages.

Thanks to the following contributors, BaseX is currently available in 10 languages:

- **Dutch** : Huib Verweij
- **English** : BaseX Team
- **French** : Maud Ingarao
- **German** : BaseX Team
- **Hungarian** : Kiss-Kálmán Dániel
- **Indonesian** : Andria Arisal
- **Italian** : Massimo Franceschet
- **Japanese** : Toshio HIRAI and Kazuo KASHIMA
- **Mongolian** : Tuguldur Jamiyansharav
- **Romanian** : Adrian Berila
- **Russian** : Oleksandr Shpak and Max Shamaev
- **Spanish** : Carlos Marcos

It is easy to translate BaseX into your native language! This is how you can proceed:

Working with the sources

If you have downloaded all BaseX sources via Eclipse or Git, you may proceed as follows:

All language files are placed in the `src/main/resources/lang` directory of the main project:

1. Create a copy of an existing translation file (e.g., `English.lang`) and rename it to your target language (e.g. `Hawaiian.lang`).
2. Enter your name and contact information in the second line.
3. If you are using Eclipse, refresh the project (via *Project* → *Refresh*); if you are using Maven, type in `mvn compile`. Your new language file will be automatically detected.
4. Start the BaseX GUI, choose your language via *Options* → *Preferences...* and close the GUI.
5. Translate the texts in your language file and restart BaseX in order to see the changes.
6. Repeat the last step if you want to revise your translations.

If new strings are added to BaseX, they will automatically be added to your language files in English. The history view in GitHub is helpful to see which strings have recently been updated to a file.

Updating BaseX.jar

You can directly add new languages to the JAR file. JAR files are nothing else than ZIP archives, and all language files are placed in the `lang` directory into the JAR file:

1. Unzip an existing translation file (e.g., `English.lang`) and rename it to your target language (e.g. `Hawaiian.lang`)

2. Enter your name and contact information in the second line and translate the texts

3. Update your JAR file by copying the translated file into the zipped `lang` directory. Your new language file will be automatically detected.

4. Start BaseX.jar, choose your language via *Options* → *Preferences*... and restart BaseX to see the changes

You can also directly assign a language in the `.basex` configuration file, which is placed in your home directory. The language is assigned to the `LANG` option. In order to see where the text keys are used within BaseX, you can set `LANGKEY` to `true`.

Part VIII. Web Technology

Chapter 83. RESTXQ

Read this entry online in the BaseX Wiki.

This page presents one of the Web Application services. It describes how to use the RESTXQ API of BaseX.

RESTXQ, introduced by Adam Retter, is an API that facilitates the use of XQuery as a server-side processing language for the Web. RESTXQ has been inspired by Java's JAX-RS API: it defines a pre-defined set of XQuery 3.0 annotations for mapping HTTP requests to XQuery functions, which in turn generate and return HTTP responses.

Please note that BaseX provides various extensions to the original draft of the specification:

- Multipart types are supported, including `multipart/form-data`
- A `%rest:error` annotation can be used to catch XQuery errors
- Servlet errors can be redirected to other RESTXQ pages
- A RESTXQ Module provides some helper functions
- Parameters are implicitly cast to the type of the function argument
- The Path Annotation can contain regular expressions
- `%input` annotations, support for input-specific content-type parameters
- `%rest:single` annotation to cancel running RESTXQ functions
- Quality factors in the Accept header will be evaluated
- *Version 9.0* : Support for server-side quality factors in the `%rest:produces` annotation

Introduction

Preliminaries

The RESTXQ service is accessible via `http://localhost:8984/`.

All RESTXQ annotations are assigned to the `http://exquery.org/ns/restxq` namespace, which is statically bound to the `rest` prefix. A *Resource Function* is an XQuery function that has been marked up with RESTXQ annotations. When an HTTP request comes in, a resource function will be invoked that matches the constraints indicated by its annotations.

If a RESTXQ URL is requested, the `RESTXQPATH` module directory and its sub-directories will be traversed, and all XQuery files will be parsed for functions with RESTXQ annotations. Sub-directories that include an `.ignore` file will be skipped.

To speed up processing, the functions of the existing XQuery modules are automatically cached in main memory:

- Functions will be invalidated and parsed again if the timestamp of their module changes.
- File monitoring can be adjusted via the `PARSERESTXQ` option. In productive environments with a high load, it may be recommendable to change the timeout, or completely disable monitoring.
- If files are replaced while the web server is running, the RESTXQ module cache should be explicitly invalidated by calling the static root path `/.init` or by calling the rest:init function.

Examples

A first RESTXQ function is shown below:

```
module namespace page = 'http://basex.org/examples/web-page';

declare %rest:path("hello/{$who}") %rest:GET function page:hello($who) {
  <response>
    <title>Hello { $who }!</title>
  </response>
};
```

If the URI http://localhost:8984/hello/World is accessed, the result will be:

```
<response>
  <title>Hello World!</title>
</response>
```

The next function demonstrates a POST request:

```
declare
  %rest:path("/form")
  %rest:POST
  %rest:form-param("message","{$message}", "(no message)")
  %rest:header-param("User-Agent", "{$agent}")
function page:hello-postman(
  $message as xs:string,
  $agent   as xs:string*
) as element(response) {
  <response type='form'>
    <message>{ $message }</message>
    <user-agent>{ $agent }</user-agent>
  </response>
};
```

If you post something (e.g. using curl or the embedded form at http://localhost:8984/)...

```
curl -i -X POST --data "message='CONTENT'" http://localhost:8984/form
```

...you will receive something similar to the following result:

```
HTTP/1.1 200 OK
Content-Type: application/xml; charset=UTF-8
Content-Length: 107
Server: Jetty(8.1.11.v20130520)
```

```
<response type="form">
  <message>'CONTENT'</message>
  <user-agent>curl/7.31.0</user-agent>
</response>
```

Request

This section shows how annotations are used to handle and process HTTP requests.

Constraints

Constraints restrict the HTTP requests that a resource function may process.

Paths

A resource function must have a single *Path Annotation* with a single string as argument. The function will be called if a URL matches the path segments and templates of the argument. *Path templates* contain variables in

curly brackets, and map the corresponding segments of the request path to the arguments of the resource function. The first slash in the path is optional.

The following example contains a path annotation with three segments and two templates. One of the function arguments is further specified with a data type, which means that the value for `$variable` will be cast to an `xs:integer` before being bound:

```
declare %rest:path("/a/path/{$with}/some/{$variable}")
  function page:test($with, $variable as xs:integer) { ... };
```

Variables can be enhanced by regular expressions:

```
(: Matches all paths with "app" as first, a number as second, and "order" as third
 segment :)
declare %rest:path("app/{$code=[0-9]+}/order")
  function page:order($full-path) { ... };

(: Matches all other all paths starting with "app/" :)
declare %rest:path("app/{$path=.+}")
  function page:others($path) { ... };
```

Content Negotiation

Two following annotations can be used to restrict functions to specific content types:

- **HTTP Content Types** : A function will only be invoked if the HTTP `Content-Type` header of the request matches one of the given content types. Example:

```
%rest:consumes("application/xml", "text/xml")
```

- **HTTP Accept** : A function will only be invoked if the HTTP `Accept` header of the request matches one of the defined content types. Example:

```
%rest:produces("application/atom+xml")
```

By default, both content types are `*/*`. Quality factors supplied by a client will also be considered in the path selection process. If a client supplies the following accept header…

```
*/*;q=0.5,text/html;q=1.0
```

…and if two RESTXQ functions exist with the same `path` annotation, one with the `produces` annotation `*/*`, and another with `text/html`, the second function will be called, because the quality factor for `text/html` documents is highest.

With *Version 9.0*, support for server-side quality factors was added. If multiple function candidates are left over after the above steps, the `qs` parameter will be considered. The function with the highest quality factor will be favored:

```
%rest:produces("text/html;qs=1")
%rest:produces("*/*;qs=0.8")
```

Note that the annotation will *not* affect the content type of the actual response. You will need to supply an additional `%output:media-type` annotation.

HTTP Methods

Default Methods

The HTTP method annotations are equivalent to all HTTP request methods except TRACE and CONNECT. Zero or more methods may be used on a function; if none is specified, the function will be invoked for each method.

The following function will be called if GET or POST is used as request method:

```
declare %rest:GET %rest:POST %rest:path("/post")
  function page:post() { "This was a GET or POST request" };
```

The POST and PUT annotations may optionally take a string literal in order to map the HTTP request body to a function argument. Once again, the target variable must be embraced by curly brackets:

```
declare %rest:PUT("{$body}") %rest:path("/put")
  function page:put($body) { "Request body: " || $body };
```

Custom Methods

Custom HTTP methods can be specified with the `%rest:method` annotation:

```
declare %rest:method("RETRIEVE")
  function page:retrieve() { "RETRIEVE was specified as request method." };
```

Content Types

The body of a POST or PUT request will be converted to an XQuery item. Conversion can be controlled by specifying a content type. It can be further influenced by specifying additional content-type parameters:

Content-Type	Parameters (`;name=value`)	Type of resulting XQuery item
`text/xml`, `application/xml`		`document-node()`
`text/*`		`xs:string`
`application/json`	JSON Options	`document-node()` or `map(*)`
`text/html`	HTML Options	`document-node()`
`text/comma-separated-values`	CSV Options	`document-node()` or `map(*)`
others		`xs:base64Binary`
`multipart/*`		sequence (see next paragraph)

For example, if `application/json;lax=yes` is specified as content type, the input will be transformed to JSON, and the lax QName conversion rules will be applied, as described in the JSON Module.

Input options

Conversion options for JSON, CSV and HTML can also be specified via annotations with the `input` prefix. The following function interprets the input as text with the CP1252 encoding and treats the first line as header:

```
declare
  %rest:path("/store.csv")
  %rest:POST("{$csv}")
  %input:csv("header=true,encoding=CP1252")
function page:store-csv($csv as document-node()) {
  "Number of rows: " || count($csv/csv/record)
};
```

Multipart Types

The single parts of a multipart message are represented as a sequence, and each part is converted to an XQuery item as described in the last paragraph.

A function that is capable of handling multipart types is identical to other RESTXQ functions:

```
declare
  %rest:path("/multipart")
  %rest:POST("{$data}")
  %rest:consumes("multipart/mixed") (: optional :)
function page:multipart($data as item()*) {
  "Number of items: " || count($data)
};
```

Parameters

The following annotations can be used to bind request values to function arguments. Values will implicitly be cast to the type of the argument.

Query Parameters

The value of the *first parameter*, if found in the query component, will be assigned to the variable specified as *second parameter*. If no value is specified in the HTTP request, all additional parameters will be bound to the variable (if no additional parameter is given, an empty sequence will be bound):

```
declare
  %rest:path("/params")
  %rest:query-param("id", "{$id}")
  %rest:query-param("add", "{$add}", 42, 43, 44)
function page:params($id as xs:string?, $add as xs:integer+) {
  <result id="{ $id }" sum="{ sum($add) }"/>
};
```

HTML Form Fields

Form parameters are specified the same way as query parameters. Their values are the result of HTML forms submitted with the content type `application/x-www-form-urlencoded`.

```
%rest:form-param("parameter", "{$value}", "default")
```

File Uploads

Files can be uploaded to the server by using the content type `multipart/form-data` (the HTML5 `multiple` attribute enables the upload of multiple files):

```
<form action="/upload" method="POST" enctype="multipart/form-data">
  <input type="file" name="files"  multiple="multiple"/>
  <input type="submit"/>
</form>
```

The file contents are placed in a map, with the filename serving as key. The following example shows how uploaded files can be stored in a temporary directory:

```
declare
  %rest:POST
  %rest:path("/upload")
  %rest:form-param("files", "{$files}")
function page:upload($files) {
  for $name    in map:keys($files)
  let $content := $files($name)
  let $path    := file:temp-dir() || $name
  return (
    file:write-binary($path, $content),
    <file name="{ $name }" size="{ file:size($path) }"/>
```

```
  )
};
```

HTTP Headers

Header parameters are specified the same way as query parameters:

```
%rest:header-param("User-Agent", "{$user-agent}")
%rest:header-param("Referer", "{$referer}", "none")
```

Cookies

Cookie parameters are specified the same way as query parameters:

```
%rest:cookie-param("username", "{$user}")
%rest:cookie-param("authentication", "{$auth}", "no_auth")
```

Query Execution

Updated with Version 9.0: The old status code `410` (which indicates to the client that a resource is permanently removed) was replaced with `460`.

In many RESTXQ search scenarios, input from browser forms is processed and search results are returned. User experience can generally be made more interactive if an updated search request is triggered with each key click. However, this may lead to many expensive parallel requests, from which only the result of the last request will be relevant for the client.

With the `%rest:single` annotation, it can be enforced that only one instance of a function will be executed for the same client. If the same function will be called for the second time, the already running query will be stopped, and the HTTP error code `460` will be returned instead:

```
(: If fast enough, returns the result. Otherwise, if called again, raises 460 :)
declare
  %rest:path("/search")
  %rest:query-param("term", "{$term}")
  %rest:single
function page:search($term as xs:string) {
  <ul>{
    for $result in db:open('large-db')//*[text() = $term]
    return <li>{ $result }</li>
  }</ul>
};
```

By specifying a string along with the annotation, functions can be bundled together, and one request can be canceled by calling another one.

This is shown by another example, in which the first function can be interrupted by the second one. If you call both functions in separate browser tabs, you will note that the first tab will return `460`, and the second one will return <xml>stopped</xml>.

```
declare
  %rest:path("/compute")
  %rest:single("EXPENSIVE")
function local:compute() {
  (1 to 100000000000000)[. = 0]
};

declare
  %rest:path("/stop")
```

```
  %rest:single("EXPENSIVE")
function local:stop() {
  <xml>stopped</xml>
};
```

The following things should be noted:

- If a query will be canceled, there will be no undesirable side-effects. For example, it won't be possible to kill a query if it is currenly updating the database or perfoming any other I/O operations. As a result, the termination of a running query can take some more time as expected.
- The currently executed function is bound to the current session. This way, a client will not be able to cancel requests from other clients. As a result, functions can only be stopped if there was at least one previous successful response, in which initial session data was returned to the client.

Response

By default, a successful request is answered with the HTTP status code `200` (OK) and is followed by the given content. An erroneous request leads to an error code and an optional error message (e.g. `404` for "resource not found").

Custom Response

Custom responses can be built from within XQuery by returning an `rest:response` element, an `http:response` child node that matches the syntax of the EXPath HTTP Client Module specification, and more optional child nodes that will be serialized as usual. A function that reacts on an unknown resource may look as follows:

```
declare %rest:path("") function page:error404() {
  <rest:response>
    <http:response status="404" message="I was not found.">
      <http:header name="Content-Language" value="en"/>
      <http:header name="Content-Type" value="text/html; charset=utf-8"/>
    </http:response>
  </rest:response>
};
```

Forwards and Redirects

The two XML elements `rest:forward` and `rest:redirect` can be used in the context of Web Applications, precisely in the context of RESTXQ. These nodes allow e.g. multiple XQuery Updates in a row by redirecting to the RESTXQ path of updating functions. Both wrap a URL to a RESTXQ path. The wrapped URL should be properly encoded via `fn:encode-for-uri()`.

Note that, currently, these elements are not part of RESTXQ specification.

rest:forward

Usage: wrap the location as follows

```
<rest:forward>{ $location }</rest:forward>
```

This results in a server-side forwarding, which as well reduces traffic among client and server. A forwarding of this kind will not change the URL seen from the client's perspective.

As an example, returning

```
<rest:forward>/hello/universe</rest:forward>
```

would internally forward to http://localhost:8984/hello/universe

rest:redirect

The function `web:redirect` can be used to create a redirect response element. Alternatively, the following element can be sent:

```
<rest:redirect>{ $location }</rest:redirect>
```

It is an abbreviation for:

```
<rest:response>
  <http:response status="302">
    <http:header name="location" value="{ $location }"/>
  </http:response>
</rest:response>
```

The client decides whether to follow this redirection. Browsers usually will, tools like curl won't unless `-L` is specified.

Output

The content-type of a response can be influenced by the user via Serialization Parameters. The steps are described in the REST chapter. In RESTXQ, serialization parameters can be specified in the query prolog, via annotations, or within the REST response element:

Query Prolog

In main modules, serialization parameters may be specified in the query prolog. These parameters will then apply to all functions in a module. In the following example, the content type of the response is overwritten with the `media-type` parameter:

```
declare option output:media-type 'text/plain';

declare %rest:path("version1") function page:version1() {
  'Keep it simple, stupid'
};
```

Annotations

Global serialization parameters can be overwritten via `%output` annotations. The following example serializes XML nodes as JSON, using the JsonML format:

```
declare
  %rest:path("cities")
  %output:method("json")
  %output:json("format=jsonml")
function page:cities() {
  element cities {
    db:open('factbook')//city/name
  }
};
```

The next function, when called, generates XHTML headers, and `text/html` will be set as content type:

```
declare
  %rest:path("done")
  %output:method("xhtml")
  %output:omit-xml-declaration("no")
  %output:doctype-public("-//W3C//DTD XHTML 1.0 Transitional//EN")
  %output:doctype-system("http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd")
function page:html() {
```

```
  <html xmlns="http://www.w3.org/1999/xhtml">
    <body>done</body>
  </html>
};
```

Response Element

Serialization parameters can also be specified in a REST reponse element in a query. Serialization parameters will be overwritten:

```
declare %rest:path("version3") function page:version3() {
  <rest:response>
    <output:serialization-parameters>
      <output:media-type value='text/plain'/>
    </output:serialization-parameters>
  </rest:response>,
  'Not that simple anymore'
};
```

Error Handling

XQuery Errors

XQuery runtime errors can be processed via *error annotations*. Error annotations have one or more arguments, which represent the error codes to be caught. The codes equal the names of the XQuery 3.0 try/catch construct:

Precedence	Syntax	Example
1	`prefix:name` `Q{uri}name`	`err:FORG0001` `Q{http://www.w3.org/2005/xqt-errors}FORG0001`
2	`prefix:*` `Q{uri}*`	`err:*` `Q{http://www.w3.org/2005/xqt-errors}*`
3	`*:name`	`*:FORG0001`
4	`*`	`*`

All error codes that are specified for a function must have the same precedence. The following rules apply when catching errors:

- Codes with a higher precedence (smaller number) will be given preference.
- A global RESTXQ error will be raised if two functions with conflicting codes are found.

Similar to try/catch, the pre-defined variables (`code`, `description`, `value`, `module`, `line-number`, `column-number`, `additional`) can be bound to variables via *error parameter annotations*, which are specified the same way as query parameters.

Errors may occur unexpectedly. However, they can also be triggered by a query, as demonstrated by the following example:

```
declare
  %rest:path("/check/{$user}")
function page:check($user) {
  if($user = ('jack', 'lisa'))
  then 'User exists'
  else fn:error(xs:QName('err:user'), $user)
};
```

```
declare
  %rest:error("err:user")
  %rest:error-param("description", "{$user}")
function page:user-error($user) {
  'User "' || $user || '" is unknown'
};
```

An XQuery error in a RESTXQ context delivers by default a HTTP status code 400 error back to the client. However, you can also define a custom error code by using the third argument of the error function:

```
declare
  %rest:path("/teapot")
function page:teapot() {
  fn:error(xs:QName('error'), "I'm a teapot", 418)
};
```

HTTP Errors

Errors that occur outside RESTXQ can be caught by adding `error-page` elements with an error code and a target location to the `web.xml` configuration file (find more details in the Jetty Documentation):

```
<error-page>
  <error-code>404</error-code>
  <location>/error404</location>
</error-page>
```

The target location may be another RESTXQ function. The request:attribute function can be used to request details on the caught error:

```
declare %rest:path("/error404") function page:error404() {
  "URL: " || request:attribute("javax.servlet.error.request_uri") || ", " ||
  "Error message: " || request:attribute("javax.servlet.error.message")
};
```

User Authentication

If you want to provide restricted access to parts of a web applications, you will need to check permissions before returning a response to the client. With *Version 9.0* of BaseX, a Permissions layer was introduced to facilitate permission checks.

Functions

The Request Module contains functions for accessing data related to the current HTTP request. Two modules exist for setting and retrieving server-side session data of the current user (Session Module) and all users known to the HTTP server (Sessions Module). The RESTXQ Module provides functions for requesting RESTXQ base URIs and generating a WADL description of all services. Please note that the namespaces of all of these modules must be explicitly specified via module imports in the query prolog.

The following example returns the current host name:

```
import module namespace request = "http://exquery.org/ns/request";

declare %rest:path("/host-name") function page:host() {
  'Remote host name: ' || request:remote-hostname()
};
```

References

Documentation:

- RESTXQ Specification , First Draft
- RESTful XQuery, Standardised XQuery 3.0 Annotations for REST . Paper, XMLPrague, 2012
- RESTXQ . Slides, MarkLogic User Group London, 2012
- Web Application Development . Slides from XMLPrague 2013

Examples:

- Sample code combining XQuery and JavaScript: Materials and paper from Amanda Galtman, Balisage 2016.
- DBA : The Database Administration interface, bundled with the full distributions of BaseX.

Changelog

Version 9.0

- Added: Support for server-side quality factors in the `%rest:produces` annotation
- Updated: Status code `410` was replaced with `460`
- Removed: `restxq` prefix

Version 8.4

- Added: `%rest:single` annotation

Version 8.1

- Added: support for input-specific content-type parameters
- Added: `%input` annotations

Version 8.0

- Added: Support for regular expresssions in the Path Annotation
- Added: Evaluation of quality factors that are supplied in the Accept header

Version 7.9

- Updated: XQuery Errors, extended error annotations
- Added: `%rest:method`

Version 7.7

- Added: Error Handling, File Uploads, Multipart Types
- Updated: RESTXQ function may now also be specified in main modules (suffix: `*.xq`).
- Updated: the RESTXQ prefix has been changed from `restxq` to `rest`.
- Updated: parameters are implicitly cast to the type of the function argument
- Updated: the RESTXQ root url has been changed to `http://localhost:8984/`

Version 7.5

- Added: new XML elements `<rest:redirect/>` and `<rest:forward/>`

Chapter 84. Permissions

Read this entry online in the BaseX Wiki.

This page presents the web application permission layer of BaseX, which can be used along with RESTXQ.

Non-trivial web applications require a user management: Users need to log in to a web site in order to get access to protected pages; Depending on their status (role, user group, …), they can be offered different views; etc.

With *Version 9.0* of BaseX, a light-weight permission layer has been added that simplifies permission checks a lot:

- Permission strings can be attached to RESTXQ functions.
- With security functions, you can ensure that access to RESTXQ functions will only be granted to clients with sufficient permissions.

Preliminaries

All permission annotations are assigned to the `http://basex.org/modules/perm` namespace, which is statically bound to the `perm` prefix.

Annotations

Permission Strings

With the `%perm:allow` annotation, one or more permission strings can be attached to a RESTXQ function:

```
(:~ Login page (visible to everyone). :)
declare
  %rest:path("/")
  %output:method("html")
function local:login() {
  <html>
    Please log in:
    <form action="/login-check" method="post">
      <input name="name"/>
      <input type="password" name="pass"/>
      <input type="submit"/>
    </form>
  </html>
};

(:~ Main page (restricted to logged in users). :)
declare
  %rest:path("/main")
  %output:method("html")
function local:main() {
  <html>
    Welcome to the main page:
    <a href='/main/admin'>admin area</a>,
    <a href='/logout'>log out</a>.
  </html>
};

(:~ Admin page. :)
declare
  %rest:path("/main/admin")
  %output:method("html")
  %perm:allow("admin")
function local:admin() {
```

```
  <html>
    Welcome to the admin page.
  </html>
};
```

The permission strings may denote ids, users, user groups, applications, or any other realms. It is completely up to the user which strings are used, and which functions will be annotated. In the given example code, only the last function has a `%perm:allow` annotation.

Checking Permissions

Functions that are marked with `%perm:check` are so-called *Security Functions*. These functions will be invoked before the actually requested function will be evaluated. Two arguments can be specified with the annotation:

- A path can be specified as first argument:
  - The security function will only be called if the path of the client request starts with the specified path.
  - In contrast to RESTXQ, all subordinate paths will be accepted as well.
  - If no path argument is specified, `/` is assigned instead.
- A variable can be specified in the second argument. A map with the following keys will be bound to that variable:
  - `allow` : Permission strings attached to the requested function.
  - `path` : Original path of the client request.
  - `method` : Method of the client request (`GET`, `POST`, …).

An example:

```
import module namespace Session = 'http://basex.org/modules/session';

(:~
 : Global permission checks.
 : Rejects any usage of the HTTP DELETE method.
 :)
declare %perm:check %rest:DELETE function local:check() {
  error((), 'Access denied to DELETE method.')
};

(:~
 : Permission check: Area for logged-in users.
 : Checks if a session id exists for the current user; if not, redirects to the
 login page.
 :)
declare %perm:check('/main') function local:check-app() {
  let $user := Session:get('id')
  where empty($user)
  return web:redirect('/')
};

(:~
 : Permissions: Admin area.
 : Checks if the current user is admin; if not, redirects to the main page.
 : @param $perm  map with permission data
 :)
declare %perm:check('/main/admin', '{$perm}') function local:check-admin($perm) {
  let $user := Session:get('id')
  where not(user:list-details($user)/@permission = $perm?allow)
  return web:redirect('/main')
};
```

Some notes:

- If several permission functions are available that match the user request, all of them will be called one after another. The function with the shortest path will be called first. Accordingly, in the example, if the `/main/admin` URL is requested, all three security functions will be run in the given order.
- If a security function raises an error or returns any XQuery value (e.g. a redirection to another web page), no other functions will be invoked. This means that the function that has been requested by the client will only be evaluated if all security functions yield no result and no error.
- As shown in the first function, the `%perm:check` annotation can be combined with other RESTXQ annotations, excluding `%rest:path` and `%rest:error`.
- In the example, it is assumed that a logged in user is bound to a session variable (see further below).

The permission layer was designed to provide as much flexibility as possible to the web application developer: It is possible to completely work without permission strings, and realize all access checks based on the request information (path, method, and properties returned by the Request Module). It is also possible (but rather unhandy) to accompany each RESTXQ function by its individual security function. The bare minimum is a single `%perm:check` function. Without this function, existing `%perm:allow` annotations will be ignored.

Authentication

There are numerous ways how users can be authenticated in a web application (via OAuth, LDAP, …). The approach demonstrated on this page is pretty basic and straightforward:

- A login HTML page allows you to enter your credentials (user name, password).
- A login check function checks if the typed in data matches one of the database users. If the input is valid, a session id will be set, and the user will be redirected to the main page. Otherwise, the redirection points back to the login page.
- A logout page deletes the session id.

The following lines of code complete the image:

```
declare
  %rest:path("/login-check")
  %rest:query-param("name", "{$name}")
  %rest:query-param("pass", "{$pass}")
function local:login($name, $pass) {
  try {
    user:check($name, $pass),
    Session:set('id', $name),
    web:redirect("/main")
  } catch user:* {
    web:redirect("/")
  }
};

declare
  %rest:path("/logout")
function local:logout() {
  Session:delete('id'),
  web:redirect("/")
};
```

For a full round trip, check out the source code of the DBA that is bundled with BaseX.

Changelog

The Module was introduced with Version 9.0.

Chapter 85. REST

Read this entry online in the BaseX Wiki.

This page presents one of the Web Application services. It describes how to use the REST API of BaseX.

BaseX offers a RESTful API for accessing database resources via URLs. REST (REpresentational State Transfer) facilitates a simple and fast access to databases through HTTP. The HTTP methods GET, PUT, DELETE, and POST can be used to interact with the database.

Usage

By default, REST services are available at `http://localhost:8984/rest/`. If no default credentials are specified in the URL or when starting the web application, they will be requested by the client (see further).

A web browser can be used to perform simple GET-based REST requests and display the response. Some alternatives for using REST are listed in the Usage Examples.

URL Architecture

The root URL lists all available databases. The following examples assume that you have created a database instance from the factbook.xml document:

```
http://localhost:8984/rest
```

```
<rest:databases resources="1" xmlns:rest="http://basex.org/rest">
  <rest:database resources="1" size="1813599">factbook</rest:database>
</rest:databases>
```

The resources of a database can be listed by specifying the database, and potential sub directories, in the URL. In the given example, a single XML document is stored in the *factbook* database:

```
http://localhost:8984/rest/factbook
```

```
<rest:database name="factbook" resources="1" xmlns:rest="http://basex.org/rest">
  <rest:resource type="xml" content-type="application/xml"
 size="77192">factbook.xml</rest:resource>
</rest:database>
```

The contents of a database can be retrieved by directly addressing the resource:

```
http://localhost:8984/rest/factbook/factbook.xml
```

If a resource is not found, an HTTP response will be generated with `404` as status code.

Parameters

The following **parameters** can be applied to the operations:

- **Variables** :External variables can be *bound* before a query is evaluated (see below for more).
- **Context** :The `context` parameter may be used to provide an initial XML context node.
- **Options** :Specified Options are applied before the actual operation will be performed.
- **Serialization** :All Serialization parameters known to BaseX can be specified as query parameters. Parameters that are specified within a query will be interpreted by the REST server before the output is generated.

While **Options** can be specified for all operations, the remaining parameters will only make sense for **Query** and **Run**.

Request

GET Method

If the GET method is used, all query parameters are directly specified within the URL. Additionally, the following **operations** can be specified:

- `query` : Evaluate an XQuery expression. If a database or database path is specified in the URL, it is used as initial query context.
- `command` : Execute a single database command.
- `run` : Evaluate an XQuery file or command script located on the server. The file path is resolved against the directory specified by `RESTPATH` (before, it was resolved against `WEBPATH`).

Examples

- Lists all resources found in the **tmp** path of the *factbook* database:`http://localhost:8984/rest/factbook/tmp`
- Serializes a document as JSONML:`http://localhost:8984/rest/factbook/factbook.xml?method=json&json=format=jsonml`
- `US-ASCII` is chosen as output encoding, and the query `eval.xq` is evaluated:`http://localhost:8984/rest?run=eval.xq&encoding=US-ASCII`
- The next URL lists all database users that are known to BaseX:`http://localhost:8984/rest?command=show+users`

POST Method

The body of a POST request is interpreted as XML fragment, which specifies the operation to perform. The name of the root element determines how the body will be evaluated:

- `commands` (new since *Version 9.0*): Run Command Script
- `query` : Execute XQuery expression
- `run` : Run server-side file (query or command script)
- `command` : Execute single command

With *Version 9.0*, the REST namespace of the root element has become optional. This means, for example, that existing command scripts can be sent to the server without any modifications:

- Create an empty database and return database information:

```
<commands>
  <create-db name='db'/>
  <info-db/>
</commands>
```

For the other commands, the following child elements are supported:

Name	Description
`text`	Required; contains the query string, command string, or file to be run

`parameter`	Serialization parameter (with `@name` and `@value` attributes)
`option`	Database option (with `@name` and `@value` attributes)
`variable`	Variable bindings
`context`	Initial context item

Examples

- Return the first five city names of the **factbook** database:

```
<rest:query xmlns:rest="http://basex.org/rest">
  <rest:text><![CDATA[ (//city/name)[position() <= 5] ]]></rest:text>
</rest:query>
```

- Return string lengths of all text nodes that are found in the node that has been specified as initial context node:

```
<query>
  <text>for $i in .//text() return string-length($i)</text>
  <context>
    <xml>
      <text>Hello</text>
      <text>World</text>
    </xml>
  </context>
</query>
```

- Return the registered database users encoded in `ISO-8859-1`:

```
<command>
  <text>show users</text>
  <parameter name='encoding' value='ISO-8859-1'/>
</command>
```

- Create a new database from the specified input and preserve all whitespaces:

```
<command>
  <text>create db test http://files.basex.org/xml/xmark.xml</text>
  <option name='chop' value='false'/>
</command>
```

- Bind value to the `$person` variable and run query `find-person.xq`, which must be located in the directory specified by `WEBPATH`:

```
<run>
  <variable name='person' value='Johannes Müller'/>
  <text>find-person.xq</text>
</run>
```

PUT Method

The PUT method is used to create new databases, or to add or update existing database resources:

- **Create Database** :A new database is created if the URL only specifies the name of a database. If the request body contains XML, a single document is created, adopting the name of the database.

- **Store Resource** :A resource is added to the database if the URL contains a database path. If the addressed resource already exists, it is replaced by the new input.

There are two ways to store non-XML data in BaseX:

- **Store as Raw Data** : If `application/octet-stream` is chosen as content-type, the input is added as Binary Data.
- **Convert to XML** : Incoming data is converted to XML if a parser is available for the specified content-type. The following content types are supported:
  - `application/json` : Stores JSON as XML.
  - `text/plain` : Stores plain text input as XML.
  - `text/comma-separated-values` : Stores CSV text input as XML.
  - `text/html` : Stores HTML input as XML.

Conversion can be influenced by specifying additional content-type parameters (see RESTXQ for more information).

If raw data is added and if no content type, or a wrong content, is specified, a `400` (BAD REQUEST) error will be raised.

Examples

- A new database with the name **XMark** is created. If XML input is sent in the HTTP body, the resulting database resource will be called **XMark.xml**:`http://localhost:8984/rest/XMark`
- A new database is created, and no whitespaces will be removed from the passed on XML input:`http://localhost:8984/rest/XMark?chop=false`
- The contents of the HTTP body will be taken as input for the document **one.xml**, which will be stored in the **XMark** database:`http://localhost:8984/rest/XMark/one.xml`

An HTTP response with status code `201` (CREATED) is sent back if the operation was successful. Otherwise, the server will reply with `404` (if a specified database was not found) or `400` (if the operation could not be completed).

Have a look at the usage examples for more detailed examples using Java and shell tools like cURL.

DELETE Method

The DELETE method is used to delete databases or resources within a database.

Example

- The **factbook** database is deleted:`http://localhost:8984/rest/factbook`
- All resources of the **XMark** database are deleted that reside in the **tmp** path:`http://localhost:8984/rest/XMark/tmp/`

The HTTP status code `404` is returned if no database is specified. `200` (OK) will be sent in all other cases.

Assigning Variables

GET Method

All query parameters that have not been processed before will be treated as variable assignments:

Example

- The following request assigns two variables to a server-side query file `mult.xq` placed in the HTTP directory:`http://localhost:8984/rest?run=mult.xq&$a=21&$b=2`

```
(: XQuery file: mult.xq :)
declare variable $a as xs:integer external;
declare variable $b as xs:integer external;
<mult>{ $a * $b }</mult>
```

The dollar sign can be omitted as long as the variable name does not equal a parameter keyword (e.g.: `method`).

POST Method

If `query` or `run` is used as operation, external variables can be specified via the `<variable/>` element:

```
<query xmlns="http://basex.org/rest">
  <text><![CDATA[
    declare variable $x as xs:integer external;
    declare variable $y as xs:integer external;
    <mult>{ $a * $b }</mult>
  ]]></text>
  <variable name="a" value="21"/>
  <variable name="b" value="2"/>
</query>
```

Response

Content Type

As the content type of a REST response cannot necessarily be dynamically determined, it can be enforced by the user. The final content type of a REST response is chosen as follows:

1. If the serialization parameter `media-type` is supplied, it will be adopted as content-type.
2. Otherwise, if the serialization parameter `method` is supplied, the content-type will be chosen according to the following mapping:
   - `xml` , `adaptive`, `basex` → `application/xml`
   - `xhtml` → `text/html`
   - `html` → `text/html`
   - `text` → `text/plain`
   - `json` → `application/json`
3. If no media-type or serialization method is supplied, the content type of a response depends on the chosen REST operation:
   - **Query** /**Run** → `application/xml`
   - **Command** → `text/plain`
   - **Get** → `application/xml`, or content type of the addressed resource

Serialization parameters can either be supplied as query parameters or within the query.

The following three example requests all return `<a/>` with `application/xml` as content-type:

```
http://localhost:8984/rest?query=%3Ca/%3E     http://localhost:8984/rest?
query=%3Ca/%3E&method=xml http://localhost:8984/rest?query=%3Ca/%3E&media-
type=application/xml
```

Usage Examples

Java

Authentication

Most programming languages offer libraries to communicate with HTTP servers. The following example demonstrates how easy it is to perform a DELETE request with Java.

Basic access authentication can be activated in Java by adding an authorization header to the `HttpURLConnection` instance. The header contains the word `Basic`, which specifies the authentication method, followed by the Base64-encoded `USER:PASSWORD` pair. As Java does not include a default conversion library for Base64 data, the internal BaseX class `org.basex.util.Base64` can be used for that purpose:

```
import java.net.*;
import org.basex.util.*;

public final class RESTExample {
  public static void main(String[] args) throws Exception {
    // The java URL connection to the resource.
    URL url = new URL("http://localhost:8984/rest/factbook");

    // Establish the connection to the URL.
    HttpURLConnection conn = (HttpURLConnection) url.openConnection();
    // Set as DELETE request.
    conn.setRequestMethod("DELETE");

    // User and password.
    String user = "bob";
    String pw ="alice";
    // Encode user name and password pair with a base64 implementation.
    String encoded = Base64.encode(user + ":" + pw);
    // Basic access authentication header to connection request.
    conn.setRequestProperty("Authorization", "Basic " + encoded);

    // Print the HTTP response code.
    System.out.println("HTTP response: " + conn.getResponseCode());

    // Close connection.
    conn.disconnect();
  }
}
```

Content-Types

The content-type of the input can easily be included, just add the following property to the connection (in this example we explicitly store the input file as raw):

```
// store input as raw
conn.setRequestProperty("Content-Type", "application/octet-stream");
```

See the PUT Requests section for a description of the possible content-types.

Find Java examples for all methods here: GET, POST, PUT, DELETE.

Command Line

Tools such as the Linux commands Wget or cURL exist to perform HTTP requests (try copy & paste):

GET

- `curl -i "http://localhost:8984/rest/factbook?query=//city/name"`

POST

- `curl -i -X POST -H "Content-Type: application/xml" -d "<query xmlns='http://basex.org/rest'><text>//city/name</text></query>""http://localhost:8984/rest/factbook"`
- `curl -i -X POST -H "Content-Type: application/xml" -T query.xml "http://localhost:8984/rest/factbook"`

PUT

- `curl -i -X PUT -T "etc/xml/factbook.xml""http://localhost:8984/rest/factbook"`
- `curl -i -X PUT -H "Content-Type: application/json" -T "plain.json""http://localhost:8984/rest/plain"`

DELETE

- `curl -i -X DELETE "http://admin:admin@localhost:8984/rest/factbook"`

Changelog

Version 9.0

- Added: Support for command scripts in the POST Method.
- Updated: The REST namespace in the POST Method has become optional.

Version 8.1

- Added: Support for input-specific content-type parameters
- Updated: The run operation now resolves file paths against the RESTPATH option.

Version 8.0

- Removed: `wrap` parameter

Version 7.9

- Updated: Also evaluate command scripts via the `run` operation.

Version 7.2

- Removed: Direct evaluation of adresses resources with `application/xquery` as content type

Version 7.1.1

- Added: `options` parameter for specifying database options

Version 7.1

- Added: PUT request: automatic conversion to XML if known content type is specified

Version 7.0

- REST API introduced, replacing the old JAX-RX API

Chapter 86. WebDAV

Read this entry online in the BaseX Wiki.

This page presents one of the Web Application services. It describes how to use the WebDAV file system interface.

BaseX offers access to the databases and documents using the WebDAV protocol. WebDAV provides convenient means to access and edit XML documents by representing BaseX databases and documents in the form of a file system hierarchy.

The implementation in BaseX is based on the Milton library. Currently, only Basic Authentication is supported.

Usage

By default, the BaseX HTTP server makes the WebDAV service accessible at `http://localhost:8984/webdav/`. If no default credentials are specified, they will be requested by the client (see further). It can be accessed by either `http://<httphost>:<httpport>/webdav/` or `webdav://<httphost>:<httpport>/webdav/`, depending on your WebDAV client.

Please note that the file size of XML documents will be displayed as 0 bytes, as the actual file size can only be determined if the full document is being returned and serialized. This may cause problems with some WebDAV clients (e.g. NetDrive or WebDrive).

Authorization

The WebDAV service uses the database user credentials in order to perform authentication and authorization. If database user and password are explicitly specified when starting the BaseX HTTP Server using the corresponding startup options, WebDAV will not request additional user authentication from the client.

Root Directory

In the WebDAV root directory, all existing databases are listed. As new resources can only be stored inside a database, it is not possible to store files in the root directory. If a file is copied on top level, a new database will be created, which contains this resource.

Resources

XML Documents

Uploaded files that start with an angle bracket will be stored as XML files. XML entities will be decoded during this process.

If a file is downloaded, the characters with the following code points will be encoded as entities:

- 160 (non-breaking space)
- 8192–8207, 8232–8239, 8287–8303 (see http://www.w3schools.com/charsets/ref_utf_punctuation.asp)

Binary Files

If XML parsing files, or if the first character of the input is no angle bracket, the file will be stored as binary resource.

Locking

The BaseX WebDAV implementation supports locking. It can be utilized with clients which support this feature (e.g. oXygen Editor). EXCLUSIVE and SHARED locks are supported, as well as WRITE locks.

Note: WebDAV locks are stored in a database called `~webdav`. If the database is deleted, it will automatically be recreated along with the next lock operations. If a resource remains locked, it can be unlocking by removing the correspondent `<w:lockinfo>` entry.

WebDAV Clients

Please check out the following tutorials to get WebDAV running on different operating systems and with oXygen:

- Windows 7 and up
- Windows XP
- Mac OSX 10.4+
- GNOME and Nautilus
- KDE
- oXygen Editor

Changelog

Version 7.7

- Added: Locking

Version 7.0

- WebDAV API introduced

Chapter 87. WebDAV: Windows 7

Read this entry online in the BaseX Wiki.

This page belongs to the WebDAV page. It describes how to get the WebDAV API running with Windows 7.

- Open the Explorer
- Open the "Map network drive..." dialog by right-clicking on "My Computer"
- Click on the link "Connect to a Web site that you can use to store your documents and pictures."



- Click "Next", select "Choose a custom network location" and click "Next" again.



- Enter the URL address of the BaseX WebDAV Server (e.g. `http://localhost:8984/webdav`) and click "Next".



If a message saying that the folder is not valid, this is because Microsoft WebClient is not configured to use Basic HTTP authentication. Please check out the following StackOverflow entry in order to enable Basic HTTP authentication.

- Enter a name for the network location and click "Next".



- The BaseX WebDAV can be accessed from the Explorer window.



Chapter 88. WebDAV: Windows XP

Read this entry online in the BaseX Wiki.

This page belongs to the WebDAV page. It describes how to get the WebDAV API running with Windows XP.

- In the "My Network Places" view, double click on "Add Network Place":



- Confirm the upcoming introductory dialog:



- Select "Choose another network location" in the next dialog:



- Next, specify the BaseX WebDAV URL:



- Enter the user/password combination to connect to the WebDAV service:



- Assign a name to your WebDAV connection:



- Finish the wizard:



- You can now see all BaseX databases in the Windows Explorer:


File Edit View Favorites Tools Help
Address http://localhost:8984/webdav/
Folders
Desktop
My Documents
My Computer
My Network Places
Entire Network
BaseX WebDAV
factbook
Recycle Bin
Name
Internet Address
Size
Type
Modified
factbook
http://localhost:8984/webdav/factbook
Web Folder
1 objects

Chapter 89. WebDAV: Mac OSX

Read this entry online in the BaseX Wiki.

This page belongs to the WebDAV page. It describes how to get the WebDAV API running with Mac OS X 10.4+.

- Mac OS X supports WebDAV since 10.4/Tiger
- Open Finder, choose Go -> Connect to Server:



- Enter BaseX WebDAV URL (eg. http://localhost:8984/webdav) - do not use webdav://-scheme! Press Connect:



- Enter the user credentials:

- That's it, now the databases can be browsed:


webdav
FAVORITES
All My Files
Applications
Desktop
Documents
Downloads
Movies
Music
Pictures
SHARED
localhost
Name
factbook
factbook.xml
test
factbook.xml
<mondial>
<continent id="f0_119" name="Europe"/>
<continent id="f0_123" name="Asia"/>
<continent id="f0_126" name="America"/>
<continent id="f0_129" name="Australia/Oceania"/>
<continent id="f0_132" name="Africa"/>
<country id="f0_136" name="Albania" capital="f0_1461" population="3249136"
datacode="AL" total_area="28750" population_growth="1.34" infant_mortality="49.2"
gdp_agri="55" gdp_total="4100" inflation="16" indep_date="28 11 1912"
government="emerging democracy" car_code="AL">
<name>Albania</name>
<city id="f0_1461" country="f0_136" longitude="10.7" latitude="46.2">
<name>Tirane</name>
<population year="87">192000</population>
</city>
<city id="f0_36498" country="f0_136" longitude="19.2" latitude="42.2">
<name>Shkoder</name>
<population year="87">62000</population>
<located_at type="lake" water="f0_39058"/>
</city>
<city id="f0_36504" country="f0_136" longitude="19.3" latitude="41.2">
<name>Durres</name>
<population year="87">60000</population>
<located_at type="sea" water="f0_38042"/>
</city>
<city id="f0_36509" country="f0_136" longitude="19.3" latitude="40.3">
<name>Vlore</name>
<population year="87">56000</population>
<located_at type="sea" water="f0_38042"/>
</city>
<city id="f0_36514" country="f0_136" longitude="20.1" latitude="41.1">
<name>Elbasan</name>
<population year="87">53000</population>
</city>
<city id="f0_36518" country="f0_136" longitude="20.5" latitude="40.4">
<name>Korce</name>
Line: 1 Column: 1
XML
Tab Size: 4

Chapter 90. WebDAV: GNOME

Read this entry online in the BaseX Wiki.

This page belongs to the WebDAV page. It describes how to get the WebDAV API running with GNOME and Nautilus.

- In Nautilus choose File -> Connect to Server:



- Choose "WebDAV (HTTP)" from the "Type" drop-down and enter the server address, port and user credentials:



- After clicking "Connect" the databases can be browsed:



Chapter 91. WebDAV: KDE

Read this entry online in the BaseX Wiki.

This page belongs to the WebDAV page. It describes how to get the WebDAV API running with KDE.

- KDE SC provides two file managers - Dolphin and Konqueror, which both support WebDAV using the "webdav://" URL prefix. Start Dolphin or Konqueror and enter the BaseX WebDAV URL (eg. webdav://localhost:8984/webdav):



- Enter the user credentials:



- After clicking "OK" the databases can be browsed:


File Edit View Go Tools Settings Help
webdav://localhost:8984/webdav/
Name Size Date
myproject 3 items 14.09.2011 15:17
data 1 item 27.09.2011 19:40
records.xml 0 B 27.09.2011 19:40
images 2 items 14.09.2011 16:56
image1.gif 13,0 KiB 14.09.2011 16:56
image2.gif 13,0 KiB 27.09.2011 19:00
xquery 1 item 14.09.2011 15:17
hello.xq 90 B 14.09.2011 15:17
10 Folders
Unknown size

Chapter 92. XForms

Read this entry online in the BaseX Wiki.

This page is part of the Developer Section and belongs to the Web Application stack. It describes how to use XForms with BaseX.

XForms provides mechanisms to display and edit the contents of XML snippets in the browser without resorting to JavaScript. In combination with the RESTXQ API and the database backend, this is an elegant way of building web applications that completely reside in the XML stack.

Internals

If an HTML document with XForms elements is requested, a web form is generated, which allows users to edit the contents of an XML file. The data model stays consistent during this process, i.e. the data types are always as described in the models. Actions can be configured as well: the model can e. g. be sent to a server and processed further, using the REST or RESTXQ APIs.

Run the example

Several implementations of the XForms Recommendation are available (some AJAX-based, some client-side). In this article, we will focus on the light-weight, LGPL-licensed XSLTForms project from Alain Couthures. The following steps are required to get the XForms example running:

- download the xsltforms.zip example file, which includes the demo page and XSLTForms, and extract its contents to your `webapp` directory
- start a BaseX HTTP server
- open a browser and visit the URL `http://localhost:8984/static/xforms-demo.xml`

This is the head section of the XForms demo:

```
<?xml-stylesheet href="xsltforms/xsltforms.xsl" type="text/xsl"?>
<html xmlns="http://www.w3.org/1999/xhtml" xmlns:xf="http://www.w3.org/2002/
xforms">
  <!-- ... -->
</html>
```

The processing instruction in the first line tells the browser where to find the XSLTForms implementation. The rules of the XML Stylesheet will then be applied to transform the XForms elements in the document to HTML. As the XForms code is interpreted, it can not be inspected in the browser, but you can press `F1` to enter the debug mode.

Usually, the XForms Model is placed in the head section of the HTML document:

```
<xf:model>
  <xf:instance>
    <track xmlns="">
      <metadata>
        <title>Like A Rolling Stone</title>
        <artist>Bob Dylan</artist>
        <date>1965-06-21</date>
        <genre>Folk</genre>
      </metadata>
    </track>
  </xf:instance>
  <xf:bind id="_date" nodeset="//date" type="xs:date"/>
```

```
  </xf:model>
```

It contains an instance of the model and a binding. The model is some plain XML, and the `xf:bind` elements can be used to bind elements to a specific type.

The data can be accessed with the `xf:output` element, and the XML nodes to be displayed are addressed via XPath 1.0 in the `ref` attribute. For example, the artist is addressed via:

```
<xf:output ref="//artist"/>
```

To modify the XML instance, `xf:input` elements are used. With the following code,

```
<xf:input ref="//date" incremental="true"/>
```

an input element is displayed that allows users to change the date. As `xs:date` was bound to dates in the data model, a date picker will be presented for choosing a valid date.

Further reading

For further reading, you are invited to

- check out the XForms Wikibooks page,
- look into the XForms 2.0 specification, or
- join the xsltforms-support mailing list.

Part IX. Client APIs

Chapter 93. Clients

Read this entry online in the BaseX Wiki.

This page is part of the Developer Section. It describes how to communicate with BaseX from other programming languages.

You can use the following light-weight language bindings to connect to a running BaseX server instance, execute database commands and evaluate XQuery expressions.

Most clients provide two modes:

- Standard Mode : connecting to a server, sending commands
- Query Mode : defining queries, binding variables, iterative evaluation

Please see the Server Protocol for more information on the available commands. Currently, we offer bindings for the following programming languages:

BaseX 7.x, BaseX 8.x and later

- Java : The default implementation
- C++ : contributed by Jean-Marc Mercier
- C# , contributed by the BaseX Team and Martín Ferrari
- C , contributed by the BaseX Team
- Golang : contributed by Christian Baune
- Erlang : contributed by Zachary Dean
- node.js : contributed by Andy Bunce
- Perl , contributed by the BaseX Team
- PHP : updated by James Ball
- Python : contributed by Hiroaki Itoh
- Python , using BaseX REST services: contributed by Luca Lianas
- Ruby , contributed by the BaseX Team

With **Version 8.0**, authentication has changed. Some of the language bindings have not been updated yet. The update is rather trivial, though (see here for more details); we are looking forward to your patches!

BaseX 7.x (outdated)

- ActionScript : contributed by Manfred Knobloch
- Haskell : contributed by Leo Wörteler
- Lisp : contributed by Andy Chambers
- node.js : contributed by Hans Hübner (deviating from client API)
- Qt : contributed by Hendrik Strobelt
- Rebol : contributed by Sabu Francis
- Scala : contributed by Manuel Bernhardt
- Scala (simple implementation)
- VB , contributed by the BaseX Team

Many of the interfaces contain the following files:

- `BaseXClient` contains the code for creating a session, sending and executing commands and receiving results. An inner `Query` class facilitates the binding of external variables and iterative query evaluation.
- `Example` demonstrates how to send database commands.
- `QueryExample` shows you how to evaluate queries in an iterative manner.

- `QueryBindExample` shows you how to bind a variable to your query and evaluates the query in an iterative manner.
- `CreateExample` shows how new databases can be created by using streams.
- `AddExample` shows how documents can be added to a database by using streams.

Changelog

Version 8.0

- Updated: cram-md5 replaced with digest authentication

Chapter 94. Standard Mode

Read this entry online in the BaseX Wiki.

In the standard mode of the Clients, a database command can be sent to the server using the `execute()` function of the `Session`. This functions returns the whole result. With the `info()` function, you can request some information on your executed process. If an error occurs, an exception with the error message will be thrown.

Usage

The standard execution works as follows:

1. Create a new session instance with hostname, port, username and password.
2. Call the `execute()` function of the session with the database commands as argument.
3. Receive the result of a successfully executed command. If an error occurs, an exception is thrown.
4. Optionally, call `info()` to get some process information
5. Continue using the client (back to 2.), or close the session.

Example in PHP

Taken from our repository:

```
<?php
/*
 * This example shows how database commands can be executed.
 * Documentation: http://basex.org/api
 *
 * (C) BaseX Team 2005-15, BSD License
 */
include("BaseXClient.php");

try {
  // initialize timer
  $start = microtime(true);

  // create session
  $session = new Session("localhost", 1984, "admin", "admin");

  // perform command and print returned string
  print $session->execute("xquery 1 to 10");

  // close session
  $session->close();

  // print time needed
  $time = (microtime(true) - $start) * 1000;
  print "\n$time ms\n";

} catch (Exception $e) {
  // print exception
  print $e->getMessage();
}
?>
```

Chapter 95. Query Mode

Read this entry online in the BaseX Wiki.

The query mode of the Clients allows you to bind external variables to a query and evaluate the query in an iterative manner. The `query()` function of the `Session` instance returns a new query instance.

Usage

The query execution works as follows:

1. Create a new session instance with hostname, port, username and password.
2. Call `query()` with your XQuery expression to get a query object.
3. Optionally bind variables to the query with one of the `bind()` functions.
4. Optionally bind a value to the context item via `context()`.
5. Iterate through the query object with the `more()` and `next()` functions.
6. As an alternative, call `execute()` to get the whole result at a time.
7. `info()` gives you information on query evaluation.
8. `options()` returns the query serialization parameters.
9. Don't forget to close the query with `close()`.

PHP Example

Taken from our repository:

```
<?php
/*
 * This example shows how queries can be executed in an iterative manner.
 * Documentation: http://basex.org/api
 *
 * (C) BaseX Team 2005-15, BSD License
 */
include("BaseXClient.php");

try {
  // create session
  $session = new Session("localhost", 1984, "admin", "admin");

  try {
    // create query instance
    $input = 'declare variable $name external; '.
      'for $i in 1 to 10 return element { $name } { $i }';
    $query = $session->query($input);

    // bind variable
    $query->bind("$name", "number");

    // print result
    print $query->execute()."\n";

    // close query instance
    $query->close();
```

```
  } catch (Exception $e) {
    // print exception
    print $e->getMessage();
  }

  // close session
  $session->close();

} catch (Exception $e) {
  // print exception
  print $e->getMessage();
}
?>
```

Changelog

Version 7.2

- Added: `context()` function

Chapter 96. Server Protocol

Read this entry online in the BaseX Wiki.

This page presents the classes and functions of the BaseX Clients, and the underlying protocol, which is utilized for communicating with the database server. A detailed example demonstrates how a concrete byte exchange can look like.

Workflow

- All clients are based on the client/server architecture. Hence, a BaseX database server must be started first.
- Each client provides a session class or script with methods to connect to and communicate with the database server. A socket connection will be established by the constructor, which expects a host, port, user name and password as arguments.
- The `execute()` method is called to launch a database command. It returns the result or throws an exception with the received error message.
- The `query()` method creates a query instance. Variables and the context item can be bound to that instance, and the result can either be requested via `execute()`, or in an iterative manner with the `more()` and `next()` functions. If an error occurs, an exception will be thrown.
- The `create()`, `add()`, `replace()` and `store()` method pass on input streams to the corresponding database commands.
- To speed up execution, an output stream can be specified by some clients; this way, all results will be directed to that output stream.
- Most clients are accompanied by some example files, which demonstrate how database commands can be executed or how queries can be evaluated.

Transfer Protocol

All Clients use the following client/server protocol to communicate with the server. The description of the protocol is helpful if you want to implement your own client.

Conventions

- `\xx` : single byte.
- `{...}` : utf8 strings or raw data, suffixed with a `\00` byte. To avoid confusion with this end-of-string byte, all transfered `\00` and `\FF` bytes are prefixed by an additional `\FF` byte.

Authentication

Digest

Digest authentication is used since Version 8.0:

1. Client connects to server socket
2. Server sends a **realm** and **nonce**, separated by a colon: `{realm:nonce}`
3. Client sends the **user name** and a hash value. The hash is composed of the md5 hash of
   a. the md5 hash of the **user name**, **realm**, and **password** (all separated by a colon), and
   b. the **nonce**: `{username} {md5(md5(username:realm:password) + nonce)}`
4. Server replies with `\00` (success) or `\01` (error)

CRAM-MD5

CRAM-MD5 was discarded, because unsalted md5 hashes could easily be uncovered using rainbow tables. However, most client bindings still provide support for the outdated handshaking, as it only slightly differs from the new protocol:

1. Client connects to server socket
2. Server sends a **nonce** (timestamp): `{nonce}`
3. Client sends the **user name** and a hash value. The hash is composed of the md5 hash of
   a. the md5 of the **password** and
   b. the **nonce**: `{username} {md5(md5(password) + nonce)}`
4. Server replies with `\00` (success) or `\01` (error)

Clients can easily be implemented to both support `digest` and `cram-md5` authentication: If the first server response contains no colon, `cram-md5` should be chosen.

Command Protocol

The following byte sequences are sent and received from the client (please note that a specific client may not support all of the presented commands):

Command	Client Request	Server Response	Description
COMMAND	`{command}`	`{result} {info} \00`	Executes a database command.
QUERY	`\00 {query}`	`{id} \00`	Creates a new query instance and returns its id.
CREATE	`\08 {name} {input}`	`{info} \00`	Creates a new database with the specified input (may be empty).
ADD	`\09 {name} {path} {input}`	`{info} \00`	Adds a new resource to the opened database.
REPLACE	`\0C {path} {input}`	`{info} \00`	Replaces a resource with the specified input.
STORE	`\0D {path} {input}`	`{info} \00`	Stores a binary resource in the opened database.
# error		`{` *partial result* `} {error} \01`	Error feedback.

Query Command Protocol

Queries are referenced via an `id`, which has been returned by the `QUERY` command (see above).

Query Command	Client Request	Server Response	Description
CLOSE	`\02 {id}`	`\00 \00`	Closes and unregisters the query with the specified id.
BIND	`\03 {id} {name} {value} {type}`	`\00 \00`	Binds a value to a variable. The type will be ignored if the string is empty.
RESULTS	`\04 {id}`	`\xx {item} ... \xx {item} \00`	Returns all resulting items as strings, prefixed by a single byte (`\xx`) that

			represents the Type ID. This command is called by the `more()` function of a client implementation.
EXECUTE	`\05 {id}`	`{result} \00`	Executes the query and returns the result as a single string.
INFO	`\06 {id}`	`{result} \00`	Returns a string with query compilation and profiling info.
OPTIONS	`\07 {id}`	`{result} \00`	Returns a string with all query serialization parameters, which can e.g. be assigned to the SERIALIZER option.
CONTEXT	`\0E {id} {value} {type}`	`\00 \00`	Binds a value to the context. The type will be ignored if the string is empty.
UPDATING	`\1E {id}`	`{result} \00`	Returns `true` if the query contains updating expressions; `false` otherwise.
FULL	`\1F {id}`	`XDM {item} ... XDM {item} \00`	Returns all resulting items as strings, prefixed by the XDM Meta Data. This command is e. g. used by the XQJ API.

As can be seen in the table, all results end with a single `\00` byte, which indicates that the process was successful. If an error occurs, an additional byte `\01` is sent, which is then followed by the `error` message string.

Binding Sequences

Also sequences can be bound to variables and the context:

- `empty-sequence()` must be supplied as type if an empty sequence is to be bound.
- Multiple items are supplied via the `{value}` argument and separated with `\01` bytes.
- Item types are specified by appending `\02` and the type in its string representation to an item. If no item type is specified, the general type is used.

Some examples for the `{value}` argument:

- the two integers `123` and `789` are encoded as `123`, `\01`, `789` and `\00` (`xs:integer` may be specified via the `{type}` argument).
- the two items `xs:integer(123)` and `xs:string('ABC')` are encoded as `123`, `\02`, `xs:integer`, `\01`, `ABC`, `\02`, `xs:string` and `\00`.

Example

In the following example, a client registers a new session and executes the INFO database command. Next, it creates a new query instance for the XQuery expression `1, 2+'3'`. The query is then evaluated, and the server returns the result of the first subexpression `1` and an error for the second sub expression. Finally, the query instance and client session are closed.

- **Client** connects to the database server socket
- **Server** sends realm and timestamp "BaseX:1369578179679": `# 42 61 73 65 58 3A 31 33 36 39 35 37 38 31 37 39 36 37 39 00`
- **Client** sends user name "jack": `6A 61 63 6B 00 #`
- **Client** sends hash: md5(md5("jack:BaseX:topsecret") + "1369578179679") = "ca664a31f8deda9b71ea3e79347f6666": `63 61 36 ... 00 #`
- **Server** replies with success code: `# 00`
- **Client** sends the "INFO" command: `49 4E 46 4F 00 #`
- **Server** responds with the result "General Information...": `# 47 65 6e 65 ... 00`
- **Server** additionally sends an (empty) info string: `# 00`
- **Client** creates a new query instance for the XQuery "1, 2+'3'": `00 31 2C 20 32 2B 27 33 27 00 #`
- **Server** returns query id "1" and a success code: `# 31 00 00`
- **Client** requests the query results via the RESULTS protocol command and its query id: `04 31 00 #`
- **Server** returns the first result ("1", type xs:integer): `# 52 31 00`
- **Server** sends a single `\00` byte instead of a new result, which indicates that no more results can be expected: `# 00`
- **Server** sends the error code `\01` and the error message ("Stopped at..."): `# 01 53 74 6f ... 00`
- **Client** closes the query instance: `02 31 00 #`
- **Server** sends a response (which is equal to an empty info string) and success code: `# 00 00`
- **Client** closes the socket connection

Constructors and Functions

Most language bindings provide the following constructors and functions:

Session

- Create and return session with host, port, user name and password:`Session(String host, int port, String name, String password)`
- Execute a command and return the result:`String execute(String command)`
- Return a query instance for the specified query:`Query query(String query)`
- Create a database from an input stream:`void create(String name, InputStream input)`
- Add a document to the current database from an input stream:`void add(String path, InputStream input)`
- Replace a document with the specified input stream:`void replace(String path, InputStream input)`
- Store raw data at the specified path:`void store(String path, InputStream input)`
- Return process information:`String info()`
- Close the session:`void close()`

Query

- Create query instance with session and query:`Query(Session session, String query)`
- Bind an external variable:`void bind(String name, String value, String type)`The type can be an empty string.
- Bind the context item:`void context(String value, String type)`The type can be an empty string.
- Execute the query and return the result:`String execute()`
- Iterator: check if a query returns more items:`boolean more()`
- Iterator: return the next item:`String next()`
- Return query information:`String info()`
- Return serialization parameters:`String options()`
- Return if the query may perform updates:`boolean updating()`
- Close the query:`void close()`

Changelog

Version 8.2

- Removed: `WATCH` and `UNWATCH` command

Version 8.0

- Updated: cram-md5 replaced with digest authentication
- Updated: `BIND` command: support more than one item

Version 7.2

- Added: Query Commands CONTEXT, UPDATING and FULL
- Added: Client function `context(String value, String type)`

Chapter 97. Server Protocol: Types

Read this entry online in the BaseX Wiki.

This article lists extended type information that is returned by the Server Protocol.

XDM Meta Data

In most cases, the XDM meta data is nothing else than the Type ID. There are three exceptions: document-node(), attribute() and xs:QName items are followed by an additional `{URI}` string.

Type IDs

The following table lists the type IDs that are returned by the server. Currently, all node kinds are of type `xs:untypedAtomic`:

Type ID	Node Kind/Item Type	Type
7	Function item	*function*
8	`node()`	*node*
9	`text()`	*node*
10	`processing-instruction()`	*node*
11	`element()`	*node*
12	`document-node()`	*node*
13	`document-node(element())`	*node*
14	`attribute()`	*node*
15	`comment()`	*node*
32	`item()`	*atomic value*
33	`xs:untyped`	*atomic value*
34	`xs:anyType`	*atomic value*
35	`xs:anySimpleType`	*atomic value*
36	`xs:anyAtomicType`	*atomic value*
37	`xs:untypedAtomic`	*atomic value*
38	`xs:string`	*atomic value*
39	`xs:normalizedString`	*atomic value*
40	`xs:token`	*atomic value*
41	`xs:language`	*atomic value*
42	`xs:NMTOKEN`	*atomic value*
43	`xs:Name`	*atomic value*
44	`xs:NCName`	*atomic value*
45	`xs:ID`	*atomic value*
46	`xs:IDREF`	*atomic value*
47	`xs:ENTITY`	*atomic value*
48	`xs:float`	*atomic value*
49	`xs:double`	*atomic value*
50	`xs:decimal`	*atomic value*
51	`xs:precisionDecimal`	*atomic value*

52	`xs:integer`	*atomic value*
53	`xs:nonPositiveInteger`	*atomic value*
54	`xs:negativeInteger`	*atomic value*
55	`xs:long`	*atomic value*
56	`xs:int`	*atomic value*
57	`xs:short`	*atomic value*
58	`xs:byte`	*atomic value*
59	`xs:nonNegativeInteger`	*atomic value*
60	`xs:unsignedLong`	*atomic value*
61	`xs:unsignedInt`	*atomic value*
62	`xs:unsignedShort`	*atomic value*
63	`xs:unsignedByte`	*atomic value*
64	`xs:positiveInteger`	*atomic value*
65	`xs:duration`	*atomic value*
66	`xs:yearMonthDuration`	*atomic value*
67	`xs:dayTimeDuration`	*atomic value*
68	`xs:dateTime`	*atomic value*
69	`xs:dateTimeStamp`	*atomic value*
70	`xs:date`	*atomic value*
71	`xs:time`	*atomic value*
72	`xs:gYearMonth`	*atomic value*
73	`xs:gYear`	*atomic value*
74	`xs:gMonthDay`	*atomic value*
75	`xs:gDay`	*atomic value*
76	`xs:gMonth`	*atomic value*
77	`xs:boolean`	*atomic value*
78	`basex:binary`	*atomic value*
79	`xs:base64Binary`	*atomic value*
80	`xs:hexBinary`	*atomic value*
81	`xs:anyURI`	*atomic value*
82	`xs:QName`	*atomic value*
83	`xs:NOTATION`	*atomic value*

Chapter 98. Java Examples

Read this entry online in the BaseX Wiki.

This page is part of the Developer Section. The following Java code snippets demonstrate how easy it is to run database commands, create collections, perform queries, etc. by integrating the BaseX code. Most examples are taken from our basex-examples repository, in which you will find some more use cases.

Local Examples

The following code snippets work in *embedded* mode; they do not rely on an additional server instance:

- RunCommands.java creates and drops database and index instances, prints a list of all existing databases.
- RunQueries.java shows three variants of running queries.
- BindContext.java demonstrates how a value can be bound as context item.
- BindVariables.java demonstrates how a value can be bound to a variable.
- CreateCollection.java creates and manages a collection.
- QueryCollection.java creates, runs queries against it and drops a collection.
- WikiExample.java creates a database from an url (wiki instance), runs a query against it and drops the database.

Server Examples

The examples below take advantage of the client/server architecture:

- ServerCommands.java launches server-side commands using a client session.
- ServerAndLocal.java processes server results locally.
- ServerConcurrency.java runs concurrent queries.
- ServerQueries.java shows how iterative queries can be performed.
- UserExample.java manages database users.

XQuery Module Examples

BaseX provides Java Bindings for accessing external Java code via XQuery functions. The following examples show how this feature can be utilized:

- FruitsExample.java demonstrates how Java classes can be imported as XQuery modules.
- FruitsModule.java is a simple demo module called by `FruitsExample`.
- ModuleDemo.java is a simple XQuery demo module that demonstrates how XQuery items can be processed from Java. It is derived from the `QueryModule` class.
- QueryModule.java is located in the BaseX core. Java query modules can extend this class to get access to the current query context and enrich functions with properties ().

XQJ API

The implementation of the BaseX XQJ API (closed-source) has been written by Charles Foster. It uses the client/server architecture. The basex-examples repository contains various examples on how to use XQJ.

Client API

- BaseXClient.java provides an implementation of the Server Protocol.
- Example.java demonstrates how commands can be executed on a server.
- QueryExample.java shows how queries can be executed in an iterative manner.
- QueryBindExample.java shows how external variables can be bound to XQuery expressions.
- CreateExample.java shows how new databases can be created.
- AddExample.java shows how documents can be added to databases, and how existing documents can be replaced.
- BinaryExample.java shows how binary resource can be added to and retrieved from the database.

REST API

- RESTGet.java presents the HTTP GET method.
- RESTPost.java presents the HTTP POST method.
- RESTPut.java presents the HTTP PUT method.
- RESTAll.java runs all examples at one go.

XML:DB API (deprecated)

Note that the XML:DB API does not talk to the server and can thus only be used in embedded mode.

- XMLDBCreate.java creates a collection using XML:DB.
- XMLDBQuery.java runs a query using XML:DB.
- XMLDBInsert.java inserts a document into a database using XML:DB.

Part X. Extensions

Chapter 99. Docker

Read this entry online in the BaseX Wiki.

This page is part of the Developer Section.

The BaseX server is available as automated build `basex/basexhttp` on the Docker Hub, providing both release and nightly builds. All images are automatically rebuilt if Docker provides updated base images.

Running a BaseX Container

Updated with Version 9.0: New default Home Directory.

To start a BaseX container based on the latest development release publishing the BaseX server and HTTP ports 1984 and 8984 and bind-mounting your user's `data` directory, run

```
docker run -ti \
    --name basexhttp \
    --publish 1984:1984 \
    --publish 8984:8984 \
    --volume "$(pwd)/basex/data":/srv/basex/data \
    basex/basexhttp:latest
```

By passing any other BaseX executable, you can also for example run a BaseX client connecting to the linked BaseX server for management operations on the BaseX command line:

```
docker run -ti \
    --link basexhttp:basexhttp \
    basex/basexhttp:latest basexclient -nbasexhttp
```

BaseX is run under the `basex` user with fixed user ID 1984. The user's home directory is `/srv`. Several ports are exposed:

Port	Description
1984	Server port
8984	HTTP port
8985	HTTP stop port

Leaving BaseX defaults but `--publish`ing them under another external port is recommended if you want to change the ports.

Security Considerations

The Docker image ships the unchanged default credentials. Especially if you publish the server port 1984 or link a public DBA instance against the container, make sure to change the default credentials. When publishing ports, consider which interfaces to bind to, paying special attention to the server port.

A common use case will be linking a well-researched and mature reverse proxy link nginx against the application container. Goals are to reduce exposure of BaseX and Jetty, adding TLS-encryption, serve static resources like images and perform URL rewrites as needed. If you need to access the command line, you can always `docker exec` into the container and run `basexclient`.

Running your own Application

If you want to add your own application in a Docker image, create an image `FROM basex/basexhttp:[tag]` with `[tag]` being the BaseX version you're developing against. Unless configured otherwise, you will add your application code to `/srv/basex/webapp` and modules to `/srv/basex/repo`.

Example: DBA

An example for creating your own Docker image based on `basex/basexhttp` is the DBA application. A `Dockerfile` was added to the source code's root directory. The very simple file contains only few statements:

```
FROM basex/basexhttp:latest
MAINTAINER BaseX Team <basex-talk@mailman.uni-konstanz.de>
COPY . /srv/basex/webapp
```

For general production usage, you should choose a fixed version instead of the development branch behind `latest`, so your application does not suddenly break because of unnoticed API changes. The most relevant part happens in the `COPY` statement, which adds the file contents to the `webapp` directory. That's already it -- you're ready to run.

Advanced Usage

BaseX Configuration

If you need to adjust the BaseX configuration to tune the default options, add a `.basex` file to `/srv`:

```
COPY .basex /srv/basex
```

Options not defined in the `.basex` file with be automatically set to the default values. Users and passwords can be defined by adding a `users.xml` file, which is described on the User Management page.

Jetty Configuration

If you need to change the embedded web server configuration, you can always `COPY` a `WEB-INF` folder containing the required files and overwrite the predefined configuration.

Java Runtime Parameters

Larger applications and databases might require adjusted JRE parameters like increasing the memory limit. You can change those by setting the `BASEX_JVM` environment variable:

```
ENV BASEX_JVM="-Xmx2048m"
```

Installing Debian Packages

The `basex/basexhttp` Docker image is build own the official Maven Docker image `maven:3-jdk-8-alpine`, which in turn derives from alpine. You can add arbitrary packages via APK. Make sure to switch to the `root` user context before installing packages and back to the `basex` user afterwards. As common in the Docker environment, you need to fetch the package catalog using `apt-get update` before installing packages and should clean up afterwards to keep the image small. This example installs some libraries required for image manipulation and adds them to the `$CLASSPATH`:

```
USER root

RUN apk update && apk add --no-cache git


USER basex
```

Chapter 100. YAJSW

Read this entry online in the BaseX Wiki.

This page is part of the Developer Section.

BaseX server can be configured to run as an always-on service in Windows (or daemon in Linux) using YAJSW.

Some basics of YAJSW

- Each service running with YAJSW has a configuration file which lives in the `conf` folder.
- Installing and controlling services is done from the command line. Run a command prompt as administrator, then navigate to the folder where you placed YAJSW, e.g. `cd C:\Programs\yajsw\yajsw-beta-12.05`
- If you need to change configuration of a service follow this sequence:
  1. Stop the service `java -jar wrapper.jar --stop conf\wrapper.name.conf`
  2. Remove the service `java -jar wrapper.jar --remove conf\wrapper.name.conf`
  3. Make your changes to the wrapper or application configuration.
  4. Install the service `java -jar wrapper.jar --install conf\wrapper.name.conf`
  5. Start the service `java -jar wrapper.jar --start conf\wrapper.name.conf`

YAJSW comes with some helpful convenience scripts in the 'bat' and 'bin' folders. This set of instructions does not use these convenience scripts.

Gather the files

- Download the latest version of BaseX. Select the Zip Archive.
- Download the latest version of YAJSW.
- Download the latest version of Java.

Install BaseX as a Windows Service

The instructions on this page are known to work using Windows Server 2012R2, BaseX 8.4.2, YAJSW 12.05 beta, Java 1.8.0_77 64-bit from Oracle.

Install Java

Install Java using the Java installer for your operating system. Use a 64-bit version if you can.

Put files into position

These instructions assume you will be placing BaseX and YAJSW in C:\Programs, but you can choose a different location.

1. Create folder `C:\Programs`
2. Extract YAJSW to `C:\Programs\yajsw\yajsw-beta-12.05`
3. Extract BaseX to `C:\Programs\BaseX\basex`

Install BaseX as a service

Create wrapper config file `wrapper.basex.conf` and place it in YAJSW's `conf` folder. You can use the example below. You may need to modify this example to:

- Specify the location of java.exe
- Change the amount of memory available to BaseX from 1024m (for example, 512m or 2048m)

```
# YAJSW configuration for BaseX

wrapper.java.command=C:/ProgramData/Oracle/Java/javapath/java.exe

wrapper.working.dir=C:\\Programs\\BaseX\\basex

wrapper.java.app.mainclass=org.basex.BaseXHTTP

wrapper.java.classpath.1 = .\\BaseX.jar
wrapper.java.classpath.2 = .\\lib\\*.jar
wrapper.java.classpath.3 = .\\lib\\custom\\*.jar

wrapper.java.additional.1 = -Xmx1024m
wrapper.java.additional.2 = -Dfile.encoding=utf-8

wrapper.ntservice.name=BaseX
wrapper.ntservice.displayname=BaseX
wrapper.ntservice.description=BaseX XQuery database
wrapper.ntservice.starttype=DELAYED_AUTO_START

wrapper.console.loglevel=INFO
wrapper.logfile=${wrapper.working.dir}\\data\\.logs\\wrapper-basex.log
wrapper.logfile.maxsize=10m
wrapper.logfile.maxfiles=10

wrapper.on_exit.0=SHUTDOWN
wrapper.on_exit.default=RESTART
```

After you have created the wrapper configuration file:

1. Open a command prompt as administrator
2. Navigate to the YAJSW folder: `cd C:\Programs\yajsw\yajsw-beta-12.05`
3. Install the service: `java -jar wrapper.jar --install conf\wrapper.basex.conf`
4. Start the service: `java -jar wrapper.jar --start conf\wrapper.basex.conf`

BaseX server is now running as a service, and will start automatically when Windows starts. At this point you should go ahead and set a password for the admin user.

1. Open a web browser and go to http://localhost:8984/dba (or http://host:8984/dba from your computer, replace 'host' with the address of the server) to open the database administration web console.
2. Log in with username 'admin' password 'admin'
3. Click on *Users* to navigate to the user management screen.
4. Click on the *admin* user
5. Set a password for the admin user and then click Save.

Chapter 101. Android

Read this entry online in the BaseX Wiki.

It is possible to create an Android port of BaseX. Therefore the present tutorial outlines the creation of a BaseX Android library, which can be used in any other application project. For the creation of the library the IDE Android Studio[1] is used, but the steps are more or less equal using the Eclipse IDE.

Creating the Android Library Project

The first step is to create an Android library project, which will be later modified to represent the BaseX Android library. In Android Studio the 'Create New Project' menu item needs to be chosen. In order to this the displayed window appears.



It is important that the minimum Android version is Gingerbread 2.3.3, because of some String methods used in BaseX which are not supported by Android versions older than Gingerbread. To create an Android library project, the 'Mark this project as library' item need to be checked. An Android library is not executable and therefore does not need the creation of an Activity, which is the reason why this item is unchecked in the picture above. After finishing the dialog Android Studio creates an empty library project with all needed folders and files. The next step is to copy the BaseX code into the created project folder 'src/main/java'. Except the package 'gui' and the Java file 'BaseXGui.java' inside the 'src.main.java.org.basex'[2] package can be copied into the project folder. Android does not support Java AWT and Swing, which is the reason for not copying the gui package.

Adjusting the Code

After successfully copying the corresponding BaseX packages and java files into the created Android library project a few adjustments have to be done in order to get a working Android library. At this moment the BaseX source code is presented in the Android library project as well as an empty android package, as it is shown in the following image.


BaseXLibrary - [~/Projects/BaseXLibrary] - Android Studio (Preview)
File Edit View Navigate Code Analyze Refactor Build Run Tools
BaseXLibrary
Project
BaseXLibrary (~/Projects/BaseXLibrary)
.idea
BaseXLibrary [BaseXLibrary-BaseXLibrary]
build
libs
src
main
java
org.basex
android
api.dom
build
core
data
index
io
query
server
util
BaseX
BaseXClient
BaseXServer
res
AndroidManifest.xml
.gitignore
BaseXLibrary-BaseXLibrary.iml
build.gradle
proguard-rules.txt
gradle
.gitignore
BaseXLibrary.iml
build.gradle
gradle.properties
gradlew
gradlew.bat
local.properties
settings.gradle

In the empty android package a new Java class needs to be created, this class is used to create the necessary BaseX files and communicate with BaseX. This class needs the data directory of the application for storing the corresponding BaseX files. This files should be stored in the apps /data/data/.. folder which is only accessible from the application. This information is only available inside the applications context and not inside a library project, therefore it is necessary to pass this information to this class at the constructor call. The following source code shows a minimal example for a BaseX class.

```
public class BaseXDatabase {
 private Context basexContext = null;

 public BaseXDatabase(String data_dir) {
  basexContext = new Context(data_dir);
 }

}
```

This class can be called in every Android application which uses the BaseX library with the following call, for example:

```
BaseXDatabase baseXDatabase = new BaseXDatabase(getApplicationInfo().dataDir);
```

At the moment it is not possible to use the BaseX library, therefore more adjustments have to be done in the BaseX code. First it is necessary to add an additional constructor to the Context class to create the BaseX files in the right directory and adjust the default constructor of it. The following code shows the changes inside the Context.java file:

```
public Context(String data_dir) {
 this(true, (Prop.HOME = data_dir + "/"), (Prop.USERHOME = data_dir + "/"));
 File dir = new File(Prop.HOME, "basex/data");
 if(!dir.exists()) {
  if(!dir.mkdir()) {
   android.util.Log.i("BASEX", "CREATING BASEX DIRECTORIES");
  }
 }
}

private Context(final boolean file, String home, String userhome) {
  this(new MainProp(file));
}
```

As shown in the adjustment above, it is necessary to set the two variables 'Prop.HOME' and Prop.USERHOME' during the constructor call. In the BaseX code those variables are final, which need also be changed in order to set them during the call. The reason for this change is that the in BaseX used System.getProperty(user.dir) returns an empty string in Android[3].

The next adjustment, which needs to be done, is to remove not supported packages inside the BaseX code. Therefore the package 'org.basex.query.util.crypto' need to be removed, because it uses external packages which are not supported by Android. The class which uses these files can be found inside the FNCrypto.java file in the 'query.func' package. This file needs to be deleted as well as its usage inside the Function.java file, which can also be found inside the 'query.func' package. The following lines need to be removed:

```
  /** XQuery function. */
  _CRYPTO_HMAC(FNCrypto.class, "hmac(message,key,algorithm[,encoding])",
      arg(STR, STR, STR, STR_ZO), STR),
  /** XQuery function. */
  _CRYPTO_ENCRYPT(FNCrypto.class, "encrypt(input,encryption,key,algorithm)",
      arg(STR, STR, STR, STR), STR),
  /** XQuery function. */
  _CRYPTO_DECRYPT(FNCrypto.class, "decrypt(input,type,key,algorithm)",
      arg(STR, STR, STR, STR), STR),
```

```
  /** XQuery function. */
  _CRYPTO_GENERATE_SIGNATURE(FNCrypto.class, "generate-signature" +
      "(input,canonicalization,digest,signature,prefix,type[,item1][,item2])",
      arg(NOD, STR, STR, STR, STR, STR, ITEM_ZO, ITEM_ZO), NOD),
  /** XQuery function. */
  _CRYPTO_VALIDATE_SIGNATURE(FNCrypto.class, "validate-signature(node)", arg(NOD),
BLN),

  URIS.put(FNCrypto.class, CRYPTOURI);
```

The result of this adjustment is, that it is now possible to use BaseX as an Android library, with the lack of support of the following XQuery functions:

- hmac(string,string,string[,string])
- encrypt(string,string,string,string)
- decrypt(string,string,string,string)
- generate-signature(node,string,string,string,string,string[,item][,item])
- validate-signature(node)

Using the BaseX Android Library

To use the BaseX library the above created BaseXDatabase class can be extended with additional methods which are delegating requests to the BaseX database and return the results. An example of this can be seen in the following code:

```
public String executeXQuery(String query) throws IOException {
 if(basexContext != null)
  return new XQuery(query).execute(basexContext);
 else
  Log.e("BaseXDatabase", "No context");
 return "";
}
```

This methods of the BaseXDatabase class can now be used in every Android application which includes the created BaseX Android library. It is possible to create a .jar, or an .aar[4] file out of the BaseX library, by just building the source code. This file need to be copied inside the lib folder of the Android project which wants to use the library. Additionally the build file of the application needs to be adjusted to use the library. Using Gradle, the Android build system, it can be done by adding the following line to the gradle build file. This tells the build system that every library, inside the libs folder, is being compiled into the projects file.

```
dependencies {
    compile fileTree(dir: 'libs', include: ['*.jar', '*.aar'])
}
```

Part XI. Advanced User's Guide

Chapter 102. Advanced User's Guide

Read this entry online in the BaseX Wiki.

This page is one of the Main Sections of the documentation. It contains details on the BaseX storage and the Server architecture, and presents some more GUI features.

Storage

- Configuration : BaseX start files and directories
- Backups : Backup and restore databases
- Catalog Resolver Information on entity resolving
- Storage Layout : How data is stored in the database files

Use Cases

- Statistics : Exemplary statistics on databases created with BaseX
- Twitter : Storing live tweets in BaseX

Server and Query Architecture

- User Management : User management in the client/server environment
- Transaction Management : Insight into the BaseX transaction management
- Logging : Description of the server logs

Chapter 103. Configuration

Read this entry online in the BaseX Wiki.

This article is part of the Advanced User's Guide. It gives some more insight into the configuration of BaseX.

Configuration Files

BaseX maintains some configuration files, which are stored in the project's Home Directory:

- `.basex` contains all options that are relevant for running the server or standalone versions of BaseX.
- `.basexgui` defines all options relevant to the BaseX GUI.
- `.basexhistory` contains commands that have been typed in most recently.
- `.basexhome` can be created by a user to mark a folder as home directory. Its contents do not matter, so it is usually empty.

Note that:

- Depending on your OS and configuration, files and folders with a '.' prefix may be hidden.
- In the Web Application context, options can be defined in the `web.xml` file.

Home Directory

Updated with Version 9.0:

As BaseX is distributed in different flavors, and may be started from different locations, it dynamically determines its home directory:

- First, the **Java system property** `org.basex.path` is checked. If it contains a value, it is chosen as directory path.
- If not, the **current user directory** (defined by the system property `user.dir`) is chosen if the `.basex` or `.basexhome` file is found in this directory.
- If not, the **application directory** (the folder in which BaseX is located) is chosen if one of these two files is found.
- In all other cases, a `basex` subdirectory in the **user home directory** will be returned. The user home directory is retrieved via the `HOME` environment variable, or (if unassigned), from the Java system property `user.home`. Before *Version 9.0*, the home directory itself was returned.

If BaseX is used in an embedded environment (such as a servlet in a Web Application), it may not immediately be clear what directory was chosen. You can run the XQuery expression `Q{org.basex.util.Prop}HOMEDIR()` to find out.

Database Directory

Updated with Version 9.0:

Databases consists of several binary files. These are located in a directory named by the name of the database. The database root directory is named `data`.

The database path can be changed as follows:

- GUI: Choose *Options* → *Preferences* and choose a new database path.

- General: edit the `DBPATH` option in the `.basex` configuration file

Note: Existing databases will not automatically be moved to the new destination.

Log Files

Log files are stored in text format in a `.logs` sub-directory of the database folder (see Logging for more information).

Changelog

Version 9.0

- Updated: Detection and configuration of home directory and subdirectories.

Version 8.0

- Updated: `.basexperm` is obsolete. Users are now stored in `users.xml` in the database directory (see User Management for more information).

Version 7.7

- Updated: The `.basexhome` file marks a folder as home directory.

Chapter 104. Backups

Read this entry online in the BaseX Wiki.

This page is part of the Advanced User's Guide. The following two paragraphs demonstrate how to create a backup and restore the database within BaseX.

GUI Example

1. Start the BaseX GUI and create a new database in *Database* → *New...* with your XML document.
2. Go to *Database* → *Manage...* and create a backup of your database. The backup will be created in the database directory.
3. Go to *Database* → *Add...* and add another document.
4. Go to *Database* → *Manage...* and restore your database. The database will be restored from the latest backup of to the database found in the database directory.

Console Example

1. Start the BaseX Standalone client from a console.
2. Create a new database via the CREATE DB command.
3. Use the CREATE BACKUP command to back up your database.
4. Add a new document via ADD: `ADD AS newdoc.xml <newdoc/>`
5. Use the RESTORE command to restore the original database.
6. Type in XQUERY / to see the restored database contents.

The same commands can be used with a BaseX client connected to a remote Database Server.

Chapter 105. Catalog Resolver

Read this entry online in the BaseX Wiki.

This article is part of the Advanced User's Guide. It clarifies how to deal with external DTD declarations when parsing XML data.

Overview

XML documents often rely on Document Type Definitions (DTDs). While parsing a document with BaseX, entities can be resolved with respect to that particular DTD. By default, the DTD is only used for entity resolution.

XHTML, for example, defines its doctype via the following line:

```
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Strict//EN""http://www.w3.org/TR/
xhtml1/DTD/xhtml1-strict.dtd">
```

Fetching `xhtml1-strict.dtd` obviously involves network traffic. When dealing with single files, this may seem tolerable, but importing large collections benefits from caching these resources. Depending on the remote server, you will experience significant speed improvements when caching DTDs locally.

XML Entity and URI Resolvers

BaseX comes with a default URI resolver that is usable out of the box.

To enable entity resolving you have to provide a valid XML Catalog file, so that the parser knows where to look for mirrored DTDs.

A simple working example for XHTML might look like this:

```
<?xml version="1.0"?>
<catalog prefer="system" xmlns="urn:oasis:names:tc:entity:xmlns:xml:catalog">
   <rewriteSystem systemIdStartString="http://www.w3.org/TR/xhtml1/DTD/"
 rewritePrefix="file:///path/to/dtds/" />
</catalog>
```

This rewrites all systemIds starting with: *http://www.w3.org/TR/xhtml1/DTD/* to *file:///path/to/dtds/*.

The XHTML DTD `xhtml1-strict.dtd` and all its linked resources will now be loaded from the specified path.

GUI Mode

When running BaseX in GUI mode, simply provide the path to your XML Catalog file in the *Parsing* Tab of the Database Creation Dialog.

Console & Server Mode

To enable Entity Resolving in Console Mode, assign a catalog file path to the `CATFILE` option. All subsequent `ADD` commands will use the specified catalog file to resolve entities.

The **paths** to your catalog file and the actual DTDs are either absolute or relative to the *current working directory*. When using BaseX in Client-Server-Mode, this is relative to the *server's* working directory.

Please Note

Entity resolving only works if the internal XML parser is switched off (which is the default case). If you use the internal parser, you can manually specify whether you want to parse DTDs and entities or not.

Using other Resolvers

There might be some cases when you do not want to use the built-in resolver that Java provides by default (via `com.sun.org.apache.xml.internal.resolver.*`).

BaseX offers support for the Apache-maintained XML Commons Resolver, available for download here.

To use it add **resolver.jar** to the classpath when starting BaseX:

```
java -cp basex.jar:resolver.jar org.basex.BaseXServer
```

More Information

- Wikipedia on Document Type Definitions
- Apache XML Commons Article on Entity Resolving
- XML Entity and URI Resolvers , Sun
- XML Catalogs. OASIS Standard, Version 1.1. 07-October-2005.

Chapter 106. Storage Layout

Read this entry online in the BaseX Wiki.

This article is part of the Advanced User's Guide. It presents some low-level details on how data is stored in the database files.

Data Types

The following data types are used for specifying the storage layout:

Type	Description	Example (native → hex integers)
Num	Compressed integer (1-5 bytes), specified in Num.java	15 → 0F; 511 → 41 FF
Token	Length (*Num*) and bytes of UTF8 byte representation	Hello → 05 48 65 6c 6c 6f
Double	Number, stored as token	123 → 03 31 32 33
Boolean	Boolean (1 byte, 00 or 01)	true → 01
Nums , *Tokens* , *Doubles*	Arrays of values, introduced with the number of entries	1,2 → 02 01 31 01 32
TokenSet	Key array (*Tokens*), next/bucket/size arrays (3x *Nums*)	

Database Files

The following tables illustrate the layout of the BaseX database files. All files are suffixed with .basex.

Meta Data, Name/Path/Doc Indexes: inf

Description	Format	Method
1. Meta Data	1. Key/value pairs, in no particular order (*Token* / *Token*): • Examples: FNAME, TIME, SIZE, ... • PERM → Number of users (*Num*), and name/password/permission values for each user (*Token* / *Token* / *Num*)2. Empty key as finalizer	DiskData() MetaData() Users()
2. Main memory indexes	1. Key/value pairs, in no particular order (*Token* / *Token*): • TAGS → Element Name Index • ATTS → Attribute Name Index • PATH → Path Index • NS → Namespaces • DOCS → Document Index2. Empty key as finalizer	DiskData()
2 a) Name Index Element/attribute names	1. Token set, storing all names (*TokenSet*)2. One StatsKey instance per entry:2.1. Content kind (*Num*):2.1.1. Number: min/max (*Doubles*)2.1.2. Category: number of entries (*Num*), entries (*Tokens*)2.2. Number of entries (*Num*)2.3. Leaf flag (*Boolean*)2.4.	Names() TokenSet.read() StatsKey()

	Maximum text length (*Double* ; legacy, could be *Num*)	
2 b) Path Index	1. Flag for path definition (*Boolean* , always true; legacy)2. PathNode:2.1. Name reference (*Num*)2.2. Node kind (*Num*)2.3. Number of occurrences (*Num*)2.4. Number of children (*Num*)2.5. *Double* ; legacy, can be reused or discarded2.6. Recursive generation of child nodes ($\rightarrow$ 2)	PathSummary() PathNode()
2 c) Namespaces	1. Token set, storing prefixes (*TokenSet*)2. Token set, storing URIs (*TokenSet*)3. NSNode:3.1. pre value (*Num*)3.2. References to prefix/URI pairs (*Nums*)3.3. Number of children (*Num*)3.4. Recursive generation of child nodes ($\rightarrow$ 3)	Namespaces() NSNode()
2 d) Document Index	Array of integers, representing the distances between all document pre values (*Nums*)	DocIndex()

Node Table: `tbl`, `tbli`

- `tbl` : Main database table, stored in blocks.
- `tbli` : Database directory, organizing the database blocks.

Some more information on the node storage is available.

Texts: `txt`, `atv`

- `txt` : Heap file for text values (document names, string values of texts, comments and processing instructions)
- `atv` : Heap file for attribute values.

Value Indexes: `txtl`, `txtr`, `atvl`, `atvr`

Text Index:

- `txtl` : Heap file with ID lists.
- `txtr` : Index file with references to ID lists.

The **Attribute Index** is contained in the files `atvl` and `atvr`, the **Token Index** in `tokl` and `tokr`. All have the same layout.

For a more detailed discussion and examples of these file formats please see Index File Structure.

Full-Text Fuzzy Index: `ftxx`, `ftxy`, `ftxz`

...may soon be reimplemented.

Chapter 107. Node Storage

Read this entry online in the BaseX Wiki.

This article describes the Storage Layout of the main database table.

Node Table

BaseX stores all XML nodes in a flat table. The node table of a database can be displayed via the INFO STORAGE command:

```
$ basex -c"create db db <xml>HiThere</xml>" -c"info storage"

PRE  DIS  SIZ  ATS  ID  NS  KIND  CONTENT
-----------------------------------------
  0    1    3    1   0   0  DOC   db.xml
  1    1    2    1   1   0  ELEM  xml
  2    1    1    1   2   0  TEXT  HiThere
```

PRE Value

The *pre* value of a node represents the order in which the XML nodes are visited by a SAX parser. It is actually not stored in the database; instead, it is implicitly given by the table position. As a result, it will change whenever a node with a smaller *pre* values is added to or deleted from a database.

ID Value

Each database node has a persistent *id* value, which remains valid after update operations, and which is referenced by the value indexes. As long as no updates are performed on a database, the *pre* and *id* values are identical. The values will remain to be identical if new nodes are exclusively added to the end of the database. If nodes are deleted or inserted somewhere else, the values will diverge, as shown in the next example:

```
$ basex -c"create db db <xml>HiThere</xml>" -q"insert node <b/> before /xml" -
c"info storage"

PRE  DIS  SIZ  ATS  ID  NS  KIND  CONTENT
-----------------------------------------
  0    1    4    1   0   0  DOC   db.xml
  1    1    1    1   3   0  ELEM  b
  2    2    2    1   1   0  ELEM  xml
  3    1    1    1   2   0  TEXT  HiThere
```

The db:node-pre and db:node-id functions can be called to retrieve the *pre* and *id* values of a node, and db:open-pre and db:open-id can be used to go back and retrieve the original node. By default, *id* lookups are expensive. If the UPDINDEX option is turned on, an additional index will be maintained to speed up the process.

Block Storage

BaseX logically splits the `tbl.basex` file into blocks with length 4096 bytes, i.e. each block can have max 256 records each with length 16 bytes. The records within a block are sorted by their pre value (which, therefore, can be implicitly determined and need not be saved).

For each block BaseX stores in a separate file (`tbli.basex`) the smallest pre value within that block (and since the records are sorted, that will be the pre value of the first record stored in the block). These will be referred as fpre from now on. The physical address of each block is stored in `tbli.basex`, too.

Since these two maps will not grow excessively large, but are accessed resp. changed on each read resp. write operation, they are kept in main memory and flushed to disk on closing the database.

A newly created database with 256 + 10 records will occupy the first two blocks with physical addresses 0 and 4096. The corresponding fpre's will be 0 and 256.

If a record with pre = 12 is to be inserted, it needs to be stored in the first block, which is, however, full. In this case, a new block with physical address 8192 will be allocated, the records with pre values from 12 to 255 will be copied to the new block, the new record will be stored in the old block at pre = 12, and the two maps will look like this:

```
fpre's = 0, 13, 257
addr's = 0, 8192, 4096
```

Basically, the old records remain in the first block, but they will not be read, since the fpre's array says that only 13 records are stored in the first block. This causes redundant storage of the records with old pres from 13 to 255.

Additionally to these two maps (fpre's and addr's), BaseX maintains a bit map (which is also stored in `tbli.basex`) which reflects which physical blocks are free and which not, so that when a new block is needed, an already free one will be reused.

Chapter 108. User Management

Read this entry online in the BaseX Wiki.

This article is part of the Advanced User's Guide. The user management defines which permissions are required by a user to perform a database command or XQuery expression.

Permissions are mostly relevant in the client/server architecture, as the Standalone Mode and the GUI is run with admin permissions. There are a few exceptions such as the xquery:eval function: Its execution scope can also be limited by specifying a permission.

Please take care of usual security measures: ensure that your password will not end up in your bash history, avoid sending passwords via ordinary REST requests, etc.

Rules

In the permission hierarchy below, the existing permissions are illustrated. A higher permission includes all lower permissions. For example, all users who have the `write` permission assigned will also be able to execute commands requiring `read` permission.

Local permissions are applied to databases. They have a higher precedence and override global permissions.



Permissions hierarchy User names must follow the valid names constraints, and the database patterns must follow the Glob Syntax.

Operations

For all operations, admin permissions are required:

Commands

Create user 'test' (password will be entered on command line). By default, the user will have no permissions ('none'):

```
> CREATE USER test
```

Change password of user 'test' to '71x343sd#':

```
> ALTER PASSWORD test 71x343sd#
```

Grant local write permissions to user 'test':

```
> GRANT write ON unit* TO test
```

Note: Local permissions overwrite global permissions. As a consequence, the 'test' user will only be allowed to access (i.e., read and write) database starting with the letters 'unit'. If no local permissions are set, the global rights are inherited.

Show global permissions:

```
> SHOW USERS
```

XQuery

The available user functions are listed in the User Module:

Create user 'test' with no permissions:

```
db:create('test', 'top-secret')
```

Show detailed information about user 'test':

```
user:list-details()[@name = 'test']
```

Drop user 'test':

```
user:drop('test')
```

Storage

The permission file `users.xml` is stored in the database directory. This file can be manually edited; it will be parsed once when BaseX is started.

Salted SHA256 hashes are used for authentication (the current timestamp will be used as salt). Additionally, digest hashes are used in the client/server architecture and the Language Bindings, and in the HTTP Context if the AUTHMETHOD is set to `Digest`.

Changelog

Revised in Version 8.0.

Chapter 109. Transaction Management

Read this entry online in the BaseX Wiki.

This article is part of the Advanced User's Guide. The BaseX client-server architecture offers ACID-safe transactions, with multiple readers and writers. Here is some more information about the transaction management.

Introduction

In a nutshell, a transaction is equal to a command or query. So each command or query sent to the server becomes a transaction.

Incoming requests are parsed and checked for errors on the server. If the command or query is not correct, the request will not be executed, and the user will receive an error message. Otherwise the request becomes a transaction and gets into the transaction monitor.

Please note that:

- Locks *cannot be synchronized* across BaseX instances that run in different JVMs. If concurrent write operations are to be performed, we generally recommend working with the client/server or the HTTP architecture .
- An *unexpected abort* of the server during a transaction, caused by a hardware failure or power cut, may lead to an inconsistent database state if a transaction was active at shutdown time. So it is advisable to use the BACKUP command to regularly backup your database. If the worst case occurs, you can try the INSPECT command to check if your database has obvious inconsistencies, and use RESTORE to restore the last backed up version of the database.

XQuery Update

Many update operations are triggered by XQuery Update expressions. When executing an updating query, all update operations of the query are stored in a pending update list. They will be executed all at once, so the database is updated atomically. If any of the update sub-operations is erroneous, the overall transaction will be aborted.

Concurrency Control

BaseX provides support for multiple read and single write operations (using preclaiming and starvation-free two phase locking). This means that:

- Read transactions are executed in parallel.
- If an updating transaction comes in, it will be queued and executed after all previous read transaction have been executed.
- Subsequent operations (read or write) will be queued until the updating transaction has completed.
- Jobs without database access will never be locked. Globally locking jobs can now be executed in parallel with non-locking jobs.
- Each database has its own queue: An update on database A will not block operations on database B. This is under the premise that it can be statically determined, i.e., before the transaction is evaluated, which databases will be accessed by a transaction (see below).
- The number of maximum parallel transactions can be adjusted with the `PARALLEL` option.
- By default, read transactions are favored, and transactions that access no databases can be evaluated even if the transactions limit has been reached. This behavior can be changed via the `FAIRLOCK` option.

XQuery Locks

By default, access to external resources (files on hard disk, HTTP requests, ...) is not controlled by the transaction monitor of BaseX. You can use custom XQuery locks to do so:

Query Options

- You can declare custom locks via the `query:read-lock` and `query:write-lock` options in the query prolog.
- The value of the option contains the lock string, or multiple ones (separated with commas).
- Similar to the internal database locks, write locks block all other operations while read locks allow parallel access.
- The internal locks and XQuery locks can co-exist (there will be no conflicts, even if your lock string equals the name of a database that will be locked by the transaction manager).

In the following two example modules, locks have been added to prevent concurrent write operations on the same file:

```
module namespace read = 'read';

(:~ Read lock on CONFIG key. :)
declare option query:read-lock 'CONFIG';

declare function read:config() {
  file:read-text('config.txt')
};
```

```
module namespace write = 'write';

(:~ Write lock on CONFIG key. :)
declare option query:write-lock 'CONFIG';

declare function write:file($data) {
  file:write-text('config.txt', $data)
};
```

Some explanations:

- If a query is parsed that is going to call the `read:file` function, a read lock will be acquired for the user-defined `CONFIG` lock string before query evaluation.
- If `write:file` is referenced by a query, a write lock on this lock string will be set for this query.
- If a query references `write:file`, it will be queued until there is no running query left that has `files` locked.
- If the writing query will be evaluated, all other queries that will set a `files` lock (reading or writing) will have to wait.

In practice, it's often sufficient to only work with (exclusive) write locks.

Java Modules

Locks can also be acquired on Java functions which are imported and invoked from an XQuery expression. It is advisable to explicitly lock Java code whenever it performs sensitive read and write operations.

Limitations

Commands

Database locking works with all commands unless the glob syntax is used, such as in the following command call:

- `DROP DB new*` : drop all databases starting with "new"

XQuery

Deciding which databases will be accessed by a complex XQuery expression is a non-trivial task. Database detection works for the following types of queries:

- `//item` , read-locking of the database opened by a client
- `doc('factbook')` , read-locking of "factbook"
- `collection('db/path/to/docs')` , read-locking of "db"
- `fn:sum(1 to 100)` , locking nothing at all
- `delete nodes doc('test')//*[string-length(local-name(.)) > 5]` , write-locking of "test"

All databases will be locked by queries of the following kind:

- `for $db in ('db1', 'db2') return doc($db)`
- `doc(doc('test')/reference/text())`
- `let $db := 'test' return insert nodes <test/> into doc($db)`

You can consult the query info output (which you find in the Info View of the GUI or which you can turn on by setting `QUERYINFO` to `true`) to find out which databases have been locked by a query.

File-System Locks

Update Operations

During a database update, a locking file `upd.basex` will reside in that database directory. If the update fails for some unexpected reason, or if the process is killed ungracefully, this file will not be deleted. In this case, the database cannot be opened anymore, and the message "Database ... is being updated, or update was not completed" will be shown instead.

If the locking file is manually removed, you may be able to reopen the database, but you should be aware that database may have got corrupt due to the interrupted update process, and you should revert to the most recent database backup.

Database Locks

To avoid database corruptions that are caused by accidental write operations from different JVMs, a shared lock is requested on the database table file (`tbl.basex`) whenever a database is opened. If an update operation is triggered, and if no exclusive lock can be acquired, it will be rejected with the message "Database ... is currently opened by another process.".

Please note that you cannot 100% rely on this mechanism, as it is not possible to synchronize operations across different JVMs. You will be safe when using the client/server or HTTP architecture.

Changelog

Version 8.6

- Updated: New `FAIRLOCK` option, improved detection of lock patterns.

Version 7.8

- Added: Locks can also be acquired on Java functions.

Version 7.6

- Added: database locking introduced, replacing process locking.

Version 7.2.1

- Updated: pin files replaced with shared/exclusive filesystem locking.

Version 7.2

- Added: pin files to mark open databases.

Version 7.1

- Added: update lock files.

Chapter 110. Logging

Read this entry online in the BaseX Wiki.

This article is part of the Advanced User's Guide. It describes how client operations are logged by the server. The server logs can e.g. be used to get an overview of all processes executed on your server, trace any errors or compile performance statistics.

Introduction

The server logs are written in plain text. In your Database Directory, you can find a folder named `.logs` in which all log files are stored with the according date. Note that, depending on your OS and configuration, files and folders beinning with a `.` may be hidden. The log directory can be changed via the `LOGPATH` option.

Some more notes on the logging facility:

- HTTP requests are included in the log files.
- Logging can be turned on/off via the LOG option.
- The maximum length of logging messages can be changed via LOGMSGMAXLEN.
- The Admin Module provides access to the log files from XQuery.

RESTXQ

Non-trivial web applications provide the ability for users to sign in and out. User handling can be realized with session attributes (see e. g. the DBA code).

By default, RESTXQ code is run with admin permissions. However, as it is more interesting to know which user has called a function, the RESTXQ user string (which is `admin` by default, and which will show up in the log data) will be overwritten by the value of an `id` session attribute. If the request path includes `/dba/`, the `dba` session attribute will be assigned.

If the following function is called more than once, `joe` will appear as user in the second and subsequent log entries:

```
import module namespace Session = 'http://basex.org/modules/session';
declare %rest:path('/session-id') function local:f() {
  Session:set('id', 'joe'),
  'I am Joe'
};
```

Format

Example 1

```
01:18:12.892   SERVER           admin   OK        Server was started (port: 1984)
01:18:15.436   127.0.0.1:4722   jack    REQUEST   XQUERY for $i in 1 to 5 return
 random:double()
01:18:15.446   127.0.0.1:4722   jack    OK        Query executed in 2.38 ms.
                2.72 ms
01:18:15.447   127.0.0.1:4722   jack    REQUEST   EXIT
01:18:15.447   127.0.0.1:4722   jack    OK
                0.39 ms
```

A server has been started and a user `jack` has connected to the server to perform a query and exit properly.

Example 2

```
01:23:33.251   127.0.0.1:4736   john   OK        QUERY[0] 'hi'   0.44 ms
01:23:33.337   127.0.0.1:4736   john   OK        ITER[0]         1.14 ms
01:23:33.338   127.0.0.1:4736   john   OK        INFO[0]         0.36 ms
01:23:33.339   127.0.0.1:4736   john   OK        CLOSE[0]        0.21 ms
01:23:33.359   127.0.0.1:4736   john   REQUEST   EXIT
01:23:33.359   127.0.0.1:4736   john   OK                        0.14 ms
```

A user `john` has performed an iterative query, using one of the client APIs.

Example 3

```
01:31:51.888   127.0.0.1:4803   admin   REQUEST   [GET] http://localhost:8984/rest/
factbook
01:31:51.892   127.0.0.1:4803   admin   200
           4.43 ms
```

An admin user has accessed the `factbook` database via REST.

Changelog

Version 8.6

- Added: The log directory can be changed with the `LOGPATH` option.
- Updated: Include session attributes in log data.

Part XII. Use Cases

Chapter 111. Statistics

Read this entry online in the BaseX Wiki.

This article is part of the Advanced User's Guide. It lists statistics on various databases instances that have been created with BaseX, with value and full-text indexes turned off. The URLs to the original sources, if available or public, are listed below.

Databases in BaseX are light-weight. If a database limit is reached, you can distribute your documents across multiple database instances and access all of them with a single XQuery expression.

Databases

Instances	FileSize	#Files	DbSize	#Nodes	#Attr	#ENames	#ANames	#URIs	Height
Limits	**512 GiB**(2^39 Bytes)	**536'870'912**(2^29)	*no limit*	**2'147'483'648**(2^31)	*no limit*	**32768**(2^15)	**32768**(2^15)	**256**(2^8)	*no limit*
RuWikiHist	421 GiB	1	416 GiB	324'848'508	3	21	6	2	6
ZhWikiHist	126 GiB	1	120 GiB	179'199'662	2	21	6	2	6
EnWiktionary	79 GiB	1	75 GiB	134'380'393	3	21	6	2	6
XMark	55 GiB	1	64 GiB	1'615'071'348	48	74	9	0	13
EnWikiMeta	54 GiB	1	52 GiB	401'456'348	3	21	6	2	6
MedLine	38 GiB	379	36 GiB	1'623'764'225	24	84	6	0	9
iProClass	36 GiB	1	37 GiB	1'631'218'984	4	245	4	2	9
Inex2009	31 GiB	2'666'500	34 GiB	1'336'110'639	39	28'034	451	1	37
CoPhIR	29 GiB	10'000'000	31 GiB	1'104'623'370	10	42	42	0	8
EnWikipedia	26 GiB	1	25 GiB	198'546'747	3	24	21	2	6
XMark	22 GiB	1	26 GiB	645'997'962	2	74	9	0	13
InterPro	14 GiB	1	19 GiB	860'304'235	5	7	15	0	4
Genome1	13 GiB	1	13 GiB	432'628'105	12	26	101	2	6
NewYorkTimes	12 GiB	1'855'659	13 GiB	280'407'005	5	41	33	0	6
TrEMBL	11 GiB	1	14 GiB	589'650'535	3	47	30	2	7
XMark	11 GiB	1	13 GiB	323'083'409	2	74	9	0	13
IntAct	7973 MiB	25'624	6717 MiB	297'478'392	7	64	22	2	14
Freebase	7366 MiB	1	10 GiB	443'627'994	8	61	283	1	93
SDMX	6356 MiB	1	8028 MiB	395'871'872	2	22	6	3	7
OpenStreetMap	5312 MiB	1	5171 MiB	6'910'669	3	19	5	2	6
SwissProt	4604 MiB	1	5422 MiB	241'274'406	8	70	39	2	7
EURLex	4815 MiB	1	5532 MiB	167'328'039	23	186	46	1	12
Wikicorpus	4492 MiB	659'338	4432 MiB	157'948'561	12	1'257	2'687	2	50
EnWikiRDF	3679 MiB	1	3537 MiB	98'433'194	1	11	2	11	4
CoPhIR	2695 MiB	1'000'000	2882 MiB	101'638'857	10	42	42	0	8
MeSH	2091 MiB	1	2410 MiB	104'845'813	3	6	5	2	5
FreeDB	1723 MiB	1	2462 MiB	102'901'519	2	7	3	0	4
XMark	1134 MiB	1	1303 MiB	32'298'989	2	74	9	0	13

DeepFS	810 MiB	1	850 MiB	44'821'506	4	3	6	0	24
LibraryUKN	760 MiB	1	918 MiB	46'401'941	3	23	3	0	5
Twitter	736 MiB	1'177'495	767 MiB	15'309'015	0	8	0	0	3
Organizations	733 MiB	1'019'132	724 MiB	33'112'392	3	38	9	0	7
DBLP	694 MiB	1	944 MiB	36'878'181	4	35	6	0	7
Feeds	692 MiB	444'014	604 MiB	5'933'713	0	8	0	0	3
MedLineSupp	477 MiB	1	407 MiB	21'602'141	5	55	7	0	9
AirBase	449 MiB	38	273 MiB	14'512'851	1	111	5	0	11
MedLineDesc	260 MiB	1	195 MiB	10'401'847	5	66	8	0	9
ZDNET	130 MiB	95'663	133 MiB	3'060'186	21	40	90	0	13
JMNEdict	124 MiB	1	171 MiB	8'592'666	0	10	0	0	5
XMark	111 MiB	1	130 MiB	3'221'926	2	74	9	0	13
Freshmeat	105 MiB	1	86 MiB	3'832'028	1	58	1	0	6
DeepFS	83 MiB	1	93 MiB	4'842'638	4	3	6	0	21
Treebank	82 MiB	1	92 MiB	3'829'513	1	250	1	0	37
DBLP2	80 MiB	170'843	102 MiB	4'044'649	4	35	6	0	6
DDI	76 MiB	3	39 MiB	2'070'157	7	104	16	21	11
Alfred	75 MiB	1	68 MiB	3'784'285	0	60	0	0	6
University	56 MiB	6	66 MiB	3'468'606	1	28	4	0	5
MediaUKN	38 MiB	1	45 MiB	1'619'443	3	21	3	0	5
HCIBIB2	32 MiB	26'390	33 MiB	617'023	1	39	1	0	4
Nasa	24 MiB	1	25 MiB	845'805	2	61	8	1	9
MovieDB	16 MiB	1	19 MiB	868'980	6	7	8	0	4
KanjiDic2	13 MiB	1	18 MiB	917'833	3	27	10	0	6
XMark	11 MiB	1	13 MiB	324'274	2	74	9	0	13
Shakespear	7711 KiB	1	9854 KiB	327'170	0	59	0	0	9
TreeOfLife	5425 KiB	1	7106 KiB	363'560	7	4	7	0	243
Thesaurus	4288 KiB	1	4088 KiB	201'798	7	33	9	0	7
MusicXML	3155 KiB	17	2942 KiB	171'400	8	179	56	0	8
BibDBPub	2292 KiB	3'465	2359 KiB	80'178	1	54	1	0	4
Factbook	1743 KiB	1	1560 KiB	77'315	16	23	32	0	6
XMark	1134 KiB	1	1334 KiB	33'056	2	74	9	0	13

This is the meaning of the attributes:

- *FileSize* is the original size of the input documents
- *#Files* indicates the number of stored XML documents
- *#DbSize* is the size of the resulting database (excluding the value index structures)
- *#Nodes* represents the number of XML nodes (elements, attributes, texts, etc.) stored in the database
- *#Attr* indicates the maximum number of attributes stored for a single element
- *#ENames* and #ANames reflect the number of distinct element and attribute names
- *#URIs* represent the number of distinct namespace URIs

- *Height* indicates the maximum level depth of the stored nodes

Sources

Instances	Source
AirBase	http://air-climate.eionet.europa.eu/databases/airbase/airbasexml
Alfred	http://alfred.med.yale.edu/alfred/alfredWithDescription.zip
BibDBPub	http://inex.is.informatik.uni-duisburg.de/2005/
CoPhIR	http://cophir.isti.cnr.it/
DBLP	http://dblp.uni-trier.de/xml
DBLP2	http://inex.is.informatik.uni-duisburg.de/2005/
DDI	http://tools.ddialliance.org/
EnWikiMeta	http://dumps.wikimedia.org/enwiki/latest/enwiki-latest-pages-meta-current.xml.bz2
EnWikipedia	http://dumps.wikimedia.org/enwiki/latest/enwiki-latest-pages-articles.xml.bz2
EnWikiRDF	http://www.xml-benchmark.org/ generated with xmlgen
EnWiktionary	http://dumps.wikimedia.org/enwiktionary/latest/enwiktionary-latest-pages-meta-history.xml.7z
EURLex	http://www.epsiplatform.eu/
Factbook	http://www.cs.washington.edu/research/xmldatasets/www/repository.html
Freebase	http://download.freebase.com/wex
FreeDB	http://www.xmldatabases.org/radio/xmlDatabases/projects/FreeDBtoXML
Freshmeat	http://freshmeat.net/articles/freshmeat-xml-rpc-api-available
Genome1	ftp://ftp.ncbi.nih.gov/snp/organisms/human_9606/XML/ds_ch1.xml.gz
HCIBIB2	http://inex.is.informatik.uni-duisburg.de/2005/
Inex2009	http://www.mpi-inf.mpg.de/departments/d5/software/inex
IntAct	ftp://ftp.ebi.ac.uk/pub/databases/intact/current/index.html
InterPro	ftp://ftp.bio.net/biomirror/interpro/match_complete.xml.gz
iProClass	ftp://ftp.pir.georgetown.edu/pir_databases/iproclass/iproclass.xml.gz
JMNEdict	ftp://ftp.monash.edu.au/pub/nihongo/enamdict_doc.html
KanjiDic2	http://www.csse.monash.edu.au/~jwb/kanjidic2
MedLine	http://www.nlm.nih.gov/bsd
MeSH	http://www.nlm.nih.gov/mesh/xmlmesh.html
MovieDB	http://eagereyes.org/InfoVisContest2007Data.html

MusicXML	http://www.recordare.com/xml/samples.html
Nasa	http://www.cs.washington.edu/research/xmldatasets/www/repository.html
NewYorkTimes	http://www.nytimes.com/ref/membercenter/nytarchive.html
OpenStreetMap	http://dump.wiki.openstreetmap.org/osmwiki-latest-files.tar.gz
Organizations	http://www.data.gov/raw/1358
RuWikiHist	http://dumps.wikimedia.org/ruwiki/latest/ruwiki-latest-pages-meta-history.xml.7z
SDMX	http://www.metadatatechnology.com/
Shakespeare	http://www.cafeconleche.org/examples/shakespeare
SwissProt	ftp://ftp.uniprot.org/pub/databases/uniprot/current_release/knowledgebase
Thesaurus	http://www.drze.de/BELIT/thesaurus
Treebank	http://www.cs.washington.edu/research/xmldatasets
TreeOfLife	http://tolweb.org/data/tolskeletaldump.xml
TrEMBL	ftp://ftp.uniprot.org/pub/databases/uniprot/current_release/knowledgebase
Wikicorpus	http://www-connex.lip6.fr/~denoyer/wikipediaXML
XMark	http://www.xml-benchmark.org/ generated with xmlgen
ZDNET	http://inex.is.informatik.uni-duisburg.de/2005/
ZhWikiHist	http://dumps.wikimedia.org/zhwiki/latest/zhwiki-latest-pages-meta-history.xml.7z
LibraryUKN	generated from university library data
MediaUKN	generated from university library data
DeepFS	generated from filesystem structure
University	generated from students test data
Feeds	compiled from news feeds
Twitter	compiled from Twitter feeds

Chapter 112. Twitter

Read this entry online in the BaseX Wiki.

This article is part of the Advanced User's Guide. It is about the usage of BaseX for processing and storing the live data stream of Twitter. We illustrate some statistics about the Twitter data and the performance of BaseX.

As Twitter attracts more and more users (over 140 million active users in 2012) and is generating large amounts of data (over 340 millions of short messages ('tweets') daily), it became a really exciting data source for all kind of analytics. Twitter provides the developer community with a set of APIs for retrieving the data about its users and their communication, including the Streaming API for data-intensive applications, the Search API for querying and filtering the messaging content, and the REST API for accessing the core primitives of the Twitter platform.

BaseX as Twitter Storage

For retrieving the Twitter stream we connect with the Streaming API to the endpoint of Twitter and receive a never ending tweet stream. As Twitter delivers the tweets as JSON objects the objects has to be converted into XML fragments. For this purpose the parse function of the XQuery JSON Module is used. In the examples section both versions are shown (tweet as JSON and tweet as XML). For storing the tweets including the meta-data, we use the standard *insert* function of XQuery Update.

Twitter's Streaming Data

Each tweet object in the data stream contains the tweet message itself and over 60 data fields (for further information see the fields description). The following section shows the amount of data, that is delivered by the Twitter Streaming API to the connected endpoints with the 10% gardenhose access per hour on the 6th of the months February, March, April and May. It is the pure public live stream without any filtering applied.

Statistics



Day	Description	Amount
Mon, 6-Feb-2012	Total tweets	30.824.976
	Average tweets per hour	1.284.374
	Average tweets per minute	21.406
	Average tweets per second	356
Tue, 6-Mar-2012	Total tweets	31.823.776
	Average tweets per hour	1.325.990
	Average tweets per minute	22.099
	Average tweets per second	368
Fri, 6-Apr-2012	Total tweets	34.638.976
	Average tweets per hour	1.443.290

	Average tweets per minute	24.054
	Average tweets per second	400
Sun, 6-May-2012	Total tweets	35.982.976
	Average tweets per hour	1.499.290
	Average tweets per minute	24.988
	Average tweets per second	416

Example Tweet (JSON)


```
{
  "contributors": null,
  "text": "Using BaseX for storing the Twitter Stream",
  "geo": null,
  "retweeted": false,
  "in_reply_to_screen_name": null,
  "possibly_sensitive": false,
  "truncated": false,
  "entities": {
    "urls": [
    ],
    "hashtags": [
    ],
    "user_mentions": [
    ]
  },
  "in_reply_to_status_id_str": null,
  "id": 1984009055807*****,
  "in_reply_to_user_id_str": null,
  "source": "<a href=\"http:\/\/twitterfeed.com\" rel=\"nofollow\">twitterfeed<\/
a>",
  "favorited": false,
  "in_reply_to_status_id": null,
  "retweet_count": 0,
  "created_at": "Fri May 04 13:17:16 +0000 2012",
  "in_reply_to_user_id": null,
  "possibly_sensitive_editable": true,
  "id_str": "1984009055807*****",
  "place": null,
  "user": {
    "location": "",
    "default_profile": true,
    "statuses_count": 9096,
    "profile_background_tile": false,
    "lang": "en",
    "profile_link_color": "0084B4",
    "id": 5024566**,
    "following": null,
    "protected": false,
    "favourites_count": 0,
    "profile_text_color": "333333",
    "contributors_enabled": false,
    "verified": false,
    "description": "http:\/\/basex.org",
    "profile_sidebar_border_color": "C0DEED",
    "name": "BaseX",
    "profile_background_color": "C0DEED",
    "created_at": "Sat Feb 25 04:05:30 +0000 2012",
    "default_profile_image": true,
    "followers_count": 860,
```

```
    "geo_enabled": false,
    "profile_image_url_https": "https:\/\/si0.twimg.com\/sticky\/
default_profile_images\/default_profile_0_normal.png",
    "profile_background_image_url": "http:\/\/a0.twimg.com\/images\/themes\/
theme1\/bg.png",
    "profile_background_image_url_https": "https:\/\/si0.twimg.com\/images\/themes
\/theme1\/bg.png",
    "follow_request_sent": null,
    "url": "http:\/\/adf.ly\/5ktAf",
    "utc_offset": null,
    "time_zone": null,
    "notifications": null,
    "friends_count": 2004,
    "profile_use_background_image": true,
    "profile_sidebar_fill_color": "DDEEF6",
    "screen_name": "BaseX",
    "id_str": "5024566**",
    "show_all_inline_media": false,
    "profile_image_url": "http:\/\/a0.twimg.com\/sticky\/default_profile_images\/
default_profile_0_normal.png",
    "is_translator": false,
    "listed_count": 0
  },
  "coordinates": null
}
```

Example Tweet (XML)

```
<json booleans="retweeted possibly__sensitive truncated favorited
 possibly__sensitive__editable default__profile profile__background__tile
 protected contributors__enabled verified default__profile__image geo__enabled
 profile__use__background__image show__all__inline__media is__translator"
  numbers="id retweet__count statuses__count favourites__count followers__count
 friends__count listed__count"
  nulls="contributors geo in__reply__to__screen__name
 in__reply__to__status__id__str in__reply__to__user__id__str
 in__reply__to__status__id in__reply__to__user__id place following
 follow__request__sent utc__offset time__zone notifications coordinates"
  arrays="urls indices hashtags user__mentions"
  objects="json entities user">
  <contributors/>
  <text>Using BaseX for storing the Twitter Stream</text>
  <geo/>
  <retweeted>false</retweeted>
  <in__reply__to__screen__name/>
  <possibly__sensitive>false</possibly__sensitive>
  <truncated>false</truncated>
  <entities>
    <urls/>
    <hashtags/>
    <user__mentions/>
  </entities>
  <in__reply__to__status__id__str/>
  <id>1984009055807*****</id>
  <in__reply__to__user__id__str/>
  <source><a href="http://twitterfeed.com" rel="nofollow">twitterfeed</a></source>
  <favorited>false</favorited>
  <in__reply__to__status__id/>
  <retweet__count>0</retweet__count>
  <created__at>Fri May 04 13:17:16 +0000 2012</created__at>
  <in__reply__to__user__id/>
  <possibly__sensitive__editable>true</possibly__sensitive__editable>
  <id__str>1984009055807*****</id__str>
  <place/>
```

```
  <user>
    <location/>
    <default__profile>true</default__profile>
    <statuses__count>9096</statuses__count>
    <profile__background__tile>false</profile__background__tile>
    <lang>en</lang>
    <profile__link__color>0084B4</profile__link__color>
    <id>5024566**</id>
    <following/>
    <protected>false</protected>
    <favourites__count>0</favourites__count>
    <profile__text__color>333333</profile__text__color>
    <contributors__enabled>false</contributors__enabled>
    <verified>false</verified>
    <description>http://basex.org</description>
    <profile__sidebar__border__color>C0DEED</profile__sidebar__border__color>
    <name>BaseX</name>
    <profile__background__color>C0DEED</profile__background__color>
    <created__at>Sat Feb 25 04:05:30 +0000 2012</created__at>
    <default__profile__image>true</default__profile__image>
    <followers__count>860</followers__count>
    <geo__enabled>false</geo__enabled>
    <profile__image__url__https>https://si0.twimg.com/sticky/
default_profile_images/default_profile_0_normal.png</profile__image__url__https>
    <profile__background__image__url>http://a0.twimg.com/images/themes/theme1/
bg.png</profile__background__image__url>
    <profile__background__image__url__https>https://si0.twimg.com/images/themes/
theme1/bg.png</profile__background__image__url__https>
    <follow__request__sent/>
    <url>http://adf.ly/5ktAf</url>
    <utc__offset/>
    <time__zone/>
    <notifications/>
    <friends__count>2004</friends__count>
    <profile__use__background__image>true</profile__use__background__image>
    <profile__sidebar__fill__color>DDEEF6</profile__sidebar__fill__color>
    <screen__name>BaseX</screen__name>
    <id__str>5024566**</id__str>
    <show__all__inline__media>false</show__all__inline__media>
    <profile__image__url>http://a0.twimg.com/sticky/default_profile_images/
default_profile_0_normal.png</profile__image__url>
    <is__translator>false</is__translator>
    <listed__count>0</listed__count>
  </user>
  <coordinates/>
</json>
```

BaseX Performance

The test show the time BaseX needs to insert large amounts of real tweets into a database. We can derive that BaseX scales very well and can keep up with the incoming amount of tweets in the stream. Some lower values can occur, cause the size of the tweets differ according to the meta-data contained in the tweet object. Note: The `AUTOFLUSH` option is set to `FALSE` (default: `SET AUTOFLUSH TRUE`)

System Setup: Mac OS X 10.6.8, 3.2 GHz Intel Core i3, 8 GB 1333 MHz DDR3 RAM BaseX Version: BaseX 7.3 beta

Insert with XQuery Update

These tests show the performance of BaseX performing inserts with XQuery Update as single updates per tweet or bulk updates with different amount of tweets. The initial database just contained a root node `<tweets/>` and all incoming tweets are inserted after converting from JSON to XML into the root node. The time needed for the inserts includes the conversion time.

Single Updates

Amount of tweets	Time in seconds	Time in minutes	Database Size (without indexes)
1.000.000	492.26346	8.2	3396 MB
2.000.000	461.87326	7.6	6997 MB
3.000.000	470.7054	7.8	10452 MB